Issued: 2016-3-25

TEST REPORT

Applicant Name & : POMCUBE Inc.

Address 19363 Brockton Ln Saratoga California United States 95070

Sample Description

Product : iCAN

Model No. : 2AGZ2-PO1AAW1

Electrical Rating : 90-130Vac/60Hz/Max.10A

Date Received : 03 November 2015

Date Test Conducted : 05 November 2015-22 March 2016

Test standards : 47 CFR PART 1, Subpart I, Section 1.1310

Test Result : Pass

Conclusion : The submitted samples complied with the above standard.

Remark : None

Prepared and Checked By:

Sky Zhu

Project Engineer

Intertek Guangzhou

. 1

Helen Ma

Team Leader

Approved By:

Intertek Guangzhou

25 March 2016

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch
Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China
Tel / Fax: 86-20-8213 9688/86-20-3205 7538

© 2016 Intertek

Signature

Report No.: 151104034GZU-004 Issued: 2016-3-25

CONTENT

TES	T REPO	DRT	1
1	TEST I	RESULTS SUMMARY	3
2	RESUI	LTS CONCLUSION	
3	EMF T	EST	5
3.	1 EMF	3	5
	3.1.1	Used Test Equipment	4
	3.1.2	Standard Requirement	4
		Test Data	

Issued: 2016-3-25

TEST RESULTS SUMMARY

1

Test Item	Standard	Result
EMF	47 CFR PART 1, Subpart I, Section 1.1310	Pass

Remark: When determining the test results, measurement uncertainty of tests has been considered.

Issued: 2016-3-25

Results Conclusion

(with Justification)

RE: EMF Testing Performed on the iCAN, Models: Error! Reference source not found., 2AGZ2-PO1AAW1.

We only test this EUT wireless charger function, and found it comply the standard 47 CFR PART 1, Subpart I, Section 1.1310 table 1 limit requirement.

During the test used the simulating coil connects the resistance as load.

2

The production units are required to conform to the initial sample as received when the units are placed on the market.

Issued: 2016-3-25

3 EMF TEST

3.1 EMF

Test Result: Pass

3.1.1 Used Test Equipment

Equip. No.	Equipment	Model	Manufacturer	Cal. date	Due date
EM007-03	Exposure Level Tester	ELT-400	NARDA	2015/12/11	2016/12/11

3.1.2 Standard Requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	-		F/300	6
1500-100000	-		5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

3.1.3 Test Data

Operating condition: Output DC 5V/1A

Input Voltage: 120V/60Hz

Ambient Condition: 24°C 50%RH

Issued: 2016-3-25

Test distance: 10cm surrounding the device from all simultaneous transmitting coils Electric Field Emission:


Test Position	Probe Measure Result (V/m)	Limit (V/m)	30% Limit(V/m)
Side 1	14.6	614	184.2
Side 2	15.8	614	184.2
Side 3	16.9	614	184.2
Side 4	15.2	614	184.2
Тор	16.7	614	184.2

Magnetic Field Emission


Test Position	Probe Measure Result (A/m)	Limit (A/m)	30% Limit(A/m)
Side 1	0.043	1.63	0.489
Side 2	0.044	1.63	0.489
Side 3	0.047	1.63	0.489
Side 4	0.044	1.63	0.489
Top	0.047	1.63	0.489


Issued: 2016-3-25

Appendix I - Photos of test setup



Report No.: 151104034GZU-004 Issued: 2016-3-25





Report No.: 151104034GZU-004 Issued: 2016-3-25

