

Report No.: SZEM151200808701

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan

District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com Page: 1 of 27

FCC REPORT

Application No: SZEM1512008087RG (SGS SH No.: SHEM1512004677CR)

Applicant: Letv Sports Flying Pigeon Technology (Tianjin) Co., Ltd.

Product Name: LETV BIKE STARLY

Mode No.(EUT): STARLY

Standards: 47 CFR Part 2 (2014)

47 CFR Part 22 subpart H (2014) 47 CFR Part 24 subpart E (2014)

Test Method: FCC KDB 971168 D01 Power Meas License Digital Systems v02r02

ANSI/TIA-603-D-2010

FCC ID: 2AGZB-GENE-UB1

Date of Receipt: 2015-12-30

Date of Test: 2016-01-08 to 2016-01-11

Date of Issue: 2016-05-05

Test Result : PASS *

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

^{*} In the configuration tested, the EUT detailed in this report complied with the standards specified above.



Report No.: SZEM151200808701

Page: 2 of 27

2 Version

	Revision Record			
Version	Chapter	Date	Modifier	Remark
00		2016-05-05		Original

Authorized for issue by:		
Tested By	David Chen	2016-01-11
	(David Chen) /Project Engineer	Date
Prepared By	Hedy Wen.	2016-05-05
	(Hedy Wen) /Clerk	Date
Checked By	John Hog	2016-05-05
	(Jim Huang) /Reviewer	Date

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 3 of 27

3 Test Summary

3.1 Cellular Band (824-849 MHz Paired With 869-894 MHz)

Tr.	`			
Test Item	FCC Rule No.	Requirements	Test Result	Verdict
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913, §24.232	FCC: ERP ≤ 2 W.	Section 1 of Appendix B	PASS
Peak-Average Ratio	§24.232	≤13dB	Section 2 of Appendix B	PASS
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	PASS
Bandwidth	§2.1049(h), §22.917, §24.238	OBW:No limit EBW: No limit	Section 4 of Appendix B	PASS
Band Edge Compliance	§2.1051, §22.917, §24.238	≤ -13dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	PASS
Spurious emissions at antenna terminals	§2.1051, §22.917, §24.238	FCC: ≤ -13dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	PASS
Field strength of spurious radiation	§2.1051, §22.917, §24.238	FCC: ≤ -13dBm/100 kHz,	Section 7 of Appendix B	PASS
Frequency stability	§2.1055, §22.355, §24.235	≤ ±2.5ppm.	Section 8 of Appendix B	PASS

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 4 of 27

4 Content

			Page
1	CO	VER PAGE	1
2	VE	RSION	
_	۷LI	\01014	
3	TES	ST SUMMARY	
	3.1	CELLULAR BAND (824-849 MHz PAIRED WITH 869-894 MHz)	3
4	CO	NTENT	4
5	GEI	NERAL INFORMATION	6
	5.1	CLIENT INFORMATION	6
	5.2	GENERAL DESCRIPTION OF EUT	6
	5.3	TEST MODE	6
	5.4	TEST ENVIRONMENT	6
	5.5	TEST FREQUENCY	7
	5.6	TEST LOCATION	7
	5.7	TEST FACILITY	8
	5.8	DEVIATION FROM STANDARDS	8
	5.9	ABNORMALITIES FROM STANDARD CONDITIONS	8
	5.10	OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
	5.11	TECHNICAL SPECIFICATION	(
6	DES	SCRIPTION OF TESTS	10
	6.1	CONDUCTED OUTPUT POWER	10
	6.2	EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	10
	6.3	OCCUPIED BANDWIDTH	11
	6.4	BAND EDGE AT ANTENNA TERMINALS	12
	6.5	Spurious And Harmonic Emissions at Antenna Terminal	12
	6.6	PEAK-AVERAGE RATIO	13
	6.7	FIELD STRENGTH OF SPURIOUS RADIATION	13
	6.8	FREQUENCY STABILITY / TEMPERATURE VARIATION	14
	6.9	TEST SETUPS	16
	6.9	1 Test Setup 1	16



Report No.: SZEM151200808701

Page: 5 of 27

	6.9.2	Test Setup 2	17
	6.9.3	Test Setup 3	18
		Test Setup 4	
	6.10 T	EST CONDITIONS	20
7	MAIN	TEST INSTRUMENTS	22
8	MEAS	UREMENT UNCERTAINTY	25
9	PHOT	OGRAPHS - EUT TEST SETUP	26
	9.1 R	RADIATED SPURIOUS EMISSION	26
10	PHOT	OGRAPHS - EUT CONSTRUCTIONAL DETAILS	27





Report No.: SZEM151200808701

Page: 6 of 27

5 General Information

5.1 Client Information

Applicant:	Letv Sports Flying Pigeon Technology (Tianjin) Co., Ltd.	
Address of Applicant:	8th Road & Jingba Linking-up Road, Jinghai Economic Development Zone, Tianjin	

5.2 General Description of EUT

Product Name:	LETV BIKE STARLY
Model No.:	STARLY
Sample Type:	Mobile production
Antenna Type:	Integral
Antenna Gain:	GSM 850: 1.22dBi;
	PCS1900: 1.81dBi;
	WCDMA B5: 1.22dBi.
Battery:	Lithium-ion battery: 3.7V 2750mAh(charge by USB)

5.3 Test Mode

Test Mode	Test Modes Description	
GSM/TM1	GSM system, GPRS/EGPRS, GMSK modulation	
GSM/TM2	GSM system, EGPRS, 8PSK modulation	
UMTS/TM1	UMTS system, WCDMA, QPSK modulation	

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

5.4 Test Environment

Environment Parameter	Selected Va	llues During Tests
Relative Humidity	52%	
Atmospheric Pressure:	1025Pa	
Temperature	TN	25 °C
	VL	3.5V
Voltage :	VN	3.7V
	VH	4.2V

NOTE: VL= lower extreme test voltage

VN= nominal voltage

VH= upper extreme test voltage

TN= normal temperature

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 7 of 27

5.5 Test Frequency

Took Mode	TV / DV	RF Channel		
Test Mode	TX / RX	Low (L)	Middle (M)	High (H)
	TX	Channel 128	Channel 192	Channel 251
CCMOEO	1.	824.2MHz	836.6MHz	848.8MHz
GSM850	RX	Channel 128	Channel 192	Channel 251
	KA	869.2MHz	881.6MHz	893.8MHz
Test Mode	TX / RX		RF Channel	
rest wode	IA/KA	Low (L)	Middle (M)	High (H)
	TX	Channel 512	Channel 661	Channel 810
GSM1900		1850.2MHz	1880.0MHz	1909.8MHz
GSW1900	RX	Channel 512	Channel 661	Channel 810
		1930.2 MHz	1960.0 MHz	1989.8 MHz
Test Mode	TX / RX		RF Channel	
rest wode		Low (L)	Middle (M)	High (H)
	TX	Channel 4132	Channel 4182	Channel 4233
MODAAA DAALD S		826.4MHz	836.4MHz	846.6MHz
WCDMA BAND 5	RX	Channel 4357	Channel 4407	Channel 4458
	KΛ	871.4 MHz	881.4 MHz	891.6 MHz

5.6 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM151200808701

Page: 8 of 27

5.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC - Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

• Industry Canada (IC)

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

5.8 Deviation from Standards

None.

5.9 Abnormalities from Standard Conditions

None.

5.10Other Information Requested by the Customer

None.



Report No.: SZEM151200808701

Page: 9 of 27

5.11 Technical Specification

Characteristics	Description			
Dalla O at T	☐ GSM			
Radio System Type	□ UMTS			
	GSM850	Transmission (TX):	Transmission (TX): 824 to 849 MHz	
	GSIVI650	Receiving (RX): 869	9 to 894 MHz	
Supported Frequency	GSM1900	Transmission (TX):	Transmission (TX): 1850 to 1910 MHz	
Range	GSW1900	Receiving (RX): 193	Receiving (RX): 1930 to 1990 MHz	
	UMTS 850	Transmission (TX):	Transmission (TX): 824 to 849 MHz	
	- OW13 030	Receiving (RX): 869	Receiving (RX): 869 to 894 MHz	
	For GSM850:			
	GPRS/	1 TXSlot	33.5±1dBm	
	EGPRS -	2 TXSlots	32.5±1dBm	
	(GMSK)	3 TXSlots	30.5±1dBm	
	(Sinory)	4 TXSlots	29.5±1dBm	
		1 TXSlot	28.0±1dBm	
	EGPRS	2 TXSlots	27.0±1dBm	
	(8PSK)	3 TXSlots	25.0±1dBm	
		4 TXSlots	24.0±1dBm	
Toward TV Output	For GSM1900:			
Target TX Output Power	GPRS/	1 TXSlot	30.5±1dBm	
1 01101	EGPRS -	2 TXSlots	29.5±1dBm	
	(GMSK)	3 TXSlots	28.0±1dBm	
		4 TXSlots	27.5±1dBm	
	<u> </u>	1 TXSlot	28.0±1dBm	
	EGPRS	2 TXSlots	27.0±1dBm	
	(8PSK)	3 TXSlots	25.0±1dBm	
		4 TXSlots	24.0±1dBm	
	For WCDMA Band 5:			
	WCDMA Band 5	HSDPA	23.0±1dBm	
	Wobiiii Cana o	HSUPA	22.5±1dBm	
Supported Channel	GSM system:	⊠200 kHz	⊠200 kHz	
Bandwidth	UMTS system:	⊠5 MHz	⊠5 MHz	
Designation of	GSM850:	249KGXW		
Emissions	GSM1900:		258KGXW	
(Note: the necessary bandwidth of which is	UMTS850:	4M11F9W		
the worst value from				
the measured				
occupied bandwidths for each type of				
channel bandwidth				
configuration.)				



Report No.: SZEM151200808701

Page: 10 of 27

6 Description of Tests

6.1 Conducted Output Power

Measurement Procedure:

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

Note: Reference test setup 1

6.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure:

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 0.8m high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8). Calculate power in dBm by the following formula:

ERP (dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

Where:

Pg is the generator output power into the substitution antenna.



Report No.: SZEM151200808701

Page: 11 of 27

Above 1GHz test procedure as below:

1). Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber

2). Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3). Test the EUT in the lowest channel, the middle channel the Highest channel
- 4). The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5). Repeat above procedures until all frequencies measured was complete.

Note: Reference test setup 2

6.3 Occupied Bandwidth

Measurement Procedure:

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

Note: Reference test setup 1



Report No.: SZEM151200808701

Page: 12 of 27

6.4 Band Edge at Antenna Terminals

Measurement Procedure:

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

Note: Reference test setup 1

6.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure:

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

Note: Reference test setup 1



Report No.: SZEM151200808701

Page: 13 of 27

6.6 Peak-Average Ratio

Measurement Procedure:

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

Note: Reference test setup 1

6.7 Field Strength of Spurious Radiation

Measurement Procedure:

Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)



Report No.: SZEM151200808701

Page: 14 of 27

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] – cable loss [dB]+antenna gain[dBd or dBi]. The substitute Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log10(Power [Watts]).

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel and the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete

Note: Reference test setup 3

6.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of ANSI/TIA-603-D-2010. The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).



Report No.: SZEM151200808701

Page: 15 of 27

2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.

3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

Note: Reference test setup 4






Report No.: SZEM151200808701

Page: 16 of 27

6.9 Test Setups

6.9.1 Test Setup 1




Ground Reference Plane



Report No.: SZEM151200808701

Page: 17 of 27

6.9.2 Test Setup 2






Figure 1. 30MHz to 1GHz




Figure 2. above 1GHz




Figure 1. 30MHz to 1GHz

Figure 2. above 1GHz

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 18 of 27

6.9.3 Test Setup 3





Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. above 1GHz




Figure 2. 30MHz to 1GHz

Figure 3. above 1GHz


[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 19 of 27

6.9.4 Test Setup 4



Ground Reference Plane



Report No.: SZEM151200808701

Page: 20 of 27

6.10 Test Conditions

Test Case		Test Conditions	
Transmit	Average Power,	Test Environment	Ambient Climate & Rated Voltage
Output Power	Total	Test Setup	Test Setup 1
Data		RF Channels (TX)	L, M, H
			(L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
	Average Power,	Test Environment	Ambient Climate & Rated Voltage
	Spectral Density (if required)	Test Setup	Test Setup 1
	(ii required)	RF Channels (TX)	L, M, H
			(L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
Peak-to-Ave	rage Ratio	Test Environment	Ambient Climate & Rated Voltage
(if required)		Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H
			(L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
Modulation C	Characteristics	Test Environment	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1
		RF Channels (TX)	M
			(M= middle channe)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
Bandwidth	Occupied	Test Environment	Ambient Climate & Rated Voltage
	Bandwidth	Test Setup	Test Setup 1
		RF Channels (TX)	L, M, H
			(L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
	Emission	Test Environment	Ambient Climate & Rated Voltage
	Bandwidth	Test Setup	Test Setup 1
	(if required)	RF Channels (TX)	L, M, H
			(L= low channel, M= middle channel, H= high channel)
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;
Band Edges	Compliance	Test Environment	Ambient Climate & Rated Voltage
		Test Setup	Test Setup 1



Report No.: SZEM151200808701

Page: 21 of 27

	RF Channels (TX)	L, H	
	, ,	(L= low channel, H= high channel)	
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;	
Spurious Emission at Antenna	Test Environment	Ambient Climate & Rated Voltage	
Terminals	Test Setup	Test Setup 1	
	RF Channels (TX)	L, H	
		(L= low channel, M= middle channel, H= high channel)	
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;	
Field Strength of Spurious	Test Environment	Ambient Climate & Rated Voltage	
Radiation	Test Setup	Test Setup 2	
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;	
		NOTE: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.	
	RF Channels (TX)	L, M, H	
		(L= low channel, M= middle channel, H= high channel)	
Frequency Stability	Test Env.	(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;	
		(2) VL, VN and VH of Rated Voltage at Ambient Climate.	
	Test Setup	Test Setup 3	
	RF Channels (TX)	L, M, H	
		(L= low channel, M= middle channel, H= high channel)	
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;	



Report No.: SZEM151200808701

Page: 22 of 27

7 Main Test Instruments

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2015-05-13	2016-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEL0312	2015-09-16	2016-09-16
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-11-15	2017-11-15
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-17	2016-10-17
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2014-11-24	2017-11-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2015-05-13	2016-05-13
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-17	2016-10-17
9	Coaxial cable	SGS	N/A	SEL0027	2015-05-13	2016-05-13
10	Coaxial cable	SGS	N/A	SEL0189	2015-05-13	2016-05-13
11	Coaxial cable	SGS	N/A	SEL0121	2015-05-13	2016-05-13
12	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
13	Band filter	Amindeon	82346	SEL0094	2015-05-13	2016-05-13
14	Barometer	Chang Chun	DYM3	SEL0088	2015-05-13	2016-05-13
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09
16	Humidity/ Temperature Indicator	Shanhai Qixiang	ZJ1-2B	SEL0103	2015-10-24	2016-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2015-05-13	2016-05-13
18	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2015-05-13	2016-05-13
19	Universal radio communication tester	Rohde & Schwarz	CMU200	SEL0091	2015-10-23	2016-10-23
20	Universal radio communication tester	Rohde & Schwarz	CMU200	SEL0194	2015-10-23	2016-10-23

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms.e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 23 of 27

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEL0198	2015-03-01	2016-03-01
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2015-05-13	2016-05-13
3	EMI Test software	AUDIX	E3	SEL0201	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0202	2015-03-01	2016-03-01
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2014-11-15	2017-11-15
6	Amplifier (0.1-1300MHz)	HP	8447D	SEL0153	2015-10-09	2016-10-09
7	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEL0311	2015-06-14	2018-06-14
8	Low Noise Amplifier	Black Diamond Series	BDLNA- 0118- 352810	SEL0319	2015-10-09	2016-10-09
9	Band filter	Amindeon	Asi 3314	SEL0094	2015-05-13	2016-05-13



Report No.: SZEM151200808701

Page: 24 of 27

RF co	RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-09	2016-10-09
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24	2016-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-17	2016-10-17
4	Coaxial cable	SGS	N/A	SEL0178	2015-05-13	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0179	2015-05-13	2016-05-13
6	Barometer	ChangChun	DYM3	SEL0088	2015-05-13	2016-05-13
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2015-04-25	2016-04-25
8	POWER METER	R&S	NRVS	SEL0144	2015-10-09	2016-10-09
9	Universal radio communication tester	Rohde & Schwarz	CMU200	SEL0091	2015-10-23	2016-10-23
10	Universal radio communication tester	Rohde & Schwarz	CMU200	SEL0194	2015-10-23	2016-10-23
11	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2015-04-25	2016-04-25
12	Universal radio communication tester	Anritsu	8820C	SEL0401	2015-04-25	2016-04-25
13	MXA Signal Analyzer	Agilent Technologies Inc	N9020A	SEL0257	2015-07-18	2016-07-18

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



Report No.: SZEM151200808701

Page: 25 of 27

8 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Test Item	Extended Uncertainty	Data
Transmit Output Power Data	Power [dBm]	U = 0.37 dB
Bandwidth	Magnitude [%]	U = 0.2%
Band Edge Compliance	Disturbance Power [dBm]	U = 2.0 dB
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = 2.0 dB
Field Strength of Spurious	ERP [dBm]	For 3 m Chamber:
Radiation		U = 4.5 dB (30 MHz to 1GHz)
		U = 3.3 dB (above 1 GHz)
		For 10 m Chamber:
		U = 4.5 dB (30 MHz to 1GHz)
		U = 3.2 dB (above 1 GHz)
Frequency Stability	Frequency Accuracy [ppm]	U = 0.24 ppm







Report No.: SZEM151200808701

Page: 26 of 27

9 Photographs - EUT Test Setup

9.1 Radiated Spurious Emission







Report No.: SZEM151200808701

Page: 27 of 27

10 Photographs - EUT Constructional Details

Refer to the < STARLY External Photos-FCC > & < STARLY Internal Photos-FCC>

The End

[&]quot;This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."