FCC Test Report

Report No.: AGC05683151202FE03

FCC ID : 2AGZVPULSE

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Soundbrenner Pulse

BRAND NAME : Soundbrenner

MODEL NAME : Pulse

CLIENT : Soundbrenner Limited

DATE OF ISSUE : Jan.05,2016

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Rules

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC05683151202FE03 Page 2 of 47

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan.05,2016	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	7
5. SYSTEM TEST CONFIGURATION	
5.1. CONFIGURATION OF EUT SYSTEM	
5.2. EQUIPMENT USED IN EUT SYSTEM	8
5.3. SUMMARY OF TEST RESULTS	8
6. TEST FACILITY	9
7. ALL TEST EQUIPMENT LIST	
8. RADIATED EMISSION	9
8.1TEST LIMIT	11
8.2. MEASUREMENT PROCEDURE	12
8.3. TEST SETUP	
8.4. TEST RESULT	16
9. BAND EDGE EMISSION	29
9.1. MEASUREMENT PROCEDURE	29
9.2 TEST SETUP	29
9.3 RADIATED TEST RESULT	30
10 20DB BANDWIDTH	34
10.1. MEASUREMENT PROCEDURE	
10.2. TEST SET-UP	
10.3. LIMITS AND MEASUREMENT RESULTS	34
11. FCC LINE CONDUCTED EMISSION TEST	37

Report No.: AGC05683151202FE03 Page 4 of 47

APPENDIX B: PHOTOGRAPHS OF EUT	41
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	39
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	38
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	38
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	38
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	37
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST	37

Page 5 of 47

1. VERIFICATION OF CONFORMITY

Applicant	Soundbrenner Limited
Address	R1009-1012, 10/F., K. Wah Centre, 191 Java Road, North Point, Hong Kong
Manufacturer	Gaojin Electronics (Shenzhen) Co., Ltd
Address	11 FangKeng Road, Pinghu Village, Pinghu Town, Longgang, Shenzhen, Guangdong Province
Product Designation	Soundbrenner Pulse
Brand Name	Soundbrenner
Test Model	Pulse
Date of test	Dec.11,2015 to Dec.15,2015
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested By	Matt Zhang	
	Matt Zhang(Zhang Liang)	Jan.05,2016
Reviewed By	Formersto ce	
	Forrest Lei(Lei Yonggang)	Jan.05,2016
Approved By	Silya shong	
	Solger Zhang(Zhang Hongyi) Authorized Officer	Jan.05,2016

Page 6 of 47

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

	<u> </u>	
Operation Frequency	2.402 GHz to 2.480GHz	
RF Output Power	-9.21dBm(Max)	
Bluetooth Version	V4.1	
Modulation	GFSK	
Number of channels	40	
Hardware Version	1.0.0	
Software Version	1.0.0	
Antenna Designation	Ceramic Antenna (Met 15.203 Antenna requirement)	
Antenna Gain	0.8dBi	
Power Supply	DC 3.7V by battery	
Note: The LISP port only used for charging and cap't be used to transfer data with DC		

Note: The USB port only used for charging and can't be used to transfer data with PC.

The EUT is not active when charging.

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402MHZ
	1	2404MHZ
	:	:
2400 2402 FM 17	19	2440 MHZ
2400~2483.5MHZ	20	2442 MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

Page 7 of 47

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 % \circ

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION	
1	Low channel GFSK	
2	Middle channel GFSK	
3	High channel GFSK	
4	BT Link	

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.

Page 8 of 47

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

14	For the second	NA - I-INI-	ID 0'('('	D
Item	Equipment	Model No.	ID or Specification	Remark
1	Soundbrenner Pulse	Soundbrenn	Pulse	EUT
2	Control box	N/A	N/A	A.E
3	PC	SONY	E1412AYCW	A.E
4	USB Cable	N/A	0.6m, unshielded	A.E
5	AC adapter	GPE0538	1.1m,unshielded	A.E
6	Temporary Antenna Connector	T10	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWITH	Compliant

Report No.: AGC05683151202FE03 Page 9 of 47

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location Building D,Baoding Technology Park,Guangming Road2,Dongcheng D Dongguan, Guangdong, China,	
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7. ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site										
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration					
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016					
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016					
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016					
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016					
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016					
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A					
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016					
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016					
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016					
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016					

Report No.: AGC05683151202FE03 Page 10 of 47

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site										
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration					
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016					
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016					
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016					
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016					
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016					
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016					
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A					
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016					
Radiation Cable 1	MXT	RS1	R005	June 6, 2015	June 5, 2016					
Radiation Cable 2	MXT	RS1	R006	June 6, 2015	June 5, 2016					

Page 11 of 47

8. RADIATED EMISSION

8.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics		
	(millivolts/meter)	(microvolts/meter)		
900-928MHz	50	500		
2400-2483.5MHz	50	500		
5725-5875MHz	50	500		
24.0-24.25GHz	250	2500		

Standard FCC 15.209

Frequency	Distance	Field Strengths Limit				
(MHz)	(MHz) Meters		dB(μV)/m			
0.009 ~ 0.490	300	2400/F(kHz)				
0.490 ~ 1.705	30	24000/F(kHz)				
1.705 ~ 30	30	30				
30 ~ 88	3	100	40.0			
88 ~ 216	3	150	43.5			
216 ~ 960	3	200	46.0			
960 ~ 1000	3	500	54.0			
Above 1000	3	Other:74.0 dB(µV)/m (Peak) 54.0 dB(µV)/m (Average)				

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Page 12 of 47

8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1.5MHz VBW and RBW for peak reading. Then 1.5MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC05683151202FE03 Page 13 of 47

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting			
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP			
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP			
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP			
Start ~Stop Frequency	1GHz~26.5GHz			
Start Stop Frequency	1.5MHz/1.5MHz for Peak, 1.5MHz/10Hz for Average			

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 14 of 47

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz



Report No.: AGC05683151202FE03 Page 15 of 47

RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 16 of 47

8.4. TEST RESULT


(Modulation:GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: Low Channel Tx

Note:


Polarization: Horizontal Temperature: 23.3
Power: Humidity: 56.9 %

Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		138.3167	10.99	14.92	25.91	43.50	-17.59	peak			
2		230.4667	17.17	13.16	30.33	46.00	-15.67	peak			
3		398.6000	16.03	19.06	35.09	46.00	-10.91	peak			
4		597.4500	6.63	23.67	30.30	46.00	-15.70	peak			
5	*	749.4167	11.88	26.61	38.49	46.00	-7.51	peak		·	
6		899.7667	6.84	28.60	35.44	46.00	-10.56	peak			

Page 17 of 47

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Polarization: Vertical

Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: Low Channel Tx

Note:

Power:	Humidity: 56.9 %
Distance:	

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		167.4167	1.96	14.86	16.82	43.50	-26.68	peak			
2		230.4667	10.59	11.99	22.58	46.00	-23.42	peak			
3		385.6667	0.54	18.98	19.52	46.00	-26.48	peak			
4		521.4667	0.08	21.71	21.79	46.00	-24.21	peak			
5		683.1333	-1.52	24.74	23.22	46.00	-22.78	peak		·	
6	*	767.2000	1.14	26.87	28.01	46.00	-17.99	peak			


RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 18 of 47

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: Middle Channel Tx

Note:

Polarization:	Horizontal	Temperature: 23.3
Power:		Humidity: 56.9 %


Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		135.0833	10.04	14.38	24.42	43.50	-19.08	peak			
2		230.4667	17.17	13.16	30.33	46.00	-15.67	peak			
3		400.2167	16.68	19.08	35.76	46.00	-10.24	peak			
4		600.6833	10.11	23.73	33.84	46.00	-12.16	peak			
5	*	749.4167	9.98	26.61	36.59	46.00	-9.41	peak			
6		799.5333	8.74	27.31	36.05	46.00	-9.95	peak			

Humidity: 56.9 %

Page 19 of 47

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Power:

Distance:

Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: Middle Channel Tx

Freq.

MHz 131.8500

230.4667

398.6000

450.3333

597.4500

749.4167

Note:

Mk No.

> 1 2

3

4

5

6

Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
13.31	11.80	25.11	43.50	-18.39	peak			
17.17	11.99	29.16	46.00	-16.84	peak			
10.44	19.06	29.50	46.00	-16.50	peak			
9.56	20.59	30.15	46.00	-15.85	peak			

peak

peak

46.00 -15.44

46.00 -10.98

Polarization: Vertical

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

22.72

26.61

7.84

8.41

2. The "Factor" value can be calculated automatically by software of measurement system.

30.56

35.02

Page 20 of 47

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: High Channel Tx

Note:

Polarization: *Horizontal* Temperature: 23.3 Power: Humidity: 56.9 %


Distance:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		127.0000	12.30	13.03	25.33	43.50	-18.17	peak			
2		230.4667	18.45	13.16	31.61	46.00	-14.39	peak			
3		400.2167	9.56	19.08	28.64	46.00	-17.36	peak			
4		600.6833	5.81	23.73	29.54	46.00	-16.46	peak			
5	*	749.4167	7.86	26.61	34.47	46.00	-11.53	peak			
6		899.7667	5.68	28.60	34.28	46.00	-11.72	peak			

Humidity: 56.9 %

Page 21 of 47

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Polarization: Vertical

Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Soundbrenner Pulse

M/N: Pulse

Mode: High Channel Tx

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		170.6500	12.04	14.66	26.70	43.50	-16.80	peak			
2		230.4667	16.00	11.99	27.99	46.00	-18.01	peak			
3		450.3333	7.41	20.59	28.00	46.00	-18.00	peak			
4		599.0667	7.69	22.73	30.42	46.00	-15.58	peak			
5	*	749.4167	7.01	26.61	33.62	46.00	-12.38	peak			
6		899.7667	3.27	28.60	31.87	46.00	-14.13	peak			

Power:

Distance:

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

Page 22 of 47

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: Conduction Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.000	85.02	-9.68	75.34	94.00	-18.66	AVG	100	289	
2		2402.000	95.73	-9.68	86.05	114.00	-27.95	peak			
3		3658.333	51.00	-6.91	44.09	74.00	-29.91	peak			
4		4941.667	46.20	-1.95	44.25	74.00	-29.75	peak			

Page 23 of 47

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: Conduction Polarization: Vertical Temperature: 26

Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2402.000	82.90	-9.68	73.22	94.00	-20.78	AVG	100	310	
2		2402.000	95.73	-9.68	86.05	114.00	-27.95	peak			
3		3183.333	53.61	-8.19	45.42	74.00	-28.58	peak			
4		5308.333	47.48	-1.81	45.67	74.00	-28.33	peak			

Page 24 of 47

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: Conduction Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2440.000	94.80	-9.64	85.16	114.00	-28.84	peak			
2		3633.333	51.28	-7.07	44.21	74.00	-29.79	peak			
3		4916.667	46.06	-2.02	44.04	74.00	-29.96	peak			
4	*	2440.000	83.74	-9.64	74.10	94.00	-19.90	AVG	100	315	

Page 25 of 47

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: Conduction Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1700.000	58.87	-13.28	45.59	74.00	-28.41	peak			
2		2440.000	95.24	-9.64	85.60	114.00	-28.40	peak			
3		3866.667	50.43	-5.63	44.80	74.00	-29.20	peak			
4	*	2440.000	83.87	-9.64	74.23	94.00	-19.77	AVG	100	278	

Page 26 of 47

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: Conduction Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	93.87	-9.59	84.28	114.00	-29.72	peak			
2		3650.000	51.34	-6.97	44.37	74.00	-29.63	peak			
3		5008.333	48.14	-1.80	46.34	74.00	-27.66	peak			
4	*	2480.000	82.82	-9.59	73.23	94.00	-20.77	AVG	100	184	

Page 27 of 47

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: Conduction Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance: 3m

M/N: Pluse

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	93.87	-9.59	84.28	114.00	-29.72	peak			
2		3775.000	50.49	-6.20	44.29	74.00	-29.71	peak			
3		5300.000	46.54	-1.81	44.73	74.00	-29.27	peak		·	
4	*	2480.000	83.70	-9.59	74.11	94.00	-19.89	AVG	100	311	

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Report No.: AGC05683151202FE03 Page 28 of 47

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	95.73	-9.68	86.05	114	-27.95	Horizontal
2402	95.73	-9.68	86.05	114	-27.95	Vertical
2440	94.80	-9.64	85.16	114	-28.84	Horizontal
2440	95.24	-9.64	85.60	114	-28.40	Vertical
2480	93.87	-9.59	84.28	114	-29.72	Horizontal
2480	93.87	-9.59	84.28	114	-29.72	Vertical

Average value

•						
Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	85.02	-9.68	75.34	94	-18.66	Horizontal
2402	82.90	-9.68	73.22	94	-20.78	Vertical
2440	83.74	-9.64	74.10	94	-19.90	Horizontal
2440	83.87	-9.64	74.23	94	-19.77	Vertical
2480	82.82	-9.59	73.23	94	-20.77	Horizontal
2480	83.70	-9.59	74.11	94	-19.89	Vertical

Page 29 of 47

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE


1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1.5MHz / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP




Page 30 of 47

9.3 RADIATED TEST RESULT

(Modulation:GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: Conduction Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance:


M/N: Pluse

Mode: Low Channel TX

N	lo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
			MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
Γ	1		2249.883	34.26	10.15	44.41	74.00	-29.59	peak			
Γ	2		2319.242	34.55	10.23	44.78	74.00	-29.22	peak			
Γ	3	*	2402.267	75.72	10.32	86.04	74.00	12.04	peak			

Page 31 of 47

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: Conduction Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance:


M/N: Pluse

Mode: Low Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2246.125	32.26	10.15	42.41	74.00	-31.59	peak			
2		2306.600	31.70	10.22	41.92	74.00	-32.08	peak			
3	*	2402.267	74.59	10.32	84.91	74.00	10.91	peak			

Page 32 of 47

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: Conduction Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Soundbrenner Pluse Distance:


M/N: Pluse

Mode: High Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2479.687	75.90	10.41	86.31	74.00	12.31	peak			
2		2487.790	33.28	10.42	43.70	74.00	-30.30	peak			
3		2496.517	34.94	10.43	45.37	74.00	-28.63	peak			

Page 33 of 47

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: Conduction Polariza
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power:

Polarization: Vertical

Temperature: 26

EUT: Soundbrenner Pluse

Distance:

Humidity: 60 %

M/N: Pluse

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBuV	dBuV/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.237	74.61	10.41	85.02	74.00	11.02	peak			
2		2486.910	30.17	10.42	40.59	74.00	-33.41	peak			
3		2494.427	30.94	10.42	41.36	74.00	-32.64	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 34 of 47


10 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP

(BLOCK DIAGRAM OF CONFIGURATION)




Note: The EUT has been used temporary antenna connector for testing.

10.3. LIMITS AND MEASUREMENT RESULTS


BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL						
Applicable Limite	Measurement Result					
Applicable Limits	Test Da	Criteria				
	Low Channel	1.239	PASS			
N/A	Middle Channel	1.243	PASS			
	High Channel	1.240	PASS			

Page 35 of 47

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



Page 36 of 47

TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 37 of 47

11. FCC LINE CONDUCTED EMISSION TEST


11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francis	Maximum RF Line Voltage					
Frequency	Q.P.(dBuV)	Average(dBuV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 38 of 47

11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.4.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by PC or by adapter which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.


11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST


N/A


Page 39 of 47


APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP









Page 41 of 47

APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT




Page 42 of 47

BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



Page 43 of 47





LEFT VIEW OF EUT



RIGHT VIEW OF EUT




VIEW OF EUT (Port)




Page 45 of 47

OPEN VIEW OF EUT




INTERNAL VIEW OF EUT-1




Report No.: AGC05683151202FE03 Page 46 of 47


INTERNAL VIEW OF EUT-2




INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



----END OF REPORT----