

Report No.: SUCR250400030607

Rev.: 01 Page: 1 of 8

## **TEST REPORT**

**Application No.:** SUCR2504000306AT

**Applicant:** Shanghai Sunmi Technology Co.,Ltd.

**Address of Applicant:** Room 505, No. 388, Song Hu Road, Yang Pu District, Shanghai, China

Manufacturer: Shanghai Sunmi Technology Co.,Ltd.

Address of Manufacturer: Room 505, No. 388, Song Hu Road, Yang Pu District, Shanghai, China

**EUT Description: Smart Interactive Terminal** 

Model No.: F962A Trade Mark: **SUNMI** 

FCC ID: 2AH25F962AL

Standards: 47 CFR Part 2.1091

FCC KDB 447498 D01 v06

April 24, 2025 Date of Receipt: Date of Issue: June 12, 2025

**Test Result:** PASS\*

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or

Wireless Laboratory

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. South of No. 6 Plant, No. 1, RunSheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

t (86-512) 6229 2980 www.sgsgroup.com.cn

email: CN.Doccheck@sgs.com

In the configuration tested, the EUT complied with the standards specified above.



Report No.: SUCR250400030607

Rev.: 01 Page: 2 of 8

## Version

	Revision Record							
Version Description Date Remark								
01	Original	June 12, 2025	/					

Authorized for issue by:		
Tested By	Hayley Zhang	
	Hayley Zhang / Project Manager	
Approved By	Cloud Peng	
	Cloud Peng/Technical Manager	



Report No.: SUCR250400030607

Rev.: 01 Page: 3 of 8

### **Contents**

1	Gei	neral Information	. 4
		Client Information	
	1.2	Test Facility	. 4
		General Description of EUT	
2	RF	Exposure Evaluation	. 6
	2.1	RF Exposure Compliance Requirement	. 6



Report No.: SUCR250400030607

Rev.: 01 Page: 4 of 8

#### 1 General Information

#### 1.1 Client Information

Applicant: Shanghai Sunmi Technology Co.,Ltd.	
Address of Applicant: Room 505, No.388 Song Hu Road, Yang Pu District, Shanghai, China	
Manufacturer:	Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer:	Room 505, No.388 Song Hu Road, Yang Pu District, Shanghai, China

#### 1.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

• Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC -Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327



Report No.: SUCR250400030607

Rev.: 01 Page: 5 of 8

### 1.3 General Description of EUT

EUT Description:	Smart Interactive Te	rminal				
Model No.:	F962A, F9E2A					
Trade Mark:	SUNMI					
Hardware Version:	6225Coreboard_MB	_V3.0				
Software Version:	4.0.12					
Power Supply:	20V					
	Bluetooth:	0.4dBi	WIFI 2.4G:	0.4dBi		
	5G WIFI(U-NII-1):	-1.0dBi	5G WIFI(U-NII- 2A):	-0.8dBi		
Antenna Gain:	5G WIFI(U-NII-2C):	-0.4dBi	5G WIFI(U-NII-3):	-0.8dBi		
	Note:					
	The antenna gain are derived from the gain information report provided by the manufacturer.					

Note: \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.



Report No.: SUCR250400030607

Rev.: 01 Page: 6 of 8

### 2 RF Exposure Evaluation

### 2.1 RF Exposure Compliance Requirement

#### **2.1.1 Limits**

Frequency range (MHz)				Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposures									
0.3-3.0	614	1.63	*(100)	6					
3.0-30	1842/f	4.89/f	*(900/f2)	6					
30-300	61.4	0.163	1.0	6					
300-1500	1	1	f/300	6					
1500-100,000	1	1	5	6					
	(B) Limits for General Population/Uncontrolled Exposure								
0.3-1.34	614	1.63	*(100)	30					
1.34-30	824/f	2.19/f	*(180/f2)	30					
30-300	27.5	0.073	0.2	30					
300-1500	1	1	f/1500	30					
1500-100,000	1	1	1.0	30					

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula:  $Pd = (Pout*G)/(4*Pi*R^2)$ 

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 2.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

<sup>\*=</sup>Plane-wave equivalent power density



Report No.: SUCR250400030607

Rev.: 01 Page: 7 of 8

#### 2.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

Band	Frequency	Max power (dBm)	Ant Gain (dBi)	ERP (dBm)	Max ERP (mW)	Max Power (mW)	ERP 20 (mW)	Distance R (cm)	Limit (mW)	Result	Ratio
Bluetooth	2441	13.23	0.4	11.48	14.06	21.04	3060	20	3060	Pass	0.01
WLAN 2.4GHz	2437	26.81	0.4	25.06	320.63	479.73	3060	20	3060	Pass	0.16
WLAN 5GHz B1	5230	18.97	-1	15.82	38.19	78.89	3060	20	3060	Pass	0.03
WLAN 5GHz B2	5270	18.55	-0.8	15.6	36.31	71.61	3060	20	3060	Pass	0.02
WLAN 5GHz B3	5670	19.58	-0.4	17.03	50.47	90.78	3060	20	3060	Pass	0.03
WLAN 5GHz B4	5795	19.29	-0.8	16.34	43.05	84.92	3060	20	3060	Pass	0.03



Report No.: SUCR250400030607

Rev.: 01 Page: 8 of 8

#### 2.1.4 Exposure calculations for multiple sources

To ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \le 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration	
1	Bluetooth+ WiFi 2.4G+ WiFi 5G	

No.	Mode	Result Ratio	Total Ratio	Limit	Result
	Bluetooth	0.01			Pass
1	WiFi 2.4G	0.16	0.20	1.00	
	WiFi 5G	0.03			

Remark: This WWAN Band was recalculated on worst Band.

---End of Report---