

TEST REPORT

No. I19D00060-SAR01

For

Client: Shanghai Sunmi Technology Co.,Ltd.

Production: POS System

Model Name: L3512

Brand Name: SUNMI

FCC ID: 2AH25L3512

Hardware Version: HXSMB60A

Software Version: Neostra-N-Single-OS7.1-32bit-V15_20181

Issued date: 2019-05-13





NOTE

- 1. The test results in this test report relate only to the devices specified in this report.
- 2. This report shall not be reproduced except in full without the written approval of East China Institute of Telecommunications.
- For the test results, the uncertainty of measurement is not taken into account when
 judging the compliance with specification, and the results of measurement or the
 average value of measurement results are taken as the criterion of the compliance with
 specification directly.
- 4. It has been confirmed with the customer that the Highest Frame-Averaged Output Power and Antenna gain information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences will be borne by the customer.

Test Laboratory:

East China Institute of Telecommunications

Add: 7-8F, G Area, No.668, Beijing East Road, Huangpu District, Shanghai, P. R. China

Page Number: 2 of 10

Report Issued Date: May 13, 2019

Tel: +86 21 63843300 FAX: +86 21 63843301

E-Mail: welcome@ecit.org.cn



Page Number : 3 of 10 Report Issued Date :May 13, 2019



Revision Version

Report Number	Revision	Date	Memo
I19D00060-SAR01	01	2019-05-13	Second creation of test report

Page Number : 4 of 10 Report Issued Date :May 13, 2019



CONTENTS

1.	TEST LABORATORY	5
1.1.	TESTING LOCATION	5
1.2.	PROJECT DATA	5
1.3.	SIGNATURE	5
2.	CLIENT INFORMATION	. 6
2.1.	APPLICANT INFORMATION	. 6
2.2.	MANUFACTURER INFORMATION	. 6
3.	EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	. 7
3.1.	ABOUT EUT	. 7
3.2.	INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	. 7
3.3.	INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	. 7
4.	REFERENCE DOCUMENTS FOR FCC	. 8
4.1.	APPLICABLE STANDARDS	. 8
4.2.	TEST LIMITS	. 8
5.	TEST RESULTS	. 9
5.1.	RF POWER OUTPUT	. 9
5.2.	CALCULATION INFORMATION	. 9
53	POWED DENSITY CALCULATIONS	10



1. Test Laboratory

1.1. Testing Location

Company Name:	ECIT Shanghai, East China Institute of Telecommunications
Address:	7-8F, G Area,No. 668, Beijing East Road, Huangpu District,
	Shanghai, P. R. China
Postal Code:	200001
Telephone:	(+86)-021-63843300
Fax:	(+86)-021-63843301
FCC Registration NO.:	489729

1.2. Project Data

Project Leader:	Yu Anlu

1.3. Signature

Yan Hang

(Prepared this test report)

Fu Erliang


Page Number: 5 of 10

Report Issued Date :May 13, 2019

(Reviewed this test report)

博二良

Zheng Zhongbin
(Approved this test report)





2. Client Information

2.1. Applicant Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.

Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai,

China

Telephone: N/A
Postal Code: N/A

2.2. Manufacturer Information

Company Name: Shanghai Sunmi Technology Co.,Ltd.

Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai,

Page Number: 6 of 10

Report Issued Date :May 13, 2019

Address: China

Telephone: N/A
Postal Code: N/A

Page Number: 7 of 10

Report Issued Date :May 13, 2019



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description	POS System
Model name	L3512
WLAN 2.4G Frequency Band	b/g/n
BT Frequency Band	BT;BLE

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N01	N/A	HXSMB60A	Neostra-N-Single-OS7. 1-32bit-V15_20181008	2019-04-17

^{*}EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer	
		1	1		

^{*}AE ID: is used to identify the test sample in the lab internally.



4. Reference Documents For FCC

4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47, Part 2, FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS

Section 1.1310 Radiofrequency radiation exposure limits

4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

Limits for Occupational / Controlled Exposure

Frequency	Electric	Field	Magnetic	Field	Power	Density	Averaging	
Range	Strength	(E)	Strength	(H)	(S)		Times E 2, H 2	
[MHz]	[V/m]		[A/m]		[mW/cm2]		or S [miniutes]	
0.3 - 3.0	614		1.63		(100)*		6	
3.0 - 30	1824/f		4.89/f		(900/f)*		6	
30 – 300	61.4		0.163		1.0		6	
300 – 1500					F/300		6	
1500 - 100000					5		6	

Limits for General Population / Uncontrolled Exposure

Frequency	Electric	Field	Magnetic	Field	Power	Density	Averaging	
Range	Strength	(E)	Strength	(H)	(S)		Times E 2, H 2	
[MHz]	[V/m]		[A/m]		[mW/cm2]		or S [miniutes]	
0.3 – 1.34	614		1.63		(100)*		30	
1.34 – 30	824/f		2.19/f		(180/f)*		30	
30 – 300	27.5		0.073		0.2		30	
300 – 1500					F/1500		30	
1500 - 100000					1.0		30	

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for General Population / Uncontrolled Exposure are applicable.

Page Number: 8 of 10 Report Issued Date: May 13, 2019

Page Number: 9 of 10

Report Issued Date :May 13, 2019



5. Test Results

5.1. RF Power Output

Band	Max power(dBm)	Highest Frame-Averaged Output Power (dBm)	Antenna Gain (dBi)
WLAN 2.4G 802.11b	16.5	16.5	0.87
WLAN 2.4G 802.11g	13.5	13.5	0.87
WLAN 2.4G 802.11 n20	12.5	12.5	0.87
WLAN 2.4G 802.11 n40	12.5	12.5	0.87
ВТ	8	8	0.87
BLE	7	7	0.87

5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

Given
$$S = \frac{P \times G}{4\Pi d^2}$$
 Equation 1

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Page Number: 10 of 10

Report Issued Date :May 13, 2019



5.3. Power density calculations

Band	Highest Output Power (dBm)	Antenna Gain (dBi)	Numeric antenna gain	Power density at 20cm	Limit mW/cm ²	Power density/ Limit
WLAN 2.4G 802.11b	16.5	0.87	1.222	0.011	1.0	0.011
WLAN 2.4G 802.11g	13.5	0.87	1.222	0.005	1.0	0.005
WLAN 2.4G 802.11 n20	12.5	0.87	1.222	0.004	1.0	0.004
WLAN 2.4G 802.11 n40	12.5	0.87	1.222	0.004	1.0	0.004
ВТ	8	0.87	1.222	0.002	1.0	0.002
BLE	7	0.87	1.222	0.001	1.0	0.001

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band

The product is under the MPE limits. All is pass.

********END OF REPORT*******