

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 1 of 575

TEST REPORT

Application No.: SUCR2501000021IT
Applicant: Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer: Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
EUT Description: Wireless Data Terminal
Model No.: TF31B
Trade Mark: SUNMI
FCC ID: 2AH25M3L
Standards: FCC 47 CFR Part 2, Subpart J
FCC 47 CFR Part 15, Subpart E
Date of Receipt: January 9, 2025
Date of Test: January 20, 2025 to March 14, 2025
Date of Issue: May 21, 2025, Amendment 02: June 9, 2025

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 2 of 575

Version

Revision Record			
Version	Description	Date	Remark
01	Original	May 21, 2025	/
02	Updated	June 9, 2025	PAG Comment
This report supersedes our previous report SUCR250100002105, issued on 2025/05/21, which is hereby deemed null and void.			

Authorized for issue by:				
Tested By				
		Hayley Zhang / Project Manager		
Approved By				
		Cloud Peng/Technical Manager		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 3 of 575

Contents

Version	2
1 Test Summary	4
2 General Information	6
2.1 Details of Client	6
2.2 Test Location	6
2.3 Test Facility	6
2.4 General Description of EUT	7
2.5 Test Environment and Mode	10
2.6 Description of Support Units	10
2.7 Worst-case configuration and mode	10
3 Equipment List	11
4 Measurement Uncertainty (95% confidence levels, k=2)	13
5 Test results and Measurement Data	14
5.1 Antenna Requirement	14
5.2 AC Power Line Conducted Emissions	16
5.3 Duty Cycle	20
5.4 Conducted Output Power	21
5.5 26dB Emission Bandwidth	22
5.6 6dB Emission Bandwidth	23
5.7 99% Occupied Bandwidth	24
5.8 Power Spectral Density	25
5.9 Radiated Spurious Emissions	26
5.10 Restricted bands around fundamental frequency	28
5.11 Dynamic Frequency Selection	30
6 Photographs - Setup Photos	34
7 Appendix	35



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 4 of 575

1 Test Summary

Test Item	Band ^[1]	FCC rules No.	Test Requirements	Test Result	Result
Antenna Requirement	--	15.203/15.407(a)	--	Clause 3.1	PASS
26dB Emission Bandwidth	Band I	15.407(a)(1)	No limit.	Clause 3.5	For Report Purpose
	Band II-A	15.407(a)(2)			
	Band II-C	15.407(a)(2)			
6dB Emission Bandwidth	Band III	15.407(e)	≥ 500 kHz.	Clause 3.6	PASS
99% Occupied Bandwidth	Band I	KDB 789033 D02§ D	No limit.	Clause 3.7	For Report Purpose
	Band II-A				
	Band II-C				
	Band III				
Duty Cycle	Band I Band II-A Band II-C Band III	--	No limit.	Clause 3.3	For Report Purpose
Maximum Conducted Output Power	Band I	15.407(a)(iv)	< 250mW	Clause 3.4	PASS
	Band II-A	15.407(a)(2)	<MIN{250mW, 11dBm+10*lg(EBW)}		
	Band II-C		< 1W		
	Band III	15.407(a)(3)			
Maximum Power Spectral Density	Band I	15.407(a)(iv)	<11dBm/MHz	Clause 3.8	PASS
	Band II-A	15.407(a)(2)	<11dBm/MHz		
	Band II-C				
	Band III	15.407(a)(3)	<30dBm/500KHz		
Radiated Spurious Emissions	Band I	15.407(b) 15.205/15.209	F<1GHz: §15.209 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.15-5.35 GHz). F≥1GHz & in-restricted: §15.209 limit (AV&PK).	Clause 3.9	PASS
	Band II-A	15.407(b) 15.205/15.209	F<1GHz: §15.209 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.25-5.35 GHz). F≥1GHz & in-restricted: §15.209 limit (AV&PK).		PASS
	Band II-C	15.407(b) 15.205/15.209	F<1GHz: §15.209 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.47-5.725 GHz). F≥1GHz & in-restricted: §15.209 limit (AV&PK).		PASS
	Band III	15.407(b) 15.205/15.209	F<1GHz: §15.209 limit (QP) F≥1GHz &out-restricted:(PK) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz		PASS



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 5 of 575

Test Item	Band ^[1]	FCC rules No.	Test Requirements	Test Result	Result
			above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. F≥1GHz & in-restricted: §15.209 limit (AV&PK).		
Restricted bands around fundamental frequency	Band I Band II-A Band II-C Band III	15.407(b) 15.205/15.209	---	Clause 3.10	PASS
AC Power Line Conducted Emissions	Band I Band II-A Band II-C Band III	15.207	---	Clause 3.2	PASS
Dynamic Frequency Selection	Band II-A Band II-C	15.407	Channel Move Time:10 Seconds	Clause 3.11	PASS
Frequency Stability	Band I Band II-A Band II-C Band III	15.407(g)	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual	N/A	N/A
Note 1: Band I: 5150-5250MHz Band II-A: 5250-5350MHz Band II-C: 5470-5725MHz Band III: 5725-5850MHz					



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 6 of 575

2 General Information

2.1 Details of Client

Applicant:	Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant:	Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer:	Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer:	Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China

2.2 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	Ives Cheng, King-p Li

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 7 of 575

2.4 General Description of EUT

EUT Description:	Wireless Data Terminal		
Model No.:	TF31B		
Trade Mark:	SUNMI		
Hardware Version:	V1.2		
Software Version:	T602AA_EVT_14.0_SUNMI_202503131820.00-00		
Power Supply:	3.87V from battery		
WLAN Mode Supported:	802.11a:	20 MHz channel bandwidth	
	802.11n:	20 MHz / 40 MHz channel bandwidth	
	802.11ac:	20 MHz / 40 MHz / 80 MHz channel bandwidth	
	802.11ax:	20 MHz / 40 MHz / 80 MHz channel bandwidth	
Operation Frequency:	5150MHz to 5250MHz 5250MHz to 5350MHz 5470MHz to 5725MHz 5725MHz to 5850MHz		
Modulation Type:	802.11a:	OFDM (BPSK, QPSK, 16QAM, 64QAM)	
	802.11n:	OFDM (BPSK, QPSK, 16QAM, 64QAM)	
	802.11ac:	OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)	
	802.11ax:	OFDM/OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)	
Channel Spacing:	20MHz:	802.11a/n(HT20)/ac(VHT20)/ax(HE20)/be(EHT20)	
	40MHz:	802.11n(HT40)/ac(VHT40)/ax(HE40)/be(EHT40)	
	80MHz:	802.11ac(VHT80)/ax(HE80)/be(EHT80)	
Antenna Type:	FPC Antenna		
Antenna Gain:	5150MHz to 5250MHz: 2.6dBi(Ant3); -2.51dBi(Ant2) 5250MHz to 5350MHz: 2.7dBi(Ant3); -1.72dBi(Ant2) 5470MHz to 5725MHz: 2.56dBi(Ant3); 0.97dBi(Ant2) 5725MHz to 5850MHz: 2.1dBi(Ant3); 0.92dBi(Ant2)		
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.		
Smart System:	☒ SISO	802.11a	
	☒ MIMO	802.11n/ac/ax: 2Tx & 2Rx	
TPC Function:	☒ Support, ☐ Not Support		
DFS Function:	☐ Master		
	☐ Slave with radar detection		☒ Slave without radar detection
RF Cable:	2dB		
Remark: 1.As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.			



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 8 of 575

2.The device does not support 802.11ax OFDMA Partial RU tones (26T, 52T, 106T, etc.)

3.In FCC 15.31, for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table, and the selected channel to perform the test as below:

Frequency range over which device operates	Number of Measurement Frequencies Required	Location of Measurement Frequency in Band of Operation
1 MHz or less	1	centre
1 MHz to 10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near centre

For UNII Band I:

Mode	Channel	Frequency(MHz)
IEEE 802.11a/n/ac/ax 20MHz	The Lowest channel	5180
	The Middle channel	5200
	The Highest channel	5240
IEEE 802.11n/ac/ax 40MHz	The Lowest channel	5190
	The Highest channel	5230
IEEE 802.11ac/ax 80MHz	The Middle channel	5210

For UNII Band II-A:

Mode	Channel	Frequency(MHz)
IEEE 802.11a/n/ac/ax 20MHz	The Lowest channel	5260
	The Middle channel	5280
	The Highest channel	5320
IEEE 802.11n/ac/ax 40MHz	The Lowest channel	5270
	The Highest channel	5310
IEEE 802.11ac/ax 80MHz	The Middle channel	5290



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 9 of 575

For UNII Band II-C:		
Mode	Channel	Frequency(MHz)
IEEE 802.11a/n/ac/ax 20MHz	The Lowest channel	5500
	The Middle channel	5580
	The Highest channel	5700
IEEE 802.11n/ac/ax 40MHz	The Lowest channel	5510
	The Middle channel	5550
	The Highest channel	5670
IEEE 802.11ac/ax 80MHz	The Middle channel	5530

For UNII Band III:		
Mode	Channel	Frequency(MHz)
IEEE 802.11a/n/ac/ax 20MHz	The Lowest channel	5745
	The Middle channel	5785
	The Highest channel	5825
IEEE 802.11n/ac/ax 40MHz	The Lowest channel	5755
	The Highest channel	5795
IEEE 802.11ac/ax 80MHz	The Middle channel	5775



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 10 of 575

2.5 Test Environment and Mode

Environment Parameter	101 kPa Selected Values During Tests	
Relative Humidity	44-46 % RH Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	22~23	3.87
Remark: NV: Normal Voltage NT: Normal Temperature		

2.6 Description of Support Units

Description	Manufacturer	Model No.	FCC ID
Router	ASUS	GT-AXE11000	MSQ-RTAXJF00

2.7 Worst-case configuration and mode

Low data rate was used to test on antenna port conducted tests and radiated spurious emissions since it has the highest maximum power. Following are the worst-case data rates set for test:

Modulation Type	SISO - Data Rate	CDD/MIMO - Data Rate
802.11a	6 Mbps	/
802.11n (HT 20)	/	MCS0 (13 Mbps)
802.11n (HT 40)	/	MCS0 (27 Mbps)
802.11ac (VHT 20)	/	MCS0 (13 Mbps)
802.11ac (VHT 40)	/	MCS0 (27 Mbps)
802.11ac (VHT 80)	/	MCS0 (58.5 Mbps)
802.11ax (HE 20)	/	MCS0 (16 Mbps)
802.11ax (HE 40)	/	MCS0 (32 Mbps)
802.11ax (HE 80)	/	MCS0 (68 Mbps)



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 11 of 575

3 Equipment List

RF Test Equipment					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Shielding Room	Brilliant-emc	N/A	SUWI-04-08-01	2022/11/09	2025/11/08
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2024/02/18	2025/02/17
				2025/02/13	2026/02/12
Measurement Software	Tonscend	TST272 V2.0	SUWI-03-55-03	NCR	NCR
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	2024/05/08	2025/05/07
Temperature Chamber	ESPEC	SU-242	SUWI-01-13-02	2024/05/09	2025/05/08
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-05	2024/02/04	2025/02/03
				2025/01/21	2026/01/20
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	2024/02/04	2025/02/03
				2025/01/15	2026/01/14
Power meter	Anritsu	ML2495A	SUWI-01-31-01	2024/11/19	2025/11/18
Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	2024/11/19	2025/11/18
MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	2024/02/04	2025/02/03
				2025/01/15	2026/01/14
Router	ASUS	GT-AXE11000(FCC ID MSQ-RTAXJF00)	SUWI-03-14-02	NCR	NCR
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	2024/11/19	2025/11/18

CE Test System					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	2025/01/15	2026/01/14
Temperature and humidity meter*	MingGao	TH101B	SUWI-01-01-06	2025/02/13	2026/02/12
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-03	2024/05/06	2025/05/05
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-04	2024/05/06	2025/05/05
Measurement Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	NCR	NCR

*Note:The CE was tested from 2025/02/20 to 2025/02/26.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 12 of 575

9*6*6 Test Equipment					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	2023/06/03	2026/06/02
Temperature and humidity meter*	MingGao	TH101B	SUWI-01-01-05	2025/02/13	2026/02/12
Signal Analyzer	ROHDE &SCHWARZ	FSW43	SUWI-01-02-04	2024/05/08	2025/05/07
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	2024/11/21	2025/11/20
Test receiver*	ROHDE &SCHWARZ	ESR7	SUWI-01-10-01	2025/01/15	2026/01/14
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	2023/11/25	2025/11/24
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	2023/05/13	2025/05/12
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	2023/05/12	2025/05/11
Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	2023/05/13	2025/05/12
Amplifier*	Tonscend	TAP9K3G40	SUWI-01-14-01	2025/01/16	2026/01/15
Amplifier*	Tonscend	TAP01018050	SUWI-01-14-02	2025/01/16	2026/01/15
Amplifier*	Tonscend	TAP18040048	SUWI-01-14-03	2025/01/20	2026/01/19
Measurement Software	Tonscend	JS32-RE V4.0.0.0	SUWI-02-09-04	NCR	NCR

*Note:The RSE was tested from 2025/02/20 to 2025/02/26.

Remark: NCR=No Calibration Requirement.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 13 of 575

4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	±0.54dB
2	RF power density, conducted	±1.03dB
3	Spurious emissions, conducted	±0.54dB
4	Radio Frequency	1%
5	Duty Cycle	±0.37%
6	Occupied Bandwidth	1%
7	Conduction Emission	± 2.90dB (150kHz to 30MHz)
8	Radiated Emission	± 3.13dB (9k -30MHz)
		± 4.8dB (30M -1GHz)
		± 4.8dB (1GHz to 18GHz)
		± 4.80dB (Above 18GHz)
Remark: The U _{lab} (lab Uncertainty) is less than U _{CISPR/ETSI} (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 14 of 575

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15 Section 15.203
The antenna is FPC Antenna and no consideration of replacement. The best case gain of the antenna is 5150MHz to 5250MHz: 2.6dBi(Ant3); -2.51dBi(Ant2) 5250MHz to 5350MHz: 2.7dBi(Ant3); -1.72dBi(Ant2) 5470MHz to 5725MHz: 2.56dBi(Ant3); 0.97dBi(Ant2) 5725MHz to 5850MHz: 2.1dBi(Ant3); 0.92dBi(Ant2) <i>Note:</i> <i>The antenna gain are derived from the gain information report provided by the manufacturer.</i> <i>Remark:</i> <i>As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.</i>	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 15 of 575

Cyclic Delay Diversity (CDD) System:

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

If all antennas have the same gain, G_{ANT} , Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,
 $Array\ Gain = 10 \log(N_{ANT}/N_{SS} = 1) \text{ dB}$.
- For power measurements on IEEE 802.11 devices:
 $Array\ Gain = 0 \text{ dB}$ (i.e., no array gain) for $N_{ANT} \leq 4$;

For power, the directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain.

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The Power and PSD limit should be modified if the directional gain of eut is over 6dbi.

The EUT supports CDD System.

All antennas have Unequal antenna gain:

Operation Frequency	ANT Gain0 (dBi)	ANT Gain1 (dBi)	Directional gain For Power (dBi)	Directional gain For PSD (dBi)	Power Limit Reduction (dBm)	PSD Limit Reduction (dBm)
5150MHz to 5250MHz	2.6	-2.51	2.6	3.43	0	0
5250MHz to 5350MHz	2.7	-1.72	2.7	3.78	0	0
5470MHz to 5725MHz	2.56	0.97	2.56	4.81	0	0
5725MHz to 5850MHz	2.1	0.92	2.1	4.54	0	0

5150MHz to 5250MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

5250MHz to 5350MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

5470MHz to 5725MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

5725MHz to 5850MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
 Rev.: Amendment 02
 Page: 16 of 575

5.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15 Section 15.207		
Test Method:	ANSI C63.10: 2013 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Receiver Setup:	RBW = 9kHz, VBW = 30kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
 Rev.: Amendment 02
 Page: 17 of 575

Test Setup:	
Test Mode:	BT Link + WIFI 2.4G Link + WIFI 5G/6E Link
Instruments Used:	Refer to section 6 for details.
Test Results:	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105


Rev.: Amendment 02

Page: 18 of 575

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 19 of 575

Phase: Neutral




Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1770	10.19	44.97	55.16	64.63	9.47	18.58	28.77	54.63	25.86	PASS
2	0.2355	10.16	41.89	52.05	62.25	10.20	17.52	27.68	52.25	24.57	PASS
3	0.2895	10.15	37.74	47.89	60.54	12.65	15.05	25.20	50.54	25.34	PASS
4	0.3480	10.16	35.54	45.70	59.01	13.31	14.79	24.95	49.01	24.06	PASS
5	0.4605	10.16	30.80	40.96	56.68	15.72	17.39	27.55	46.68	19.13	PASS
6	0.5820	10.19	25.92	36.11	56.00	19.89	9.62	19.81	46.00	26.19	PASS


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value = Reading[dBμV] + Factor(Lisn factor[dB] + cable loss[dB]).
3. Margin = Limit[dBμV] – Value[dBμV]


5.3 Duty Cycle

Test Requirement:	ANSI C63.10 :2013 Section 12.2
Test Method:	ANSI C63.10 :2013 Section 12.2
Test Setup:	
Instruments Used:	Refer to section 6 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 3.7 for details.
Limit:	No restriction limits
Test Results:	For report purpose
The detailed test data see: Appendix	


5.4 Conducted Output Power

Test Requirement:	47 CFR Part 15 Section 15.407(a)	
Test Method:	ANSI C63.10 :2013 Section 12.3.3.2	
Test Setup:	 * Test with power meter (Detector function: Average) Method PM-G is measurement using a gated RF average power meter. Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.	
Test Instruments:	Refer to section 6 for details.	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates	
Final Test Mode:	Refer to section 3.7 for details.	
Limit:	Frequency Band	Limit
	5150-5250MHz	Not exceed 250mW(23.98dBm)
	5250-5350MHz	The lesser of 250mW(23.98dBm) or 11+ 10logB
	5470-5725MHz	The lesser of 250mW(23.98dBm) or 11+ 10logB
	5725-5850MHz	Not exceed 1W(30dBm)
	*Where B is the 26dB emission bandwidth in MHz	
Test Results:	Pass	
The detailed test data see: Appendix		


5.5 26dB Emission Bandwidth

Test Requirement:	47 CFR Part 15 Section 15.407(a), KDB 789033 D02& C
Test Method:	ANSI C63.10: 2013 Section 12.4.1
Test Setup:	
Instruments Used:	Refer to section 6 for details.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 3.7 for details.
Limit:	No restriction limits
Test Results:	For Report Purpose
The detailed test data see: Appendix	


5.6 6dB Emission Bandwidth

Test Requirement:	47 CFR Part 15 Section 15.407(e)	
Test Method:	ANSI C63.10: 2013 Section 12.4.1	
Test Setup:		
Test Instruments:	Refer to section 6 for details.	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates	
Final Test Mode:	Refer to section 3.7 for details.	
Limit:	Frequency Band	Limit
	5725-5850MHz	At least 500kHz
Test Results:	Pass	
The detailed test data see: Appendix		

5.7 99% Occupied Bandwidth

Test Requirement:	KDB 789033 D02§ D
Test Method:	ANSI C63.10: 2013 Section 12.4.2
Test Setup:	
Instruments Used:	Refer to section 6 for details.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 3.7 for details.
Limit:	No restriction limits
Test Results:	For Report Purpose
The detailed test data see: Appendix	

5.8 Power Spectral Density

Test Requirement:	47 CFR Part 15 Section 15.407(a)	
Test Method:	ANSI C63.10: 2013 Section 12.5 KDB 789033 D02 v02r01, Section F.	
Test Setup:		
Instruments Used:	Refer to section 6 for details.	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates	
Final Test Mode:	Refer to section 3.7 for details.	
Limit:	Frequency Band	Limit
	5150-5250MHz	The power spectral density less than 11dBm/1MHz
	5250-5350MHz	The power spectral density less than 11dBm/1MHz
	5470-5725MHz	The power spectral density less than 11dBm/1MHz
	5725-5850MHz	The power spectral density less than <30dBm/500KHz
Test Results:	Pass	
The detailed test data see: Appendix		

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15 Section 15.205 and 15.209
Test Method:	ANSI C63.10: 2013 Section 6.4 / 6.5 / 6.6
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)
Test frequency:	9kHz ~ 40GHz(or 10 Harmonic)

Test Setup:




Figure 1. 9kHz to 30MHz




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz test, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz test, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. (Distance from antenna to EUT is 1m for measurements >18GHz). - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the
-----------------	--



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02


Page: 27 of 575

	rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. Test the EUT in the outermost channels. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete. j. The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported k. The disturbance above 18GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. l. At a measurement distance of 1 meter the limit line was increased by $20 \times \text{LOG}(3/1) = 9.54 \text{ dB}$.
Test Configuration:	Measurements below 30MHz • RBW = 10 kHz • VBW = 30 kHz • Detector = Peak & Average & Quasi-peak • Trace mode = max hold Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq 3 \text{ MHz}$ • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10Hz, when duty cycle is no less than 98 percent. • VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Refer to section 3.7 for details. For below 1GHz part, through pre-scan all channels, but only the worst case is recorded in the report.
Instruments Used:	Refer to section 6 for details.
Test Results:	Pass
The detailed test data see: Appendix	

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15 Section 15.407(b)		
Test Method:	ANSI C63.10: 2013 Section 12.7		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:



Test Procedure:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.
- Test the EUT in the outermost channels.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 29 of 575

Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Refer to section 3.7 for details.
Instruments Used:	Refer to section 6 for details.
Test Results:	Pass
The detailed test data see: Appendix	

5.11 Dynamic Frequency Selection

5.11.1 DFS Overview

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required
Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 31 of 575

5.11.2 DFS Detection Thresholds

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz	-62 dBm
EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

5.11.3 RADAR TEST WAVEFORMS

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μ sec)	PRI (μ sec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μ sec, with a minimum increment of 1 μ sec, excluding PRI values selected in Test A	$\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 32 of 575

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

Radar Type	Number of Trials	Number of Successful Detections	Minimum Percentage of Successful Detection
1	35	29	82.9%
2	30	18	60%
3	30	27	90%
4	50	44	88%
Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$			

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 33 of 575

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 7 – Frequency Hopping Radar Test Waveform

Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30

5.11.4 Response Requirements

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel move</i> (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

The detailed test data see: **Appendix**



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 34 of 575

6 Photographs - Setup Photos

Refer to Appendix A.2 WLAN Setup Photos.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 35 of 575

7 Appendix

1. Duty Cycle

1.1 Test Result

1.1.1 ANT2

ANT2									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	2.794	2.941	95.00	0.22	0.03
802.11n (HT20)	MIMO	5180	/	/	1.321	1.468	89.99	0.46	0.06
802.11n (HT40)	MIMO	5190	/	/	1.266	1.414	89.53	0.48	0.06
802.11ac (VHT80)	MIMO	5210	/	/	0.612	0.712	85.96	0.66	0.03
802.11ax (HEW20)	MIMO	5180	SU	/	1.329	1.477	89.98	0.46	0.00
802.11ax (HEW40)	MIMO	5190	SU	/	1.269	1.418	89.49	0.48	0.03
802.11ax (HEW80)	MIMO	5210	SU	/	0.612	0.712	85.96	0.66	0.06

1.1.2 ANT3

ANT3									
Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11a	SISO	5180	/	/	2.794	2.941	95.00	0.22	0.03
802.11n (HT20)	MIMO	5180	/	/	1.323	1.469	90.06	0.45	0.03
802.11n (HT40)	MIMO	5190	/	/	1.266	1.414	89.53	0.48	0.03
802.11ac (VHT80)	MIMO	5210	/	/	0.612	0.712	85.96	0.66	0.03
802.11ax (HEW20)	MIMO	5180	SU	/	1.329	1.476	90.04	0.46	0.03
802.11ax (HEW40)	MIMO	5190	SU	/	1.268	1.417	89.48	0.48	0.04
802.11ax (HEW80)	MIMO	5210	SU	/	0.613	0.713	85.97	0.66	0.06



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 36 of 575

2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	99% Occupied Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	2	17.540	/	Pass
					3	17.974	/	Pass
		5200	/	/	2	17.534	/	Pass
					3	18.094	/	Pass
		5240	/	/	2	17.766	/	Pass
					3	17.929	/	Pass
		5260	/	/	2	17.546	/	Pass
					3	17.635	/	Pass
		5300	/	/	2	17.572	/	Pass
					3	17.598	/	Pass
		5320	/	/	2	17.589	/	Pass
					3	17.605	/	Pass
		5500	/	/	2	17.581	/	Pass
					3	17.669	/	Pass
		5580	/	/	2	17.434	/	Pass
					3	17.620	/	Pass
		5700	/	/	2	17.492	/	Pass
					3	17.535	/	Pass
		5745	/	/	2	17.504	/	Pass
					3	17.555	/	Pass
802.11n (HT20)	MIMO	5180	/	/	2	18.666	/	Pass
					3	18.799	/	Pass
		5200	/	/	2	18.692	/	Pass
					3	18.725	/	Pass
		5240	/	/	2	18.727	/	Pass
					3	18.828	/	Pass
		5260	/	/	2	18.319	/	Pass
					3	18.745	/	Pass
		5300	/	/	2	18.370	/	Pass
					3	18.685	/	Pass
		5320	/	/	2	18.376	/	Pass
					3	18.805	/	Pass
		5500	/	/	2	18.411	/	Pass
					3	18.796	/	Pass
		5580	/	/	2	18.653	/	Pass
					3	18.598	/	Pass
		5700	/	/	2	18.688	/	Pass
					3	18.703	/	Pass
		5745	/	/	2	18.663	/	Pass
					3	18.750	/	Pass
		5785	/	/	2	18.674	/	Pass
					3	18.620	/	Pass
		5825	/	/	2	18.662	/	Pass
					3	18.720	/	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 37 of 575

802.11n (HT40)	MIMO	5190	/	/	2	36.775	/	Pass
					3	36.840	/	Pass
		5230	/	/	2	37.038	/	Pass
					3	37.188	/	Pass
		5270	/	/	2	36.862	/	Pass
					3	36.772	/	Pass
		5310	/	/	2	36.744	/	Pass
					3	36.889	/	Pass
		5510	/	/	2	36.868	/	Pass
					3	36.799	/	Pass
		5550	/	/	2	36.917	/	Pass
					3	36.819	/	Pass
802.11ac (VHT80)	MIMO	5670	/	/	2	36.884	/	Pass
					3	36.841	/	Pass
		5755	/	/	2	36.913	/	Pass
					3	36.853	/	Pass
		5795	/	/	2	37.156	/	Pass
					3	37.075	/	Pass
		5210	/	/	2	75.982	/	Pass
					3	75.950	/	Pass
		5290	/	/	2	75.972	/	Pass
					3	76.043	/	Pass
802.11ax (HEW20)	MIMO	5530	/	/	2	75.885	/	Pass
					3	75.852	/	Pass
		5610	/	/	2	75.844	/	Pass
					3	75.880	/	Pass
		5775	/	/	2	75.855	/	Pass
					3	75.862	/	Pass
		5180	SU	/	2	18.773	/	Pass
					3	18.704	/	Pass
		5200	SU	/	2	18.665	/	Pass
					3	18.640	/	Pass
		5240	SU	/	2	18.732	/	Pass
					3	18.684	/	Pass
		5260	SU	/	2	18.687	/	Pass
					3	18.628	/	Pass
		5300	SU	/	2	18.665	/	Pass
					3	18.707	/	Pass
		5320	SU	/	2	18.687	/	Pass
					3	18.613	/	Pass
		5500	SU	/	2	18.646	/	Pass
					3	18.716	/	Pass
802.11ax (HEW40)	MIMO	5580	SU	/	2	18.531	/	Pass
					3	18.480	/	Pass
		5700	SU	/	2	18.546	/	Pass
					3	18.530	/	Pass
		5745	SU	/	2	18.611	/	Pass
					3	18.655	/	Pass
		5785	SU	/	2	18.482	/	Pass
					3	18.542	/	Pass
		5825	SU	/	2	18.603	/	Pass
					3	18.528	/	Pass
		5190	SU	/	2	36.554	/	Pass
					3	36.574	/	Pass
		5230	SU	/	2	36.692	/	Pass
					3	36.667	/	Pass
802.11ax (HEW20)	MIMO	5270	SU	/	2	36.473	/	Pass
					3	36.514	/	Pass
		5310	SU	/	2	36.653	/	Pass
					3	36.615	/	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 38 of 575

		5510	SU	/	2	36.579	/	Pass
					3	36.515	/	Pass
		5550	SU	/	2	36.489	/	Pass
					3	36.533	/	Pass
		5670	SU	/	2	36.516	/	Pass
					3	36.635	/	Pass
		5755	SU	/	2	36.483	/	Pass
					3	36.531	/	Pass
		5795	SU	/	2	36.542	/	Pass
					3	36.490	/	Pass
802.11ax (HEW80)	MIMO	5210	SU	/	2	75.903	/	Pass
					3	75.898	/	Pass
		5290	SU	/	2	75.840	/	Pass
					3	75.807	/	Pass
		5530	SU	/	2	75.763	/	Pass
					3	75.712	/	Pass
		5610	SU	/	2	75.811	/	Pass
					3	75.748	/	Pass
		5775	SU	/	2	75.723	/	Pass
					3	75.707	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5745	/	/	2	15.235	>=0.5	Pass
					3	15.230	>=0.5	Pass
		5785	/	/	2	15.227	>=0.5	Pass
					3	15.226	>=0.5	Pass
		5825	/	/	2	15.230	>=0.5	Pass
					3	15.231	>=0.5	Pass
802.11n (HT20)	MIMO	5745	/	/	2	15.241	>=0.5	Pass
					3	15.241	>=0.5	Pass
		5785	/	/	2	15.235	>=0.5	Pass
					3	15.240	>=0.5	Pass
		5825	/	/	2	15.244	>=0.5	Pass
					3	15.245	>=0.5	Pass
802.11n (HT40)	MIMO	5755	/	/	2	35.244	>=0.5	Pass
					3	35.250	>=0.5	Pass
		5795	/	/	2	35.227	>=0.5	Pass
					3	35.230	>=0.5	Pass
802.11ac (VHT80)	MIMO	5775	/	/	2	75.246	>=0.5	Pass
					3	75.247	>=0.5	Pass
802.11ax (HEW20)	MIMO	5745	SU	/	2	15.259	>=0.5	Pass
					3	15.258	>=0.5	Pass
		5785	SU	/	2	15.251	>=0.5	Pass
					3	15.252	>=0.5	Pass
		5825	SU	/	2	15.261	>=0.5	Pass
					3	15.259	>=0.5	Pass
802.11ax (HEW40)	MIMO	5755	SU	/	2	35.261	>=0.5	Pass
					3	35.259	>=0.5	Pass
		5795	SU	/	2	35.250	>=0.5	Pass
					3	35.248	>=0.5	Pass
802.11ax (HEW80)	MIMO	5775	SU	/	2	75.247	>=0.5	Pass
					3	75.248	>=0.5	Pass

2.1.3 26dB BW



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 39 of 575

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	26dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11a	SISO	5180	/	/	2	20.967	/	Pass
					3	26.107	/	Pass
		5200	/	/	2	20.957	/	Pass
					3	32.685	/	Pass
		5240	/	/	2	21.299	/	Pass
					3	25.964	/	Pass
		5260	/	/	2	21.102	/	Pass
					3	21.359	/	Pass
		5300	/	/	2	20.972	/	Pass
					3	21.265	/	Pass
		5320	/	/	2	21.176	/	Pass
					3	21.326	/	Pass
		5500	/	/	2	21.340	/	Pass
					3	21.341	/	Pass
		5580	/	/	2	21.122	/	Pass
					3	21.159	/	Pass
802.11n (HT20)	MIMO	5180	/	/	2	32.722	/	Pass
					3	26.174	/	Pass
		5200	/	/	2	30.356	/	Pass
					3	26.010	/	Pass
		5240	/	/	2	30.299	/	Pass
					3	26.384	/	Pass
		5260	/	/	2	26.360	/	Pass
					3	21.878	/	Pass
		5300	/	/	2	25.896	/	Pass
					3	22.851	/	Pass
		5320	/	/	2	26.962	/	Pass
					3	25.914	/	Pass
		5500	/	/	2	30.229	/	Pass
					3	26.412	/	Pass
		5580	/	/	2	21.078	/	Pass
					3	21.474	/	Pass
802.11n (HT40)	MIMO	5190	/	/	2	68.913	/	Pass
					3	45.247	/	Pass
		5230	/	/	2	57.922	/	Pass
					3	62.778	/	Pass
		5270	/	/	2	62.807	/	Pass
					3	70.140	/	Pass
		5310	/	/	2	53.714	/	Pass
					3	53.568	/	Pass
		5510	/	/	2	43.512	/	Pass
					3	44.567	/	Pass
		5550	/	/	2	40.568	/	Pass
					3	44.345	/	Pass
802.11ac (VHT80)	MIMO	5670	/	/	2	44.492	/	Pass
					3	41.230	/	Pass
		5210	/	/	2	87.794	/	Pass
					3	81.579	/	Pass
		5290	/	/	2	86.155	/	Pass
					3	83.100	/	Pass
		5530	/	/	2	86.736	/	Pass
					3	93.684	/	Pass
		5610	/	/	2	80.979	/	Pass
					3	81.738	/	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105

Rev.: Amendment 02

Page: 40 of 575

802.11ax (HEW20)	MIMO	5180	SU	/	2	21.841	/	Pass
					3	22.173	/	Pass
		5200	SU	/	2	21.846	/	Pass
					3	21.859	/	Pass
		5240	SU	/	2	21.892	/	Pass
					3	21.608	/	Pass
		5260	SU	/	2	21.453	/	Pass
					3	21.260	/	Pass
		5300	SU	/	2	21.417	/	Pass
					3	21.427	/	Pass
		5320	SU	/	2	21.606	/	Pass
					3	21.573	/	Pass
802.11ax (HEW40)	MIMO	5500	SU	/	2	21.357	/	Pass
					3	21.578	/	Pass
		5580	SU	/	2	21.164	/	Pass
					3	21.262	/	Pass
		5700	SU	/	2	21.401	/	Pass
					3	21.176	/	Pass
		5190	SU	/	2	39.952	/	Pass
					3	40.129	/	Pass
		5230	SU	/	2	40.082	/	Pass
					3	39.834	/	Pass
		5270	SU	/	2	39.750	/	Pass
					3	39.993	/	Pass
802.11ax (HEW80)	MIMO	5310	SU	/	2	40.057	/	Pass
					3	45.136	/	Pass
		5510	SU	/	2	39.894	/	Pass
					3	39.720	/	Pass
		5550	SU	/	2	39.692	/	Pass
					3	39.791	/	Pass
		5670	SU	/	2	39.660	/	Pass
					3	39.779	/	Pass
		5210	SU	/	2	86.981	/	Pass
					3	80.954	/	Pass
		5290	SU	/	2	81.270	/	Pass
					3	81.511	/	Pass
		5530	SU	/	2	81.267	/	Pass
					3	81.215	/	Pass
		5610	SU	/	2	81.540	/	Pass
					3	81.360	/	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 41 of 575

2.2 Test Graph


2.2.1 OBW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 42 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 43 of 575







SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 44 of 575

802.11a_LCH_5260MHz_ANT2_NTNV




802.11a_LCH_5260MHz_ANT3_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 45 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 46 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 47 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 48 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 49 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 50 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 51 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 52 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 53 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 54 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 55 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 56 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 57 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 58 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 59 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 60 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 61 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 62 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 63 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 64 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 65 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 66 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 67 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 68 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 69 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 70 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 71 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 72 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 73 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 74 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 75 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 76 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 77 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 78 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 79 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 80 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 81 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 82 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 83 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 84 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 85 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 86 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 87 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 88 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 89 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 90 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 91 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 92 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 93 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 94 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 95 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 96 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 97 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 98 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 99 of 575




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
 Rev.: Amendment 02
 Page: 100 of 575

802.11ax(HEW80)_MCH_5210MHz_SU_/_ANT2_NTNV




802.11ax(HEW80)_MCH_5210MHz_SU_/_ANT3_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 101 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 102 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 103 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 104 of 575






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 105 of 575


2.2.2 6dB BW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 106 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 107 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 108 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 109 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 110 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 111 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 112 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 113 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 114 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 115 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 116 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 117 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 118 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 119 of 575






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 120 of 575


2.2.3 26dB BW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 121 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 122 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 123 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 124 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 125 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 126 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 127 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 128 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 129 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 130 of 575






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 131 of 575



802.11n(HT20)_LCH_5260MHz_ANT2_NTNV




802.11n(HT20)_LCH_5260MHz_ANT3_NTNV






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 133 of 575



802.11n(HT20)_HCH_5320MHz_ANT2_NTNV




802.11n(HT20)_HCH_5320MHz_ANT3_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 135 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 136 of 575




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
 Rev.: Amendment 02
 Page: 137 of 575

802.11n(HT20)_HCH_5700MHz_ANT2_NTNV




802.11n(HT20)_HCH_5700MHz_ANT3_NTNV





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 138 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 139 of 575





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002105
Rev.: Amendment 02
Page: 140 of 575

