

Band: PCS1900								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	1850.2	28.91	1.2	30.11	<=33.00	Pass
			1880	29.31	1.2	30.51	<=33.00	Pass
			1909.8	29.35	1.2	30.55	<=33.00	Pass
	EGPRS	1 TX Slot	1850.2	23.74	1.2	24.94	<=33.00	Pass
		2 TX Slots	1850.2	21.05	1.2	22.25	<=33.00	Pass
		3 TX Slots	1850.2	19.03	1.2	20.23	<=33.00	Pass
		4 TX Slots	1850.2	17.69	1.2	18.89	<=33.00	Pass
		1 TX Slot	1880	25.68	1.2	26.88	<=33.00	Pass
		2 TX Slots	1880	21.47	1.2	22.67	<=33.00	Pass
		3 TX Slots	1880	19.55	1.2	20.75	<=33.00	Pass
		4 TX Slots	1880	18.56	1.2	19.76	<=33.00	Pass
		1 TX Slot	1909.8	23.59	1.2	24.79	<=33.00	Pass
		2 TX Slots	1909.8	21.11	1.2	22.31	<=33.00	Pass
		3 TX Slots	1909.8	19.09	1.2	20.29	<=33.00	Pass
		4 TX Slots	1909.8	17.91	1.2	19.11	<=33.00	Pass
Note1: EIRP=Conducted Power+Antenna Gain								