

Band: PCS1900								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	GSM	GSM	1850.2	28.91	2.67	31.58	<=33.00	Pass
			1880	29.31	2.67	31.98	<=33.00	Pass
			1909.8	29.35	2.67	32.02	<=33.00	Pass
	EGPRS	1 TX Slot	1850.2	23.74	2.67	26.41	<=33.00	Pass
		2 TX Slots	1850.2	21.05	2.67	23.72	<=33.00	Pass
		3 TX Slots	1850.2	19.03	2.67	21.7	<=33.00	Pass
		4 TX Slots	1850.2	17.69	2.67	20.36	<=33.00	Pass
		1 TX Slot	1880	25.68	2.67	28.35	<=33.00	Pass
		2 TX Slots	1880	21.47	2.67	24.14	<=33.00	Pass
		3 TX Slots	1880	19.55	2.67	22.22	<=33.00	Pass
		4 TX Slots	1880	18.56	2.67	21.23	<=33.00	Pass
		1 TX Slot	1909.8	23.59	2.67	26.26	<=33.00	Pass
		2 TX Slots	1909.8	21.11	2.67	23.78	<=33.00	Pass
		3 TX Slots	1909.8	19.09	2.67	21.76	<=33.00	Pass
		4 TX Slots	1909.8	17.91	2.67	20.58	<=33.00	Pass
Note1: EIRP=Conducted Power+Antenna Gain								