



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 1 of 80

TEST REPORT

Application No.: SUCR2501000024IT
Applicant: Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer: Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer: Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
EUT Description: Wireless Data Terminal
Model No.: TF31A
Trade Mark: SUNMI
FCC ID: 2AH25M3W
Standards: FCC 47 CFR Part 2, Subpart J
FCC 47 CFR Part 15, Subpart C
Date of Receipt: January 9, 2025
Date of Test: January 20, 2025 to March 14, 2025
Date of Issue: May 27, 2025

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.
Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Wireless Laboratory

South of No. 6 Plant, No. 1, RunSheng Road, Suzhou Industrial Park,
Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000

t (86-512) 6229 2980
www.sgsgroup.com.cn



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 2 of 80

Version

Revision Record			
Version	Description	Date	Remark
00	Original	May 27, 2025	/

Authorized for issue by:				
Tested By				
		Hayley ZhangProject Manager		
Approved By				
		Cloud Peng/Technical Manager		



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 3 of 80

Contents

Version	2
1 Test Summary	4
2 General Information	5
2.1 Details of Client	5
2.2 Test Location	5
2.3 Test Facility	5
2.4 General Description of EUT	6
2.5 Test Environment	8
2.6 Description of Support Units	8
3 Equipment List	9
4 Measurement Uncertainty (95% confidence levels, k=2)	11
5 Test results and Measurement Data	12
5.1 Antenna Requirement	12
5.2 AC Power Line Conducted Emissions	13
5.3 Duty Cycle	17
5.4 Conducted Output Power	18
5.5 DTS (6 dB) Bandwidth & 99% Occupied Bandwidth	19
5.6 Power Spectral Density	20
5.7 Band-edge for RF Conducted Emissions	21
5.8 RF Conducted Spurious Emissions	22
5.9 Radiated Spurious Emissions	23
5.10 Restricted bands around fundamental frequency	26
6 Photographs - Setup Photos	28
7 Appendix	29



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 4 of 80

1 Test Summary

Test Item	FCC Rule No.	Test Method	Test Result	Result
Antenna Requirement	15.203/15.247(b)	--	Clause 3.1	PASS
AC Power Line Conducted Emission	15.207	ANSI C63.10 2013 Section 6.2	Clause 3.2	PASS
Duty cycle	--	ANSI C63.10 2013 Section 11.6	Clause 3.3	For Report Purpose
Conducted Output Power	15.247 (b)(3)	ANSI C63.10 2013 Section 11.9.1.3	Clause 3.4	PASS
DTS (6 dB) Bandwidth & 99% Occupied Bandwidth	15.247 (a)(2)	ANSI C63.10 2013 Section 11.8 Option 2 / 6.9.3	Clause 3.5	PASS
Power Spectral Density	15.247 (e)	ANSI C63.10 2013 Section 11.10.2	Clause 3.6	PASS
Band-edge for RF Conducted Emissions	15.247(d)	ANSI C63.10 2013 Section 11.13.3	Clause 3.7	PASS
RF Conducted Spurious Emissions	15.247(d)	ANSI C63.10 2013 Section 11.11	Clause 3.8	PASS
Radiated Spurious Emissions	15.205/15.209	ANSI C63.10 2013 Section 11.12	Clause 3.9	PASS
Restricted bands around fundamental frequency (Radiated Emission)	15.205/15.209	ANSI C63.10 2013 Section 11.12	Clause 3.10	PASS



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 5 of 80

2 General Information

2.1 Details of Client

Applicant:	Shanghai Sunmi Technology Co.,Ltd.
Address of Applicant:	Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China
Manufacturer:	Shanghai Sunmi Technology Co.,Ltd.
Address of Manufacturer:	Room 505,No.388,Song Hu Road,Yang Pu District,Shanghai,China

2.2 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	Ives Cheng, King-p Li

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 6 of 80

2.4 General Description of EUT

EUT Description:	Wireless Data Terminal
Model No.:	TF31A
Trade Mark:	SUNMI
Hardware Version:	V1.2
Software Version:	T602AA_EVT_14.0_SUNMI_202503131820.00-00
Power Supply:	3.87V from battery
Operation Frequency:	2400MHz~2483.5MHz fc = 2402 MHz + N * 2 MHz, where: -fc = "Operating Frequency" in MHz, -N = "Channel Number" with the range from 0 to 39.
Bluetooth version:	Bluetooth V5.3
Modulation Type:	GFSK
Number of Channel:	40
Rates Type*:	☒ Provided by client
	1M PHY 2M PHY
Antenna Type:	FPC Antenna
Antenna Gain:	-1.74dBi
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.
RF Cable:	1dB
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 7 of 80

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz
Remark:							
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:							
Channel				Frequency			
BLE 1M:							
The Lowest channel(CH0)				2402MHz			
The Middle channel(CH19)				2440MHz			
The Highest channel(CH39)				2480MHz			
BLE 2M:							
The Lowest channel(CH1)				2404MHz			
The Middle channel(CH19)				2440MHz			
The Highest channel(CH38)				2478MHz			



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 8 of 80

2.5 Test Environment

Environment Parameter	101 kPa Selected Values During Tests	
Relative Humidity	44-46 % RH Ambient	
Value	Temperature(℃)	Voltage(V)
NTNV	22~23	3.87
Remark: NV: Normal Voltage NT: Normal Temperature		

2.6 Description of Support Units

The EUT has been tested as an independent unit.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 9 of 80

3 Equipment List

RF Test Equipment					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Shielding Room	Brilliant-emc	N/A	SUWI-04-08-01	2022/11/09	2025/11/08
Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2024/02/18	2025/02/17
				2025/02/13	2026/02/12
Measurement Software	Tonscend	TST272 V2.0	SUWI-03-55-03	NCR	NCR
Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	2024/05/08	2025/05/07
Temperature Chamber	ESPEC	SU-242	SUWI-01-13-02	2024/05/09	2025/05/08
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-05	2024/02/04	2025/02/03
				2025/01/21	2026/01/20
DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	2024/02/04	2025/02/03
				2025/01/15	2026/01/14
Power meter	Anritsu	ML2495A	SUWI-01-31-01	2024/11/19	2025/11/18
Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	2024/11/19	2025/11/18
MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	2024/02/04	2025/02/03
				2025/01/15	2026/01/14
Router	ASUS	GT-AXE11000(FCC ID MSQ-RTAXJF00)	SUWI-03-14-02	NCR	NCR
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	2024/11/19	2025/11/18

CE Test System					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	2025/01/15	2026/01/14
Temperature and humidity meter*	MingGao	TH101B	SUWI-01-01-06	2025/02/13	2026/02/12
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-03	2024/05/06	2025/05/05
Artificial network	ROHDE&SCHWARZ	ENV216	SUWI-01-19-04	2024/05/06	2025/05/05
Measurement Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	NCR	NCR

*Note:The CE was tested from 2025/03/02 to 2025/03/10.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 10 of 80

RSE Test Equipment					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal.Due date (yyyy/mm/dd)
Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	2023/06/03	2026/06/02
Temperature and humidity meter*	MingGao	TH101B	SUWI-01-01-05	2025/02/13	2026/02/12
Signal Analyzer	ROHDE &SCHWARZ	FSW43	SUWI-01-02-04	2024/05/08	2025/05/07
Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-07	2024/11/21	2025/11/20
Test receiver*	ROHDE &SCHWARZ	ESR7	SUWI-01-10-01	2025/01/15	2026/01/14
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	2023/11/25	2025/11/24
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	2023/05/13	2025/05/12
Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	2023/05/12	2025/05/11
Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	2023/05/13	2025/05/12
Amplifier*	Tonscend	TAP9K3G40	SUWI-01-14-01	2025/01/16	2026/01/15
Amplifier*	Tonscend	TAP01018050	SUWI-01-14-02	2025/01/16	2026/01/15
Amplifier*	Tonscend	TAP18040048	SUWI-01-14-03	2025/01/20	2026/01/19
Measurement Software	Tonscend	JS32-RE V4.0.0.0	SUWI-02-09-04	NCR	NCR

*Note:The RSE was tested from 2025/03/02 to 2025/03/10.

Remark: NCR=No Calibration Requirement.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 11 of 80

4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	$\pm 0.54\text{dB}$
2	RF power density, conducted	$\pm 1.03\text{dB}$
3	Spurious emissions, conducted	$\pm 0.54\text{dB}$
4	Radio Frequency	1%
5	Duty Cycle	$\pm 0.37\%$
6	Occupied Bandwidth	1%
7	Conduction Emission	$\pm 2.90\text{dB}$ (150kHz to 30MHz)
8	Radiated Emission	$\pm 3.13\text{dB}$ (9k -30MHz)
		$\pm 4.8\text{dB}$ (30M -1GHz)
		$\pm 4.8\text{dB}$ (1GHz to 18GHz)
		$\pm 4.80\text{dB}$ (Above 18GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 12 of 80

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(b)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
The antenna is FPC Antenna and no consideration of replacement. The best case gain of the antenna is -1.74dBi. <i>Note:</i> <i>The antenna gain are derived from the gain information report provided by the manufacturer.</i> <i>Remark:</i> <i>As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.</i>	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01


Page: 13 of 80

5.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Receiver Setup:	RBW = 9kHz, VBW = 30kHz		
Limit:	Frequency range(MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
 Rev.: 01
 Page: 14 of 80

Test Setup:	
Test Mode:	BT Link + WIFI 2.4G Link + WIFI 5G/6E Link
Instruments Used:	Refer to section 6 for details.
Test Results:	Pass



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402


Rev.: 01

Page: 15 of 80

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 16 of 80

Phase: Neutral




Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1770	10.19	43.48	53.67	64.63	10.96	20.32	30.51	54.63	24.12	PASS
2	0.1860	10.19	42.80	52.99	64.21	11.22	22.64	32.83	54.21	21.38	PASS
3	0.2985	10.15	35.27	45.42	60.28	14.86	18.84	28.99	50.28	21.29	PASS
4	0.4110	10.16	29.54	39.70	57.63	17.93	12.50	22.66	47.63	24.97	PASS
5	0.4200	10.16	29.02	39.18	57.45	18.27	12.34	22.50	47.45	24.95	PASS
6	0.5505	10.18	24.87	35.05	56.00	20.95	9.80	19.98	46.00	26.02	PASS


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value = Reading[dBμV] + Factor(Lisn factor[dB] + cable loss[dB]).
3. Margin = Limit[dBμV] – Value[dBμV]


5.3 Duty Cycle

Test Requirement:	ANSI C63.10 :2013 Section 11.6
Test Method:	ANSI C63.10 :2013 Section 11.6
Test Setup:	
Instruments Used:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	No restriction limits
Test Results:	For Report Purpose
The detailed test data see: Appendix	


5.4 Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 :2013 Section 11.9.1.3
Test Setup:	 * Test with power meter (Detector function: Peak)
Test Instruments:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	30dBm
Test Results:	Pass
The detailed test data see: Appendix	


5.5 DTS (6 dB) Bandwidth & 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10: 2013 Section 11.8 Option 2 / 6.9.3
Test Setup:	
Instruments Used:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	≥ 500 kHz for DTS Bandwidth
Test Results:	Pass
The detailed test data see: Appendix	


5.6 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 :2013 Section 11.10.2
Test Setup:	
Test Instruments:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	$\leq 8.00\text{dBm}/3\text{kHz}$
Test Results:	Pass
The detailed test data see: Appendix	

5.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.13.3
Test Setup:	
Instruments Used:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass
The detailed test data see: Appendix	

5.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	
Instruments Used:	Refer to section 6 for details
Test Mode:	Transmitting with GFSK modulation.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass
The detailed test data see: Appendix	

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 :2013 Section 11.12				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Test Frequency:	9kHz ~ 25GHz				
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Distance from antenna to EUT is 1m for measurements >18GHz). - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Test the EUT in the lowest channel, the middle channel, the Highest channel. - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete. - The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported - The disturbance above 18GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. - At a measurement distance of 1 meter the limit line was increased by $20 \cdot \text{LOG}(3/1) = 9.54 \text{ dB}$.
Test Configuration:	Measurements below 30MHz • RBW = 10 kHz • VBW = 30 kHz • Detector = Peak & Average & Quasi-peak • Trace mode = max hold Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 25 of 80

	• Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with GFSK modulation. Charge + Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Charge + Transmitting mode, For below 1GHz part, through pre-scan all channels, but only the worst case is recorded in the report.
Instruments Used:	Refer to section 6 for details
Test Results:	Pass
The detailed test data see: Appendix	

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel
-----------------	--



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 27 of 80

	h. Test the EUT in the lowest channel , the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case. j. Repeat above procedures until all frequencies measured was complete.
Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10 Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with GFSK modulation. Charge + Transmitting mode.
Final Test Mode:	Transmitting with GFSK modulation. Pretest the EUT at Charge + Transmitting mode. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 6 for details
Test Results:	Pass
The detailed test data see: Appendix	



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 28 of 80

6 Photographs - Setup Photos

Refer to Appendix A.2 WLAN Setup Photos.



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 29 of 80

7 Appendix

1. Duty Cycle

1.1 Test Result

1.1.1 Ant2

Ant2							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.379	0.626	60.54	2.18	0.02
2M	SISO	2404	0.211	0.625	33.76	4.72	0.05



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 30 of 80

2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	2	1.036	/	Pass
		2440	2	1.036	/	Pass
		2480	2	1.039	/	Pass
2M	SISO	2404	2	2.076	/	Pass
		2440	2	2.079	/	Pass
		2478	2	2.080	/	Pass

2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	2	0.688	≥ 0.5	Pass
		2440	2	0.688	≥ 0.5	Pass
		2480	2	0.689	≥ 0.5	Pass
2M	SISO	2404	2	1.374	≥ 0.5	Pass
		2440	2	1.361	≥ 0.5	Pass
		2478	2	1.367	≥ 0.5	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 31 of 80

2.2 Test Graph


2.2.1 OBW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 32 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 33 of 80






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 34 of 80


2.2.2 6dB BW





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 35 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 36 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 37 of 80

3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT2	Limit	
1M	SISO	2402	11.05	<=30	Pass
		2440	12.24	<=30	Pass
		2480	10.27	<=30	Pass
2M	SISO	2404	12.18	<=30	Pass
		2440	12.08	<=30	Pass
		2478	11.09	<=30	Pass
Note1: Antenna Gain: Ant2: -1.74dBi;					



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 38 of 80

4. Maximum Power Spectral Density

4.1 Test Result

4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT2	Limit	
1M	SISO	2402	-5.14	<=8	Pass
		2440	-3.86	<=8	Pass
		2480	-5.84	<=8	Pass
2M	SISO	2404	-7.31	<=8	Pass
		2440	-6.28	<=8	Pass
		2478	-8.44	<=8	Pass




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 39 of 80

4.2 Test Graph


4.2.1 PSD





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 40 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 41 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 42 of 80

5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	2	9.07
		2440	2	10.27
		2480	2	9.22
2M	SISO	2404	2	8.34
		2440	2	10.40
		2478	2	8.27

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.

5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	2	10.27	-9.73	Pass
		2440	2	10.27	-9.73	Pass
		2480	2	10.27	-9.73	Pass
2M	SISO	2404	2	10.40	-9.60	Pass
		2440	2	10.40	-9.60	Pass
		2478	2	10.40	-9.60	Pass

Note1: Refer to FCC Part 15.247 (d) and ANSI C63.10-2020, the channel contains the maximum PSD level was used to establish the reference level.




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 43 of 80

5.2 Test Graph


5.2.1 Ref





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 44 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 45 of 80






SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 46 of 80


5.2.2 CSE





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 47 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 48 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.


Report No.: SUCR250100002402
Rev.: 01
Page: 49 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 50 of 80





SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402


Rev.: 01

Page: 51 of 80

Radiated Spurious Emissions

Radiated emission below 1GHz

Worst case Mode: BLE 1M_Channel 39



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	42.8525	40.03	-33.81	18.79	25.00	40.00	15.00	Horizontal
2	48.43	39.32	-33.72	18.80	24.40	40.00	15.60	Horizontal
3	65.1625	40.08	-33.49	17.22	23.81	40.00	16.19	Horizontal
4	97.6575	36.24	-33.16	14.23	17.32	43.50	26.18	Horizontal
5	124.09	34.28	-32.88	17.50	18.90	43.50	24.60	Horizontal
6	195.1425	44.57	-32.29	15.39	27.67	43.50	15.83	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 52 of 80

BLE 1M_Channel 39



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	Factor [dB]	AF [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity
1	42.3675	48.28	-33.82	18.74	33.20	40.00	6.80	Vertical
2	49.1575	49.99	-33.70	18.77	35.05	40.00	4.95	Vertical
3	64.92	51.20	-33.49	17.22	34.94	40.00	5.06	Vertical
4	107.8425	40.63	-33.02	15.52	23.13	43.50	20.37	Vertical
5	121.4225	40.08	-32.90	17.24	24.42	43.50	19.08	Vertical
6	201.9325	42.27	-32.23	15.38	25.42	43.50	18.08	Vertical

Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:
Value = Reading(dBμV) + AF(dB/m) + Factor(dB):
AF = Antenna Factor(dB/m)
Factor = Cable Factor(dB) - Preamplifier gain(dB)
Margin = Limit(dBμV/m) – Value(dBμV/m)
- All channels have been tested, but only the worst case data displayed in this report.




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 53 of 80

Transmitter emission Above 1GHz

BLE 1M_Channel 00




Flnal Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	4094	51.51	31.45	-42.45	40.51	74.00	33.49	Horizontal
2	5402.5	51.08	33.12	-40.89	43.31	74.00	30.69	Horizontal
3	6935	48.66	35.97	-38.35	46.29	74.00	27.71	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 54 of 80

BLE 1M_Channel 00




Final Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	4251	49.72	31.70	-42.09	39.33	74.00	34.67	Vertical
2	6295	49.93	35.39	-39.55	45.77	74.00	28.23	Vertical
3	10662.5	42.52	38.23	-30.86	49.89	74.00	24.11	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 55 of 80

BLE 1M_Channel 19




Final Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	4992	50.40	33.18	-41.45	42.13	74.00	31.87	Horizontal
2	6215.5	49.87	35.23	-39.59	45.51	74.00	28.49	Horizontal
3	7794	48.07	36.89	-36.80	48.16	74.00	25.84	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 56 of 80

BLE 1M_Channel 19




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4857	51.37	32.89	-41.33	42.93	74.00	31.07	Vertical
2	6313.5	49.23	35.43	-39.50	45.16	74.00	28.84	Vertical
3	7707	48.85	36.81	-37.30	48.36	74.00	25.64	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 57 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4505	51.58	32.11	-42.02	41.67	74.00	32.33	Horizontal
2	6176	49.35	35.15	-39.68	44.83	74.00	29.17	Horizontal
3	7417.5	47.91	36.50	-37.87	46.54	74.00	27.46	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 58 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4349	50.93	31.86	-42.09	40.70	74.00	33.30	Vertical
2	5804	49.09	34.13	-40.27	42.96	74.00	31.04	Vertical
3	6941	48.64	35.98	-38.35	46.27	74.00	27.73	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 59 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4232	50.10	31.67	-42.11	39.66	74.00	34.34	Horizontal
2	5885.5	50.24	34.41	-40.19	44.46	74.00	29.54	Horizontal
3	6841.5	49.30	35.94	-38.41	46.83	74.00	27.17	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 60 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4017	50.49	31.33	-42.70	39.12	74.00	34.88	Vertical
2	5464	49.92	33.11	-40.71	42.31	74.00	31.69	Vertical
3	7286.5	48.69	36.34	-37.45	47.58	74.00	26.42	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 61 of 80

BLE 2M_Channel 19




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4565.5	49.92	32.24	-41.76	40.41	74.00	33.59	Horizontal
2	5571.5	49.99	33.34	-40.69	42.64	74.00	31.36	Horizontal
3	7184	48.15	36.22	-38.07	46.30	74.00	27.70	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 62 of 80

BLE 2M_Channel 19




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4361	50.60	31.88	-42.10	40.37	74.00	33.63	Vertical
2	5277	49.27	33.14	-40.89	41.53	74.00	32.47	Vertical
3	6929	48.59	35.97	-38.34	46.22	74.00	27.78	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 63 of 80

BLE 2M_Channel 38



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4101.5	50.88	31.46	-42.43	39.92	74.00	34.08	Horizontal
2	5374.5	51.22	33.13	-40.90	43.44	74.00	30.56	Horizontal
3	7118	47.85	36.14	-38.11	45.88	74.00	28.12	Horizontal




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 64 of 80

BLE 2M_Channel 38



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	4783	49.98	32.72	-41.50	41.20	74.00	32.80	Vertical
2	5812	48.88	34.16	-40.26	42.78	74.00	31.22	Vertical
3	7679.5	47.49	36.78	-37.42	46.85	74.00	27.15	Vertical

Remark:

- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:
Level = Reading(dBμV) + AF(dB/m) + Factor(dB):
AF = Antenna Factor(dB/m)
Factor = Cable Factor(dB) - Preamplifier gain(dB)
Margin = Limit(dBμV/m) – Level(dBμV/m)
- All channels have been tested, but only the worst case data displayed in this report.
- Both peak and average measured complies with the limit line, so test result is "PASS"




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 65 of 80

Restricted bands around fundamental frequency

BLE 1M_Channel 00




Final Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	2355.63	50.26	27.08	-23.29	54.05	74.00	19.95	Horizontal
2	2385.4	49.73	27.15	-23.31	53.57	74.00	20.43	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 66 of 80

BLE 1M_Channel 00




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2364.6	37.70	27.10	-23.30	41.51	54.00	12.49	Horizontal
2	2388.52	37.80	27.15	-23.31	41.64	54.00	12.36	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 67 of 80

BLE 1M_Channel 00




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2365.12	37.90	27.10	-23.30	41.71	54.00	12.29	Vertical
2	2388.78	37.81	27.16	-23.31	41.65	54.00	12.35	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 68 of 80

BLE 1M_Channel 00




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2364.47	50.01	27.10	-23.30	53.82	74.00	20.18	Vertical
2	2384.49	50.51	27.15	-23.31	54.35	74.00	19.65	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 69 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.92	50.97	27.36	-23.27	55.06	74.00	18.94	Horizontal
2	2486.68	50.52	27.37	-23.27	54.62	74.00	19.38	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 70 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.28	38.95	27.37	-23.27	43.05	54.00	10.95	Horizontal
2	2488.12	38.08	27.37	-23.27	42.19	54.00	11.81	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 71 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.16	38.37	27.37	-23.27	42.47	54.00	11.53	Vertical
2	2487.88	38.00	27.37	-23.27	42.11	54.00	11.89	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 72 of 80

BLE 1M_Channel 39




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.98	50.22	27.36	-23.27	54.32	74.00	19.68	Vertical
2	2487.82	50.30	27.37	-23.27	54.41	74.00	19.59	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 73 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2371.36	50.76	27.12	-23.30	54.58	74.00	19.42	Horizontal
2	2387.48	49.31	27.15	-23.31	53.15	74.00	20.85	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 74 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2371.49	37.64	27.12	-23.30	41.46	54.00	12.54	Horizontal
2	2389.69	37.67	27.16	-23.31	41.51	54.00	12.49	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 75 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2372.14	37.67	27.12	-23.30	41.49	54.00	12.51	Vertical
2	2388.78	37.68	27.16	-23.31	41.52	54.00	12.48	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 76 of 80

BLE 2M_Channel 01




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2369.02	50.11	27.11	-23.30	53.92	74.00	20.08	Vertical
2	2387.22	49.55	27.15	-23.31	53.39	74.00	20.61	Vertical



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 77 of 80

BLE 2M_Channel 38




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.76	50.94	27.37	-23.27	55.04	74.00	18.96	Horizontal
2	2487.04	50.58	27.37	-23.27	54.68	74.00	19.32	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 78 of 80

BLE 2M_Channel 38




Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2483.62	38.03	27.36	-23.27	42.12	54.00	11.88	Horizontal
2	2488.9	38.01	27.38	-23.27	42.12	54.00	11.88	Horizontal



SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402
Rev.: 01
Page: 79 of 80

BLE 2M_Channel 38



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.22	37.97	27.37	-23.27	42.07	54.00	11.93	Vertical
2	2487.46	38.07	27.37	-23.27	42.17	54.00	11.83	Vertical




SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

Report No.: SUCR250100002402

Rev.: 01

Page: 80 of 80

BLE 2M_Channel 38



Final Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	2484.34	50.12	27.37	-23.27	54.22	74.00	19.78	Vertical
2	2487.28	50.13	27.37	-23.27	54.23	74.00	19.77	Vertical

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier gain. The basic equation with a sample calculation is as follows:

Level = Reading(dBμV) + AF(dB/m) + Factor(dB):

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier gain(dB)

Margin = Limit(dBμV/m) – Level(dBμV/m)

- 2) Both peak and average measured complies with the limit line, so test result is "PASS"

---End of Report---