


FCC PART 15.247 TEST REPORT

For

Shanghai Sunmi Technology Co.,Ltd.

Room 605, Block 7, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai 200433 China

FCC ID: 2AH25NT211

Report Type: Original Report	Product Type: Thermal POS Printer
Test Engineer:	Sam Ye 
Report Number:	RKSA200109001-00B
Report Date:	2020-03-05
Reviewed By:	Oscar Ye EMC Manager 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	14
FCC §15.203 - ANTENNA REQUIREMENT.....	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	18
FACTOR & OVER LIMIT CALCULATION.....	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	25
APPLICABLE STANDARD	25
EUT SETUP	25
EMI TEST RECEIVER SETUP.....	26
TEST PROCEDURE	26
CORRECTED AMPLITUDE & MARGIN CALCULATION	26
TEST RESULTS SUMMARY	26
TEST DATA	27
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	55
APPLICABLE STANDARD	55
TEST PROCEDURE	55
TEST DATA	55
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	63
APPLICABLE STANDARD	63
TEST PROCEDURE	63
TEST DATA	64
FCC §15.247(d) – BAND EDGE.....	67

APPLICABLE STANDARD	67
TEST PROCEDURE	67
TEST DATA	67
BLE MODE LEFT SIDE	71
BLE MODE RIGHT SIDE	71
FCC §15.247(e) - POWER SPECTRAL DENSITY	72
APPLICABLE STANDARD	72
TEST PROCEDURE	72
TEST DATA	72
802.11B MODE LOW CHANNEL.....	74
802.11B MODE MIDDLE CHANNEL	74
802.11B MODE HIGH CHANNEL.....	75
802.11G MODE LOW CHANNEL.....	75
802.11G MODE MIDDLE CHANNEL	76
802.11G MODE HIGH CHANNEL.....	76
802.11N-HT20 MODE LOW CHANNEL	77
802.11N-HT20 MODE MIDDLE CHANNEL.....	77
802.11N-HT20 MODE HIGH CHANNEL	78
BLE MODE LOW CHANNEL	78
BLE MODE MIDDLE CHANNEL.....	79
BLE MODE HIGH CHANNEL	79

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Shanghai Sunmi Technology Co.,Ltd.
Tested Model	NT211
Product Type	Thermal POS Printer
Power Supply	AC 100-240V
RF Function	2.4G Wi-Fi, BLE(1Mbps)
Operating Band/Frequency	2.4G Wi-Fi: 2412-2462MHz BLE(1Mbps): 2402-2480MHz
Channel Number	2.4G Wi-Fi: 11, BLE(1Mbps): 40
Channel Separation	2.4G Wi-Fi: 5MHz, BLE(1Mbps): 2MHz
Modulation Type	BLE(1Mbps): GFSK; Wi-Fi: OFDM,DSSS
Antenna Type	Wi-Fi/BLE: PCB Antenna
Maximum Antenna Gain	Wi-Fi/BLE: 2.42dBi

**All measurement and test data in this report was gathered from production sample serial number: 20200109001.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-01-09)*

Objective

This report is prepared on behalf of *Shanghai Sunmi Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS Submittal with FCC ID: 2AH25NT211
FCC Part 15.22H24E PCB Submittal with FCC ID: 2AH25NT211

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

Equipment Modifications


No modification was made to the EUT tested.

EUT Exercise Software


RF test tool: SecureCRT.exe

Pre-scan with all the data rates, and the worst case was performed as below:


Mode	Data Rate	Power Level
802.11b	1 Mbps	Default
802.11g	6 Mbps	Default
802.11n-HT20	MCS0	Default
BLE	1Mbps	Default

Duty Cycle:**802.11b Mode Middle Channel**


802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



BLE Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	98.61	1.423	0.70	0.06
802.11n-HT20	98.96	1.327	0.75	0.05
BLE	68.32	0.427	2.34	1.65

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Cash Box	/	/
DELL	Notebook	GX620	D65874152

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	EUT	LISN/AC source
RJ12 Cable	3.0	EUT	Cash Box
Type-C Cable	1.0	EUT	Notebook

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-11-30	2020-11-29
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2019-12-26	2022-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-08-27	2020-08-26
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems, inc	Amplifier	2641-1	491	2019-02-20	2020-02-19
A.H.Systems, inc	Amplifier	2641-1	491	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2019-03-22	2020-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-11-30	2020-11-29
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Sunmi	RF Cable	Sunmi 01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	/	/
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data (worst case):

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi	2412-2462	2.42	1.75	23.50	223.87	20	0.0779	1.00
BLE	2402-2480	2.42	1.75	8.50	7.08	20	0.0025	1.00
Bluetooth	2402-2480	2.42	1.75	10.00	10.00	20	0.0035	1.00

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
GPRS 850	824.2-848.8	1.82	1.52	26.00	398.11	20	0.1204	0.55
GPRS 1900	1850.2-1909.8	1.82	1.52	22.24	167.49	20	0.0507	1.00

Note 1:

GPRS 850: Tune-up maximum output power with 4 slots is 29.00 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 26.00dBm.

GPRS 1900: Tune-up maximum output power with 3 slots is 26.50 dBm, so the tune-up time based Ave. power compared to slotted Ave. power is 22.24 dBm.

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Time based Ave. power compared to slotted Ave. power	-9 dB	-6 dB	-4.26 dB	-3 dB

Note 2:

Wi-Fi and BT/BLE cannot transmit simultaneously.

Wi-Fi & GPRS or BT/BLE & GPRS can transmit simultaneously; the worst condition is Wi-Fi & GPRS 850 as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0779/1.00 + 0.1204/0.55 = 0.2968 < 1.0$$

Conclusion: The device meets MPE at distance 20cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PCB antenna for Wi-Fi and Bluetooth, and the antenna gain is 2.42 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data**Environmental Conditions**

Temperature:	20.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Sam Ye on 2020-02-25.


Test Result: Compliant.

For Wi-Fi Mode:*EUT operation mode: Transmitting in 802.11g mode low channel (worst case)***AC 120V/60 Hz, Line**

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	9.80	19.82	29.62	56.00	-26.38	Average
2	0.150	31.80	19.82	51.62	66.00	-14.38	QP
3	0.391	3.10	19.75	22.85	48.03	-25.18	Average
4	0.391	12.30	19.75	32.05	58.03	-25.98	QP
5	0.579	9.30	19.75	29.05	46.00	-16.95	Average
6	0.579	14.50	19.75	34.25	56.00	-21.75	QP
7	1.734	13.70	19.84	33.54	46.00	-12.46	Average
8	1.734	15.10	19.84	34.94	56.00	-21.06	QP
9	2.900	10.50	19.46	29.96	46.00	-16.04	Average
10	2.900	16.50	19.46	35.96	56.00	-20.04	QP
11	4.070	16.40	19.47	35.87	46.00	-10.13	Average
12	4.070	18.20	19.47	37.67	56.00	-18.33	QP

AC 120V/60 Hz, Neutral

Date: 2020-02-25




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	10.00	19.82	29.82	56.00	-26.18	Average
2	0.150	32.30	19.82	52.12	66.00	-13.88	QP
3	0.205	4.00	19.82	23.82	53.40	-29.58	Average
4	0.205	23.70	19.82	43.52	63.40	-19.88	QP
5	0.546	14.20	19.75	33.95	46.00	-12.05	Average
6	0.546	17.10	19.75	36.85	56.00	-19.15	QP
7	1.645	13.90	19.84	33.74	46.00	-12.26	Average
8	1.645	16.80	19.84	36.64	56.00	-19.36	QP
9	2.765	13.30	19.47	32.77	46.00	-13.23	Average
10	2.765	17.70	19.47	37.17	56.00	-18.83	QP
11	3.840	13.80	19.47	33.27	46.00	-12.73	Average
12	3.840	17.40	19.47	36.87	56.00	-19.13	QP

Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)


2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

For BLE Mode:*EUT operation mode: Transmitting in high channel (worst case)***AC 120V/60 Hz, Line**

	Freq	Read		Limit	Over	
	MHz	Level	Factor	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.152	3.00	19.82	22.82	55.91	-33.09 Average
2	0.152	26.50	19.82	46.32	65.91	-19.59 QP
3	0.215	-2.20	19.82	17.62	53.01	-35.39 Average
4	0.215	17.60	19.82	37.42	63.01	-25.59 QP
5	0.585	15.60	19.75	35.35	46.00	-10.65 Average
6	0.585	16.10	19.75	35.85	56.00	-20.15 QP
7	1.744	17.80	19.84	37.64	46.00	-8.36 Average
8	1.744	18.90	19.84	38.74	56.00	-17.26 QP
9	2.915	18.70	19.46	38.16	46.00	-7.84 Average
10	2.915	19.20	19.46	38.66	56.00	-17.34 QP
11	4.092	16.90	19.47	36.37	46.00	-9.63 Average
12	4.092	18.60	19.47	38.07	56.00	-17.93 QP

AC 120V/60 Hz, Neutral

Date: 2020-02-25



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.156	1.90	19.82	21.72	55.65	-33.93	Average
2	0.156	25.60	19.82	45.42	65.65	-20.23	QP
3	0.201	-1.90	19.82	17.92	53.58	-35.66	Average
4	0.201	18.30	19.82	38.12	63.58	-25.46	QP
5	0.570	17.10	19.75	36.85	46.00	-9.15	Average
6	0.570	17.50	19.75	37.25	56.00	-18.75	QP
7	1.716	15.80	19.84	35.64	46.00	-10.36	Average
8	1.716	17.00	19.84	36.84	56.00	-19.16	QP
9	2.854	18.09	19.47	37.56	46.00	-8.44	Average
10	2.854	18.59	19.47	38.06	56.00	-17.94	QP
11	3.985	17.20	19.47	36.67	46.00	-9.33	Average
12	3.985	18.10	19.47	37.57	56.00	-18.43	QP

Note:


1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

Transmitting simultaneously test:

(The worst case **Wi-Fi 802.11g mode low channel** and **GPRS 850 middle channel** transmitting simultaneously was recorded)


AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	2.70	19.82	22.52	56.00	-33.48	Average
2	0.150	25.00	19.82	44.82	66.00	-21.18	QP
3	0.204	-0.70	19.82	19.12	53.45	-34.33	Average
4	0.204	17.40	19.82	37.22	63.45	-26.23	QP
5	0.567	17.20	19.75	36.95	46.00	-9.05	Average
6	0.567	18.10	19.75	37.85	56.00	-18.15	QP
7	1.707	18.60	19.84	38.44	46.00	-7.56	Average
8	1.707	19.10	19.84	38.94	56.00	-17.06	QP
9	2.839	18.49	19.47	37.96	46.00	-8.04	Average
10	2.839	19.29	19.47	38.76	56.00	-17.24	QP
11	5.112	16.30	19.49	35.79	50.00	-14.21	Average
12	5.112	18.10	19.49	37.59	60.00	-22.41	QP

AC 120V/60 Hz, Neutral

Date: 2020-02-25





	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	1.80	19.82	21.62	56.00	-34.38	Average
2	0.150	25.00	19.82	44.82	66.00	-21.18	QP
3	0.194	-3.20	19.82	16.62	53.84	-37.22	Average
4	0.194	18.50	19.82	38.32	63.84	-25.52	QP
5	0.567	17.00	19.75	36.75	46.00	-9.25	Average
6	0.567	17.80	19.75	37.55	56.00	-18.45	QP
7	1.707	18.10	19.84	37.94	46.00	-8.06	Average
8	1.707	18.90	19.84	38.74	56.00	-17.26	QP
9	2.839	18.49	19.47	37.96	46.00	-8.04	Average
10	2.839	18.89	19.47	38.36	56.00	-17.64	QP
11	3.985	17.20	19.47	36.67	46.00	-9.33	Average
12	3.985	18.40	19.47	37.87	56.00	-18.13	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBUV) + Factor (dB) - Limit (dBUV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	21.1~21.5 °C
Relative Humidity:	50~52 %
ATM Pressure:	101.2~101.5 kPa

The testing was performed by Sam Ye from 2020-01-21 to 2020-03-05.


Test Result: Compliant.

EUT operation mode: Transmitting

For Wi-Fi Mode:

Spurious Emission Test:**30MHz-1GHz:**

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11g mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
35.880000	31.70	100.0	V	271.0	-7.9	40.00	8.30
83.162450	23.03	200.0	V	151.0	-17.7	40.00	16.97
200.555250	22.62	200.0	V	182.0	-12.3	43.50	20.88
288.568100	21.54	100.0	H	115.0	-10.9	46.00	24.46
336.004100	28.67	100.0	H	299.0	-9.7	46.00	17.33
893.977200	31.39	100.0	V	0.0	-0.1	46.00	14.61

1GHz-18GHz:**802.11b Mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	31.93	200.0	V	185.0	-12.3	54.00	22.07
1061.200000	36.13	---	200.0	V	185.0	-12.3	74.00	37.87
1204.000000	---	36.50	200.0	H	249.0	-11.5	54.00	17.50
1204.000000	45.36	---	200.0	H	249.0	-11.5	74.00	28.64
1596.700000	---	29.96	200.0	V	141.0	-9.6	54.00	24.04
1596.700000	38.52	---	200.0	V	141.0	-9.6	74.00	35.48
2130.500000	---	33.91	200.0	V	205.0	-7.9	54.00	20.09
2130.500000	43.53	---	200.0	V	205.0	-7.9	74.00	30.47
4824.000000	40.54	---	200.0	V	320.0	-0.5	74.00	33.46
4824.000000	---	35.34	200.0	V	320.0	-0.5	54.00	18.66
17685.500000	---	47.78	200.0	V	335.0	14.0	54.00	6.22
17685.500000	56.60	---	200.0	V	335.0	14.0	74.00	17.40

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1205.700000	---	36.54	200.0	H	249.0	-11.5	54.00	17.46
1205.700000	44.90	---	200.0	H	249.0	-11.5	74.00	29.10
1595.000000	---	30.98	200.0	V	185.0	-9.6	54.00	23.02
1595.000000	39.19	---	200.0	V	185.0	-9.6	74.00	34.81
2128.800000	---	34.44	200.0	V	200.0	-7.9	54.00	19.56
2128.800000	43.30	---	200.0	V	200.0	-7.9	74.00	30.70
4874.000000	---	34.56	150.0	H	185.0	-0.5	54.00	19.44
4874.000000	40.88	---	150.0	H	185.0	-0.5	74.00	33.12
7311.000000	---	40.09	150.0	H	296.0	6.0	54.00	13.91
7311.000000	49.01	---	150.0	H	296.0	6.0	74.00	24.99
17462.800000	56.72	---	200.0	V	287.0	14.1	74.00	17.28
17462.800000	---	48.94	200.0	V	287.0	14.1	54.00	5.06

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1205.700000	---	37.23	200.0	H	244.0	-11.5	54.00	16.77
1205.700000	44.64	---	200.0	H	244.0	-11.5	74.00	29.36
1671.500000	37.18	---	150.0	V	344.0	-9.4	74.00	36.82
1671.500000	---	29.62	150.0	V	344.0	-9.4	54.00	24.38
2130.500000	42.41	---	100.0	V	186.0	-7.9	74.00	31.59
2130.500000	---	33.20	100.0	V	186.0	-7.9	54.00	20.80
4924.000000	---	34.89	200.0	H	215.0	-0.4	54.00	19.11
4924.000000	43.19	---	200.0	H	215.0	-0.4	74.00	30.81
7386.000000	---	40.08	150.0	H	125.0	6.0	54.00	13.92
7386.000000	49.34	---	150.0	H	125.0	6.0	74.00	24.66
17456.000000	---	46.96	150.0	H	67.0	14.1	54.00	7.04
17456.000000	56.91	---	150.0	H	67.0	14.1	74.00	17.09

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	34.24	---	200.0	V	204.0	-12.3	74.00	39.76
1061.200000	---	29.29	200.0	V	204.0	-12.3	54.00	24.71
1192.100000	44.71	---	200.0	H	244.0	-11.6	74.00	29.29
1192.100000	---	36.75	200.0	H	244.0	-11.6	54.00	17.25
1685.100000	38.08	---	200.0	V	234.0	-9.3	74.00	35.92
1685.100000	---	28.85	200.0	V	234.0	-9.3	54.00	25.15
2123.700000	41.54	---	200.0	V	204.0	-7.9	74.00	32.46
2123.700000	---	31.74	200.0	V	204.0	-7.9	54.00	22.26
4824.000000	41.24	---	200.0	H	303.0	-0.5	74.00	32.76
4824.000000	---	33.13	200.0	H	303.0	-0.5	54.00	20.87
17486.600000	---	47.73	200.0	V	81.0	14.2	54.00	6.27
17486.600000	57.58	---	200.0	V	81.0	14.2	74.00	16.42

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1062.900000	---	32.40	200.0	V	176.0	-12.3	54.00	21.60
1062.900000	35.99	---	200.0	V	176.0	-12.3	74.00	38.01
1205.700000	47.21	---	200.0	H	249.0	-11.5	74.00	26.79
1205.700000	---	37.66	200.0	H	249.0	-11.5	54.00	16.34
1685.100000	---	30.41	200.0	V	336.0	-9.3	54.00	23.59
1685.100000	38.30	---	200.0	V	336.0	-9.3	74.00	35.70
2127.100000	---	34.45	200.0	V	206.0	-7.9	54.00	19.55
2127.100000	44.35	---	200.0	V	206.0	-7.9	74.00	29.65
4874.000000	---	34.23	150.0	V	204.0	-0.5	54.00	19.77
4874.000000	42.83	---	150.0	V	204.0	-0.5	74.00	31.17
17551.200000	---	47.50	200.0	H	58.0	14.2	54.00	6.50
17551.200000	57.20	---	200.0	H	58.0	14.2	74.00	16.80

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1204.000000	---	36.05	200.0	H	246.0	-11.5	54.00	17.95
1204.000000	46.07	---	200.0	H	246.0	-11.5	74.00	27.93
1685.100000	---	31.68	200.0	V	335.0	-9.3	54.00	22.32
1685.100000	38.41	---	200.0	V	335.0	-9.3	74.00	35.59
2130.500000	---	34.38	150.0	V	204.0	-7.9	54.00	19.62
2130.500000	43.05	---	150.0	V	204.0	-7.9	74.00	30.95
3577.200000	---	32.86	150.0	V	145.0	-3.3	54.00	21.14
3577.200000	43.02	---	150.0	V	145.0	-3.3	74.00	30.98
4924.000000	---	34.28	150.0	H	205.0	-0.4	54.00	19.72
4924.000000	41.76	---	150.0	H	205.0	-0.4	74.00	32.24
17524.000000	---	47.93	200.0	V	0.0	14.2	54.00	6.07
17524.000000	56.72	---	200.0	V	0.0	14.2	74.00	17.28

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	30.40	200.0	V	205.0	-12.3	54.00	23.60
1061.200000	35.39	---	200.0	V	205.0	-12.3	74.00	38.61
1193.800000	---	38.06	200.0	H	250.0	-11.6	54.00	15.94
1193.800000	45.97	---	200.0	H	250.0	-11.6	74.00	28.03
1598.400000	---	30.36	200.0	V	161.0	-9.6	54.00	23.64
1598.400000	39.37	---	200.0	V	161.0	-9.6	74.00	34.63
2128.800000	---	33.27	150.0	V	204.0	-7.9	54.00	20.73
2128.800000	43.16	---	150.0	V	204.0	-7.9	74.00	30.84
4824.000000	---	35.15	200.0	H	236.0	-0.5	54.00	18.85
4824.000000	41.07	---	200.0	H	236.0	-0.5	74.00	32.93
17452.600000	---	47.07	200.0	V	117.0	14.0	54.00	6.93
17452.600000	56.43	---	200.0	V	117.0	14.0	74.00	17.57

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	27.81	200.0	V	159.0	-12.3	54.00	26.19
1061.200000	37.75	---	200.0	V	159.0	-12.3	74.00	36.25
1192.100000	---	36.68	200.0	H	250.0	-11.6	54.00	17.32
1192.100000	45.84	---	200.0	H	250.0	-11.6	74.00	28.16
1595.000000	---	30.12	200.0	V	144.0	-9.6	54.00	23.88
1595.000000	38.38	---	200.0	V	144.0	-9.6	74.00	35.62
2123.700000	---	33.42	200.0	V	203.0	-7.9	54.00	20.58
2123.700000	41.99	---	200.0	V	203.0	-7.9	74.00	32.01
4874.000000	---	32.25	200.0	V	351.0	-0.5	54.00	21.75
4874.000000	41.75	---	200.0	V	351.0	-0.5	74.00	32.25
17563.100000	---	47.71	150.0	V	130.0	14.2	54.00	6.29
17563.100000	56.19	---	150.0	V	130.0	14.2	74.00	17.81

High Channel: 2462MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1064.600000	---	30.56	200.0	V	184.0	-12.3	54.00	23.44
1064.600000	35.20	---	200.0	V	184.0	-12.3	74.00	38.80
1205.700000	---	38.21	200.0	H	244.0	-11.5	54.00	15.79
1205.700000	46.07	---	200.0	H	244.0	-11.5	74.00	27.93
1685.100000	---	29.63	150.0	V	347.0	-9.3	54.00	24.37
1685.100000	38.50	---	150.0	V	347.0	-9.3	74.00	35.50
2130.500000	---	35.31	200.0	V	214.0	-7.9	54.00	18.69
2130.500000	43.33	---	200.0	V	214.0	-7.9	74.00	30.67
4250.400000	---	33.98	150.0	V	356.0	-1.4	54.00	20.02
4250.400000	43.84	---	150.0	V	356.0	-1.4	74.00	30.16
17503.600000	---	47.46	150.0	H	155.0	14.3	54.00	6.54
17503.600000	56.37	---	150.0	H	155.0	14.3	74.00	17.63

18GHz-25GHz:


Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case low channel of 802.11g mode in Z-axis of orientation was recorded

Horizontal



Date: 21.JAN.2020 11:23:49

Vertical



Date: 21.JAN.2020 11:33:14

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

802.11b Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	50.44	---	200.0	H	60.0	2.8	74.00	23.56
2390.000000	---	45.90	200.0	H	60.0	2.8	54.00	8.10
2390.000000	---	44.08	200.0	V	257.0	2.8	54.00	9.92
2390.000000	49.65	---	200.0	V	257.0	2.8	74.00	24.35
High Channel: 2462MHz								
2483.500000	---	42.67	150.0	H	98.0	3.0	54.00	11.33
2483.500000	52.54	---	150.0	H	98.0	3.0	74.00	21.46
2483.500000	51.09	---	200.0	V	178.0	3.0	74.00	22.91
2483.500000	---	41.71	200.0	V	178.0	3.0	54.00	12.29

802.11g Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	50.32	200.0	H	294.0	2.8	54.00	3.68
2390.000000	60.22	---	200.0	H	294.0	2.8	74.00	13.78
2390.000000	---	49.22	150.0	V	206.0	2.8	54.00	4.78
2390.000000	58.44	---	150.0	V	206.0	2.8	74.00	15.56
High Channel: 2462MHz								
2483.500000	64.79	---	150.0	H	85.0	3.0	74.00	9.21
2483.500000	---	51.43	150.0	H	85.0	3.0	54.00	2.57
2483.500000	60.35	---	150.0	V	81.0	3.0	74.00	13.65
2483.500000	---	49.86	150.0	V	81.0	3.0	54.00	4.14

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	55.59	---	150.0	H	307.0	2.8	74.00	18.41
2390.000000	---	48.69	150.0	H	307.0	2.8	54.00	5.31
2390.000000	---	46.34	100.0	V	318.0	2.8	54.00	7.66
2390.000000	53.10	---	100.0	V	318.0	2.8	74.00	20.90
High Channel: 2462MHz								
2483.500000	58.24	---	200.0	H	85.0	3.0	74.00	15.76
2483.500000	---	52.91	200.0	H	85.0	3.0	54.00	1.09
2483.500000	55.39	---	150.0	V	158.0	3.0	74.00	18.61
2483.500000	---	49.68	150.0	V	158.0	3.0	54.00	4.32

For BLE Mode:**Spurious Emission Test:****30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high** channel of operation in the Z axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
33.606900	29.34	100.0	V	82.0	-5.9	40.00	10.66
84.328550	26.51	100.0	V	196.0	-17.7	40.00	13.49
145.587200	22.35	100.0	H	148.0	-12.1	43.50	21.15
287.997200	26.72	200.0	V	261.0	-10.9	46.00	19.28
479.993300	30.53	100.0	V	0.0	-6.7	46.00	15.47
891.930900	32.38	100.0	V	226.0	-0.1	46.00	13.62

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1198.900000	---	36.08	150.0	V	87.0	-11.6	54.00	17.92
1198.900000	43.24	---	150.0	V	87.0	-11.6	74.00	30.76
1525.300000	---	28.24	150.0	V	351.0	-9.8	54.00	25.76
1525.300000	39.89	---	150.0	V	351.0	-9.8	74.00	34.11
1678.300000	---	29.76	150.0	H	236.0	-9.3	54.00	24.24
1678.300000	38.60	---	150.0	H	236.0	-9.3	74.00	35.40
4804.000000	---	32.54	150.0	V	6.0	-0.6	54.00	21.46
4804.000000	41.17	---	150.0	V	6.0	-0.6	74.00	32.83
7868.000000	---	39.58	100.0	H	328.0	6.8	54.00	14.42
7868.000000	49.62	---	100.0	H	328.0	6.8	74.00	24.38
17573.300000	---	48.39	100.0	V	348.0	14.2	54.00	5.61
17573.300000	56.09	---	100.0	V	348.0	14.2	74.00	17.91

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1198.900000	43.50	---	150.0	V	86.0	-11.6	74.00	30.50
1198.900000	---	35.63	150.0	V	86.0	-11.6	54.00	18.37
1593.300000	---	30.38	100.0	V	160.0	-9.6	54.00	23.62
1593.300000	39.84	---	100.0	V	160.0	-9.6	74.00	34.16
2128.800000	---	30.22	150.0	V	189.0	-7.9	54.00	23.78
2128.800000	37.72	---	150.0	V	189.0	-7.9	74.00	36.28
4880.000000	---	33.50	150.0	V	351.0	-0.5	54.00	20.50
4880.000000	41.26	---	150.0	V	351.0	-0.5	74.00	32.74
7898.600000	---	40.10	150.0	V	190.0	6.9	54.00	13.90
7898.600000	49.58	---	150.0	V	190.0	6.9	74.00	24.42
17541.000000	---	48.95	100.0	V	115.0	14.2	54.00	5.05
17541.000000	56.20	---	100.0	V	115.0	14.2	74.00	17.80

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1198.900000	42.73	---	200.0	H	289.0	-11.6	74.00	31.27
1198.900000	---	35.75	200.0	H	289.0	-11.6	54.00	18.25
1360.400000	42.29	---	150.0	V	199.0	-10.7	74.00	31.71
1360.400000	---	29.27	150.0	V	199.0	-10.7	54.00	24.73
1678.300000	39.34	---	100.0	H	244.0	-9.3	74.00	34.66
1678.300000	---	30.88	100.0	H	244.0	-9.3	54.00	23.12
4960.000000	41.18	---	200.0	V	301.0	-0.3	74.00	32.82
4960.000000	---	34.43	200.0	V	301.0	-0.3	54.00	19.57
7905.400000	49.97	---	150.0	H	0.0	6.9	74.00	24.03
7905.400000	---	39.38	150.0	H	0.0	6.9	54.00	14.62
17432.200000	---	48.71	200.0	V	32.0	13.9	54.00	5.29
17432.200000	57.14	---	200.0	V	32.0	13.9	74.00	16.86

18GHz-25GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high** channel of operation in the Z axis of orientation was recorded)

Horizontal



Date: 21.JAN.2020 10:32:02

Vertical



Date: 21.JAN.2020 10:49:33

Restricted Bands Emissions Test:

(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	---	42.86	150.0	H	7.0	2.8	54.00	11.14
2390.000000	50.92	---	150.0	H	7.0	2.8	74.00	23.08
2390.000000	---	40.24	100.0	V	143.0	2.8	54.00	13.76
2390.000000	49.88	---	100.0	V	143.0	2.8	74.00	24.12
High Channel: 2480MHz								
2483.500000	---	42.71	100.0	H	255.0	3.0	54.00	11.29
2483.500000	50.82	---	100.0	H	255.0	3.0	74.00	23.18
2483.500000	49.34	---	100.0	V	68.0	3.0	74.00	24.66
2483.500000	---	40.08	100.0	V	68.0	3.0	54.00	13.92

Transmitting simultaneously test:

(The worst case **Wi-Fi 802.11g mode low channel** and **GPRS 850 middle channel** transmitting simultaneously in Z-axis of orientation was recorded)


30MHz-1GHz

Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
31.804150	23.30	100.0	V	25.0	-5.2	40.00	16.70
38.057700	30.93	100.0	H	51.0	-9.4	40.00	9.07
86.192450	20.36	100.0	V	231.0	-17.6	40.00	19.64
120.696650	16.21	100.0	V	231.0	-11.2	43.50	27.29
260.009750	33.91	100.0	H	181.0	-11.8	46.00	12.09
528.002600	28.16	100.0	H	191.0	-5.9	46.00	17.84

1GHz-18GHz

Note:


1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1095.200000	---	31.86	200.0	H	117.0	-12.1	54.00	22.14
1095.200000	37.38	---	200.0	H	117.0	-12.1	74.00	36.62
1198.900000	---	35.22	200.0	V	57.0	-11.6	54.00	18.78
1198.900000	41.70	---	200.0	V	57.0	-11.6	74.00	32.30
1511.700000	---	29.36	150.0	H	124.0	-9.9	54.00	24.64
1511.700000	36.49	---	150.0	H	124.0	-9.9	74.00	37.51
3759.100000	---	43.10	200.0	V	26.0	-2.7	54.00	10.90
3759.100000	47.47	---	200.0	V	26.0	-2.7	74.00	26.53
5639.300000	---	40.20	200.0	V	0.0	1.7	54.00	13.80
5639.300000	46.37	---	200.0	V	0.0	1.7	74.00	27.63
17384.600000	---	48.50	150.0	V	269.0	13.7	54.00	5.50
17384.600000	55.44	---	150.0	V	269.0	13.7	74.00	18.56


18GHz-25GHz

Horizontal



Date: 5.MAR.2020 12:06:21


Vertical




Date: 5.MAR.2020 12:35:59



Conducted Spurious Emissions at Antenna Port

802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel**802.11g Mode Low Channel**


802.11g Mode Middle Channel




802.11g Mode High Channel





802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel**BLE Mode Low Channel**

BLE Mode Middle Channel



BLE Mode High Channel




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**Test Data****Environmental Conditions**

Temperature:	21.1 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Sam Ye on 2020-02-18.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	10.160	≥ 0.5
Middle	2437	9.138	≥ 0.5
High	2462	9.679	≥ 0.5
802.11g Mode			
Low	2412	15.391	≥ 0.5
Middle	2437	15.451	≥ 0.5
High	2462	15.932	≥ 0.5
802.11n-HT20 Mode			
Low	2412	15.631	≥ 0.5
Middle	2437	15.631	≥ 0.5
High	2462	15.271	≥ 0.5
BLE Mode			
Low	2402	0.764	≥ 0.5
Middle	2440	0.764	≥ 0.5
High	2480	0.764	≥ 0.5


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	21.8 °C
Relative Humidity:	54 %
ATM Pressure:	101.2 kPa


The testing was performed by Sam Ye on 2020-02-18.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	20.05	30	Pass
Middle	2437	20.14	30	Pass
High	2462	20.30	30	Pass
802.11g Mode				
Low	2412	23.49	30	Pass
Middle	2437	23.24	30	Pass
High	2462	23.47	30	Pass
802.11n-HT20 Mode				
Low	2412	22.82	30	Pass
Middle	2437	22.92	30	Pass
High	2462	22.77	30	Pass
BLE Mode				
Low	2402	7.99	30	Pass
Middle	2440	8.25	30	Pass
High	2480	8.38	30	Pass


BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions


Temperature:	21.3 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa

The testing was performed by Sam Ye on 2020-02-18.


Test Result: Compliant.

*EUT operation mode: Transmitting***802.11b Mode Left Side****802.11b Mode Right Side**


802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side



BLE Mode Left Side



BLE Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	22.1 °C
Relative Humidity:	48 %
ATM Pressure:	101.1 kPa


The testing was performed by Sam Ye on 2020-02-18.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-4.12	≤ 8
Middle	2437	-4.79	≤ 8
High	2462	-5.45	≤ 8
802.11g Mode			
Low	2412	-8.58	≤ 8
Middle	2437	-9.56	≤ 8
High	2462	-10.05	≤ 8
802.11n-HT20 mode			
Low	2412	-10.37	≤ 8
Middle	2437	-10.03	≤ 8
High	2462	-10.75	≤ 8
BLE Mode			
Low	2402	-6.38	≤ 8
Middle	2440	-6.24	≤ 8
High	2480	-6.01	≤ 8


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




BLE Mode Low Channel



BLE Mode Middle Channel



BLE Mode High Channel



***** END OF REPORT *****