



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



TEST REPORT

Applicant: Shanghai Sunmi Technology Co.,Ltd.

Address: Room 505, No. 388 Song Hu Road, Yang Pu District, Shanghai, China

FCC ID: 2AH25T8910B

Product Name: Handheld Wireless Terminal

Model Number: T8910

Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR22050079-00C

Date Of Issue: 2022-08-18

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 DESCRIPTION OF TEST CONFIGURATION.....	7
1.2.2 Support Equipment List and Details	7
1.2.3 Support Cable List and Details	7
1.2.4 Block Diagram of Test Setup.....	8
1.3 MEASUREMENT UNCERTAINTY	9
2. SUMMARY OF TEST RESULTS	10
3. REQUIREMENTS AND TEST PROCEDURES	11
3.1 AC LINE CONDUCTED EMISSIONS.....	11
3.1.1 Applicable Standard.....	11
3.1.2 EUT Setup.....	12
3.1.3 EMI Test Receiver Setup	12
3.1.4 Test Procedure	13
3.1.5 Corrected Amplitude & Margin Calculation.....	13
3.2 RADIATION SPURIOUS EMISSIONS.....	14
3.2.1 Applicable Standard.....	14
3.2.2 EUT Setup.....	14
3.2.3 EMI Test Receiver & Spectrum Analyzer Setup	15
3.2.4 Test Procedure	15
3.2.5 Corrected Amplitude & Margin Calculation.....	15
3.3 6 dB EMISSION BANDWIDTH:.....	16
3.3.1 Applicable Standard.....	16
3.3.2 EUT Setup.....	16
3.3.3 Test Procedure	16
3.4 MAXIMUM CONDUCTED OUTPUT POWER:.....	17
3.4.1 Applicable Standard.....	17
3.4.2 EUT Setup.....	17
3.4.3 Test Procedure	17
3.5 MAXIMUM POWER SPECTRAL DENSITY:	18
3.5.1 Applicable Standard.....	18
3.5.2 EUT Setup.....	18
3.5.3 Test Procedure	18
3.6 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE:	19
3.6.1 Applicable Standard.....	19
3.6.2 EUT Setup.....	19
3.6.3 Test Procedure	19
3.7 DUTY CYCLE:.....	20
3.7.1 EUT Setup.....	20

3.7.2 Test Procedure	20
3.8 ANTENNA REQUIREMENT.....	20
3.8.1 Applicable Standard.....	20
3.8.2 Judgment.....	20
4. Test DATA AND RESULTS.....	21
4.1 AC LINE CONDUCTED EMISSIONS.....	21
4.2 RADIATION SPURIOUS EMISSIONS.....	26
4.3 6 dB EMISSION BANDWIDTH:	39
4.4 MAXIMUM CONDUCTED OUTPUT POWER:	46
4.5 MAXIMUM POWER SPECTRAL DENSITY:	48
4.6 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE:	55
4.7 DUTY CYCLE:.....	62
5. RF EXPOSURE EVALUATION	65
5.1 APPLICABLE STANDARD.....	65
5.2 PROCEDURE.....	65
5.3 MEASUREMENT RESULT	65

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Handheld Wireless Terminal
EUT Model:	T8910
Operation Frequency:	2412-2462 MHz(802.11b/g/n ht20/n ht40) 2402-2480MHz(BLE)
Maximum Peak Output Power (Conducted):	23.94dBm(802.11b/g/n) -2.57 dBm(BLE)
Modulation Type:	DSSS, OFDM(802.11b/g/n) GFSK(BLE)
Rated Input Voltage:	DC 5V charging from adapter and DC 3.8V by battery
Serial Number:	CR220050079-RF-S1(Type-1) CR220050079-RF-S2(Type-2) CR220050079-RF-S3(Type-3)
EUT Received Date:	2022.5.25
EUT Received Status:	Good
Note: The EUT model has three configurations that Type-1 is code scanner model 3603, Type-2 is code scanner model 4170 and Type-3 is code scanner model NG001. The Type-1 was reported for Conducted Emissions and Radiation Below 1GHz test, since Type-1, Type-2 and Type-3 mode were proved to be compliance with 15.207&15.209 emission requirements in 15B report CR22050079-00A, and the worst is Type-1 mode.	

Operation Frequency Detail: For 802.11b/g/n ht20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2412	
Middle		2437	
Highest		2462	

For 802.11n ht40/:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2422	
Middle		2437	
Highest		2452	

For BLE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480
Per section 15.31(m), the below frequencies were performed the test as below:			
Test Channel		Frequency (MHz)	
Lowest		2402	
Middle		2440	
Highest		2480	

Antenna Information Detail▲:

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range	§15.203 Requirement
Shanghai Sunmi Technology Co.,Ltd.	FPC	50	0.16 dBi/ 2.4~2.5GHz	Compliance
The Method of §15.203 Compliance: ☒ Antenna must be permanently attached to the unit. ☐ Antenna must use a unique type of connector to attach to the EUT. ☐ Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

Accessory Information:

Accessory Description	Manufacturer	Model	Parameters
Adapter 1#	SHENZHEN TIANYIN ELECTRONICS CO.,LTD.	TPA-23A050200UU01	Input: AC 100-240V~50/60Hz 0.3A Output: DC 5.0V, 2000mA
Adapter 2#	JIANGSU CHENYANG ELECTRON CO.,LTD.	UC13US	Input: 100-240V~50/60Hz 0.35A Output: DC 5.0V, 2A
USB Cable	Unknown	Unknown	Unshielded, 1.2m

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

For 802.11b/g/n:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		RTL8852A MP Toolkit.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	21	22	22
802.11g	6Mbps	17	17	16
802.11n ht20	MCS0	17	17	15
802.11n ht40	MCS0	13	13	10
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

For BLE:

EUT Operation Mode:		The system was configured for testing in Engineering Mode, which was provided by the manufacturer.		
Equipment Modifications:		No		
EUT Exercise Software:		Engineering Mode		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer ▲ :				
Test Modes	Power Level Setting			
	Lowest Channel	Middle Channel	Highest Channel	
1Mbps	Default	Default	Default	
2Mbps	Default	Default	Default	

1.2.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
/	/	/	/	/	/

1.2.4 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:
Below 1GHz:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.61\text{dB}$
Power Spectral Density, conducted	$\pm 0.61\text{ dB}$
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	$\pm 1.26\text{ dB}$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 0.4\%$
Duty Cycle	1%
AC Power Lines Conducted Emission	2.8 dB (150 kHz to 30 MHz)

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a)	AC line conducted emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.203	Antenna Requirement	Compliant
FCC§15.247 (i) & §1.1307 & §2.1093	RF Exposure Evaluation	Compliant

3. REQUIREMENTS AND TEST PROCEDURES

3.1 AC Line Conducted Emissions

3.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

3.1.2 EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

3.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

3.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

3.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

3.2 Radiation Spurious Emissions


3.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.2.2 EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

3.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

3.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

3.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result


3.3 6 dB Emission Bandwidth:

3.3.1 Applicable Standard

FCC §15.247 (a)(2)

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

3.3.2 EUT Setup



3.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.8

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


3.4 Maximum conducted output power:

3.4.1 Applicable Standard

FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

3.4.2 EUT Setup



3.4.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum conducted output power may be measured using a broadband RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- a) Set the EUT in transmitting mode.
- b) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- c) Add a correction factor to the display.
- d) Set the power meter to test output power, record the result.


3.5 Maximum power spectral density:

3.5.1 Applicable Standard

FCC §15.247 (e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.5.2 EUT Setup



3.5.3 Test Procedure

According to ANSI C63.10-2013 Section 11.10.2

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \cdot \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.


3.6 100 kHz Bandwidth of Frequency Band Edge:

3.6.1 Applicable Standard

FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

3.6.2 EUT Setup



3.6.3 Test Procedure


According to ANSI C63.10-2013 Section 11.11

- Set the center frequency and span to encompass frequency range to be measured.
- Set the RBW = 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

3.7 Duty Cycle:

3.7.1 EUT Setup



3.7.2 Test Procedure

According to ANSI C63.10-2013 Section 11.6

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.8 Antenna Requirement

3.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.8.2 Judgment

Please refer to the Antenna Information detail in Section 1.

4. Test DATA AND RESULTS

4.1 AC Line Conducted Emissions

Serial Number:	CR220050079-RF-S1(Type-1) CR220050079-RF-S2(Type-2) CR220050079-RF-S3(Type-3)	Test Date:	2022-07-27~2022-08-12
Test Site:	CE	Test Mode:	Transmitting(802.11g middle channel was the worst)
Tester:	Vic Du	Test Result:	Pass


Environmental Conditions:

Temperature: (°C)	27.1~27.8	Relative Humidity: (%)	60~70	ATM Pressure: (kPa)	100.1~100.2
----------------------	-----------	------------------------------	-------	------------------------	-------------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101134	2022-04-01	2023-03-31
R&S	EMI Test Receiver	ESR3	102726	2022-07-15	2023-07-14
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UTIFLEX	C-0200-01	2022-08-07	2023-08-06
Audix	Test Software	E3	190306 (V9)	N/A	N/A


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Type-1:**Adapter 1:****Line:**


No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.164	33.93	9.61	43.54	65.27	21.73	QP
2	0.164	21.01	9.61	30.62	55.27	24.65	Average
3	0.307	31.98	9.61	41.59	60.05	18.46	QP
4	0.307	18.55	9.61	28.16	50.05	21.89	Average
5	0.523	37.26	9.61	46.87	56.00	9.13	QP
6	0.523	22.42	9.61	32.03	46.00	13.97	Average
7	0.693	34.22	9.62	43.84	56.00	12.16	QP
8	0.693	18.43	9.62	28.05	46.00	17.95	Average
9	1.733	25.63	9.63	35.26	56.00	20.74	QP
10	1.733	11.96	9.63	21.58	46.00	24.42	Average
11	14.430	24.73	9.68	34.41	60.00	25.59	QP
12	14.430	11.19	9.68	20.88	50.00	29.12	Average

Neutral:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.310	31.68	9.61	41.29	59.97	18.68	QP
2	0.310	18.11	9.61	27.72	49.97	22.25	Average
3	0.520	37.54	9.61	47.15	56.00	8.85	QP
4	0.520	21.91	9.61	31.53	46.00	14.47	Average
5	0.589	36.54	9.62	46.16	56.00	9.84	QP
6	0.589	18.35	9.62	27.97	46.00	18.03	Average
7	1.230	29.32	9.62	38.94	56.00	17.06	QP
8	1.230	12.47	9.62	22.10	46.00	23.90	Average
9	2.413	27.16	9.64	36.80	56.00	19.20	QP
10	2.413	11.15	9.64	20.79	46.00	25.21	Average
11	11.504	21.27	9.67	30.94	60.00	29.06	QP
12	11.504	10.55	9.67	20.22	50.00	29.78	Average

Adapter 2:**Line:**

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.208	30.56	9.61	40.17	63.29	23.12	QP
2	0.208	15.90	9.61	25.51	53.29	27.78	Average
3	0.312	28.07	9.61	37.68	59.91	22.23	QP
4	0.312	12.65	9.61	22.26	49.91	27.65	Average
5	0.464	29.44	9.61	39.05	56.62	17.57	QP
6	0.464	13.29	9.61	22.90	46.62	23.72	Average
7	0.556	29.65	9.62	39.27	56.00	16.73	QP
8	0.556	16.79	9.62	26.41	46.00	19.59	Average
9	1.165	28.67	9.62	38.29	56.00	17.71	QP
10	1.165	17.00	9.62	26.62	46.00	19.38	Average
11	1.539	25.46	9.63	35.08	56.00	20.92	QP
12	1.539	12.51	9.63	22.14	46.00	23.86	Average

Neutral:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.195	31.16	9.61	40.77	63.81	23.04	QP
2	0.195	14.10	9.61	23.71	53.81	30.10	Average
3	0.306	33.47	9.61	43.08	60.09	17.01	QP
4	0.306	20.77	9.61	30.38	50.09	19.71	Average
5	0.516	31.43	9.61	41.05	56.00	14.95	QP
6	0.516	17.25	9.61	26.86	46.00	19.14	Average
7	0.602	30.98	9.62	40.60	56.00	15.40	QP
8	0.602	19.22	9.62	28.84	46.00	17.16	Average
9	0.846	26.07	9.62	35.69	56.00	20.31	QP
10	0.846	12.98	9.62	22.60	46.00	23.40	Average
11	1.117	26.42	9.62	36.04	56.00	19.96	QP
12	1.117	17.42	9.62	27.04	46.00	18.96	Average

4.2 Radiation Spurious Emissions

Serial Number:	CR220050079-RF-S1(Type-1) CR220050079-RF-S2(Type-2) CR220050079-RF-S3(Type-3)	Test Date:	Below 1G: 2022-08-01~2022-08-12 Above 1G: 2022-07-28
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Gary Ling, Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.3~30.7	Relative Humidity: (%)	58~65	ATM Pressure: (kPa)	100.0~100.1
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020-10-19	2023-10-18
R&S	EMI Test Receiver	ESR3	102724	2022-07-15	2023-07-14
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2022-07-17	2023-07-16
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2022-07-17	2023-07-16
Sonoma	Amplifier	310N	186165	2022-07-17	2023-07-16
Audix	Test Software	E3	201021 (V9)	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
R&S	Spectrum Analyzer	FSV40	101591	2022-07-15	2023-07-14
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2021-08-08	2022-08-07
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2021-08-08	2022-08-07
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2021-11-10	2022-11-09
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021-02-05	2024-02-04
AH	Preamplifier	PAM-1840VH	190	2021-11-19	2022-11-18
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2021-08-08	2022-08-07
E-Microwave	Band Rejection Filter	2400-2483.5MHz	OE01902424	2021-08-08	2022-08-07
Mini Circuits	High Pass Filter	VHF-6010+	31119	2021-08-08	2022-08-07

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:

Please refer to the below table and plots.


Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.10 Figure 8, the worst orientation was photographed and it's data was recorded.

1) 30MHz-1GHz(802.11g middle channel was the worst)**Type-1:****Adapter 1:****Horizontal:**


No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.531	28.41	-4.20	24.21	40.00	15.79	Peak
2	31.510	29.00	-4.95	24.05	40.00	15.95	Peak
3	39.576	31.03	-11.18	19.85	40.00	20.15	Peak
4	78.689	36.82	-17.57	19.25	40.00	20.75	Peak
5	89.590	37.00	-17.21	19.79	43.50	23.71	Peak
6	206.398	36.18	-12.55	23.63	43.50	19.87	Peak

Vertical:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.211	33.61	-3.95	29.66	40.00	10.34	Peak
2	32.406	36.55	-5.64	30.91	40.00	9.09	Peak
3	34.882	40.30	-7.57	32.73	40.00	7.27	Peak
4	37.416	40.04	-9.49	30.55	40.00	9.45	Peak
5	39.994	44.25	-11.52	32.73	40.00	7.27	Peak
6	43.659	39.25	-13.70	25.55	40.00	14.45	Peak

Adapter 2**Horizontal:**

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	30.424	27.88	-4.12	23.76	40.00	16.24	Peak
2	38.752	34.68	-10.52	24.16	40.00	15.84	Peak
3	39.994	34.34	-11.52	22.82	40.00	17.18	Peak
4	79.800	36.01	-17.69	18.32	40.00	21.68	Peak
5	143.830	41.17	-12.20	28.97	43.50	14.53	Peak
6	285.978	36.45	-11.48	24.97	46.00	21.03	Peak

Vertical:

No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	36.254	37.90	-8.62	29.29	40.00	10.71	Peak
2	38.752	43.04	-10.52	32.52	40.00	7.48	Peak
3	39.854	43.43	-11.40	32.03	40.00	7.97	Peak
4	77.593	38.04	-17.46	20.59	40.00	19.41	Peak
5	79.800	38.55	-17.69	20.86	40.00	19.14	Peak
6	144.335	36.73	-12.20	24.53	43.50	18.97	Peak

2) 1-25GHz(Type-1 + Adapter 1 was the worst):
802.11b Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.00	72.89	PK	H	31.53	104.42	N/A	N/A
2412.00	69.91	AV	H	31.53	101.44	N/A	N/A
2412.00	74.74	PK	V	31.53	106.27	N/A	N/A
2412.00	71.45	AV	V	31.53	102.98	N/A	N/A
2390.00	29.31	PK	V	31.46	60.77	74.00	13.23
2390.00	16.20	AV	V	31.46	47.66	54.00	6.34
4824.00	44.97	PK	V	10.94	55.91	74.00	18.09
4824.00	41.43	AV	V	10.94	52.37	54.00	1.63
7236.00	33.35	PK	V	14.44	47.79	74.00	26.21
7236.00	20.77	AV	V	14.44	35.21	54.00	18.79
Middle Channel: 2437 MHz							
2437.00	74.65	PK	H	31.60	106.25	N/A	N/A
2437.00	71.41	AV	H	31.60	103.01	N/A	N/A
2437.00	76.43	PK	V	31.60	108.03	N/A	N/A
2437.00	73.39	AV	V	31.60	104.99	N/A	N/A
4874.00	43.32	PK	H	11.05	54.37	74.00	19.63
4874.00	40.03	AV	H	11.05	51.08	54.00	2.92
7311.00	33.41	PK	H	14.80	48.21	74.00	25.79
7311.00	20.67	AV	H	14.80	35.47	54.00	18.53
High Channel: 2462MHz							
2462.00	74.59	PK	H	31.63	106.22	N/A	N/A
2462.00	71.16	AV	H	31.63	102.79	N/A	N/A
2462.00	76.94	PK	V	31.63	108.57	N/A	N/A
2462.00	73.67	AV	V	31.63	105.30	N/A	N/A
2483.50	32.57	PK	V	31.64	64.21	74.00	9.79
2483.50	19.23	AV	V	31.64	50.87	54.00	3.13
4924.00	43.51	PK	V	11.18	54.69	74.00	19.31
4924.00	39.78	AV	V	11.18	50.96	54.00	3.04
7386.00	33.40	PK	V	14.89	48.29	74.00	25.71
7386.00	20.49	AV	V	14.89	35.38	54.00	18.62

802.11g Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.00	72.35	PK	H	31.53	103.88	N/A	N/A
2412.00	62.97	AV	H	31.53	94.50	N/A	N/A
2412.00	74.56	PK	V	31.53	106.09	N/A	N/A
2412.00	64.98	AV	V	31.53	96.51	N/A	N/A
2390.00	33.39	PK	V	31.46	64.85	74.00	9.15
2390.00	18.73	AV	V	31.46	50.19	54.00	3.81
4824.00	42.84	PK	V	10.94	53.78	74.00	20.22
4824.00	31.43	AV	V	10.94	42.37	54.00	11.63
7236.00	33.31	PK	V	14.44	47.75	74.00	26.25
7236.00	20.45	AV	V	14.44	34.89	54.00	19.11
Middle Channel: 2437 MHz							
2437.00	72.46	PK	H	31.60	104.06	N/A	N/A
2437.00	63.01	AV	H	31.60	94.61	N/A	N/A
2437.00	74.67	PK	V	31.60	106.27	N/A	N/A
2437.00	65.11	AV	V	31.60	96.71	N/A	N/A
4874.00	42.96	PK	V	11.05	54.01	74.00	19.99
4874.00	31.65	AV	V	11.05	42.70	54.00	11.30
7311.00	33.46	PK	V	14.80	48.26	74.00	25.74
7311.00	20.63	AV	V	14.80	35.43	54.00	18.57
High Channel: 2462MHz							
2462.00	71.35	PK	H	31.63	102.98	N/A	N/A
2462.00	61.87	AV	H	31.63	93.50	N/A	N/A
2462.00	73.12	PK	V	31.63	104.75	N/A	N/A
2462.00	63.56	AV	V	31.63	95.19	N/A	N/A
2483.50	33.94	PK	V	31.64	65.58	74.00	8.42
2483.50	18.29	AV	V	31.64	49.93	54.00	4.07
4924.00	42.26	PK	V	11.18	53.44	74.00	20.56
4924.00	30.38	AV	V	11.18	41.56	54.00	12.44
7386.00	33.54	PK	V	14.89	48.43	74.00	25.57
7386.00	20.71	AV	V	14.89	35.60	54.00	18.40

802.11n ht20 Mode:

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2412 MHz							
2412.00	72.16	PK	H	31.53	103.69	N/A	N/A
2412.00	62.39	AV	H	31.53	93.92	N/A	N/A
2412.00	74.30	PK	V	31.53	105.83	N/A	N/A
2412.00	64.39	AV	V	31.53	95.92	N/A	N/A
2390.00	35.51	PK	V	31.46	66.97	74.00	7.03
2390.00	19.14	AV	V	31.46	50.60	54.00	3.40
4824.00	36.21	PK	V	10.94	47.15	74.00	26.85
4824.00	23.31	AV	V	10.94	34.25	54.00	19.75
7236.00	33.35	PK	V	14.44	47.79	74.00	26.21
7236.00	20.46	AV	V	14.44	34.90	54.00	19.10
Middle Channel: 2437 MHz							
2437.00	72.35	PK	H	31.60	103.95	N/A	N/A
2437.00	62.58	AV	H	31.60	94.18	N/A	N/A
2437.00	74.56	PK	V	31.60	106.16	N/A	N/A
2437.00	64.79	AV	V	31.60	96.39	N/A	N/A
4874.00	36.34	PK	V	11.05	47.39	74.00	26.61
4874.00	23.51	AV	V	11.05	34.56	54.00	19.44
7311.00	33.46	PK	V	14.80	48.26	74.00	25.74
7311.00	20.63	AV	V	14.80	35.43	54.00	18.57
High Channel: 2462MHz							
2462.00	71.29	PK	H	31.63	102.92	N/A	N/A
2462.00	61.56	AV	H	31.63	93.19	N/A	N/A
2462.00	73.35	PK	V	31.63	104.98	N/A	N/A
2462.00	63.67	AV	V	31.63	95.30	N/A	N/A
2483.50	34.48	PK	V	31.64	66.12	74.00	7.88
2483.50	18.41	AV	V	31.64	50.05	54.00	3.95
4924.00	36.76	PK	V	11.18	47.94	74.00	26.06
4924.00	23.96	AV	V	11.18	35.14	54.00	18.86
7386.00	33.61	PK	V	14.89	48.50	74.00	25.50
7386.00	20.84	AV	V	14.89	35.73	54.00	18.27

802.11n ht40 Mode:


Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2422 MHz							
2422.00	66.26	PK	H	31.56	97.82	N/A	N/A
2422.00	56.01	AV	H	31.56	87.57	N/A	N/A
2422.00	68.19	PK	V	31.56	99.75	N/A	N/A
2422.00	57.90	AV	V	31.56	89.46	N/A	N/A
2390.00	32.20	PK	V	31.46	63.66	74.00	10.34
2390.00	18.76	AV	V	31.46	50.22	54.00	3.78
4844.00	34.11	PK	V	10.96	45.07	74.00	28.93
4844.00	21.26	AV	V	10.96	32.22	54.00	21.78
7266.00	33.33	PK	V	14.63	47.96	74.00	26.04
7266.00	20.43	AV	V	14.63	35.06	54.00	18.94
Middle Channel: 2437 MHz							
2437.00	65.98	PK	H	31.60	97.58	N/A	N/A
2437.00	56.62	AV	H	31.60	88.22	N/A	N/A
2437.00	67.85	PK	V	31.60	99.45	N/A	N/A
2437.00	57.43	AV	V	31.60	89.03	N/A	N/A
4874.00	34.25	PK	V	11.05	45.30	74.00	28.70
4874.00	21.37	AV	V	11.05	32.42	54.00	21.58
7311.00	33.46	PK	V	14.80	48.26	74.00	25.74
7311.00	20.59	AV	V	14.80	35.39	54.00	18.61
High Channel: 2452MHz							
2452.00	63.94	PK	H	31.63	95.57	N/A	N/A
2452.00	53.13	AV	H	31.63	84.76	N/A	N/A
2452.00	65.88	PK	V	31.63	97.51	N/A	N/A
2452.00	55.57	AV	V	31.63	87.20	N/A	N/A
2483.50	31.02	PK	V	31.64	62.66	74.00	11.34
2483.50	17.64	AV	V	31.64	49.28	54.00	4.72
4904.00	34.35	PK	V	11.14	45.49	74.00	28.51
4904.00	21.46	AV	V	11.14	32.60	54.00	21.40
7356.00	33.65	PK	V	14.80	48.45	74.00	25.55
7356.00	20.81	AV	V	14.80	35.61	54.00	18.39

BLE:**1Mbps**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
2402.00	56.81	PK	H	31.51	88.32	N/A	N/A
2402.00	53.36	AV	H	31.51	84.87	N/A	N/A
2402.00	58.61	PK	V	31.51	90.12	N/A	N/A
2402.00	54.05	AV	V	31.51	85.56	N/A	N/A
2390.00	27.14	PK	V	31.46	58.60	74.00	15.40
2390.00	14.21	AV	V	31.46	45.67	54.00	8.33
4804.00	33.13	PK	V	10.91	44.04	74.00	29.96
4804.00	20.26	AV	V	10.91	31.17	54.00	22.83
7206.00	33.11	PK	V	14.22	47.33	74.00	26.67
7206.00	20.26	AV	V	14.22	34.48	54.00	19.52
Middle Channel: 2440 MHz							
2440.00	56.95	PK	H	31.60	88.55	N/A	N/A
2440.00	53.12	AV	H	31.60	84.72	N/A	N/A
2440.00	58.62	PK	V	31.60	90.22	N/A	N/A
2440.00	54.91	AV	V	31.60	86.51	N/A	N/A
4880.00	33.26	PK	V	11.07	44.33	74.00	29.67
4880.00	20.39	AV	V	11.07	31.46	54.00	22.54
7320.00	33.31	PK	V	14.80	48.11	74.00	25.89
7320.00	20.43	AV	V	14.80	35.23	54.00	18.77
High Channel: 2480 MHz							
2480.00	56.68	PK	H	31.64	88.32	N/A	N/A
2480.00	53.11	AV	H	31.64	84.75	N/A	N/A
2480.00	58.29	PK	V	31.64	89.93	N/A	N/A
2480.00	54.71	AV	V	31.64	86.35	N/A	N/A
2483.50	27.66	PK	V	31.64	59.30	74.00	14.70
2483.50	14.48	AV	V	31.64	46.12	54.00	7.88
4960.00	33.45	PK	V	11.23	44.68	74.00	29.32
4960.00	23.61	AV	V	11.23	34.84	54.00	19.16
7440.00	33.41	PK	V	15.26	48.67	74.00	25.33
7440.00	20.62	AV	V	15.26	35.88	54.00	18.12


BLE:**2Mbps**

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector					
Low Channel: 2402 MHz							
2402.00	56.07	PK	H	31.51	87.58	N/A	N/A
2402.00	49.96	AV	H	31.51	81.47	N/A	N/A
2402.00	57.69	PK	V	31.51	89.20	N/A	N/A
2402.00	51.53	AV	V	31.51	83.04	N/A	N/A
2390.00	28.07	PK	V	31.46	59.53	74.00	14.47
2390.00	14.31	AV	V	31.46	45.77	54.00	8.23
4804.00	33.05	PK	V	10.91	43.96	74.00	30.04
4804.00	20.21	AV	V	10.91	31.12	54.00	22.88
7206.00	33.04	PK	V	14.22	47.26	74.00	26.74
7206.00	20.19	AV	V	14.22	34.41	54.00	19.59
Middle Channel: 2440 MHz							
2440.00	56.12	PK	H	31.60	87.72	N/A	N/A
2440.00	50.03	AV	H	31.60	81.63	N/A	N/A
2440.00	57.96	PK	V	31.60	89.56	N/A	N/A
2440.00	51.83	AV	V	31.60	83.43	N/A	N/A
4880.00	33.15	PK	V	11.07	44.22	74.00	29.78
4880.00	20.34	AV	V	11.07	31.41	54.00	22.59
7320.00	33.24	PK	V	14.80	48.04	74.00	25.96
7320.00	20.39	AV	V	14.80	35.19	54.00	18.81
High Channel: 2480 MHz							
2480.00	56.04	PK	H	31.64	87.68	N/A	N/A
2480.00	50.03	AV	H	31.64	81.67	N/A	N/A
2480.00	57.76	PK	V	31.64	89.40	N/A	N/A
2480.00	51.63	AV	V	31.64	83.27	N/A	N/A
2483.50	28.26	PK	V	31.64	59.90	74.00	14.10
2483.50	14.76	AV	V	31.64	46.40	54.00	7.60
4960.00	33.36	PK	V	11.23	44.59	74.00	29.41
4960.00	20.54	AV	V	11.23	31.77	54.00	22.23
7440.00	33.41	PK	V	15.26	48.67	74.00	25.33
7440.00	20.59	AV	V	15.26	35.85	54.00	18.15


Worst Test plots(802.11b mode low channel was the worst)

Vertical


1-6GHz



6-18GHz



18-25GHz



4.3 6 dB Emission Bandwidth:

Serial Number:	CR220050079-RF-S1(Type-1)	Test Date:	2022-07-11~2022-07-13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~25.9	Relative Humidity: (%)	57~60	ATM Pressure: (kPa)	100.2~100.3
----------------------	-----------	------------------------------	-------	------------------------	-------------


Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data:


Test Modes	Test Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	2412	8.16	0.5
	2437	8.56	0.5
	2462	9.04	0.5
802.11g	2412	15.52	0.5
	2437	15.36	0.5
	2462	15.6	0.5
802.11n ht20	2412	15.36	0.5
	2437	15.52	0.5
	2462	15.36	0.5
802.11n ht40	2422	35.20	0.5
	2437	35.20	0.5
	2452	35.04	0.5
BLE 1Mbps	2402	0.651	0.5
	2440	0.651	0.5
	2480	0.651	0.5
BLE 2Mbps	2402	1.116	0.5
	2440	1.116	0.5
	2480	1.116	0.5














4.4 Maximum conducted output power:

Serial Number:	CR220050079-RF-S1(Type-1)	Test Date:	2022-07-11~2022-07-13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~25.9	Relative Humidity: (%)	57~60	ATM Pressure: (kPa)	100.2~100.3
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2021XA	MY54080015	2021-07-21	2022-07-20
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07

** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Test Modes	Test Channel	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b	Lowest	2412	22.17	30
	Middle	2437	23.22	30
	Highest	2462	23.15	30
802.11g	Lowest	2412	23.77	30
	Middle	2437	23.94	30
	Highest	2462	22.60	30
802.11n ht20	Lowest	2412	23.44	30
	Middle	2437	23.59	30
	Highest	2462	22.36	30
802.11n ht40	Lowest	2422	20.02	30
	Middle	2437	19.91	30
	Highest	2452	18.08	30
BLE 1Mbps	Lowest	2402	-2.86	≤30
	Middle	2440	-2.80	≤30
	Highest	2480	-3.33	≤30
BLE 2Mbps	Lowest	2402	-2.63	≤30
	Middle	2440	-2.57	≤30
	Highest	2480	-3.11	≤30

4.5 Maximum power spectral density:

Serial Number:	CR220050079-RF-S1(Type-1)	Test Date:	2022-07-11~2022-07-13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~25.9	Relative Humidity: (%)	57~60	ATM Pressure: (kPa)	100.2~100.3
----------------------	-----------	------------------------------	-------	------------------------	-------------




Test Equipment List and Details:




Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07




* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).




Test Data:

Test Channel	Test Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	2412	-1.33	8.00
	2437	-0.13	8.00
	2462	-0.89	8.00
802.11g	2412	-7.57	8.00
	2437	-7.36	8.00
	2462	-8.42	8.00
802.11n ht20	2412	-7.75	8.00
	2437	-7.56	8.00
	2462	-9.46	8.00
802.11n ht40	2422	-14.53	8.00
	2437	-15.32	8.00
	2452	-17.12	8.00
BLE 1Mbps	2402	-17.59	8.00
	2440	-17.53	8.00
	2480	-18.06	8.00
BLE 2Mbps	2402	-20.20	8.00
	2440	-20.11	8.00
	2480	-20.68	8.00




Maximum power spectral density802.11b
Lowest Channel802.11b
Middle Channel802.11b
Highest Channel

Maximum power spectral density802.11g
Lowest Channel802.11g
Middle Channel802.11g
Highest Channel

Maximum power spectral density802.11n ht20
Lowest Channel802.11n ht20
Middle Channel802.11n ht20
Highest Channel


Maximum power spectral density802.11n ht40
Lowest Channel802.11n ht40
Middle Channel802.11n ht40
Highest Channel

BLE
1Mbps
Lowest Channel




Maximum power spectral density


BLE
2Mbps
Lowest Channel



BLE
2Mbps
Middle Channel



BLE
2Mbps
Highest Channel



4.6 100 kHz Bandwidth of Frequency Band Edge:

Serial Number:	CR220050079-RF-S1(Type-1)	Test Date:	2022-07-11~2022-07-13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~25.9	Relative Humidity: (%)	57~60	ATM Pressure: (kPa)	100.2~100.3
----------------------	-----------	------------------------------	-------	------------------------	-------------


Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07


** Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

100 kHz Bandwidth of Frequency Band Edge

802.11b
Lowest Band edge




802.11b
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge


802.11g
Lowest Band edge




802.11g
Highest Band edge



802.11n ht20
Lowest Band edge




802.11n ht20
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

802.11n ht40
Lowest Band edge




802.11n ht40
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

BLE
1Mbps
Lowest Band edge




BLE
1Mbps
Highest Band edge




100 kHz Bandwidth of Frequency Band Edge

BLE
2Mbps
Lowest Band edge



BLE
2Mbps
Highest Band edge



4.7 Duty Cycle:

Serial Number:	CR220050079-RF-S1(Type-1)	Test Date:	2022-07-11~2022-07-13
Test Site:	RF	Test Mode:	Transmitting
Tester:	Ted Min	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5~25.9	Relative Humidity: (%)	57~60	ATM Pressure: (kPa)	100.2~100.3
----------------------	-----------	------------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101943	2021-10-10	2022-10-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
eastsheep	Coaxial Attenuator	2W-SMA-JK-18G	21060301	2021-08-08	2022-08-07


* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Ton (ms)	Ton+off (ms)	Duty cycle (%)
802.11b	100	100	100.00
802.11g	100	100	100.00
802.11n ht20	100	100	100.00
802.11n ht40	100	100	100.00
BLE 1Mbps	0.406	0.623	65.17
BLE 2Mbps	0.232	0.630	36.83


Duty Cycle

802.11b




Date: 13.JUL.2022 14:22:09

802.11g



Date: 13.JUL.2022 14:21:38




802.11n ht20



Date: 13.JUL.2022 14:22:38

Duty Cycle

802.11n ht40

BLE
1MbpsBLE
2Mbps

5. RF EXPOSURE EVALUATION

5.1 Applicable Standard

FCC §15.247 (i)

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §1.1307(b)(1) of this chapter.

5.2 Procedure

According to 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.2- 1-mW Test Exemption:

Per §1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

5.3 Measurement Result

For BLE:

Frequency (MHz)	Conducted output power including Tune-up Tolerance		1-mW Test Exemption
	(dBm)	(mW)	
2402-2480	-2	0.63	Compliant

Note: Antenna gain is 0.16dBi.

Result: Compliant. RF Exposure is exemption.

Wi-Fi:

Result: Compliance. Please refer to the SAR report: CR22050053-20.

===== END OF REPORT =====