



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247 TEST REPORT

For

Shanghai Sunmi Technology Co.,Ltd.

Room 505, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai, China

FCC ID: 2AH25TF701

Report Type: Original Report	Product Type: WIRELESS DATA TERMINAL
Project Engineer:	<u>Stone Zhang</u> <i>Stone Zhang</i>
Report Number:	<u>RKSA200706001-00B</u>
Report Date:	<u>2021-06-08</u>
Reviewed By:	<u>Oscar Ye</u> <i>Oscar Ye</i> EMC Manager
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	5
RELATED SUBMITTAL(S)/GRANT(S).....	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	8
SUPPORT EQUIPMENT LIST AND DETAILS	14
EXTERNAL I/O CABLE.....	14
BLOCK DIAGRAM OF TEST SETUP	15
SUMMARY OF TEST RESULTS	17
TEST EQUIPMENT LIST	18
FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION	20
FCC §15.203 - ANTENNA REQUIREMENT.....	21
APPLICABLE STANDARD	21
ANTENNA CONNECTOR CONSTRUCTION	21
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	22
APPLICABLE STANDARD	22
EUT SETUP	22
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE	23
FACTOR & OVER LIMIT CALCULATION.....	23
TEST RESULTS SUMMARY	23
TEST DATA	23
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	28
APPLICABLE STANDARD	28
EUT SETUP	28
EMI TEST RECEIVER SETUP.....	29
TEST PROCEDURE	29
CORRECTED AMPLITUDE & MARGIN CALCULATION	29
TEST RESULTS SUMMARY	29
TEST DATA	30
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	78
APPLICABLE STANDARD	78
TEST PROCEDURE	78
TEST DATA	78
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	95
APPLICABLE STANDARD	95
TEST PROCEDURE	95
TEST DATA	96
FCC §15.247(d) – BAND EDGE.....	102
APPLICABLE STANDARD	102

TEST PROCEDURE	102
TEST DATA	102
FCC §15.247(e) - POWER SPECTRAL DENSITY	113
APPLICABLE STANDARD	113
TEST PROCEDURE	113
TEST DATA	113

GENERAL INFORMATION**Product Description for Equipment under Test (EUT)**

Applicant	Shanghai Sunmi Technology Co.,Ltd.
Product Type	WIRELESS DATA TERMINAL
Tested Model	TF701
Power Supply	DC 3.85V from battery DC 5.0/9.0/12.0/3.6~6.0/6.0~9.0/9.0~12.0V from adapter
Maximum Output Power	2.4G Wi-Fi: 802.11b:18.00 dBm 802.11g:16.83 dBm 802.11n20:19.50 dBm 802.11n40:19.79 dBm BLE(1Mbps):0.04 dBm BLE(2Mbps):0.15 dBm
RF Function	2.4G Wi-Fi, BLE(1Mbps), BLE(2Mbps)
Operating Band/Frequency	2.4G Wi-Fi: 2412-2462 MHz(b/g/n20), 2422-2452 MHz(n40) BLE(1Mbps)/BLE(2Mbps): 2402-2480 MHz
Channel Number	2.4G Wi-Fi: 11(b/g/n20), 7(n40) BLE(1Mbps)/BLE(2Mbps): 40
Channel Separation	2.4G Wi-Fi: 5 MHz, BLE(1Mbps)/BLE(2Mbps): 2 MHz
Modulation Type	2.4G Wi-Fi: OFDM,DSSS BLE(1Mbps)/BLE(2Mbps): GFSK
Antenna Type	2.4G Wi-Fi: FPC Antenna BLE(1Mbps), BLE(2Mbps): FPC Antenna
*Maximum Antenna Gain	2.4G Wi-Fi: Chain0: -1.3 dBi, Chain1: -1.3 dBi BLE(1Mbps)/BLE(2Mbps): -1.3 dBi

*Adapter-1 Information:**Model: CK18W02U**Input: AC 100-240V~50/60Hz 0.5A**Output: DC 5.0V/3A, 9V/2A, 12V/1.5A**Adapter-2 Information:**Model: TPA-10120150UU**Input: AC 100-240V 50/60Hz 0.6A**Output: DC 3.6-6V/3A, 6-9V/2A, 9-12V/1.5A**Adapter-3 Information:**Model: TPA-23A050200UU01**Input: AC100-240V 50/60Hz 0.3A**Output:5.0V, 2.0A**Adapter-4 Information:**Model: UC13US**Input: AC100-240V 50/60Hz 0.35A**Output:5.0V, 2.0A**Note: The Maximum Antenna Gain was declared by the manufacturer.***All measurement and test data in this report was gathered from production sample serial number:**RKSA200706001-1 (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-07-06)*

Objective

This report is prepared on behalf of *Shanghai Sunmi Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS submissions with FCC ID: 2AH25TF701
FCC Part 22H/24E/27/90 PCB submissions with FCC ID: 2AH25TF701
FCC Part 15.407 NII submissions with FCC ID: 2AH25TF701
FCC Part 15.225 DXX submissions with FCC ID: 2AH25TF701
FCC Part 15B JBP submissions with FCC ID: 2AH25TF701

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, EUT was tested with Channel 3, 6 and 9.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For BLE mode, EUT was tested with channel 0, 19 and 39.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
18	2438	38	2478
19	2440	39	2480

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: QRCT3

Pre-scan with all the data rates, and the worst case was performed as below:


Mode	Data Rate	Channel	Power Level setting	
			Chain0	Chain1
802.11b	1 Mbps	Low	19.5	19.5
		Middle	19.5	19.5
		High	19.5	19.5
802.11g	6 Mbps	Low	17.5	17.5
		Middle	17.5	17.5
		High	17.5	17.5
802.11n-HT20	MCS0	Low	16.5	16.5
		Middle	16.5	16.5
		High	16.5	16.5
802.11n-HT40	MCS0	Low	16.5	16.5
		Middle	16.5	16.5
		High	16.5	16.5
BLE	1Mbps	Low	Default	
		Middle	Default	
		High	Default	
	2Mbps	Low	Default	
		Middle	Default	
		High	Default	

Note: The power level setting was declared by the applicant.


Duty Cycle:

Chain0:


802.11b Mode Middle Channel




802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel




802.11n-HT40 Mode Middle Channel




Chain1:


802.11b Mode Middle Channel




802.11g Mode Middle Channel




802.11n-HT20 Mode Middle Channel



802.11n-HT40 Mode Middle Channel




BLE(1Mbps) Mode Middle Channel



Date: 11.JUL.2020 01:56:11

BLE(2Mbps) Mode Middle Channel



Date: 11.JUL.2020 01:54:09

Chain	Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
Chain0	802.11b	100	/	/	0
	802.11g	100	/	/	0
	802.11n-HT20	100	/	/	0
	802.11n-HT40	100	/	/	0
Chain1	802.11b	100	/	/	0
	802.11g	100	/	/	0
	802.11n-HT20	100	/	/	0
	802.11n-HT40	100	/	/	0
/	BLE(1Mbps)	67.35	0.423	2.364	1.717
/	BLE(2Mbps)	37.56	0.237	4.219	4.253

Note: “x” means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
BOLD	Earphone	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	EUT	Adapter
Power Cable	1.0	Adapter	LISN/AC source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b)(1) & §2.1093	RF Exposure Information	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-11-27	2020-11-26
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2020-11-27	2021-11-26
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2017-08-05	2020-08-04
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2020-08-05	2023-08-04
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2020-04-01	2021-03-31
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2021-04-01	2022-03-31
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3115	9311-4159	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	2516	2020-01-07	2023-01-06
A.H.Systems,inc	Amplifier	PAM-0118P	512	2019-08-14	2020-08-13
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-08-14	2021-08-13
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
EM Electronics Corporation	Amplifier	EM18G40G	060726	2021-03-22	2022-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14

RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-11-27	2020-11-26
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2020-11-27	2021-11-26
Rohde & Schwarz	Spectrum Analyzer	FSU26	100131	2019-07-28	2020-07-27
Rohde & Schwarz	Spectrum Analyzer	FSU26	100131	2020-07-28	2021-07-27
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Agilent	Power Meter	N1912A	MY5000492	2019-11-18	2020-11-17
Agilent	Power Meter	N1912A	MY5000492	2020-11-18	2021-11-17
Agilent	Power Sensor	N1921A	MY54210024	2019-11-18	2020-11-17
Agilent	Power Sensor	N1921A	MY54210024	2020-11-18	2021-11-17
Sunmi	RF Cable	Sunmi C01	C01	Each Time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03 -101746-zn	2020-07-28	2021-07-27
Rohde & Schwarz	LISN	ENV216	101115	2020-11-27	2021-11-26
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC § 1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below
-

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Test Result

For Wi-Fi:

Compliant, please refer to the SAR report: RKSA200706001-20A

For BLE:

For worst case:

Mode	Frequency Range (MHz)	Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE(1Mbps)	2402-2480	0.50	1.12	5.0	0.4	3.0	Yes
BLE(2Mbps)	2402-2480	0.50	1.12	5.0	0.4	3.0	Yes

Result: So the standalone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has two FPC antennas for Wi-Fi, the antenna gain is -1.3dBi for chain0 and -1.3dBi for chain1; and the EUT has an FPC antenna for BLE, the antenna gain is -1.3dBi; The antennas are permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	24.5
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Stone Zhang on 2021-06-04.


Test Result: Compliant.

Note: Adapter1/2 /3/4 are all have been tested, the worst Adapter4 data were recorded in this report.

For Wi-Fi Mode:

EUT operation mode: Transmitting in 802.11n-HT40 mode low channel (worst case)


AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.181	6.80	19.83	26.63	54.43	-27.80	Average
2	0.181	20.90	19.83	40.73	64.43	-23.70	QP
3	0.226	4.20	19.82	24.02	52.61	-28.59	Average
4	0.226	20.30	19.82	40.12	62.61	-22.49	QP
5	0.271	7.70	19.82	27.52	51.07	-23.55	Average
6	0.271	20.40	19.82	40.22	61.07	-20.85	QP
7	0.317	5.20	19.82	25.02	49.79	-24.77	Average
8	0.317	19.50	19.82	39.32	59.79	-20.47	QP
9	0.408	7.30	19.74	27.04	47.68	-20.64	Average
10	0.408	21.40	19.74	41.14	57.68	-16.54	QP
11	0.594	13.80	19.75	33.55	46.00	-12.45	Average
12	0.594	24.70	19.75	44.45	56.00	-11.55	QP

AC 120V/60 Hz, Neutral

Date: 2021-06-04



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.180	3.40	19.83	23.23	54.47	-31.24	Average
2	0.180	18.80	19.83	38.63	64.47	-25.84	QP
3	0.226	2.50	19.82	22.32	52.61	-30.29	Average
4	0.226	18.80	19.82	38.62	62.61	-23.99	QP
5	0.270	1.80	19.82	21.62	51.11	-29.49	Average
6	0.270	15.90	19.82	35.72	61.11	-25.39	QP
7	0.317	1.90	19.82	21.72	49.79	-28.07	Average
8	0.317	17.80	19.82	37.62	59.79	-22.17	QP
9	0.361	0.60	19.79	20.39	48.71	-28.32	Average
10	0.361	17.10	19.79	36.89	58.71	-21.82	QP
11	0.559	5.80	19.75	25.55	46.00	-20.45	Average
12	0.559	20.30	19.75	40.05	56.00	-15.95	QP

Note:


1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBuV) + Factor (dB) - Limit (dBuV)

For BLE Mode:

EUT operation mode: Transmitting in BLE(2Mbps) mode high channel (worst case)


AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.181	6.50	19.83	26.33	54.43	-28.10	Average
2	0.181	20.90	19.83	40.73	64.43	-23.70	QP
3	0.227	5.20	19.82	25.02	52.56	-27.54	Average
4	0.227	20.80	19.82	40.62	62.56	-21.94	QP
5	0.271	7.30	19.82	27.12	51.07	-23.95	Average
6	0.271	20.30	19.82	40.12	61.07	-20.95	QP
7	0.320	7.60	19.82	27.42	49.71	-22.29	Average
8	0.320	19.90	19.82	39.72	59.71	-19.99	QP
9	0.408	7.00	19.74	26.74	47.68	-20.94	Average
10	0.408	21.30	19.74	41.04	57.68	-16.64	QP
11	0.594	13.60	19.75	33.35	46.00	-12.65	Average
12	0.594	24.60	19.75	44.35	56.00	-11.65	QP

AC 120V/60 Hz, Neutral

Date: 2021-06-04



		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.181	4.10	19.83	23.93	54.43	-30.50	Average
2	0.181	19.20	19.83	39.03	64.43	-25.40	QP
3	0.227	3.50	19.82	23.32	52.56	-29.24	Average
4	0.227	18.60	19.82	38.42	62.56	-24.14	QP
5	0.273	4.00	19.82	23.82	51.03	-27.21	Average
6	0.273	15.80	19.82	35.62	61.03	-25.41	QP
7	0.317	1.80	19.82	21.62	49.79	-28.17	Average
8	0.317	17.40	19.82	37.22	59.79	-22.57	QP
9	0.362	2.50	19.79	22.29	48.67	-26.38	Average
10	0.362	17.80	19.79	37.59	58.67	-21.08	QP
11	0.562	5.40	19.75	25.15	46.00	-20.85	Average
12	0.562	19.30	19.75	39.05	56.00	-16.95	QP

Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)


2) Over Limit (dB) = Read level (dBUV) + Factor (dB) - Limit (dBUV)

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection mode for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	21.1~24.5 °C
Relative Humidity:	50~52 %
ATM Pressure:	101.2~101.5 kPa

The testing was performed by Stone Zhang from 2020-07-11 to 2021-05-07.

Test Result: Compliant.


EUT operation mode: Transmitting

For Wi-Fi Mode: (Power by Adapter 4 worst case)

Spurious Emission Test:

30MHz-1GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **low channel of 802.11n-HT40 mode in Z-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
36.061700	27.19	100.0	V	89.0	-7.1	40.00	12.81
64.556150	21.72	120.0	V	286.0	-15.7	40.00	18.28
95.237300	20.91	150.0	V	89.0	-15.5	43.50	22.59
185.806650	19.16	200.0	V	291.0	-13.0	43.50	24.34
269.341700	20.92	150.0	H	0.0	-11.5	46.00	25.08
326.098600	20.68	100.0	H	51.0	-10.1	46.00	25.32

1GHz-18GHz: (Power by Adapter 4 worst case)**802.11b Mode (Chain0):**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1579.700000	38.49	---	200.0	V	286.0	-16.1	74.00	35.51
1579.700000	---	27.89	200.0	V	286.0	-16.1	54.00	26.11
3454.800000	40.88	---	200.0	V	312.0	-8.9	74.00	33.12
3454.800000	---	34.06	200.0	V	312.0	-8.9	54.00	19.94
4824.000000	42.26	---	100.0	H	40.0	-5.5	74.00	31.74
4824.000000	---	37.33	100.0	H	40.0	-5.5	54.00	16.67
7303.600000	---	35.31	200.0	H	262.0	0.6	54.00	18.69
7303.600000	45.35	---	200.0	H	262.0	0.6	74.00	28.65
13797.600000	---	40.63	100.0	H	142.0	6.0	54.00	13.37
13797.600000	50.22	---	100.0	H	142.0	6.0	74.00	23.78
17826.600000	---	44.26	100.0	H	78.0	8.8	54.00	9.74
17826.600000	53.71	---	100.0	H	78.0	8.8	74.00	20.29

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1513.400000	---	25.83	100.0	V	290.0	-16.3	54.00	28.17
1513.400000	35.29	---	100.0	V	290.0	-16.3	74.00	38.71
3454.800000	---	34.43	200.0	V	319.0	-8.9	54.00	19.57
3454.800000	40.46	---	200.0	V	319.0	-8.9	74.00	33.54
4874.000000	---	31.61	100.0	V	315.0	-5.4	54.00	22.39
4874.000000	38.55	---	100.0	V	315.0	-5.4	74.00	35.45
7947.900000	---	37.04	100.0	V	351.0	1.7	54.00	16.96
7947.900000	46.04	---	100.0	V	351.0	1.7	74.00	27.96
13886.000000	---	41.14	100.0	V	340.0	6.0	54.00	12.86
13886.000000	51.02	---	100.0	V	340.0	6.0	74.00	22.98
17814.700000	---	45.91	200.0	V	72.0	8.8	54.00	8.09
17814.700000	54.31	---	200.0	V	72.0	8.8	74.00	19.69

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1554.200000	34.88	---	200.0	V	297.0	-16.2	74.00	39.12
1554.200000	---	24.32	200.0	V	297.0	-16.2	54.00	29.68
3454.800000	40.34	---	200.0	V	311.0	-8.9	74.00	33.66
3454.800000	---	34.28	200.0	V	311.0	-8.9	54.00	19.72
4924.000000	---	37.11	100.0	H	27.0	-5.3	54.00	16.89
4924.000000	42.23	---	100.0	H	27.0	-5.3	74.00	31.77
9846.800000	47.16	---	200.0	V	324.0	2.0	74.00	26.84
9848.500000	---	38.86	200.0	V	324.0	2.0	54.00	15.14
13865.600000	---	40.82	200.0	H	7.0	6.0	54.00	13.18
13865.600000	50.54	---	200.0	H	7.0	6.0	74.00	23.46
17799.400000	53.26	---	100.0	H	78.0	8.8	74.00	20.74
17799.400000	---	44.10	100.0	H	78.0	8.8	54.00	9.90

802.11g Mode (Chain0):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1765.000000	38.51	---	100.0	H	0.0	-15.4	74.00	35.49
1765.000000	---	33.01	100.0	H	0.0	-15.4	54.00	20.99
3454.800000	39.74	---	200.0	V	324.0	-8.9	74.00	34.26
3454.800000	---	33.75	200.0	V	324.0	-8.9	54.00	20.25
4824.000000	---	31.23	200.0	H	25.0	-5.5	54.00	22.77
4824.000000	39.41	---	200.0	H	25.0	-5.5	74.00	34.59
7818.700000	---	36.37	100.0	V	0.0	1.5	54.00	17.63
7818.700000	46.21	---	100.0	V	0.0	1.5	74.00	27.79
13960.800000	---	39.80	200.0	H	194.0	6.1	54.00	14.20
13960.800000	49.81	---	200.0	H	194.0	6.1	74.00	24.19
17755.200000	53.57	---	200.0	H	130.0	8.8	74.00	20.43
17755.200000	---	44.69	200.0	H	130.0	8.8	54.00	9.31

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1593.300000	---	23.26	150.0	V	288.0	-16.0	54.00	30.74
1593.300000	33.07	---	150.0	V	288.0	-16.0	74.00	40.93
3454.800000	39.84	---	200.0	V	2.0	-8.9	74.00	34.16
3454.800000	---	33.64	200.0	V	2.0	-8.9	54.00	20.36
4874.000000	---	30.13	200.0	V	155.0	-5.4	54.00	23.87
4874.000000	37.57	---	200.0	V	155.0	-5.4	74.00	36.43
7857.800000	---	37.53	200.0	H	249.0	1.6	54.00	16.47
7857.800000	45.05	---	200.0	H	249.0	1.6	74.00	28.95
13726.200000	---	38.77	150.0	H	4.0	5.9	54.00	15.23
13726.200000	49.90	---	150.0	H	4.0	5.9	74.00	24.10
17464.500000	---	43.79	150.0	V	288.0	8.8	54.00	10.21
17464.500000	53.77	---	150.0	V	288.0	8.8	74.00	20.23

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1731.000000	33.03	---	200.0	V	175.0	-15.5	74.00	40.97
1731.000000	---	23.74	200.0	V	175.0	-15.5	54.00	30.26
3454.800000	39.31	---	150.0	V	314.0	-8.9	74.00	34.69
3454.800000	---	32.17	150.0	V	314.0	-8.9	54.00	21.83
4924.000000	39.98	---	200.0	V	332.0	-5.3	74.00	34.02
4924.000000	---	33.11	200.0	V	332.0	-5.3	54.00	20.89
7205.000000	---	36.43	200.0	V	292.0	0.4	54.00	17.57
7205.000000	44.94	---	200.0	V	292.0	0.4	74.00	29.06
13064.900000	---	40.34	150.0	V	301.0	5.3	54.00	13.66
13064.900000	48.75	---	150.0	V	301.0	5.3	74.00	25.25
17734.800000	---	44.44	200.0	H	345.0	8.8	54.00	9.56
17734.800000	53.77	---	200.0	H	345.0	8.8	74.00	20.23

802.11b Mode (Chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1617.100000	---	23.20	100.0	H	65.0	-15.9	54.00	30.80
1617.100000	34.77	---	100.0	H	65.0	-15.9	74.00	39.23
3454.800000	---	34.01	200.0	V	311.0	-8.9	54.00	19.99
3454.800000	39.78	---	200.0	V	311.0	-8.9	74.00	34.22
4824.000000	---	37.97	100.0	H	1.0	-5.5	54.00	16.03
4824.000000	43.09	---	100.0	H	1.0	-5.5	74.00	30.91
7840.800000	---	37.20	100.0	V	249.0	1.6	54.00	16.80
7840.800000	45.68	---	100.0	V	249.0	1.6	74.00	28.32
12034.700000	---	37.94	200.0	H	324.0	3.8	54.00	16.06
12034.700000	47.70	---	200.0	H	324.0	3.8	74.00	26.30
17287.700000	---	42.99	200.0	V	1.0	8.2	54.00	11.01
17287.700000	52.18	---	200.0	V	1.0	8.2	74.00	21.82

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1593.300000	36.69	---	200.0	V	257.0	-16.0	74.00	37.31
1593.300000	---	24.57	200.0	V	257.0	-16.0	54.00	29.43
3454.800000	40.78	---	200.0	V	310.0	-8.9	74.00	33.22
3454.800000	---	33.37	200.0	V	310.0	-8.9	54.00	20.63
4874.000000	---	31.65	100.0	H	0.0	-5.4	54.00	22.35
4874.000000	38.59	---	100.0	H	0.0	-5.4	74.00	35.41
7873.100000	---	36.13	200.0	V	166.0	1.6	54.00	17.87
7873.100000	45.60	---	200.0	V	166.0	1.6	74.00	28.40
13180.500000	---	40.68	200.0	V	11.0	5.4	54.00	13.32
13180.500000	49.67	---	200.0	V	11.0	5.4	74.00	24.33
17682.100000	---	43.50	100.0	V	308.0	8.9	54.00	10.50
17682.100000	53.07	---	100.0	V	308.0	8.9	74.00	20.93

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1530.400000	37.21	---	200.0	V	279.0	-16.2	74.00	36.79
1530.400000	---	23.69	200.0	V	279.0	-16.2	54.00	30.31
3454.800000	41.19	---	200.0	V	319.0	-8.9	74.00	32.81
3454.800000	---	35.04	200.0	V	319.0	-8.9	54.00	18.96
4924.000000	43.55	---	100.0	H	353.0	-5.3	74.00	30.45
4924.000000	---	37.57	100.0	H	353.0	-5.3	54.00	16.43
6536.900000	---	34.11	100.0	H	73.0	-1.1	54.00	19.89
6536.900000	43.61	---	100.0	H	73.0	-1.1	74.00	30.39
9848.500000	46.89	---	100.0	V	325.0	2.0	74.00	27.11
9848.500000	---	39.52	100.0	V	325.0	2.0	54.00	14.48
17779.000000	---	44.52	200.0	V	292.0	8.8	54.00	9.48
17779.000000	53.67	---	200.0	V	292.0	8.8	74.00	20.33

802.11g Mode (Chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1768.400000	---	29.33	200.0	V	200.0	-15.3	54.00	24.67
1768.400000	35.24	---	200.0	V	200.0	-15.3	74.00	38.76
3454.800000	---	33.79	200.0	V	319.0	-8.9	54.00	20.21
3454.800000	40.76	---	200.0	V	319.0	-8.9	74.00	33.24
4824.000000	---	31.30	200.0	V	0.0	-5.5	54.00	22.70
4824.000000	39.65	---	200.0	V	0.0	-5.5	74.00	34.35
7924.100000	---	36.13	200.0	H	0.0	1.7	54.00	17.87
7924.100000	45.25	---	200.0	H	0.0	1.7	74.00	28.75
13852.000000	---	41.82	100.0	V	346.0	6.0	54.00	12.18
13852.000000	50.42	---	100.0	V	346.0	6.0	74.00	23.58
17797.700000	---	45.66	100.0	H	161.0	8.8	54.00	8.34
17797.700000	53.04	---	100.0	H	161.0	8.8	74.00	20.96

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1540.600000	33.18	---	200.0	V	292.0	-16.2	74.00	40.82
1540.600000	---	23.60	200.0	V	292.0	-16.2	54.00	30.40
3454.800000	38.79	---	150.0	V	349.0	-8.9	74.00	35.21
3454.800000	---	33.48	150.0	V	349.0	-8.9	54.00	20.52
4874.000000	---	29.87	200.0	V	0.0	-5.4	54.00	24.13
4874.000000	37.90	---	200.0	V	0.0	-5.4	74.00	36.10
9307.900000	---	36.01	200.0	H	345.0	2.0	54.00	17.99
9307.900000	46.58	---	200.0	H	345.0	2.0	74.00	27.42
13908.100000	---	40.98	150.0	V	7.0	6.1	54.00	13.02
13908.100000	49.90	---	150.0	V	7.0	6.1	74.00	24.10
17326.800000	---	42.66	150.0	V	338.0	8.3	54.00	11.34
17326.800000	53.39	---	150.0	V	338.0	8.3	74.00	20.61

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1535.500000	32.31	---	150.0	V	198.0	-16.2	74.00	41.69
1535.500000	---	22.90	150.0	V	198.0	-16.2	54.00	31.10
3454.800000	---	34.76	200.0	V	310.0	-8.9	54.00	19.24
3454.800000	41.06	---	200.0	V	310.0	-8.9	74.00	32.94
4924.000000	---	30.32	150.0	H	53.0	-5.3	54.00	23.68
4924.000000	38.51	---	150.0	H	53.0	-5.3	74.00	35.49
6870.100000	---	34.01	150.0	V	211.0	-0.4	54.00	19.99
6870.100000	43.81	---	150.0	V	211.0	-0.4	74.00	30.19
12179.200000	---	38.35	200.0	H	275.0	3.5	54.00	15.65
12179.200000	46.92	---	200.0	H	275.0	3.5	74.00	27.08
17777.300000	---	44.60	150.0	H	15.0	8.8	54.00	9.40
17777.300000	53.79	---	150.0	H	15.0	8.8	74.00	20.21

802.11n-HT20 Mode (Chain0+Chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1688.500000	31.88	---	150.0	V	148.0	-15.6	74.00	42.12
1688.500000	---	23.02	150.0	V	148.0	-15.6	54.00	30.98
3454.800000	---	33.97	200.0	V	6.0	-8.9	54.00	20.03
3454.800000	39.17	---	200.0	V	6.0	-8.9	74.00	34.83
4824.000000	39.08	---	200.0	H	24.0	-5.5	74.00	34.92
4824.000000	---	33.88	200.0	H	24.0	-5.5	54.00	20.12
6739.200000	---	33.78	200.0	V	6.0	-0.6	54.00	20.22
6739.200000	43.28	---	200.0	V	6.0	-0.6	74.00	30.72
13955.700000	---	40.96	150.0	V	0.0	6.1	54.00	13.04
13955.700000	50.42	---	150.0	V	0.0	6.1	74.00	23.58
17807.900000	---	43.43	200.0	H	274.0	8.8	54.00	10.57
17807.900000	53.66	---	200.0	H	274.0	8.8	74.00	20.34

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1555.900000	32.02	---	150.0	V	288.0	-16.1	74.00	41.98
1555.900000	---	23.46	150.0	V	288.0	-16.1	54.00	30.54
3454.800000	---	33.57	200.0	V	311.0	-8.9	54.00	20.43
3454.800000	39.60	---	200.0	V	311.0	-8.9	74.00	34.40
4874.000000	---	30.11	150.0	V	211.0	-5.4	54.00	23.89
4874.000000	39.55	---	150.0	V	211.0	-5.4	74.00	34.45
7154.000000	---	35.28	150.0	V	25.0	0.3	54.00	18.72
7154.000000	45.49	---	150.0	V	25.0	0.3	74.00	28.51
9821.300000	---	36.75	150.0	H	4.0	2.0	54.00	17.25
9821.300000	46.50	---	150.0	H	4.0	2.0	74.00	27.50
17794.300000	---	45.00	200.0	V	39.0	8.8	54.00	9.00
17794.300000	53.61	---	200.0	V	39.0	8.8	74.00	20.39

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1273.700000	31.96	---	150.0	H	283.0	-17.6	74.00	42.04
1273.700000	---	21.97	150.0	H	283.0	-17.6	54.00	32.03
3454.800000	39.29	---	200.0	V	310.0	-8.9	74.00	34.71
3454.800000	---	32.88	200.0	V	310.0	-8.9	54.00	21.12
4924.000000	38.83	---	200.0	V	0.0	-5.3	74.00	35.17
4924.000000	---	31.61	200.0	V	0.0	-5.3	54.00	22.39
8760.500000	---	36.10	200.0	H	237.0	1.6	54.00	17.90
8760.500000	46.28	---	200.0	H	237.0	1.6	74.00	27.72
13075.100000	---	39.86	150.0	H	1.0	5.3	54.00	14.14
13075.100000	49.51	---	150.0	H	1.0	5.3	74.00	24.49
17687.200000	---	44.35	200.0	V	358.0	8.9	54.00	9.65
17687.200000	53.73	---	200.0	V	358.0	8.9	74.00	20.27

802.11n-HT40 Mode (Chain0+Chain1):


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2422MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1712.300000	32.49	---	200.0	V	21.0	-15.6	74.00	41.51
1712.300000	---	23.88	200.0	V	21.0	-15.6	54.00	30.12
3454.800000	---	33.20	200.0	V	305.0	-8.9	54.00	20.80
3454.800000	39.33	---	200.0	V	305.0	-8.9	74.00	34.67
4844.000000	---	31.46	200.0	H	25.0	-5.5	54.00	22.54
4844.000000	40.44	---	200.0	H	25.0	-5.5	74.00	33.56
6671.200000	---	33.71	150.0	V	263.0	-0.8	54.00	20.29
6671.200000	43.85	---	150.0	V	263.0	-0.8	74.00	30.15
12646.700000	---	35.93	150.0	V	212.0	3.6	54.00	18.07
12646.700000	46.49	---	150.0	V	212.0	3.6	74.00	27.51
17865.700000	---	44.18	150.0	V	275.0	8.8	54.00	9.82
17865.700000	54.50	---	150.0	V	275.0	8.8	74.00	19.50

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1559.300000	32.23	---	150.0	H	292.0	-16.1	74.00	41.77
1559.300000	---	23.10	150.0	H	292.0	-16.1	54.00	30.90
3454.800000	---	32.97	150.0	V	300.0	-8.9	54.00	21.03
3454.800000	39.18	---	150.0	V	300.0	-8.9	74.00	34.82
4874.000000	---	30.06	200.0	V	127.0	-5.4	54.00	23.94
4874.000000	37.63	---	200.0	V	127.0	-5.4	74.00	36.37
8017.600000	---	36.11	150.0	H	72.0	1.8	54.00	17.89
8017.600000	46.05	---	150.0	H	72.0	1.8	74.00	27.95
13012.200000	---	39.92	150.0	V	0.0	5.2	54.00	14.08
13012.200000	48.66	---	150.0	V	0.0	5.2	74.00	25.34
17882.700000	---	44.67	200.0	H	237.0	8.8	54.00	9.33
17882.700000	53.25	---	200.0	H	237.0	8.8	74.00	20.75

High Channel: 2452MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1260.100000	31.59	---	150.0	V	269.0	-17.7	74.00	42.41
1260.100000	---	22.34	150.0	V	269.0	-17.7	54.00	31.66
3454.800000	---	33.97	200.0	V	0.0	-8.9	54.00	20.03
3454.800000	40.33	---	200.0	V	0.0	-8.9	74.00	33.67
4925.300000	---	30.60	150.0	V	81.0	-5.3	54.00	23.40
4925.300000	38.56	---	150.0	V	81.0	-5.3	74.00	35.44
7242.400000	---	35.16	200.0	V	0.0	0.5	54.00	18.84
7242.400000	44.06	---	200.0	V	0.0	0.5	74.00	29.94
9831.500000	---	36.23	200.0	V	334.0	2.0	54.00	17.77
9831.500000	46.14	---	200.0	V	334.0	2.0	74.00	27.86
17666.800000	---	43.59	150.0	V	55.0	8.9	54.00	10.41
17666.800000	53.18	---	150.0	V	55.0	8.9	74.00	20.82

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 and 802.11n-HT40 modes of operation in the X,Y and Z axes of orientation, the worst case **low channel of 802.11n-HT40 mode in Z-axis of orientation** was recorded

Horizontal

Date: 7.MAY.2021 10:31:17

Vertical

Date: 7.MAY.2021 10:41:18

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

802.11b Mode (Chain0): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	51.84	---	150.0	H	45.0	-2.9	74.00	22.16
2390.000000	---	42.93	150.0	H	45.0	-2.9	54.00	11.07
High Channel: 2462MHz								
2483.500000	45.49	---	200.0	H	308.0	-2.5	74.00	28.51
2483.500000	---	37.79	200.0	H	308.0	-2.5	54.00	16.21

802.11g Mode (Chain0): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	51.98	---	150.0	H	45.0	-2.9	74.00	22.02
2390.000000	---	43.79	150.0	H	45.0	-2.9	54.00	10.21
High Channel: 2462MHz								
2483.500000	48.57	---	150.0	H	38.0	-2.5	74.00	25.43
2483.500000	---	39.12	150.0	H	38.0	-2.5	54.00	14.88

802.11b Mode (Chain1): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	45.09	---	150.0	V	107.0	-2.9	74.00	28.91
2390.000000	---	37.68	150.0	V	107.0	-2.9	54.00	16.32
High Channel: 2462MHz								
2483.500000	45.52	---	150.0	V	298.0	-2.5	74.00	28.48
2483.500000	---	37.36	150.0	V	298.0	-2.5	54.00	16.64

802.11g Mode (Chain1): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	42.13	150.0	H	33.0	-2.9	54.00	11.87
2390.000000	49.32	---	150.0	H	33.0	-2.9	74.00	24.68
High Channel: 2462MHz								
2483.500000	---	38.24	200.0	H	49.0	-2.5	54.00	15.76
2483.500000	47.98	---	200.0	H	49.0	-2.5	74.00	26.02

802.11n-HT20 Mode (Chain0+Chain1): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.000000	---	43.44	150.0	H	309.0	-2.9	54.00	10.56
2390.000000	50.97	---	150.0	H	309.0	-2.9	74.00	23.03
High Channel: 2462MHz								
2483.500000	46.98	---	150.0	H	28.0	-2.5	74.00	27.02
2483.500000	---	39.35	150.0	H	28.0	-2.5	54.00	14.65

802.11n-HT40 Mode (Chain0+Chain1): (Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2390.000000	---	42.25	150.0	H	36.0	-2.9	54.00	11.75
2390.000000	50.13	---	150.0	H	36.0	-2.9	74.00	23.87
High Channel: 2452MHz								
2483.500000	---	42.01	200.0	H	37.0	-2.5	54.00	11.99
2483.500000	50.60	---	200.0	H	37.0	-2.5	74.00	23.40

For BLE Mode: (Power by Adapter 4 worst case)**Spurious Emission Test:****30MHz-1GHz**

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case BLE(2Mbps) mode high channel of operation in the Z axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
34.727450	28.58	100.0	V	199.0	-7.1	40.00	11.42
63.341500	22.59	150.0	V	225.0	-15.4	40.00	17.41
99.472250	21.95	110.0	V	138.0	-14.9	43.50	21.55
108.573400	21.26	200.0	V	89.0	-13.1	43.50	22.24
123.357590	17.09	150.0	V	166.0	-10.9	43.50	26.41
269.595300	18.22	100.0	V	263.0	-11.5	46.00	27.78

1GHz-18GHz: (Power by Adapter 4 worst case)**BLE(1Mbps) mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Z-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1593.300000	---	31.00	150.0	V	134.0	-16.0	54.00	23.00
1593.300000	39.31	---	150.0	V	134.0	-16.0	74.00	34.69
3031.500000	---	28.98	200.0	H	141.0	-10.0	54.00	25.02
3031.500000	37.53	---	200.0	H	141.0	-10.0	74.00	36.47
4804.000000	---	32.02	200.0	H	26.0	-5.6	54.00	21.98
4804.000000	38.70	---	200.0	H	26.0	-5.6	74.00	35.30
5731.100000	---	34.14	200.0	V	316.0	-3.5	54.00	19.86
5731.100000	43.82	---	200.0	V	316.0	-3.5	74.00	30.18
8415.400000	---	37.75	150.0	H	36.0	1.4	54.00	16.25
8415.400000	46.87	---	150.0	H	36.0	1.4	74.00	27.13
17661.700000	---	47.14	150.0	V	0.0	8.9	54.00	6.86
17661.700000	55.17	---	150.0	V	0.0	8.9	74.00	18.83

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1596.700000	39.81	---	200.0	H	59.0	-16.0	74.00	34.19
1596.700000	---	33.64	200.0	H	59.0	-16.0	54.00	20.36
2856.400000	---	30.48	150.0	V	190.0	-10.8	54.00	23.52
2856.400000	37.74	---	150.0	V	190.0	-10.8	74.00	36.26
4880.000000	---	32.88	150.0	V	25.0	-5.4	54.00	21.12
4880.000000	39.23	---	150.0	V	25.0	-5.4	74.00	34.77
6674.600000	44.80	---	150.0	V	13.0	-0.8	74.00	29.20
6674.600000	---	36.85	150.0	V	13.0	-0.8	54.00	17.15
12196.200000	---	40.50	200.0	H	46.0	3.5	54.00	13.50
12196.200000	48.52	---	200.0	H	46.0	3.5	74.00	25.48
17602.200000	---	47.44	200.0	V	168.0	8.9	54.00	6.56
17602.200000	54.78	---	200.0	V	168.0	8.9	74.00	19.22

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1545.700000	---	29.84	150.0	V	114.0	-16.2	54.00	24.16
1545.700000	42.65	---	150.0	V	114.0	-16.2	74.00	31.35
3050.200000	---	28.35	150.0	V	20.0	-10.0	54.00	25.65
3050.200000	37.57	---	150.0	V	20.0	-10.0	74.00	36.43
4960.000000	---	33.47	200.0	V	0.0	-5.3	54.00	20.53
4960.000000	40.05	---	200.0	V	0.0	-5.3	74.00	33.95
7784.700000	46.96	---	150.0	H	169.0	1.5	74.00	27.04
7784.700000	---	39.33	150.0	H	169.0	1.5	54.00	14.67
11567.200000	---	39.50	150.0	H	90.0	2.9	54.00	14.50
11567.200000	48.74	---	150.0	H	90.0	2.9	74.00	25.26
17675.300000	---	46.10	150.0	H	245.0	8.9	54.00	7.90
17675.300000	55.45	---	150.0	H	245.0	8.9	74.00	18.55

18GHz-25GHz


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high** channel of operation in the Z axis of orientation was recorded)

Horizontal



Date: 7.MAY.2021 10:56:25

Vertical



Date: 7.MAY.2021 11:10:23


BLE(2Mbps) mode: (Power by Adapter 4 worst case)*(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1595.000000	39.06	---	200.0	V	121.0	-16.0	74.00	34.94
1595.000000	---	31.82	200.0	V	121.0	-16.0	54.00	22.18
3279.700000	---	29.51	200.0	V	302.0	-9.4	54.00	24.49
3279.700000	38.68	---	200.0	V	302.0	-9.4	74.00	35.32
4804.000000	---	32.54	200.0	V	302.0	-5.6	54.00	21.46
4804.000000	39.33	---	200.0	V	302.0	-5.6	74.00	34.67
6275.100000	45.12	---	200.0	H	154.0	-2.0	74.00	28.88
6275.100000	---	35.22	200.0	H	154.0	-2.0	54.00	18.78
11490.700000	47.64	---	150.0	H	88.0	2.8	74.00	26.36
11490.700000	---	38.81	150.0	H	88.0	2.8	54.00	15.19
17677.000000	---	46.79	200.0	H	166.0	8.9	54.00	7.21
17677.000000	54.80	---	200.0	H	166.0	8.9	74.00	19.20

Middle Channel: 2440MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1595.000000	38.17	---	200.0	H	65.0	-16.0	74.00	35.83
1595.000000	---	31.26	200.0	H	65.0	-16.0	54.00	22.74
3509.200000	---	29.75	150.0	H	0.0	-8.8	54.00	24.25
3509.200000	38.98	---	150.0	H	0.0	-8.8	74.00	35.02
4880.000000	---	32.21	150.0	V	19.0	-5.4	54.00	21.79
4880.000000	40.68	---	150.0	V	19.0	-5.4	74.00	33.32
7728.600000	46.34	---	200.0	V	91.0	1.4	74.00	27.66
7728.600000	---	37.83	200.0	V	91.0	1.4	54.00	16.17
13136.300000	51.50	---	200.0	V	78.0	5.3	74.00	22.50
13136.300000	---	42.17	200.0	V	78.0	5.3	54.00	11.83
17784.100000	---	45.42	150.0	V	100.0	8.8	54.00	8.58
17784.100000	55.42	---	150.0	V	100.0	8.8	74.00	18.58

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1595.000000	---	32.22	150.0	H	63.0	-16.0	54.00	21.78
1595.000000	38.50	---	150.0	H	63.0	-16.0	74.00	35.50
3116.500000	---	29.38	200.0	V	348.0	-9.8	54.00	24.62
3116.500000	37.80	---	200.0	V	348.0	-9.8	74.00	36.20
4960.000000	39.67	---	150.0	H	181.0	-5.3	74.00	34.33
4960.000000	---	32.62	150.0	H	181.0	-5.3	54.00	21.38
7194.800000	---	38.51	150.0	V	12.0	0.4	54.00	15.49
7194.800000	46.65	---	150.0	V	12.0	0.4	74.00	27.35
10098.400000	---	37.38	150.0	H	194.0	2.0	54.00	16.62
10098.400000	46.90	---	150.0	H	194.0	2.0	74.00	27.10
17675.300000	54.56	---	200.0	H	145.0	8.9	74.00	19.44
17675.300000	---	47.16	200.0	H	145.0	8.9	54.00	6.84

18GHz-25GHz

(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case **high** channel of operation in the Z axis of orientation was recorded)

Horizontal

Date: 7.MAY.2021 11:21:16

Vertical

Date: 7.MAY.2021 11:33:52

Restricted Bands Emissions Test:*(Pre-scan in the X,Y and Z axes of orientation, the worst case Z-axis of orientation was recorded)*

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

BLE(1Mbps) mode:

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	---	36.68	200.0	V	356.0	-2.9	54.00	17.32
2390.000000	44.90	---	200.0	V	356.0	-2.9	74.00	29.10
High Channel: 2480MHz								
2483.500000	---	37.72	200.0	V	225.0	-2.5	54.00	16.28
2483.500000	43.31	---	200.0	V	225.0	-2.5	74.00	30.69

BLE(2Mbps) mode:

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	42.46	---	200.0	H	277.0	-2.9	74.00	31.54
2390.000000	---	36.99	200.0	H	277.0	-2.9	54.00	17.01
High Channel: 2480MHz								
2483.500000	---	36.37	150.0	H	49.0	-2.5	54.00	17.63
2483.500000	45.73	---	150.0	H	49.0	-2.5	74.00	28.27

Chain0:

Ref Lvl -50.07 dBm
20 dBm 6.58525050 GHz

RBW 100 kHz
VBW 300 kHz
SWT 6.4 s

RF Att 20 dB
Unit dBm

11 dB Offset
▼1 [T1] -50.07 dBm
6.58525050 GHz

-D1 5.06 dBm
-14.14 dBm

1

Center 12.515 GHz
2.497 GHz/
Span 24.97 GHz

Date: 16.APR.2021 14:53:28

Ref Lvl -49.14 dBm
20 dBm 6.58525050 GHz

RBW 100 kHz
VBW 300 kHz
SWT 6.4 s

RF Att 20 dB
Unit dBm



11 dB Offset
▼1 [T1]
-49.14 dBm
6.58525050 GHz

-D1 5.39 dBm
-14.61 dBm


1

Start 30 MHz 2.497 GHz/ Stop 25 GHz


Date: 16.APR.2021 14:21:44

802.11b Mode High Channel**802.11g Mode Low Channel**


802.11g Mode Middle Channel




802.11g Mode High Channel





802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel**802.11n-HT40 Mode Low Channel**

802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel






Chain1:



802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel**802.11g Mode Low Channel**



802.11g Mode Middle Channel**802.11g Mode High Channel**

802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel






802.11n-HT20 Mode High Channel**802.11n-HT40 Mode Low Channel**

802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel






BLE(1Mbps) Mode Low Channel**BLE(1Mbps) Mode Middle Channel**

BLE(1Mbps) Mode High Channel



BLE(2Mbps) Mode Low Channel



BLE(2Mbps) Mode Middle Channel**BLE(2Mbps) Mode High Channel**

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	24.3-24.7 °C
Relative Humidity:	45-50 %
ATM Pressure:	101.3-101.5 kPa

The testing was performed by Stone Zhang from 2020-07-11 to 2021-04-30.

Test Result: Compliant.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)		Limit (kHz)
		Chain0	Chain1	
802.11b mode				
Low	2412	8.016	8.096	≥500
Middle	2437	8.176	7.695	≥500
High	2462	8.716	8.096	≥500
802.11g mode				
Low	2412	15.872	16.353	≥500
Middle	2437	15.551	15.872	≥500
High	2462	16.513	15.792	≥500
802.11n-HT20 mode				
Low	2412	16.513	16.994	≥500
Middle	2437	15.711	16.273	≥500
High	2462	17.796	16.433	≥500
802.11n-HT40 mode				
Low	2422	36.713	35.591	≥500
Middle	2437	35.431	35.431	≥500
High	2452	36.713	36.713	≥500


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
BLE(1Mbps) Mode			
Low	2402	0.688	≥0.5
Middle	2440	0.692	≥0.5
High	2480	0.692	≥0.5
BLE(2Mbps) Mode			
Low	2402	1.173	≥0.5
Middle	2440	1.173	≥0.5
High	2480	1.173	≥0.5



Chain0:



802.11b Mode Low Channel



802.11b Mode Middle Channel



802.11b Mode High Channel**802.11g Mode Low Channel**

802.11g Mode Middle Channel**802.11g Mode High Channel**

Delta 1 [T1] 0.96 dB

RBW 100 kHz RF Att 20 dB

Ref Lvl 20 dBm VBW 300 kHz Unit dBm

20 dBm 16.51302605 MHz

11 dB Offset

▼1 [T1] -8.15 dBm

▲1 [T1] 0.96 dB

16.51302605 MHz

D1 -8.77 dBm

D2 -6.77 dBm

1MAX



IN1 IMA

Center 2.412 GHz 4 MHz/ Span 40 MHz


Date: 16.APR.2021 16:10:41

The screenshot displays a spectrum analyzer interface with the following settings and data:


- Settings:**
 - Ref Lvl: 20 dBm
 - Delta 1 [T1]: 1.71 dB
 - RBW: 100 kHz
 - RF Att: 20 dB
 - VBW: 300 kHz
 - SWT: 10 ms
 - Unit: dBm
- Measurement Data:**
 - 11 dB Offset
 - 8.47 dBm (Peak 1)
 - 2.42942485 GHz (Frequency)
 - 1.71 dB (Delta 1)
 - 15.71142285 MHz (Span)
 - 6.49 dBm (Peak 2)
 - 1MAX (Marker)
 - IN1 (Marker)
- Graph Details:**
 - Center: 2.437 GHz
 - Span: 40 MHz
 - Scale: 4 MHz/
 - Y-axis: -80 to 20 dBm
 - X-axis: 20 dBm to 20 dBm

802.11n-HT20 Mode High Channel**802.11n-HT40 Mode Low Channel**

802.11n-HT40 Mode Middle Channel




802.11n-HT40 Mode High Channel






Chain1:

802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel**802.11g Mode Low Channel**


802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel




802.11n-HT20 Mode Middle Channel




802.11n-HT20 Mode High Channel




802.11n-HT40 Mode Low Channel




802.11n-HT40 Mode Middle Channel



802.11n-HT40 Mode High Channel




BLE(1Mbps) Mode Low Channel




Date: 11.JUL.2020 00:46:29

BLE(1Mbps) Mode Middle Channel




Date: 11.JUL.2020 00:50:06

BLE(1Mbps) Mode High Channel




Date: 11.JUL.2020 00:52:47

BLE(2Mbps) Mode Low Channel




Date: 11.JUL.2020 01:29:39

BLE(2Mbps) Mode Middle Channel



Date: 11.JUL.2020 01:32:14

BLE(2Mbps) Mode High Channel



Date: 11.JUL.2020 01:36:01

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

For Wi-Fi:

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



For BLE:

According to ANSI C63.10-2013 sub-clause 11.9.1.1

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.



Test Data**Environmental Conditions**

Temperature:	24.3-24.9 °C
Relative Humidity:	48-50 %
ATM Pressure:	101.2-101.5 kPa

The testing was performed by Stone Zhang from 2020-07-11 to 2021-04-16.

Test Result: Compliant.

EUT operation mode: Transmitting

Test mode	Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)			Limit (dBm)	Result
			Chain0	Chain1	Total		
802.11b	Low	2412	18.00	17.70	/	30	Pass
	Middle	2437	17.71	17.69	/	30	Pass
	High	2462	17.04	17.61	/	30	Pass
802.11g	Low	2412	16.83	16.54	/	30	Pass
	Middle	2437	16.45	16.40	/	30	Pass
	High	2462	15.80	16.41	/	30	Pass
802.11n-HT20	Low	2412	16.69	16.29	19.50	30	Pass
	Middle	2437	16.16	16.19	19.19	30	Pass
	High	2462	15.79	16.10	18.96	30	Pass
802.11n-HT40	Low	2422	16.91	16.65	19.79	30	Pass
	Middle	2437	16.68	16.61	19.66	30	Pass
	High	2452	16.46	16.51	19.50	30	Pass

Test mode	Channel	Frequency (MHz)	Max Conducted Average Output Power (dBm)			Limit (dBm)	Result
			Chain0	Chain1	Total		
802.11b	Low	2412	13.52	13.23	/	30	Pass
	Middle	2437	13.2	13.21	/	30	Pass
	High	2462	12.49	13.13	/	30	Pass
802.11g	Low	2412	9.6	9.32	/	30	Pass
	Middle	2437	9.32	9.27	/	30	Pass
	High	2462	8.61	9.21	/	30	Pass
802.11n-HT20	Low	2412	9.47	9.19	12.34	30	Pass
	Middle	2437	8.94	9.03	12.00	30	Pass
	High	2462	8.55	9.33	11.97	30	Pass
802.11n-HT40	Low	2422	9.73	9.44	12.60	30	Pass
	Middle	2437	9.4	9.43	12.43	30	Pass
	High	2452	9.26	9.35	12.32	30	Pass

Note: The total output power = $10 \log_{10} (10^{\text{Chain 0/10}} + 10^{\text{Chain 1/10}})$

The maximum antenna gain is -1.3dBi, the device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:


Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4 ;

So:

Directional gain = GANT + Array Gain = -1.3dBi < 6dBi


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
BLE(1Mbps) Mode				
Low	2402	-0.12	30	Pass
Middle	2440	-0.71	30	Pass
High	2480	0.04	30	Pass
BLE(2Mbps) Mode				
Low	2402	0.04	30	Pass
Middle	2440	-0.57	30	Pass
High	2480	0.15	30	Pass

BLE(1Mbps) Mode Low Channel




Date: 11.JUL.2020 01:07:30

BLE(1Mbps) Mode Middle Channel




Date: 11.JUL.2020 01:09:23

BLE(1Mbps) Mode High Channel




Date: 11.JUL.2020 01:12:31

BLE(2Mbps) Mode Low Channel




Date: 11.JUL.2020 01:41:50

BLE(2Mbps) Mode Middle Channel



Date: 11.JUL.2020 01:40:53

BLE(2Mbps) Mode High Channel



Date: 11.JUL.2020 01:39:14

FCC §15.247(d) – BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.5-25.1 °C
Relative Humidity:	46-50 %
ATM Pressure:	101.1-101.3 kPa


The testing was performed by Stone Zhang from 2020-07-11 to 2021-05-10.

Test Result: Compliant.


EUT operation mode: Transmitting



Chain0:

802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side**802.11g Mode Right Side**


802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side



802.11n-HT40 Mode Left Side




802.11n-HT40 Mode Right Side




Chain1:


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side




802.11n-HT20 Mode Left Side




802.11n-HT20 Mode Right Side




802.11n-HT40 Mode Left Side



802.11n-HT40 Mode Right Side




BLE(1Mbps) Mode Left Side




Date: 11.JUL.2020 02:37:54

BLE(1Mbps) Mode Right Side




Date: 11.JUL.2020 02:31:13

BLE(2Mbps) Mode Left Side



Date: 11.JUL.2020 02:35:43

BLE(2Mbps) Mode Right Side



Date: 11.JUL.2020 02:40:04

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.5-24.7 °C
Relative Humidity:	48-52 %
ATM Pressure:	101.1-101.3 kPa

The testing was performed by Stone Zhang from 2020-07-11 to 2021-04-16.

Test Result: Compliant.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	PSD (dBm/3kHz)			Limit (dBm/3kHz)
		Chain0	Chain1	Total	
802.11b mode					
Low	2412	-5.76	-7.19	/	≤8
Middle	2437	-6.91	-6.29	/	≤8
High	2462	-7.17	-6.87	/	≤8
802.11g mode					
Low	2412	-15.8	-14.81	/	≤8
Middle	2437	-15.33	-14.64	/	≤8
High	2462	-16.18	-14.86	/	≤8
802.11n-HT20 mode					
Low	2412	-15.90	-16.76	-13.30	≤8
Middle	2437	-15.54	-16.71	-13.08	≤8
High	2462	-17.47	-16.80	-14.11	≤8
802.11n-HT40 mode					
Low	2422	-18.70	-19.08	-15.88	≤8
Middle	2437	-17.08	-17.65	-14.35	≤8
High	2452	-18.02	-19.66	-15.75	≤8

Note:

The total PSD= $10 \cdot \log_{10} (10^{\text{Chain 0/10}} + 10^{\text{Chain 1/10}})$

The maximum antenna gain is -1.3dBi. The device employed Cyclic Delay Diversity (CDD) for 802.11MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = $10 \cdot \log(N_{\text{ANT}}/N_{\text{SS}})$ dB.


So:

Directional gain = GANT + Array Gain = -1.3+10*log(2/1) = 1.71dBi.


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE(1Mbps) Mode			
Low	2402	-14.60	≤ 8
Middle	2440	-15.13	≤ 8
High	2480	-14.52	≤ 8
BLE(2Mbps) Mode			
Low	2402	-17.96	≤ 8
Middle	2440	-18.63	≤ 8
High	2480	-17.99	≤ 8

Chain0:


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel





802.11n-HT20 Low Channel




802.11n-HT20 Middle Channel




802.11n-HT20 High Channel**802.11n-HT40 Low Channel**

802.11n-HT40 Middle Channel




802.11n-HT40 High Channel




Chain1:


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel







802.11n-HT20 Low Channel




802.11n-HT20 Middle Channel



802.11n-HT20 High Channel**802.11n-HT40 Low Channel**


802.11n-HT40 Middle Channel**802.11n-HT40 High Channel**

BLE(1Mbps) Mode Low Channel




Date: 11.JUL.2020 01:19:44

BLE(1Mbps) Mode Middle Channel




Date: 11.JUL.2020 01:24:37

BLE(1Mbps) Mode High Channel




Date: 11.JUL.2020 01:23:04

BLE(2Mbps) Mode Low Channel




Date: 11.JUL.2020 01:44:30

BLE(2Mbps) Mode Middle Channel



Date: 11.JUL.2020 01:46:15

BLE(2Mbps) Mode High Channel



Date: 11.JUL.2020 01:47:48

Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******