

---

## MPE REPORT

---

Report No.: SRTC2019-9004(F)-19101201(I)

Product Name: Infrared Forehead Thermometer

Product Model: IR-FT

Applicant: Comper Chuangxiang (Beijing) Technology Co., Ltd.

Manufacturer: Comper Chuangxiang (Beijing) Technology Co., Ltd.

Specification: FCC Part §2.1091, §2.1093, §1.1307(b), §1.1310

FCC ID: 2AH2D-IRFT

The State Radio\_monitoring\_center Testing Center (SRTC)

15th Building, No.30, Shixing Street, Shijingshan District,

Beijing, P.R.China

Tel: 86-10-57996183    Fax: 86-10-57996388

## CONTENTS

<b><u>1 GENERAL INFORMATION</u></b> .....	<b>2</b>
1.1 NOTES OF THE TEST REPORT .....	2
1.2 INFORMATION ABOUT THE TESTING LABORATORY .....	2
1.3 APPLICANT'S DETAILS .....	2
1.4 MANUFACTURER'S DETAILS .....	2
<b><u>2 DESCRIPTION OF THE DEVICE UNDER TEST</u></b> .....	<b>3</b>
2.1 FINAL EQUIPMENT BUILD STATUS .....	3
<b><u>4 RESULT SUMMARY</u></b> .....	<b>4</b>
<b><u>5 TEST RESULTS</u></b> .....	<b>5</b>
5.1 AVERAGE POWER OUTPUT.....	5
5.2 SAR TEST EXCLUSION THRESHOLDS .....	6

## 1 GENERAL INFORMATION

### 1.1 Notes of the test report

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written permission of The State Radio\_monitoring\_center Testing Center (SRTC).

The test results relate only to individual items of the samples which have been tested. The certification and accreditation identifiers used in this report shall not be applicable to the tested or calibrated samples thereof. The manufacturer shall not mark the tested samples or items (or a separate part of the item) with the identifiers of certification and accreditation to mislead relevant parties about the tested samples or items.

### 1.2 Information about the testing laboratory

Company:	The State Radio_monitoring_center Testing Center (SRTC)
Address:	15th Building, No.30 Shixing Street, Shijingshan District, P.R.China
City:	Beijing
Country or Region:	P.R.China
Contacted person:	Liu Jia
Tel:	+86 10 57996183
Fax:	+86 10 57996388
Email:	liujiaf@srtc.org.cn

### 1.3 Applicant's details

Company:	Comper Chuangxiang (Beijing) Technology Co., Ltd.
Address:	Room 102,103 1st Floor, Unit 4, No.1 Kangding Street, Beijing Economic Technology Development Area, Beijing, China
City:	Beijing
Country or Region:	China
Contacted person:	Han, Du
Tel:	010-57480968
Fax:	---
Email:	registration@comper.com

### 1.4 Manufacturer's details

Company:	Comper Chuangxiang (Beijing) Technology Co., Ltd.
Address:	Room 102,103 1st Floor, Unit 4, No.1 Kangding Street, Beijing Economic Technology Development Area, Beijing, China
City:	Beijing
Country or Region:	China
Contacted person:	Han, Du
Tel:	010-57480968
Fax:	---
Email:	registration@comper.com

## 2 DESCRIPTION OF THE DEVICE UNDER TEST

### 2.1 Final Equipment Build Status

Bluetooth BLE



Frequency Range	2.4GHz~2.48GHz
Number of Channel	40
Modulation Type	GFSK
Duplex Mode	DTS
Channel Spacing	2MHz
Data Rate	1Mbps
Antenna Type	Integral Antenna
Antenna Gain	0.5dBi
Power Supply	3VDC
HW Version	V 0.2
SW Version	V 1.0

## 3 REFERENCE SPECIFICATION

Specification	Version	Title
2.1091	Sept. 20, 2017	Radiofrequency radiation exposure evaluation: mobile devices.
2.1093	Sept. 20, 2017	Radiofrequency radiation exposure evaluation: portable devices.
1.1307(b)	Apr. 22, 1986	Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
1.1310	June 4, 2013	Radiofrequency radiation exposure limits.
KDB447498	October 23, 2015	RF exposure procedures and equipment authorization policies for mobile and portable devices

**4 RESULT SUMMARY**

No.	Test case	FCC reference
1	MPE Calculation	FCC Part §2.1091, FCC Part §2.1093, FCC Part §1.1307(b) FCC Part §1.1310 KDB 447498

This Test Report Is Issued by: Mr. Peng Zhen 	Checked by: Mr. Li Bin 
Tested by: Miss. Jin Wanqing 	Issued date: 20191101

## 5 Test Results

### 5.1 Average Power Output

#### 5.1.1 Ambient condition

Temperature	Relative humidity	Pressure
22°C	40%	101.5kPa

#### 5.1.2 Test Description

A transmitter antenna terminal of EUT is connected to the power meter. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

#### 5.1.3 Test Procedure Used

KDB 558074 D01 DTS Meas Guidance v04 – Section 9.2.3


#### 5.1.4 Test Settings

The maximum average conducted output power may be measured using a broadband average RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

- a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.
  - 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
  - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
  - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal as described in Section 6.0.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding  $10\log(1/x)$ , where x is the duty cycle to the measurement result.

#### 5.1.5 Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



## 5.1.6 Test Result

### BT BLE output power

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE)	-1.04	-0.76	-0.59

### Tune-up tolerance

Modulation type	Average Power Output (dBm)		
	2402MHz (Ch0)	2440MHz (Ch19)	2480MHz (Ch39)
GFSK (LE)	-3.0~1.0	-3.0~1.0	-3.0~1.0

## 5.2 SAR Test Exclusion Thresholds

According to the KDB447498 4.3.1(a)

For 100 MHz to 6 GHz and test separation distances  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

· Power and distance are rounded to the nearest mW and mm before calculation

· The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

### Summary of Transmitters

Mode/Band	Freq (GHz)	Max. power of channel, including tune-up tolerance, (dBm)	Max. power of channel, including tune-up tolerance, (mW)	Min. test separation distance, (mm)	The calculation results (1g)	SAR test exclusion Threshold (1g)	SAR Required
Bluetooth	2.402	1	1.26	0	0.162	$\leq 3.0$	No
Bluetooth	2.440	1	1.26	0	0.161	$\leq 3.0$	No
Bluetooth	2.480	1	1.26	0	0.160	$\leq 3.0$	No

---End of Test Report---