



# SAR Exemption Evaluation Report

Product Name: ONRHYTHM 500

Model No. : 8389271,8389272,8574435

FCC ID : 2AH2P-OR50018

Applicant: DECATHLON USA LLC

Address: 2415 3rd Street, Suite 231 San

Francisco 94107, California, USA

Date of Receipt: Sep. 25, 2019

Issued Date : Sep. 25, 2019

Report No. : 1862125R-RF-US-P20V02

Report Version: V1.0

Note: The report was based on DEKRA report(1862125R-RF-US-P20V02), only update Model No..

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory.

The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to calculate the uncertainty associated with the measurement result.

This report is not used for social proof in China (or Mainland China) market.



## **Test Report Certification**

Issued Date : Sep. 25, 2019

Report No.: 1992160R-RF-US-P20V02



Product Name : ONRHYTHM 500

Applicant : DECATHLON USA LLC

Address : 2415 3rd Street, Suite 231 San Francisco 94107,

California, USA

Manufacturer : DECATHLON SA

Address : 4 Boulevard de Mons - 59650 Villeneuve d' Ascq -

**FRANCE** 

Model No. : 8389271,8389272,8574435

FCC ID : 2AH2P-OR50018

EUT Voltage : DC 2.5~3.3V

Applicable Standard : KDB 447498 D01v06

Test Result : Complied

Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.

No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,

215006, Jiangsu, China

TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098

FCC Registration Number: 800392;

Documented By :

(Adm. Specialist: Kitty Li)

Reviewed By : Frank he

(Senior Project Manager: Frank He)

Approved By : Jack zhang

(Engineering Supervisor: Jack Zhang)



### 1. RF Exposure Evaluation

#### 1.1. Limits

#### According to KDB 447498 D01 General RF Exposure Guidance v06

#### 4.3.1 Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR,where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq$  5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:
- a) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)·( f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- b) [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and  $\leq$  6 GHz
- 3) The 1-g and 10-g SAR test exclusion thresholds for below 100 MHz at test separation distances ≤ 50 mm are determined by:
- a) The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm
- b) The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq$  50 mm
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable. Note: when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.



## 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

## 1.3. Test Result of RF Exposure Evaluation

Product	:	ONRHYTHM 500			
Test Item	:	RF Exposure Evaluation			
Test Site	:	AC-6			

#### Antenna Gain:

N/A							
N/A							
	1*TX+1*RX		☐ 2*TX+2*RX ☐ 3*TX+3*RX				
	SISO						
	МІМО		Basic				
			CDD				
╽╙			Sectorized				
			Beam-forming				
	External		Dipole				
╙			Sectorized				
$\boxtimes$		$\boxtimes$	PIFA				
	Internal		PCB				
			Ceramic Chip Antenna				
			Dipole Antenna				
Ant Gain							
(dBi)							
			-2				
	N/A	N/A    1*TX+1*R   SISO    MIMO    External	N/A    1*TX+1*RX   SISO   MIMO				

Based on The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm and the formula below:

Estimated SAR=
$$\sqrt{f(GHz)} * \frac{\text{(Max Power of channel, mW)}}{\text{Min. Separation Distance, mm}}$$



Report No: 1992160R-RF-US-P20V02

Conclusion: 2.4GHz SAR was not required.

Band	Exposure Condition	Pmax (dBm)	Pmax (mw)	Distance (mm)	f(GHz)	calculation result	Stand-alone Test exclusion threshold	SAR Test
ВТ	Body	5.60	3.63	5	2.402	1.13	3.00	No

——— The End	