

# **FCC SAR Test Report**

Report No. : SA170601C08C

Applicant : DREEM SAS

Address : 7-11 Boulevard Haussmann Paris 75009, France

Product : Sleep tracking device

FCC ID : 2AH2Q-DREEM2

Brand : DREEM

Model No. : Dreem+

Standards : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013

KDB 865664 D01 v01r04, KDB 865664 D02 v01r02 KDB 248227 D01 v02r02, KDB 447498 D01 v06

Sample Received Date : Feb. 27, 2019

Date of Testing : Mar. 20, 2019 ~ Mar. 21, 2019

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location : No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By:

Gina Liu / Specialist

Approved By:

Gordon Lin / Assistant Manager



FCC Accredited No.: TW0003

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report Format Version 5.0.0 Page No. : 1 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



Page No.

: 2 of 30

Issued Date : Apr. 02, 2019

# **Table of Contents**

Ke		Control Record				
1.						
2.	Description of Equipment Under Test5					
3.	SAR Measurement System					
	3.1 Definition of Specific Absorption Rate (SAR)					
	3.2	SPEAG DASY52 System				
		3.2.1 Robot				
		3.2.2 Probes				
		3.2.3 Data Acquisition Electronics (DAE)	8			
		3.2.4 Phantoms				
		3.2.5 Device Holder				
		3.2.6 System Validation Dipoles	10			
		3.2.7 Tissue Simulating Liquids				
	3.3	SAR System Verification				
	3.4	SAR Measurement Procedure				
		3.4.1 Area & Zoom Scan Procedure				
		3.4.2 Volume Scan Procedure				
		3.4.3 Power Drift Monitoring				
		3.4.4 Spatial Peak SAR Evaluation				
		3.4.5 SAR Averaged Methods	16			
4.	SAR I	Measurement Evaluation	17			
	4.1	EUT Configuration and Setting	17			
	4.2	EUT Testing Position				
	4.3	Tissue Verification				
	4.4	System Validation				
	4.5	System Verification				
	4.6	Maximum Output Power				
		4.6.1 Maximum Target Conducted Power	2 <sup>^</sup>			
		4.6.2 Measured Conducted Power Result	23			
	4.7	SAR Testing Results				
		4.7.1 SAR Test Reduction Considerations	2			
		4.7.2 SAR Results for Head Exposure Condition (Test Separation Distance is 0 mm)	20			
		4.7.3 SAR Measurement Variability	27			
		4.7.4 Simultaneous Multi-band Transmission Evaluation	27			
5.		ration of Test Equipment	28			
6.	Measurement Uncertainty2					
7.	Inforn	nation of the Testing Laboratories	30			

Appendix A. SAR Plots of System Verification

Appendix B. SAR Plots of SAR Measurement

Appendix C. Calibration Certificate for Probe and Dipole

Appendix D. Photographs of EUT and Setup



# **Release Control Record**

Report No.	Reason for Change	Date Issued
SA170601C08C	Initial release	Apr. 02, 2019

Report Format Version 5.0.0 Page No. : 3 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



# 1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest SAR-1g Head Tested at 0 mm (W/kg)
DTS	2.4G WLAN	<mark>1.16</mark>
	5.2G WLAN	N/A
NII	5.3G WLAN	0.63
INII	5.6G WLAN	0.37
	5.8G WLAN	0.25
DSS	Bluetooth	0.36

### Note:

1. The SAR criteria (Head & Body: SAR-1g 1.6 W/kg, and Extremity: SAR-10g 4.0 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

 Report Format Version 5.0.0
 Page No.
 : 4 of 30

 Report No.: SA170601C08C
 Issued Date : Apr. 02, 2019



# 2. <u>Description of Equipment Under Test</u>

EUT Type	Sleep tracking device
FCC ID	2AH2Q-DREEM2
Brand Name	DREEM
Model Name	Dreem+
Tx Frequency Bands	WLAN: 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825
(Unit: MHz)	Bluetooth : 2402 ~ 2480
	802.11b : DSSS
	802.11a/g/n : OFDM
	Bluetooth : GFSK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.6.1 of this report
Antenna Type	Chip Antenna
Antenna Type	(Peak Antenna Gain: 0.97 dBi for 2.4GHz, -1.49 dBi for 5GHz)
EUT Stage	Production Unit

#### Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

#### **List of Accessory:**

	Brand Name	JS Power
Battery	Model Name	DREEM
Dallery	Power Rating	3.7Vdc, 1200mAh
	Type	Li-ion Li-ion

 Report Format Version 5.0.0
 Page No.
 : 5 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



# 3. SAR Measurement System

### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (p). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

### 3.2 SPEAG DASY52 System

DASY52 system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY52 software defined. The DASY52 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion form the optical into digital electric signal of the DAE and transfers data to the PC.

Report Format Version 5.0.0 Page No. : 6 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019






Fig-3.1 SPEAG DASY52 System Setup

#### 3.2.1 Robot

The DASY52 systems use the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version of CS8c from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.035 mm)
- High reliability (industrial design)
- · Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Report Format Version 5.0.0 Report No. : SA170601C08C Reference No.: 190227C19 Page No. : 7 of 30 Issued Date : Apr. 02, 2019



#### 3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μW/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μW/g)	MH
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	<i>F</i>
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	M
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	M
Dynamic Range	5 μW/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

Model	ET3DV6	100
Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz to 2.3 GHz; Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.4 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μW/g to 100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 16 mm) Tip diameter: 6.8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.7 mm	

## 3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement	-100 to +300 mV (16 bit resolution and two range settings: 4mV,	
Range	400mV)	The little
Input Offset Voltage	< 5μV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

Page No.

: 8 of 30

Issued Date : Apr. 02, 2019

Report Format Version 5.0.0 Report No. : SA170601C08C Reference No.: 190227C19



### 3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Material Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	Shell Thickness $2 \pm 0.2 \text{ mm}$ (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	



Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	



Report Format Version 5.0.0 Report No. : SA170601C08C Reference No.: 190227C19 Page No. : 9 of 30 Issued Date : Apr. 02, 2019



### 3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	

Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

## 3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with I/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	


 Report Format Version 5.0.0
 Page No.
 : 10 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



#### 3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

 Report Format Version 5.0.0
 Page No.
 : 11 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



**Table-3.1 Targets of Tissue Simulating Liquid** 

	Table-3.1 Targets of Tissue Simulating Elquid						
Frequency (MHz)	Target Permittivity	Range of ±5%	Target Conductivity	Range of ±5%			
		For Head					
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93			
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95			
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02			
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26			
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35			
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44			
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47			
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47			
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47			
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75			
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89			
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06			
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06			
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89			
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00			
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21			
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32			
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53			
		For Body					
750	55.5	52.7 ~ 58.3	0.96	0.91 ~ 1.01			
835	55.2	52.4 ~ 58.0	0.97	0.92 ~ 1.02			
900	55.0	52.3 ~ 57.8	1.05	1.00 ~ 1.10			
1450	54.0	51.3 ~ 56.7	1.30	1.24 ~ 1.37			
1640	53.8	51.1 ~ 56.5	1.40	1.33 ~ 1.47			
1750	53.4	50.7 ~ 56.1	1.49	1.42 ~ 1.56			
1800	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60			
1900	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60			
2000	53.3	50.6 ~ 56.0	1.52	1.44 ~ 1.60			
2300	52.9	50.3 ~ 55.5	1.81	1.72 ~ 1.90			
2450	52.7	50.1 ~ 55.3	1.95	1.85 ~ 2.05			
2600	52.5	49.9 ~ 55.1	2.16	2.05 ~ 2.27			
3500	51.3	48.7 ~ 53.9	3.31	3.14 ~ 3.48			
5200	49.0	46.6 ~ 51.5	5.30	5.04 ~ 5.57			
5300	48.9	46.5 ~ 51.3	5.42	5.15 ~ 5.69			
5500	48.6	46.2 ~ 51.0	5.65	5.37 ~ 5.93			
5600	48.5	46.1 ~ 50.9	5.77	5.48 ~ 6.06			
5800	48.2	45.8 ~ 50.6	6.00	5.70 ~ 6.30			

 Report Format Version 5.0.0
 Page No.
 : 12 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019





The following table gives the recipes for tissue simulating liquids.

**Table-3.2 Recipes of Tissue Simulating Liquid** 

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono- hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-		•	-	17.2	65.5	17.3
B750	0.2	-	0.2	0.8	48.8	-	50.0	-
B835	0.2	-	0.2	0.9	48.5	-	50.2	-
B900	0.2	-	0.2	0.9	48.2	-	50.5	-
B1450	-	34.0	-	0.3	-	-	65.7	-
B1640	-	32.5	-	0.3	-	-	67.2	-
B1750	-	31.0	-	0.2	-	-	68.8	-
B1800	-	29.5	-	0.4	-	-	70.1	-
B1900	-	29.5	-	0.3	-	-	70.2	-
B2000	-	30.0	-	0.2	-	-	69.8	-
B2300	-	31.0	-	0.1	-	-	68.9	-
B2450	-	31.4	-	0.1	-	-	68.5	-
B2600	-	31.8	-	0.1	-	-	68.1	-
B3500	-	28.8		0.1	-	-	71.1	-
B5G	-	-	-	-	-	10.7	78.6	10.7


 Report Format Version 5.0.0
 Page No.
 : 13 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



### 3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.



The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

Report Format Version 5.0.0 Report No. : SA170601C08C Reference No.: 190227C19 Page No. : 14 of 30 Issued Date : Apr. 02, 2019



### 3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

#### 3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan (Δx, Δy)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan (Δx, Δy)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

#### Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of  $\Delta x / \Delta y$  (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

### 3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

Report Format Version 5.0.0 Page No. : 15 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



#### 3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

#### 3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

#### 3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

Report Format Version 5.0.0 Page No. : 16 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



# 4. SAR Measurement Evaluation

### 4.1 EUT Configuration and Setting

#### <Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

#### **Initial Test Configuration**

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

#### **Subsequent Test Configuration**

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

 Report Format Version 5.0.0
 Page No.
 : 17 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



#### **SAR Test Configuration and Channel Selection**

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

- 1) The channel closest to mid-band frequency is selected for SAR measurement.
- 2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

#### Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration.


Report Format Version 5.0.0 Page No. : 18 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



### <Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

The Bluetooth call box has been used during SAR measurement and the EUT was set to DH5 mode at the maximum output power. Its duty factor was calculated as below and the measured SAR for Bluetooth would be scaled to the 100% transmission duty factor to determine compliance.



Time-domain plot for Bluetooth transmission signal

The duty factor of Bluetooth signal has been calculated as following. Duty Factor = Pulse Width / Total Period = 390 / 626 = 62.3 %

 Report Format Version 5.0.0
 Page No.
 : 19 of 30

 Report No.: SA170601C08C
 Issued Date
 : Apr. 02, 2019



### 4.2 EUT Testing Position

SAR evaluation for this wireless headband was tested with the surface of antenna location directly against the flat phantom at 0 mm separation distance.

### 4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (℃)	Measured Conductivity (σ)	Measured Permittivity (ε <sub>r</sub> )	Target Conductivity (σ)	Target Permittivity (ε <sub>r</sub> )	Conductivity Deviation (%)	Permittivity Deviation (%)
Mar. 21, 2019	Head	2450	23.2	1.867	37.958	1.8	39.2	3.72	-3.17
Mar. 20, 2019	Head	5250	23.2	4.906	36.784	4.71	35.9	4.16	2.46
Mar. 20, 2019	Head	5600	23.2	5.239	36.2	5.07	35.5	3.33	1.97
Mar. 20, 2019	Head	5750	23.2	5.37	35.688	5.22	35.4	2.87	0.81

#### Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within  $\pm 5\%$  of the target values. Liquid temperature during the SAR testing must be within  $\pm 2$  °C.

## 4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Toot	Drobo			Measured	Measured	Va	lidation for C	:W	Valida	tion for Modu	lation
Test Date	Probe S/N	Calibrati	on Point	Conductivity (σ)	Permittivity (ε <sub>r</sub> )	Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
Mar. 21, 2019	3650	Body	2450	1.867	37.958	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 20, 2019	3650	Body	5250	4.906	36.784	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 20, 2019	3650	Body	5600	5.239	36.200	Pass	Pass	Pass	OFDM	N/A	Pass
Mar. 20, 2019	3650	Body	5750	5.370	35.688	Pass	Pass	Pass	OFDM	N/A	Pass

## 4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Mar. 21, 2019	Head	2450	51.50	13.3	53.20	3.30	737	3650	579
Mar. 20, 2019	Head	5250	78.90	8.47	84.70	7.35	1145	3650	579
Mar. 20, 2019	Head	5600	80.30	8.18	81.80	1.87	1145	3650	579
Mar. 20, 2019	Head	5750	79.30	7.71	77.10	-2.77	1145	3650	579

#### Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

 Report Format Version 5.0.0
 Page No.
 : 20 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



# 4.6 Maximum Output Power

## 4.6.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

### <WLAN 2.4G>

Mode	Channel	Frequency (MHz)	Tune-up Power
	1	2412	15.0
802.11b	6	2437	15.0
	11	2462	15.0
	1	2412	14.0
802.11g	6	2437	14.0
	11	2462	14.0
	1	2412	13.5
802.11n (HT20)	6	2437	13.5
	11	2462	13.5

#### <WLAN 5.2G>

Mode	Channel	Frequency (MHz)	Tune-up Power
	36	5180	14.5
802.11a	40	5200	14.5
602.11a	44	5220	14.5
	48	5240	14.5
	36	5180	14.0
902 44n (UT20)	40	5200	14.0
802.11n (HT20)	44	5220	14.0
	48	5240	14.0

### <WLAN 5.3G>

Mode	Channel	Frequency (MHz)	Tune-up Power
	52	5260	14.5
802.11a	56	5280	14.5
602.11a	60	5300	14.5
	64	5320	14.5
	52	5260	13.0
902 44n (UT20)	56	5280	13.0
802.11n (HT20)	60	5300	13.0
	64	5320	13.0

 Report Format Version 5.0.0
 Page No.
 : 21 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



### <WLAN 5.6G>

Mode	Channel	Frequency (MHz)	Tune-up Power
	100	5500	15.5
	116	5580	15.5
802.11a	120	5600	15.5
002.11a	124	5620	15.5
	132	5660	15.5
	140	5700	15.5
	100	5500	14.0
	116	5580	14.0
902 11n (UT20)	120	5600	14.0
802.11n (HT20)	124	5620	14.0
	132	5660	14.0
	140	5700	14.0

### <WLAN 5.8G>

Mode	Channel	Frequency (MHz)	Tune-up Power
	149	5745	15.0
	153	5765	15.0
802.11a	157	5785	15.0
	161	5805	15.0
	165	5825	15.0
	149	5745	14.5
	153	5765	14.5
802.11n (HT20)	157	5785	14.5
	161	5805	14.5
	165	5825	14.5

### <Bluetooth>

Mode	Channel	Frequency (MHz)	Tune-up Power
	0	2402	9.0
Bluetooth EDR	39	2441	9.0
	78	2480	9.0
	0	2402	9.0
Bluetooth LE	19	2440	9.0
	39	2480	9.0

 Report Format Version 5.0.0
 Page No.
 : 22 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



### 4.6.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

### <WLAN 2.4G>

Mode	Channel	Frequency (MHz)	Average Power
	1	2412	14.96
802.11b	6	2437	14.97
	11	2462	14.94
	1	2412	13.93
802.11g	6	2437	13.87
	11	2462	13.81
	1	2412	12.79
802.11n (HT20)	6	2437	13.04
	11	2462	13.10

### <WLAN 5.2G>

Mode	Channel	Frequency (MHz)	Average Power
	36	5180	14.37
802.11a	40	5200	14.20
002.11a	44	5220	14.23
	48	5240	14.29
	36	5180	13.41
902 11n (UT20)	40	5200	13.39
802.11n (HT20)	44	5220	13.32
	48	5240	13.51

### <WLAN 5.3G>

Mode	Channel	Frequency (MHz)	Average Power
	52	5260	14.32
802.11a	56	5280	14.25
002.11a	60	5300	14.28
	64	5320	14.31
	52	5260	12.49
802.11n (HT20)	56	5280	12.50
602.1111 (H120)	60	5300	12.53
	64	5320	12.48

 Report Format Version 5.0.0
 Page No.
 : 23 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



### <WLAN 5.6G>

Mode	Channel	Frequency (MHz)	Average Power
	100	5500	13.57
	116	5580	14.20
802.11a	120	5600	15.10
002.11d	124	5620	15.12
	132	5660	14.19
	140	5700	14.21
	100	5500	12.65
	116	5580	13.56
902 11n (UT20)	120	5600	13.51
802.11n (HT20)	124	5620	13.47
	132	5660	13.42
	140	5700	13.51

### <WLAN 5.8G>

Mode	Channel	Frequency (MHz)	Average Power
	149	5745	14.71
	153	5765	14.73
802.11a	157	5785	14.79
	161	5805	14.72
	165	5825	14.62
	149	5745	13.21
	153	5765	13.93
802.11n (HT20)	157	5785	13.91
, ,	161	5805	14.01
	165	5825	14.00

### <Bluetooth>

Mode	Channel	Frequency (MHz)	Average Power
	0	2402	8.17
Bluetooth EDR	39	2441	8.15
	78	2480	7.63
	0	2402	8.87
Bluetooth LE	19	2440	8.04
	39	2480	7.86

 Report Format Version 5.0.0
 Page No.
 : 24 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



### 4.7 SAR Testing Results

#### 4.7.1 SAR Test Reduction Considerations

#### <KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

When SAR is not measured at the maximum power level allowed for production units, the measured SAR will be scaled to the maximum tune-up tolerance limit to determine compliance. The scaling factor for the tune-up power is defined as maximum tune-up limit (mW) / measured conducted power (mW). The reported SAR would be calculated by measured SAR x tune-up power scaling factor.

The SAR has been measured with highest transmission duty factor supported by the test mode tools for WLAN and/or Bluetooth. When the transmission duty factor could not achieve 100%, the reported SAR will be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up power. The scaling factor for the duty factor is defined as 100% / transmission duty cycle (%). The reported SAR would be calculated by measured SAR x tune-up power scaling factor x duty cycle scaling factor.

#### <KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is <= 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is <= 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is <= 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is <= 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is <= 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is <= 1.2 W/kg.

Report Format Version 5.0.0 Page No. : 25 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019





## 4.7.2 SAR Results for Head Exposure Condition (Test Separation Distance is 0 mm)

Plot No.	Band	Mode	Test Position	Ch.	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WLAN2.4G	802.11b	Rear Face	1	100.00	1.00	15.0	14.96	1.01	0.08	0.984	0.99
01	WLAN2.4G	802.11b	Rear Face	6	100.00	1.00	15.0	14.97	1.01	-0.09	1.15	<mark>1.16</mark>
	WLAN2.4G	802.11b	Rear Face	11	100.00	1.00	15.0	14.94	1.01	0.01	1.02	1.03
	WLAN2.4G	802.11b	Rear Face	6	100.00	1.00	15.0	14.97	1.01	-0.09	1.15	1.16
02	WLAN5.3G	802.11a	Rear Face	52	93.30	1.07	14.5	14.32	1.04	-0.04	0.567	<mark>0.63</mark>
	WLAN5.3G	802.11a	Rear Face	56	93.30	1.07	14.5	14.25	1.06	-0.08	0.485	0.55
	WLAN5.3G	802.11a	Rear Face	60	93.30	1.07	14.5	14.28	1.05	0.02	0.451	0.51
	WLAN5.3G	802.11a	Rear Face	64	93.30	1.07	14.5	14.31	1.04	-0.11	0.434	0.48
03	WLAN5.6G	802.11a	Rear Face	100	93.30	1.07	15.5	13.57	1.56	-0.01	0.219	<mark>0.37</mark>
	WLAN5.6G	802.11a	Rear Face	116	93.30	1.07	15.5	14.20	1.35	-0.08	0.176	0.25
	WLAN5.6G	802.11a	Rear Face	120	93.30	1.07	15.5	15.10	1.10	0.03	0.215	0.25
	WLAN5.6G	802.11a	Rear Face	124	93.30	1.07	15.5	15.12	1.09	-0.11	0.192	0.22
	WLAN5.6G	802.11a	Rear Face	132	93.30	1.07	15.5	14.19	1.35	0.02	0.164	0.24
	WLAN5.6G	802.11a	Rear Face	140	93.30	1.07	15.5	14.21	1.35	0.00	0.159	0.23
04	WLAN5.8G	802.11a	Rear Face	149	93.30	1.07	15.0	14.71	1.07	-0.08	0.220	<mark>0.25</mark>
	WLAN5.8G	802.11a	Rear Face	153	93.30	1.07	15.0	14.73	1.06	-0.07	0.212	0.24
	WLAN5.8G	802.11a	Rear Face	157	93.30	1.07	15.0	14.79	1.05	0.13	0.21	0.24
	WLAN5.8G	802.11a	Rear Face	161	93.30	1.07	15.0	14.72	1.07	0.05	0.208	0.24
	WLAN5.8G	802.11a	Rear Face	165	93.30	1.07	15.0	14.62	1.09	0.02	0.202	0.24
	BT	LE	Rear Face	0	62.30	1.61	9.0	8.87	1.03	-0.12	0.141	0.23
05	BT	LE	Rear Face	19	62.30	1.61	9.0	8.04	1.25	-0.03	0.178	<mark>0.36</mark>
	BT	LE	Rear Face	39	62.30	1.61	9.0	7.86	1.30	0.15	0.15	0.31

 Report Format Version 5.0.0
 Page No.
 : 26 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



#### 4.7.3 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

#### SAR repeated measurement procedure:

- 1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
- 2. When the highest measured SAR is >= 0.80 W/kg, repeat that measurement once.
- 3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20, or when the original or repeated measurement is >= 1.45 W/kg, perform a second repeated measurement.
- 4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20, and the original, first or second repeated measurement is >= 1.5 W/kg, perform a third repeated measurement.

Band	Mode	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WLAN2.4G	802.11b	Rear Face	6	1.15	1.15	1.00	N/A	N/A	N/A	N/A

#### 4.7.4 Simultaneous Multi-band Transmission Evaluation

There is no simultaneous transmission configuration in this device.

Test Engineer: Kevin Yao, and Chienlun Huang

Report Format Version 5.0.0 Page No. : 27 of 30
Report No.: SA170601C08C Issued Date : Apr. 02, 2019



# 5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	737	Aug. 24, 2018	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1145	Nov. 06, 2018	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3650	Jul. 27, 2018	1 Year
Data Acquisition Electronics	SPEAG	DAE3	579	Aug. 27, 2018	1 Year
Spectrum Analyzer	R&S	FSL6	102006	Mar. 23, 2018	1 Year
ENA Series Network Analyzer	Agilent	E5071C	MY46214281	Jun. 08, 2018	1 Year
MXG Analong Signal Generator	Agilent	N5181A	MY50143868	Jul. 03, 2018	1 Year
Power Meter	Anritsu	ML2495A	1218009	Jul. 03, 2018	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Jul. 03, 2018	1 Year
Thermometer	YFE	YF-160A	130504591	Mar. 23, 2018	1 Year

 Report Format Version 5.0.0
 Page No.
 : 28 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



# 6. Measurement Uncertainty

According to KDB 865664 D01, SAR measurement uncertainty analysis is required in SAR reports only when the highest measured SAR in a frequency band is  $\geq$  1.5 W/kg for 1-g SAR, and  $\geq$  3.75 W/kg for 10-g SAR. The procedures described in IEEE Std 1528-2013 should be applied. The expanded SAR measurement uncertainty must be  $\leq$  30 %, for a confidence interval of k = 2. When the highest measured SAR within a frequency band is < 1.5 W/kg for 1-g and < 3.75 W/kg for 10-g, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. Hence, the measurement uncertainty analysis is not required in this SAR report because the test result met the condition.

 Report Format Version 5.0.0
 Page No.
 : 29 of 30

 Report No. : SA170601C08C
 Issued Date
 : Apr. 02, 2019



# 7. Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

#### Taiwan HwaYa EMC/RF/Safety/Telecom Lab:

Add: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil., Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

Tel: 886-3-318-3232 Fax: 886-3-327-0892

#### Taiwan LinKou EMC/RF Lab:

Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.

Tel: 886-2-2605-2180 Fax: 886-2-2605-1924

#### Taiwan HsinChu EMC/RF Lab:

Add: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 30078, Taiwan, R.O.C.

Tel: 886-3-593-5343 Fax: 886-3-593-5342

Email: <a href="mailto:service.adt@tw.bureauveritas.com">service.adt@tw.bureauveritas.com</a>
Web Site: <a href="mailto:www.bureauveritas-adt.com">www.bureauveritas-adt.com</a>

The road map of all our labs can be found in our web site also.

---END----

 Report Format Version 5.0.0
 Page No.
 : 30 of 30

 Report No. : SA170601C08C
 Issued Date : Apr. 02, 2019



# Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as follows.

Report Format Version 5.0.0 Issued Date : Apr. 02, 2019

Report No. : SA170601C08C Reference No.: 190227C19

# **System Check H2450 190321**

**DUT: Dipole 2450 MHz; Type: D2450V2; SN: 737** 

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: H19T27N1\_0321 Medium parameters used: f = 2450 MHz;  $\sigma = 1.867$  S/m;  $\varepsilon_r = 37.958$ ;  $\rho =$ 

Date: 2019/03/21

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.5 °C; Liquid Temperature: 23.2 °C


### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=250mW/Area Scan (81x81x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm Maximum value of SAR (interpolated) = 22.3 W/kg

Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 111.1 V/m; Power Drift = -0.10 dB Peak SAR (extrapolated) = 27.6 W/kg SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.21 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.21 W/kg Maximum value of SAR (measured) = 22.4 W/kg



# System Check\_H5250\_190320

# DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1145

Communication System: CW; Frequency: 5250 MHz; Duty Cycle: 1:1

Medium: H34T60N3\_0320 Medium parameters used: f = 5250 MHz;  $\sigma = 4.906$  S/m;  $\varepsilon_r = 36.784$ ;  $\rho =$ 

Date: 2019/03/20

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.5 °C; Liquid Temperature: 23.2 °C

### DASY5 Configuration:


- Probe: EX3DV4 SN3650; ConvF(5.46, 5.46, 5.46); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 22.6 W/kg

Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 78.17 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 41.3 W/kg

SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.43 W/kgMaximum value of SAR (measured) = 25.0 W/kg



# System Check\_H5600\_190320

# DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1145

Communication System: CW; Frequency: 5600 MHz; Duty Cycle: 1:1

Medium: H34T60N3\_0320 Medium parameters used: f = 5600 MHz;  $\sigma = 5.239$  S/m;  $\varepsilon_r = 36.2$ ;  $\rho =$ 

Date: 2019/03/20

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 23.2 °C

### DASY5 Configuration:


- Probe: EX3DV4 SN3650; ConvF(5.05, 5.05, 5.05); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 19.9 W/kg

Pin=100mW/Zoom Scan (7x7x12)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 70.47 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 34.7 W/kg

SAR(1 g) = 8.18 W/kg; SAR(10 g) = 2.35 W/kgMaximum value of SAR (measured) = 21.0 W/kg



# System Check\_H5750\_190320

# DUT: Dipole 5 GHz; Type: D5GHzV2; SN: 1145

Communication System: CW; Frequency: 5750 MHz; Duty Cycle: 1:1

Medium: H34T60N3\_0320 Medium parameters used: f = 5750 MHz;  $\sigma = 5.37$  S/m;  $\varepsilon_r = 35.688$ ;  $\rho =$ 

Date: 2019/03/20

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.5 °C; Liquid Temperature: 23.2 °C


### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(5.33, 5.33, 5.33); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

**Pin=100mW/Area Scan (91x91x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 21.6 W/kg

**Pin=100mW/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm Reference Value = 63.37 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 41.6 W/kg

SAR(1 g) = 7.71 W/kg; SAR(10 g) = 2.21 W/kgMaximum value of SAR (measured) = 23.4 W/kg







# Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination, and measured SAR > 1.5 W/kg are shown as follows.

Report Format Version 5.0.0 Issued Date : Apr. 02, 2019

Report No. : SA170601C08C Reference No.: 190227C19

## P01 WLAN2.4G\_802.11b\_Rear Face\_0cm\_Ch6

#### **DUT: 190227C19**

Communication System: WLAN 2.4G; Frequency: 2437 MHz; Duty Cycle: 1:1


Medium: H19T27N1\_0321 Medium parameters used: f = 2437 MHz;  $\sigma = 1.851$  S/m;  $\epsilon_r = 38.001$ ;  $\rho = 1.851$  S/m;  $\epsilon_r = 38.001$ 

Date: 2019/03/21

 $1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.5 °C; Liquid Temperature: 23.2 °C

- Probe: EX3DV4 SN3650; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (71x171x1): Interpolated grid: dx=1.200 mm, dy=1.200 mmMaximum value of SAR (interpolated) = 1.59 W/kg
- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 25.67 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 2.71 W/kg SAR(1 g) = 1.15 W/kg; SAR(10 g) = 0.481 W/kg Maximum value of SAR (measured) = 1.84 W/kg



## P02 WLAN5.3G\_802.11a\_Rear Face\_0cm\_Ch52

#### **DUT: 190227C19**

Communication System: WLAN 5G; Frequency: 5260 MHz; Duty Cycle: 1:1.07


Medium: H34T60N3\_0320 Medium parameters used: f = 5260 MHz;  $\sigma = 4.891$  S/m;  $\epsilon_r = 36.761$ ;  $\rho =$ 

Date: 2019/03/20

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 23.2 °C

- Probe: EX3DV4 SN3650; ConvF(5.46, 5.46, 5.46); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (81x201x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.770 W/kg
- **Zoom Scan (6x6x12)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 12.14 V/m; Power Drift = -0.04 dB Peak SAR (extrapolated) = 2.48 W/kg SAR(1 g) = 0.567 W/kg; SAR(10 g) = 0.165 W/kg Maximum value of SAR (measured) = 1.43 W/kg



## P03 WLAN5.6G\_802.11a\_Rear Face\_0cm\_Ch100

#### **DUT: 190227C19**

Communication System: WLAN 5G; Frequency: 5500 MHz; Duty Cycle: 1:1.07


Medium: H34T60N3\_0320 Medium parameters used: f = 5500 MHz;  $\sigma = 5.098$  S/m;  $\epsilon_r = 36.294$ ;  $\rho =$ 

Date: 2019/03/20

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 23.2 °C

- Probe: EX3DV4 SN3650; ConvF(5.05, 5.05, 5.05); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (81x201x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.278 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 7.152 V/m; Power Drift = -0.01 dB Peak SAR (extrapolated) = 1.00 W/kg SAR(1 g) = 0.219 W/kg; SAR(10 g) = 0.047 W/kg Maximum value of SAR (measured) = 0.633 W/kg



## P04 WLAN5.8G\_802.11a\_Rear Face\_0cm\_Ch149

#### **DUT: 190227C19**

Communication System: WLAN 5G; Frequency: 5745 MHz; Duty Cycle: 1:1.07

Medium: H34T60N3\_0320 Medium parameters used: f = 5745 MHz;  $\sigma = 5.356$  S/m;  $\epsilon_r = 35.717$ ;  $\rho =$ 

Date: 2019/03/20


 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 23.2 °C

#### DASY5 Configuration:

- Probe: EX3DV4 SN3650; ConvF(5.33, 5.33, 5.33); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (81x201x1): Interpolated grid: dx=1.000 mm, dy=1.000 mm Maximum value of SAR (interpolated) = 0.281 W/kg
- Zoom Scan (6x6x12)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=2mm Reference Value = 7.050 V/m; Power Drift = -0.08 dB Peak SAR (extrapolated) = 0.956 W/kg SAR(1 g) = 0.220 W/kg; SAR(10 g) = 0.048 W/kg

Maximum value of SAR (measured) = 0.619 W/kg



## P05 BT\_LE\_Rear Face\_0cm\_Ch19

#### **DUT: 190227C19**

Communication System: BT; Frequency: 2440 MHz; Duty Cycle: 1:1.61


Medium: H19T27N1\_0321 Medium parameters used: f = 2440 MHz;  $\sigma = 1.855$  S/m;  $\varepsilon_r = 37.991$ ;  $\rho =$ 

Date: 2019/03/21

 $1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 23.2 °C

- Probe: EX3DV4 SN3650; ConvF(7.64, 7.64, 7.64); Calibrated: 2018/07/27
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn579; Calibrated: 2018/08/27
- Phantom: Twin SAM Phantom 1822; Type: QD000P40CD;
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)
- Area Scan (71x171x1): Interpolated grid: dx=1.200 mm, dy=1.200 mmMaximum value of SAR (interpolated) = 0.211 W/kg
- Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm Reference Value = 10.39 V/m; Power Drift = -0.03 dB Peak SAR (extrapolated) = 0.404 W/kg SAR(1 g) = 0.178 W/kg; SAR(10 g) = 0.078 W/kg Maximum value of SAR (measured) = 0.290 W/kg







# Appendix C. Calibration Certificate for Probe and Dipole

The SPEAG calibration certificates are shown as follows.

Report Format Version 5.0.0 Issued Date : Apr. 02, 2019

Report No. : SA170601C08C Reference No.: 190227C19

## Calibration Laboratory of Schmid & Partner Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client

B.V. ADT (Auden)

Certificate No: D2450V2-737\_Aug18

## **CALIBRATION CERTIFICATE**

Object **D2450V2 - SN:737** 

Calibration procedure(s) QA CAL-05.v10

Calibration procedure for dipole validation kits above 700 MHz

Calibration date: August 24, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID#	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-17)	In house check: Oct-18
	Name	Function	Signature
Calibrated by:	Manu Seitz	Laboratory Technician	and .
			V
Approved by:	Katja Pokovic	Technical Manager	eout

Issued: August 24, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-737\_Aug18

## **Calibration Laboratory of**

Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accreditation No.: SCS 0108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

#### Glossary:

TSL

tissue simulating liquid

ConvF N/A sensitivity in TSL / NORM x,y,z not applicable or not measured

## Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### **Additional Documentation:**

e) DASY4/5 System Handbook

#### **Methods Applied and Interpretation of Parameters:**

- Measurement Conditions: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
  point exactly below the center marking of the flat phantom section, with the arms oriented
  parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

## **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.1
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, $dy$ , $dz = 5 mm$	
Frequency	2450 MHz ± 1 MHz	

## **Head TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.7 ± 6 %	1.86 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	OWNER.	( and a

## **SAR** result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.2 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.13 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg ± 16.5 % (k=2)

## **Body TSL parameters**

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	51.8 ± 6 %	2.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		****

## **SAR** result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.9 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	6.01 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.8 W/kg ± 16.5 % (k=2)

Certificate No: D2450V2-737\_Aug18

## Appendix (Additional assessments outside the scope of SCS 0108)

## **Antenna Parameters with Head TSL**

Impedance, transformed to feed point	$55.6 \Omega + 4.1 j\Omega$
Return Loss	- 23.7 dB

### **Antenna Parameters with Body TSL**

Impedance, transformed to feed point	49.4 Ω + 7.3 jΩ
Return Loss	- 22.7 dB

## **General Antenna Parameters and Design**

Electrical Delay (one direction)	1.162 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

#### **Additional EUT Data**

Manufactured by	SPEAG
Manufactured on	August 26, 2003

Certificate No: D2450V2-737\_Aug18

#### **DASY5 Validation Report for Head TSL**

Date: 23.08.2018

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737** 

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma = 1.86 \text{ S/m}$ ;  $\varepsilon_r = 37.7$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### DASY52 Configuration:

• Probe: EX3DV4 - SN7349; ConvF(7.88, 7.88, 7.88) @ 2450 MHz; Calibrated: 30.12.2017

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 26.10.2017

• Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001

• DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 115.2 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 26.1 W/kg


SAR(1 g) = 13.2 W/kg; SAR(10 g) = 6.13 W/kg

Maximum value of SAR (measured) = 21.7 W/kg



0 dB = 21.7 W/kg = 13.36 dBW/kg

## Impedance Measurement Plot for Head TSL



## **DASY5 Validation Report for Body TSL**

Date: 24.08.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:737

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma = 2.02$  S/m;  $\epsilon_r = 51.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

#### **DASY52 Configuration:**

Probe: EX3DV4 - SN7349; ConvF(8.01, 8.01, 8.01) @ 2450 MHz; Calibrated: 30.12.2017

• Sensor-Surface: 1.4mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn601; Calibrated: 26.10.2017

• Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002

• DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

# Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.8 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 25.5 W/kg

SAR(1 g) = 12.9 W/kg; SAR(10 g) = 6.01 W/kg

Maximum value of SAR (measured) = 20.9 W/kg



0 dB = 20.9 W/kg = 13.20 dBW/kg

## Impedance Measurement Plot for Body TSL

