

FCC Test Report

Report No.: RF170601C08C-4

FCC ID: 2AH2Q-DREEM2

Test Model: Dreem+

Received Date: Feb. 27, 2019

Test Date: Mar. 07, 2019 ~ Mar. 21, 2019

Issued Date: Apr. 02, 2019

Applicant: DREEM SAS

Address: 7-11 Boulevard Haussmann Paris 75009, France

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan

Hsien 333, Taiwan, R.O.C.

FCC Registration /

788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF170601C08C-4 Page No. 1 / 23 Report Format Version:6.1.2 Reference No.: 190227C19



Table of Contents

Re	Release Control Record3			
1	Certificate of Conformity	4		
2	Summary of Test Results	5		
	2.1 Measurement Uncertainty			
3	General Information	6		
	3.1 General Description of EUT	7 8 9 9		
4	Test Types and Results	10		
	4.1 Radiated Emission and Bandedge Measurement 4.1.1 Limits of Radiated Emission and Bandedge Measurement 4.1.2 Limits of Unwanted Emission Out of the Restricted Bands 4.1.3 Test Instruments 4.1.4 Test Procedures 4.1.5 Deviation from Test Standard 4.1.6 Test Setup 4.1.7 EUT Operating Conditions 4.1.8 Test Results	. 10 11 . 12 . 13 . 13 . 14		
5	Pictures of Test Arrangements	. 22		
A	pendix – Information of the Testing Laboratories	23		



Release Control Record

Issue No.	Description	Date Issued
RF170601C08C-4	Original Release	Apr. 02, 2019

Report No.: RF170601C08C-4 Page No. 3 / 23 Reference No.: 190227C19 Report Format Version:6.1.2



1 Certificate of Conformity

Product: Sleep tracking device

Brand: DREEM

Test Model: Dreem+

Sample Status: Production Unit

Applicant: DREEM SAS

Test Date: Mar. 07, 2019 ~ Mar. 21, 2019

Standards: 47 CFR FCC Part 15, Subpart E (Section 15.407)

ANSI C63.10:2013

This report is issued as a supplementary report to BV CPS report no.: RF170601C08-1. This report shall be used by combining with its original report.

Prepared by : ________, Date: _________, Apr. 02, 2019

Ivonne Wu / Supervisor

Dylan Chiou / Project Engineer



2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)					
FCC Clause	Test Item	Result	Remarks		
15.407(b)(6)	AC Power Conducted Emissions	N/A	Refer to Note		
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -4.3 dB at 5725 MHz.		
15.407(a)(1/2/ 3)	Max Average Transmit Power	N/A	Refer to Note		
	Occupied Bandwidth Measurement	N/A	Refer to Note		
15.407(a)(1/2/ 3)	Peak Power Spectral Density	N/A	Refer to Note		
15.407(e)	15.407(e) 6 dB Bandwidth N/A Refe		Refer to Note		
15.407(g)	Frequency Stability	ty N/A Refer to Note			
15.203	15.203 Antenna Requirement Pass No antenna connector is use		No antenna connector is used.		

Note:

- 1. Only radiated emissions test had been performed for the addendum. Refer to original report for other test data.
- 2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
	9 kHz ~ 30 MHz	3.04 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.93 dB
	200 MHz ~ 1000 MHz	2.95 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	2.26 dB
Radiated Emissions above 1 GHz	18 GHz ~ 40 GHz	1.94 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	Sleep tracking device
Brand	DREEM
Test Model	Dreem+
Status of EUT	Production Unit
Power Supply Rating	5.0 Vdc (adapter or host equipment) 3.7 Vdc (Li-ion battery)
Modulation Type	64QAM, 16QAM, QPSK, BPSK
Modulation Technology	OFDM
Transfer Rate	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0 Mbps 802.11n: up to 72.2 Mbps
Operating Frequency	5180 ~ 5240 MHz, 5260 ~ 5320 MHz, 5500 ~ 5700 MHz, 5745 ~ 5825 MHz
Number of Channel	5180 ~ 5240 MHz: 4 for 802.11a, 802.11n (HT20) 5260 ~ 5320 MHz: 4 for 802.11a, 802.11n (HT20) 5500 ~ 5700 MHz: 11 for 802.11a, 802.11n (HT20) 5745 ~ 5825 MHz: 5 for 802.11a, 802.11n (HT20)
Antenna Type	Chip antenna with -1.49 dBi gain (5180 ~ 5240 MHz) Chip antenna with -1.49 dBi gain (5260 ~ 5320 MHz) Chip antenna with -1.77 dBi gain (5500 ~ 5700 MHz) Chip antenna with -1.83 dBi gain (5745 ~ 5825 MHz)
Antenna Connector N/A	
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

1. This report is issued as a supplementary report to BV CPS report no.: RF170601C08-1. The difference is listed as below. Only the worst case of original radiated emission test was verified in this report.

Report No.	FCC ID	Applicant	Brand	Model	Difference
RF170601C08-1	2AH2Q-DREEM	Rythm SAS	RYTHM	DREEM	Without BT function
RF190227C19-4	2AH2Q-DREEM2	DREEM SAS	DREEM	Dreem+	With BT function

2. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	Linshiung	SK12G-0500100Z	I/P: 100-240 Vac, 50/60 Hz, 0.2 A O/P: 5 Vdc, 1 A
Battery	JS Power	DREEM	3.7 Vdc, 1200 mAh

3. The EUT provides one transmitter and receiver.

Modulation Mode	Tx Function
802.11a	1TX
802.11n (HT20)	1TX

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.



3.2 Description of Test Modes

For 5180 ~ 5240 MHz

4 channels are provided for 802.11a, 802.11n (HT20):

Channel		Frequency (MHz)	Channel	Frequency (MHz)
	36	5180	44	5220
	40	5200	48	5240

For 5260 ~ 5320 MHz

4 channels are provided for 802.11a, 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	60	5300
56	5280	64	5320

For 5500 ~ 5700 MHz

11 channels are provided for 802.11a, 802.11n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	124	5620
104	5520	128	5640
108	5540	132	5660
112	5560	136	5680
116	5580	140	5700
120	5600		

For 5745 ~ 5825 MHz:

5 channels are provided for 802.11a, 802.11n (HT20):

, , ,				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	
149	5745	161	5805	
153	5765	165	5825	
157	5785			



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure	Applic	able To	Description
Mode	RE≥1G	RE<1G	Description
-	V	√	-

Where

RE≥1G: Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	5180-5240	802.11a	36 to 48	36	OFDM	BPSK	6.0
	5260-5320	802.11a	52 to 64	64	OFDM	BPSK	6.0
	5500-5700	802.11a	100 to 140	140	OFDM	BPSK	6.0
	5745-5825	802.11n (HT20)	149 to 159	157	OFDM	BPSK	6.5

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Frequency Band (MHz)	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
-	5500-5700	802.11a	100 to 140	140	OFDM	BPSK	6.0

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang

Report No.: RF170601C08C-4 Reference No.: 190227C19


^{2. &}quot;-" means no effect.



3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Report No.: RF170601C08C-4 Page No. 10 / 23 Reference No.: 190227C19



4.1.2 Limits of Unwanted Emission Out of the Restricted Bands

А	pplicable To	Limit			
789033 D02 Ge	eneral UNII Test Procedures	Field Strength at 3 m			
Ne	w Rules v02r01	PK: 74 (dBµV/m)	AV: 54 (dBμV/m)		
Frequency Band Applicable To		EIRP Limit	Equivalent Field Strength at 3 m		
5150~5250 MHz	15.407(b)(1)				
5250~5350 MHz	15.407(b)(2)	PK: -27 (dBm/MHz)	PK: 68.2 (dBµV/m)		
5470~5725 MHz	15.407(b)(3)				
		PK:-27 (dBm/MHz) *1	PK: 68.2 (dBµV/m) *1		
	45 407(5)(4)(;)	PK:10 (dBm/MHz) *2	PK:105.2 (dBµV/m) *2		
5725~5850 MHz	15.407(b)(4)(i)	PK:15.6 (dBm/MHz) *3	PK: 110.8 (dBµV/m) *3		
		PK:27 (dBm/MHz) *4	PK:122.2 (dBµV/m) *4		
	15.407(b)(4)(ii)	Emission limits in section 15.247(d)			

^{*1} beyond 75 MHz or more above of the band edge.

Note:

The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3}$$
 µV/m, where P is the eirp (Watts).

Report No.: RF170601C08C-4 Reference No.: 190227C19

^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.

^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.

^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



4.1.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY52260177	Aug. 20, 2018	Aug. 19, 2019
Spectrum Analyzer Agilent	N9010A	MY52220314	Dec. 13, 2018	Dec. 12, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	100115	Jan. 21, 2019	Jan. 20, 2020
Broadband Horn Antenna SCHWARZBECK	BBHA 9170	148	Nov. 25, 2018	Nov. 24, 2019
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 25, 2018	Nov. 24, 2019
BILOG Antenna SCHWARZBECK	VULB 9168	9168-472	Nov. 23, 2018	Nov. 22, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 16, 2018	Apr. 15, 2019
Loop Antenna	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
Preamplifier EMCI	EMC001340	980201	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 012645	980115	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 184045	980116	Oct. 12, 2018	Oct. 11, 2019
Preamplifier EMCI	EMC 330H	980112	Oct. 12, 2018	Oct. 11, 2019
Power Meter Anritsu	ML2495A	1012010	Sep. 05, 2018	Sep. 04, 2019
Power Sensor Anritsu	MA2411B	1315050	Sep. 04, 2018	Sep. 03, 2019
RF Coaxial Cable HUBER+SUHNNER	EMC104-SM-SM-800 0&3000	140811+170717	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable HUBER+SUHNNER	SUCOFLEX 104	EMC104-SM-SM- 1000(140807)	Oct. 12, 2018	Oct. 11, 2019
RF Coaxial Cable WOKEN	8D-FB	Cable-Ch10-01	Oct. 12, 2018	Oct. 11, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

- Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 - 2. The test was performed in HwaYa Chamber 10.
 - 3. The horn antenna and preamplifier (model: EMC 184045) are used only for the measurement of emission frequency above 1 GHz if tested.
 - 4. The IC Site Registration No. is 7450F-10.



4.1.4 Test Procedures

For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.5 Deviation from Test Standard


No deviation.

Report No.: RF170601C08C-4 Page No. 13 / 23 Report Format Version:6.1.2 Reference No.: 190227C19




4.1.6 Test Setup

<Radiated Emission below 30 MHz>




<Radiated Emission 30 MHz to 1 GHz>





<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.7 EUT Operating Conditions

- a. Placed the EUT on a testing table.
- b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.



4.1.8 Test Results

Above 1 GHz Data:

802.11a

EUT Test Condition		Measurement Detail		
Channel	Channel 36	Frequency Range	1 GHz ~ 40 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Jisyong Wang	

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5150	47.75	47.17	54	-6.25	31.56	6.34	37.32	100	34	Average
5150	59.79	59.21	74	-14.21	31.56	6.34	37.32	100	34	Peak
5180	92.63	92.01			31.59	6.37	37.34	100	34	Average
5180	99.5	98.88			31.59	6.37	37.34	100	34	Peak
*10360	56.13	58.89	68.2	-12.07	39.48	10.21	52.45	115	24	Peak
		A	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5150	46.95	46.37	54	-7.05	31.56	6.34	37.32	100	350	Average
5150	57.97	57.39	74	-16.03	31.56	6.34	37.32	100	350	Peak
5180	90.72	90.1			31.59	6.37	37.34	100	350	Average
5180	98.34	97.72			31.59	6.37	37.34	100	350	Peak
*10360	55.85	58.61	68.2	-12.35	39.48	10.21	52.45	100	291	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 5180 MHz: Fundamental Frequency
- 3. *: Out of Restricted Band
- 4. The emission levels of other frequencies were very low against the limit

Report No.: RF170601C08C-4 Reference No.: 190227C19 Page No. 16 / 23

Report Format Version:6.1.2



802.11a

EUT Test Condition		Measurement Detail		
Channel	Channel 64	Frequency Range	1 GHz ~ 40 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Jisyong Wang	

Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	89.96	89.41			31.45	6.29	37.19	189	340	Average
5320	98.88	98.33			31.45	6.29	37.19	189	340	Peak
5350	46.17	45.58	54	-7.83	31.48	6.29	37.18	189	340	Average
5350	63.18	62.59	74	-10.82	31.48	6.29	37.18	189	340	Peak
10640	45.47	48.92	54	-8.53	39.62	9.2	52.27	100	154	Average
10640	57.04	60.49	74	-16.96	39.62	9.2	52.27	100	154	Peak
		A	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5320	87.26	86.71			31.45	6.29	37.19	180	54	Average
5320	95.77	95.22			31.45	6.29	37.19	180	54	Peak
5350	45.09	44.5	54	-8.91	31.48	6.29	37.18	180	54	Average
5350	62.88	62.29	74	-11.12	31.48	6.29	37.18	180	54	Peak
10640	44.58	48.03	54	-9.42	39.62	9.2	52.27	103	127	Average
10640	56.29	59.74	74	-17.71	39.62	9.2	52.27	103	127	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 5320 MHz: Fundamental Frequency
- 3. The emission levels of other frequencies were very low against the limit



802.11a

EUT Test Condition		Measurement Detail		
Channel	Channel 140	Frequency Range	1 GHz ~ 40 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Jisyong Wang	

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5454	38.37	37.55	54	-15.63	31.56	6.34	37.08	205	317	Average
5454	61.14	60.32	74	-12.86	31.56	6.34	37.08	205	317	Peak
*5470	57.68	56.85	68.2	-10.52	31.57	6.34	37.08	205	317	Peak
5700	84.42	83.23			31.9	6.69	37.4	205	317	Average
5700	100.97	99.78			31.9	6.69	37.4	205	317	Peak
*5725	63.9	62.62	68.2	-4.3	31.96	6.75	37.43	205	317	Peak
11400	46.29	48.55	54	-7.71	39.96	9.91	52.13	177	38	Average
11400	57.38	59.64	74	-16.62	39.96	9.91	52.13	177	38	Peak
		P	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5408	38.57	37.91	54	-15.43	31.52	6.32	37.18	220	333	Average
5408	60.25	59.59	74	-13.75	31.52	6.32	37.18	220	333	Peak
*5470	58.52	57.69	68.2	-9.68	31.57	6.34	37.08	220	333	Peak
5700	80.87	79.68			31.9	6.69	37.4	220	333	Average
5700	95.59	94.4			31.9	6.69	37.4	220	333	Peak
*5725	59.37	58.09	68.2	-8.83	31.96	6.75	37.43	220	333	Peak
11400	45.85	48.11	54	-8.15	39.96	9.91	52.13	201	115	Average
11400	57.87	60.13	74	-16.13	39.96	9.91	52.13	201	115	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor
 Margin value = Emission level Limit value
- 2. 5700 MHz: Fundamental Frequency
- 3. *: Out of Restricted Band
- 4. The emission levels of other frequencies were very low against the limit



802.11n (HT20)

EUT Test Condition		Measurement Detail				
Channel	Channel 157 Frequency Range		1 GHz ~ 40 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Jisyong Wang			

<spuriou< th=""><th>s Emissic</th><th>n></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></spuriou<>	s Emissic	n>								
	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5785	84.51	83.19			32.04	6.82	37.54	200	316	Average
5785	101.59	100.27			32.04	6.82	37.54	200	316	Peak
11570	43.89	47.35	54	-10.11	39.78	10.09	53.33	100	94	Average
11570	53.44	56.9	74	-20.56	39.78	10.09	53.33	100	94	Peak
		Α	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
5785	80.93	79.61			32.04	6.82	37.54	126	254	Average
5785	97.44	96.12			32.04	6.82	37.54	126	254	Peak
11570	43.49	46.95	54	-10.51	39.78	10.09	53.33	101	178	Average
11570	53.86	57.32	74	-20.14	39.78	10.09	53.33	101	178	Peak

<out e<="" of="" th=""><th>Jana Emis</th><th>3011 (00</th><th>, <u>, , , , , , , , , , , , , , , , , , </u></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></out>	Jana Emis	3011 (00	, <u>, , , , , , , , , , , , , , , , , , </u>							
Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
*5612.7	51.45	50.34	68.2	-16.75	31.77	6.56	37.22	200	316	Peak
5653.075	49.55	48.36	70.49	-20.94	31.85	6.62	37.28	200	316	Peak
5924.3	50.48	48.68	68.72	-18.24	32.29	7.01	37.5	200	316	Peak
*6003.625	52.68	50.65	68.2	-15.52	32.4	7.14	37.51	200	316	Peak
		A	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
*5625.525	51.36	50.23	68.2	-16.84	31.79	6.56	37.22	126	254	Peak
5654.025	48.32	47.19	71.19	-22.87	31.85	6.62	37.34	126	254	Peak
5920.975	48.57	46.8	71.17	-22.6	32.26	7.01	37.5	126	254	Peak
*6013.125	51.22	49.13	68.2	-16.98	32.45	7.14	37.5	126	254	Peak

- 1. Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 5785 MHz: Fundamental Frequency
- 3. *: Out of Restricted Band
- 4. The emission levels of other frequencies were very low against the limit



9 kHz ~ 30 MHz Data:


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

30 MHz ~ 1 GHz Worst-Case Data:


802.11a

EUT Test Condition		Measurement Detail				
Channel 140		Frequency Range	30 MHz ~ 1 GHz			
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)			
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Jisyong Wang			

Horizontal



Vertical





Antenna Polarity & Test Distance: Horizontal at 3 m										
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
90.14	25.14	47.83	43.5	-18.36	8.3	0.97	31.96	188	106	Peak
174.53	30.52	49.86	43.5	-12.98	11.28	1.16	31.78	196	113	Peak
441.28	23.83	37.7	46	-22.17	16.16	1.97	32	175	83	Peak
729.37	28.25	36.12	46	-17.75	21.23	2.5	31.6	191	319	Peak
844.8	35.69	42.05	46	-10.31	22.8	2.67	31.83	118	247	Peak
940.83	32.35	37.71	46	-13.65	23.74	2.82	31.92	145	23	Peak
Antenna Polarity & Test Distance: Vertical at 3 m										
Frequency (MHz)	Emission Level	Read Level	Limit (dBuV/m)	Margin (dB)	Antenna Factor	Cable Loss (dB)	Preamp Factor	Antenna Height	Table Angle	Remark

	Antenna Folanty & Test Distance. Vertical at 3 in									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
42.61	26.25	43.09	40	-13.75	13.58	0.66	31.08	111	72	Peak
167.74	24.03	42.68	43.5	-19.47	11.96	1.15	31.76	165	243	Peak
480.08	25.31	38.18	46	-20.69	16.93	2.05	31.85	107	211	Peak
768.17	30.49	37.48	46	-15.51	21.78	2.56	31.33	102	31	Peak
864.2	32.4	38.59	46	-13.6	23.05	2.7	31.94	125	198	Peak
940.83	30.76	36.12	46	-15.24	23.74	2.82	31.92	117	207	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. The emission levels of other frequencies were very low against the limit



5 Pictures of Test Arrangements	
Please refer to the attached file (Test Setup Photo).	

Report No.: RF170601C08C-4 Reference No.: 190227C19



Appendix - Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF170601C08C-4 Reference No.: 190227C19