

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Report No.: SZEM180400290602 Fax: +86 (0) 755 2671 0594

Fax: +86 (0) 755 2671 0594 Page: 1 of 89

TEST REPORT

Application No.: SZEM1804002906CR

Applicant: Westone Laboratories, Inc

Address of Applicant: 2235 Executive Circle, Colorado Springs, Colorado, United States

Manufacturer: Westone Laboratories, Inc

Address of Manufacturer: 2235 Executive Circle, Colorado Springs, Colorado, United States

Factory: Shenzhen Horn Audio Co., Ltd.

Address of Factory: No. 6, 4th Guiha Road, Pingshan New District, Shenzhen, Guangdong,

P.R.China

Equipment Under Test (EUT):

EUT Name: Westone Bluetooth Cable 2.0

Model No.: WBT V2

FCC ID: 2AH2R-WBTV2

Trade mark: Westone

Standard(s): 47 CFR Part 15, Subpart C 15.247

Date of Receipt: 2018-04-19

Date of Test: 2018-04-25 to 2018-04-26

Date of Issue: 2018-05-03

Test Result: Pass*



EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's intengray's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEM180400290602

Page: 2 of 89

	Revision Record						
Version	on Chapter Date Modifier Remark						
01		2018-05-03		Original			

Authorized for issue by:		
	Hany Ul	
	Harry Wu /Project Engineer	
	EvicFu	
	Eric Fu /Reviewer	



Report No.: SZEM180400290602

Page: 3 of 89

2 Test Summary

Radio Spectrum Technical Requirement							
Item	Standard	Method	Requirement	Result			
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass			
Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)	Pass			

Radio Spectrum Matter Part						
Item	Standard	Method	Requirement	Result		
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(1)	Pass		
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass		
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass		
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass		
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass		
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		



Report No.: SZEM180400290602

Page: 4 of 89

3 Contents

			Page
1	COVE	R PAGE	1
2	TEST	SUMMARY	3
3	CONTI	ENTS	4
4	GENE	RAL INFORMATION	6
	4.1 D	ETAILS OF E.U.T.	6
	4.2 D	ESCRIPTION OF SUPPORT UNITS	6
	4.3 N	SEASUREMENT UNCERTAINTY	6
	4.4 T	EST LOCATION	7
		EST FACILITY	
		EVIATION FROM STANDARDS	
	4.7 A	BNORMALITIES FROM STANDARD CONDITIONS	7
5	EQUIP	MENT LIST	8
6	RADIC	SPECTRUM TECHNICAL REQUIREMENT	12
٠		NTENNA REQUIREMENT	
	6.1.1	Test Requirement:	
	6.1.2	Conclusion	
	-	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM HOPPING SEQUENCE	
	6.2.1	Test Requirement:	
	6.2.2	Conclusion	
7	RADIC	SPECTRUM MATTER TEST RESULTS	14
	7.1 C	ONDUCTED PEAK OUTPUT POWER	14
	7.1.1		
	7.1.2	Test Setup Diagram	
	7.1.3	Measurement Procedure and Data	15
		0dB Bandwidth	
	7.2.1		
	7.2.2	Test Setup Diagram	
	7.2.3	Measurement Procedure and Data	
		ARRIER FREQUENCIES SEPARATION	
		E.U.T. Operation	
	7.3.2	Test Setup Diagram	
	<i>7.3.3</i> 7.4 H	Measurement Procedure and Data	
	7.4	E.U.T. Operation	
	7.4.1 7.4.2	Test Setup Diagram	
	7.4.2	Measurement Procedure and Data	
	_	WELL TIME	
	7.5.1	E.U.T. Operation	
	7.5.2	Test Setup Diagram	
	7.5.3	Measurement Procedure and Data	
	7.6.1	ONDUCTED BAND EDGES MEASUREMENT	
	7.0.1	ONDUCTED BAND EDGES MEASUREMENT	
	7.6.2		21 21

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 5 of 89

7.7.1 E.U.T. Operation	
7.7.3 Measurement Procedure and Data	
7.8 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	24
7.8.1 E.U.T. Operation	25
7.8.2 Test Setup Diagram	
7.8.3 Measurement Procedure and Data	26
7.9 RADIATED SPURIOUS EMISSIONS	
7.9.1 E.U.T. Operation	32
7.9.2 Test Setup Diagram	32
7.9.3 Measurement Procedure and Data	33
8 APPENDIX	43-89



Report No.: SZEM180400290602

Page: 6 of 89

4 General Information

4.1 Details of E.U.T.

Power supply:	Earphone: DC3.7V, 120mAh Battery; Charging Case: DC3.7V, 200mAh Battery can be charged by Micro USB port
Bluetooth Version	V4.2
Antenna Gain:	4.9 dBi
Antenna Type:	Chip Antenna
Channel Spacing:	1MHz
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channels:	79
Operation Frequency:	2402MHz to 2480MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 ⁻⁸
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	DE Dadieted newer	4.5dB (below 1GHz)
/	RF Radiated power	4.8dB (above 1GHz)
8	Dedicted Cruvious emission test	4.5dB (Below 1GHz)
8	Radiated Spurious emission test	4.8dB (Above 1GHz)
9	Temperature test	1℃
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



Report No.: SZEM180400290602

Page: 7 of 89

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

· CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC

Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC -Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: SZEM180400290602

Page: 8 of 89

5 Equipment List

Conducted Peak Output Power						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	

20dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Carrier Frequencies Separation						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26	

Hopping Channel Number						
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date	
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26	
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26	
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A	
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12	
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A	
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26	

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 9 of 89

Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26
-------------	-----------------	------	-----------	------------	------------

Dwell Time					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2017-09-27	2018-09-26
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-02	2017-07-13	2018-07-12
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2017-09-27	2018-09-26
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2017-09-27	2018-09-26

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions-Serms-e-Document.aspx. Attention is drawn to the limitation of electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions-Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 10 of 89

Horn Antenna (1- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna(15GHz- 40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1- 1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier(100MHz- 18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier(26GHz- 40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6- 27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2017-07-13	2018-07-12
Spectrum Analyzer	Rohde & Schwarz	FSU43	SEM004-08	2018-04-02	2019-04-01
BiConiLog Antenna (26- 3000MHz)	ETS-Lindgren	3142C	SEM003-01	2017-06-27	2020-06-26
Horn Antenna (1- 18GHz)	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna(15GHz- 40GHz)	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-amplifier (0.1- 1300MHz)	HP	8447D	SEM005-02	2017-09-27	2018-09-26
Low Noise Amplifier(100MHz- 18GHz)	Black Diamond Series	BDLNA-0118- 352810	SEM005-05	2017-09-27	2018-09-27
Pre-amplifier(18-26GHz)	Rohde & Schwarz	CH14-H052	SEM005-17	2018-04-02	2019-04-01
Pre-amplifier(26GHz- 40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2018-04-02	2019-04-01
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2017-09-27	2018-09-26
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-22	2020-08-21
Band filter	N/A	N/A	SEM023-01	N/A	N/A



Report No.: SZEM180400290602

Page: 11 of 89

General used equipment	t				
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2017-09-29	2018-09-28
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2017-09-29	2018-09-28
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2018-04-08	2019-04-07



Report No.: SZEM180400290602

Page: 12 of 89

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Report No.: SZEM180400290602

Page: 13 of 89

6.2 Other requirements Frequency Hopping Spread Spectrum System Hopping Sequence

6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.247(a)(1),(g),(h)

6.2.2 Conclusion

Standard Requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1):

According to Technical Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- > Number of shift register stages: 9
- > Length of pseudo-random sequence: 29 -1 = 511 bits
- > Longest sequence of zeros: 8 (non-inverted signal)

Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

Each frequency used equally on the average by each transmitter.

According to Technical Specification, the receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g):

According to Technical Specification, the system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h):

According to Technical specification, the system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

The system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM180400290602

Page: 14 of 89

7 Radio Spectrum Matter Test Results

7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)
Test Method: ANSI C63.10 (2013) Section 7.8.5

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)	
	1 for ≥50 hopping channels	
902-928	0.25 for 25≤ hopping channels <50	
	1 for digital modulation	
	1 for ≥75 non-overlapping hopping channels	
2400-2483.5	0.125 for all other frequency hopping systems	
	1 for digital modulation	
5725-5850	1 for frequency hopping systems and digital modulation	



Report No.: SZEM180400290602

Page: 15 of 89

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.7 % RH Atmospheric Pressure: 1020 mbar

Test mode c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.1.2 Test Setup Diagram



Ground Reference Plane

7.1.3 Measurement Procedure and Data



Report No.: SZEM180400290602

Page: 16 of 89

7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247(a)(1)
Test Method: ANSI C63.10 (2013) Section 7.8.7

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.7 % RH Atmospheric Pressure: 1020 mbar

Test mode c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data



Report No.: SZEM180400290602

Page: 17 of 89

7.3 Carrier Frequencies Separation

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)
Test Method: ANSI C63.10 (2013) Section 7.8.2

Limit: 2/3 of the 20dB bandwidth base on the transmission power is less than

0.125W

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.6 % RH Atmospheric Pressure: 1020 mbar

Test mode b:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.3.2 Test Setup Diagram



Ground Reference Plane

7.3.3 Measurement Procedure and Data



Report No.: SZEM180400290602

Page: 18 of 89

7.4 Hopping Channel Number

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii)

Test Method:

Limit:

ANSI C63.10 (2013) Section 7.8.3

Frequency range(MHz)	Number of hopping channels (minimum)
002 028	50 for 20dB bandwidth <250kHz
902-928	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.6 % RH Atmospheric Pressure: 1020 mbar

Test mode b:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.4.2 Test Setup Diagram



Ground Reference Plane

7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 19 of 89

7.5 Dwell Time

Test Requirement 47 CFR Part 15, Subpart C 15.247a(1)(iii) ANSI C63.10 (2013) Section 7.8.4

Test Method:

Limit:

Frequency(MHz)	Limit		
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)		
902-928	0.4S within a 10S period(20dB bandwidth≥250kHz)		
2400 2482 5	0.4S within a period of 0.4S multiplied by the number		
2400-2483.5	of hopping channels		
5725-5850	0.4S within a 30S period		

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.5 % RH Atmospheric Pressure: 1020 mbar

Test mode b:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.5.2 Test Setup Diagram



Ground Reference Plane

7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at https://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights an obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 20 of 89

7.6 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 7.8.6

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in

§15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)



Report No.: SZEM180400290602

Page: 21 of 89

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 59.4 % RH Atmospheric Pressure: 1020 mbar

Pretest these modes to find the worst case:

b:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, $\pi/4DQPSK$ modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4DQPSK$ modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

The worst case for final test:


b:TX_Hop mode_Keep the EUT in frequency hopping mode with GFSK modulation, $\pi/4DQPSK$ modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK modulation, $\pi/4DQPSK$ modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.6.2 Test Setup Diagram



Ground Reference Plane

7.6.3 Measurement Procedure and Data



Report No.: SZEM180400290602

Page: 22 of 89

7.7 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread

spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition,

radiated emissions which fall in the restricted bands, as defined in

§15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)



Report No.: SZEM180400290602

Page: 23 of 89

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 59.5 % RH Atmospheric Pressure: 1020 mbar

Test mode c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.7.2 Test Setup Diagram



Ground Reference Plane

7.7.3 Measurement Procedure and Data



Report No.: SZEM180400290602

Page: 24 of 89

7.8 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM180400290602

Page: 25 of 89

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar


Test mode c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.

7.8.2 Test Setup Diagram





30MHz-1GHz Above 1GHz



Report No.: SZEM180400290602

Page: 26 of 89

7.8.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.
- Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Report No.: SZEM180400290602

Page: 27 of 89

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No : 02906CR

Mode : 2402 Band edge

Note : BT


	Freq						Limit Line		Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.121	5.40	28.90	41.85	51.98	44.43	74.00	-29.57	peak
2	2390.000	5.47	29.08	41.87	49.45	42.13	74.00	-31.87	peak
3 рр	2402.000	5.49	29.11	41.88	106.51	99.23	74.00	25.23	peak



Report No.: SZEM180400290602

Page: 28 of 89

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL

Job No : 02906CR

Mode : 2402 Band edge

Note : BT


	_									
		Freq			Preamp Factor					Remark
	-	MHz			——dB				——dB	
		2333.318								
2		2390.000	5.47	29.08	41.87	47.78	40.46	74.00	-33.54	peak
3	рр	2402.000	5.49	29.11	41.88	99.28	92.00	74.00	18.00	peak



Report No.: SZEM180400290602

Page: 29 of 89

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL

Job No : 02906CR

Mode : 2480 Band edge

Note : BT


	Freq			Preamp Read Factor Level					
-	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
	2480.000 2483.500								•



Report No.: SZEM180400290602

Page: 30 of 89

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL Job No : 02906CR

Mode : 2480 Band edge

Note : BT

Cable Ant Preamp Read Limit 0ver Freq Loss Factor Factor Level Level Line Limit Remark MHz dΒ dBuV dBuV/m dBuV/m dB dB dB/m 1 pp 2480.000 5.59 29.34 41.91 100.74 93.76 74.00 19.76 peak 5.60 29.35 41.91 56.06 49.10 74.00 -24.90 peak 2483.500



Report No.: SZEM180400290602

Page: 31 of 89

7.9 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Report No.: SZEM180400290602

Page: 32 of 89

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 56 % RH Atmospheric Pressure: 1020 mbar


Test mode c:TX_non-Hop mode_Keep the EUT in continuously transmitting mode with GFSK

modulation, π/4DQPSK modulation, 8DPSK modulation. All modes have been

tested and only the data of worst case is recorded in the report.


7.9.2 Test Setup Diagram





Below 30MHz

30MHz-1GHz



Above 1GHz



Report No.: SZEM180400290602

Page: 33 of 89

7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Report No.: SZEM180400290602

Page: 34 of 89

30MHz~1GHz

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

 $L_3 / L_{10} = D_{10} / D_3$

Note:

 L_3 : Level @ 3m distance. Unit: uV/m; L_{10} : Level @ 10m distance. Unit: uV/m;

D₃: 3m distance. Unit: m D₁₀: 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
40.84	13.62	4.80	15.99	24.08	40.00	-15.92	Н
157.56	14.65	5.40	18.00	25.11	43.50	-18.39	Н
290.02	15.22	5.77	19.23	25.68	46.00	-20.32	Н
443.29	18.84	8.75	29.17	29.30	46.00	-16.70	Н
654.23	23.38	14.76	49.19	33.84	46.00	-12.16	Н
887.61	27.60	23.99	79.96	38.06	46.00	-7.94	Н
39.02	14.48	5.30	17.66	24.94	40.00	-15.06	V
161.47	15.41	5.90	19.65	25.87	43.50	-17.63	V
276.12	14.43	5.27	17.55	24.89	46.00	-21.11	V
338.40	17.41	7.42	24.74	27.87	46.00	-18.13	V
572.61	22.70	13.65	45.49	33.16	46.00	-12.84	V
887.61	27.44	23.55	78.50	37.90	46.00	-8.10	V




Report No.: SZEM180400290602

Page: 35 of 89

QP value:

Mode:c; Polarization:Horizontal;



Condition: 10m HORIZONTAL

Job No. : 02906CR

Test Mode: c


	Freq			Preamp Factor				Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	40.84	6.80	13.25	32.55	26.12	13.62	29.50	-15.88
2	157.56	7.49	13.39	32.51	26.28	14.65	33.00	-18.35
3	290.02	8.03	12.41	32.45	27.23	15.22	35.60	-20.38
4	443.29	8.41	16.01	32.42	26.84	18.84	35.60	-16.76
5	654.23	9.04	19.59	32.40	27.15	23.38	35.60	-12.22
6 pp	887.61	9.50	22.06	31.64	27.68	27,60	35,60	-8.00



Report No.: SZEM180400290602

Page: 36 of 89

Mode:c; Polarization:Vertical



Condition: 10m VERTICAL

Job No. : 02906CR

Test Mode: c

	_			Preamp				
	Freq	Loss	Factor	Factor	revel	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	$\overline{\text{dBuV/m}}$	dB
1	39.02	6 78	13 19	32.56	27 07	1/ /8	30 00	_15_52
2	161.47			32.52				
3	276.12	7.98	12.04	32.46	26.87	14.43	37.00	-22.57
4	338.40	8.19	13.63	32.44	28.03	17.41	37.00	-19.59
5	572.61	8.83	18.14	32.41	28.14	22.70	37.00	-14.30
6 pp	887.61	9.50	22.06	31.64	27.52	27.44	37.00	-9.56




Report No.: SZEM180400290602

Page: 37 of 89

Above 1GHz

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Condition: 3m HORIZONTAL

Job No : 02906CR

Mode : 2402 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	_									
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1335.141	4.93	25.11	41.29	49.92	38.67	74.00	-35.33	peak
2		4304.400	7.34	33.60	42.38	49.36	47.92	74.00	-26.08	peak
3	av	4804.000	7.89	34.16	42.47	32.17	31.75	54.00	-22.25	Average
4	pp	4804.000	7.89	34.16	42.47	56.94	56.52	74.00	-17.48	peak
5		5224.153	8.44	34.45	42.29	49.70	50.30	74.00	-23.70	peak
6		7206.000	10.08	36.42	40.71	47.77	53.56	74.00	-20.44	peak
7		9608.000	10.75	37.52	37.74	43.60	54.13	74.00	-19.87	peak



Report No.: SZEM180400290602

Page: 38 of 89

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Condition: 3m VERTICAL

Job No : 02906CR

Mode : 2402 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	_									
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1335.141	4.93	25.11	41.29	51.56	40.31	74.00	-33.69	peak
2		4004.339	6.99	33.60	42.33	49.43	47.69	74.00	-26.31	peak
3	av	4804.000	7.89	34.16	42.47	31.33	30.91	54.00	-23.09	Average
4	pp	4804.000	7.89	34.16	42.47	56.10	55.68	74.00	-18.32	peak
5		6894.806	10.42	36.21	40.93	46.49	52.19	74.00	-21.81	peak
6		7206.000	10.08	36.42	40.71	47.50	53.29	74.00	-20.71	peak
7		9608.000	10.75	37.52	37.74	42.95	53.48	74.00	-20.52	peak



Report No.: SZEM180400290602

Page: 39 of 89

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:middle



Condition: 3m HORIZONTAL

Job No : 02906CR Mode : 2441 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	_									
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1335.141	4.93	25.11	41.29	51.19	39.94	74.00	-34.06	peak
2		4482.150	7.54	33.60	42.41	48.29	47.02	74.00	-26.98	peak
3 a	av	4882.000	7.97	34.30	42.48	33.62	33.41	54.00	-20.59	Average
4 p	pр	4882.000	7.97	34.30	42.48	58.40	58.19	74.00	-15.81	peak
5		6451.353	11.45	35.06	41.25	46.49	51.75	74.00	-22.25	peak
6		7323.000	10.05	36.37	40.63	46.60	52.39	74.00	-21.61	peak
7		9764.000	10.82	37.55	37.52	42.28	53.13	74.00	-20.87	peak



Report No.: SZEM180400290602

Page: 40 of 89

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:middle



Condition: 3m VERTICAL

Job No : 02906CR

Mode : 2441 TX SE


	Freq			Preamp Factor					Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	41.29	50.78	39.53	74.00	-34.47	peak
2	3992.781	6.97	33.58	42.32	49.61	47.84	74.00	-26.16	peak
3 a	v 4882.000	7.97	34.30	42.48	32.55	32.34	54.00	-21.66	Average
4 p	4882.000	7.97	34.30	42.48	57.33	57.12	74.00	-16.88	peak
5	5746.982	9.72	34.55	41.82	48.19	50.64	74.00	-23.36	peak
6	7323.000	10.05	36.37	40.63	46.76	52.55	74.00	-21.45	peak
7	9764.000	10.82	37.55	37.52	42.44	53.29	74.00	-20.71	peak



Report No.: SZEM180400290602

Page: 41 of 89

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Condition: 3m HORIZONTAL

Job No : 02906CR Mode : 2480 TX SE


			Cable	Ant	Preamp	Read		Limit	0ver	
		Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	_									
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1		1687.347	5.24	26.62	41.52	47.37	37.71	74.00	-36.29	peak
2		4254.921	7.28	33.60	42.37	48.97	47.48	74.00	-26.52	peak
3	av	4960.000	8.05	34.43	42.49	36.99	36.98	54.00	-17.02	Average
4	pp	4960.000	8.05	34.43	42.49	61.76	61.75	74.00	-12.25	peak
5		6835.278	10.58	36.05	40.97	47.04	52.70	74.00	-21.30	peak
6		7440.000	10.02	36.32	40.56	46.80	52.58	74.00	-21.42	peak
7		9920.000	10.90	37.58	37.31	42.25	53.42	74.00	-20.58	peak



Report No.: SZEM180400290602

Page: 42 of 89

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Condition: 3m VERTICAL

Job No : 02906CR Mode : 2480 TX SE

		Cable	Ant	Preamp	Read		Limit	0ver	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	4.93	25.11	41.29	53.04	41.79	74.00	-32.21	peak
2	4015.929	7.00	33.60	42.33	49.11	47.38	74.00	-26.62	peak
3 a	v 4960.000	8.05	34.43	42.49	35.45	35.44	54.00	-18.56	Average
4 p	p 4960.000	8.05	34.43	42.49	60.22	60.21	74.00	-13.79	peak
5	6640.542	11.13	35.50	41.11	46.84	52.36	74.00	-21.64	peak
6	7440.000	10.02	36.32	40.56	46.96	52.74	74.00	-21.26	peak
7	9920.000	10.90	37.58	37.31	42.09	53.26	74.00	-20.74	peak



Report No.: SZEM180400290602

Page: 43 of 89

8 Appendix

Appendix 15.247


1.20 dB Bandwidth

Test Mode	Test Channel	EBW[MHz]	Limit[MHz]	Verdict
DH5	2402	0.950		PASS
DH5	2441	0.950		PASS
DH5	2480	0.948		PASS
2DH5	2402	1.246		PASS
2DH5	2441	1.254		PASS
2DH5	2480	1.244		PASS
3DH5	2402	1.270		PASS
3DH5	2441	1.264		PASS
3DH5	2480	1.264		PASS



Report No.: SZEM180400290602

Page: 44 of 89




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602


Page: 45 of 89





Report No.: SZEM180400290602


Page: 46 of 89





Report No.: SZEM180400290602


Page: 47 of 89





Report No.: SZEM180400290602

Page: 48 of 89





Report No.: SZEM180400290602

Page: 49 of 89


2.Conducted Peak Output Power

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
DH5	2402	1.91	<=20.97	PASS
DH5	2441	3.64	<=20.97	PASS
DH5	2480	2.12	<=20.97	PASS
2DH5	2402	2.34	<=20.97	PASS
2DH5	2441	3.71	<=20.97	PASS
2DH5	2480	2.32	<=20.97	PASS
3DH5	2402	1.91	<=20.97	PASS
3DH5	2441	3.42	<=20.97	PASS
3DH5	2480	1.93	<=20.97	PASS



Report No.: SZEM180400290602

Page: 50 of 89




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SZEM180400290602


Page: 51 of 89





Report No.: SZEM180400290602


Page: 52 of 89





Report No.: SZEM180400290602


Page: 53 of 89





Report No.: SZEM180400290602

Page: 54 of 89




3. Carrier Frequency Separation

Test Mode	Test Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	2441	0.996	>=0.63	PASS
2DH5	2441	1.002	>=0.84	PASS
3DH5	2441	1.011	>=0.85	PASS



Report No.: SZEM180400290602

Page: 55 of 89




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 56 of 89




4.Dwell Time

Test Mode	Test Channel	Burst Width[ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Limit[s]	Verdict
DH1	2402	0.39	320	0.125	<0.4	PASS
DH3	2402	1.65	160	0.264	<0.4	PASS
DH5	2402	2.9	110	0.319	<0.4	PASS
2DH1	2402	0.41	320	0.131	<0.4	PASS
2DH3	2402	1.66	160	0.266	<0.4	PASS
2DH5	2402	2.9	110	0.319	<0.4	PASS
3DH1	2402	0.41	320	0.131	<0.4	PASS
3DH3	2402	1.66	160	0.266	<0.4	PASS
3DH5	2402	2.9	100	0.29	<0.4	PASS



Report No.: SZEM180400290602


Page: 57 of 89





Report No.: SZEM180400290602


Page: 58 of 89





Report No.: SZEM180400290602


Page: 59 of 89





Report No.: SZEM180400290602


Page: 60 of 89





Report No.: SZEM180400290602


Page: 61 of 89





Report No.: SZEM180400290602


Page: 62 of 89





Report No.: SZEM180400290602


Page: 63 of 89





Report No.: SZEM180400290602


Page: 64 of 89





Report No.: SZEM180400290602

Page: 65 of 89





Report No.: SZEM180400290602

Page: 66 of 89


5.Hopping Channel Number

Test Mode	Test Channel	Number of Hopping Channel[N]	Limit[N]	Verdict
DH5	2402	79	>=15	PASS
2DH5	2402	79	>=15	PASS
3DH5	2402	79	>=15	PASS



Report No.: SZEM180400290602

Page: 67 of 89




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sqs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sqs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.



Report No.: SZEM180400290602

Page: 68 of 89




6.Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Hopping	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit[dBm]	Verdict
DH5	2402	On	2.530	-57.639	<-17.47	PASS
DH5	2402	Off	1.410	-60.955	<-18.59	PASS
DH5	2480	On	1.440	-52.166	<-18.56	PASS
DH5	2480	Off	1.550	-52.859	<-18.45	PASS
2DH5	2402	On	-0.340	-59.738	<-20.34	PASS
2DH5	2402	Off	0.790	-61.673	<-19.21	PASS
2DH5	2480	On	0.480	-53.106	<-19.52	PASS
2DH5	2480	Off	0.580	-51.903	<-19.42	PASS
3DH5	2402	On	0.780	-59.789	<-19.22	PASS
3DH5	2402	Off	0.870	-61.212	<-19.13	PASS
3DH5	2480	On	-0.320	-53.466	<-20.32	PASS
3DH5	2480	Off	-0.320	-53.571	<-20.32	PASS



Report No.: SZEM180400290602

Page: 69 of 89




This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.



Report No.: SZEM180400290602


Page: 70 of 89





Report No.: SZEM180400290602


Page: 71 of 89





Report No.: SZEM180400290602


Page: 72 of 89





Report No.: SZEM180400290602


Page: 73 of 89





Report No.: SZEM180400290602

Page: 74 of 89





Report No.: SZEM180400290602

Page: 75 of 89


7.RF Conducted Spurious Emissions

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
DH5	2402	30	10000	1000	3000	1.52	-48.040	<- 18.48	PASS
DH5	2402	10000	25000	1000	3000	1.52	-55.570	<- 18.48	PASS
DH5	2441	30	10000	1000	3000	3.19	-48.790	<- 16.81	PASS
DH5	2441	10000	25000	1000	3000	3.19	-54.830	<- 16.81	PASS
DH5	2480	30	10000	1000	3000	1.64	-48.470	<- 18.36	PASS
DH5	2480	10000	25000	1000	3000	1.64	-54.630	<- 18.36	PASS
2DH5	2402	30	10000	1000	3000	0.27	-50.090	<- 19.73	PASS
2DH5	2402	10000	25000	1000	3000	0.27	-55.710	<- 19.73	PASS
2DH5	2441	30	10000	1000	3000	2.19	-49.590	<- 17.81	PASS
2DH5	2441	10000	25000	1000	3000	2.19	-55.050	<- 17.81	PASS
2DH5	2480	30	10000	1000	3000	0.77	-49.280	<- 19.23	PASS
2DH5	2480	10000	25000	1000	3000	0.77	-55.540	<- 19.23	PASS
3DH5	2402	30	10000	1000	3000	0.84	-48.890	<- 19.16	PASS
3DH5	2402	10000	25000	1000	3000	0.84	-55.460	<- 19.16	PASS
3DH5	2441	30	10000	1000	3000	1.51	-48.150	<- 18.49	PASS
3DH5	2441	10000	25000	1000	3000	1.51	-55.440	<- 18.49	PASS
3DH5	2480	30	10000	1000	3000	-0.07	-48.290	<- 20.07	PASS
3DH5	2480	10000	25000	1000	3000	-0.07	-55.330	<- 20.07	PASS




Report No.: SZEM180400290602

Page: 76 of 89






Report No.: SZEM180400290602





Report No.: SZEM180400290602


Page: 78 of 89





Report No.: SZEM180400290602


Page: 79 of 89





Report No.: SZEM180400290602


Page: 80 of 89





Report No.: SZEM180400290602


Page: 81 of 89





Report No.: SZEM180400290602


Page: 82 of 89





Report No.: SZEM180400290602


Page: 83 of 89





Report No.: SZEM180400290602


Page: 84 of 89





Report No.: SZEM180400290602


Page: 85 of 89





Report No.: SZEM180400290602


Page: 86 of 89





Report No.: SZEM180400290602


Page: 87 of 89





Report No.: SZEM180400290602


Page: 88 of 89





Report No.: SZEM180400290602

Page: 89 of 89



- End of the Report -