

Android Media Player

X99



1. DC input: Please use 5V 4A adapter
2. type-C: indicates the device that can connect to type-C
3. HDMI OUT: HDMI output supports up to 4K 60fps
4. LAN interface: Supports 1000M wired network

5.Switch: Click to restart the machine

6.TF card: Supports MicroSD card

7.USB2.0: indicates the device that supports USB2.0

8.USB3.0: Devices that support the USB3.0 protocol

Use:

1. First fix the device in the specified place (for fixed devices, refer to the installation instructions)

2. Plug the HDMI cable into the display device

3. Connect the type-c cable to the control device

4. Connect the network cable to the router or switch (if you do not connect the network cable, you need to connect the system to WIFI)

5. Plug the adapter into the socket

6. At this time, there should be display images on the display device, and the machine can be operated after the digital tube has time to display.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a

Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception,

which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum 20cm distance between the radiator and your body: Use only the supplied antenna.