



SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD

Application
For
Certification

FCC ID: 2AH3K2K1

Transmitter

Sample Description: Electric Scooter

Model: 2K1

Report No.: 160824016SZN-001

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-15]

Prepared and Checked by:

Approved by:

Sign on file

Sunny Zhou
Project Engineer

Kidd Yang
Senior Project Engineer
Date: November 27, 2016

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1

Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch
6F, D Block, Huahan Building, Langshan Road, Nanshan District, Shenzhen, P. R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751 Website: www.china.intertek-etalsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Test Equipment List



MEASUREMENT/TECHNICAL REPORT

Shenzhen Vokul Sports Equipment Co.,Ltd

Electric Scooter

FCC ID: 2AH3K2K1

This report concerns (check one): Original Grant Class II Change

Equipment Type: DSC - Part 15 Security/Remote Control Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart C for intentional radiator – the new 47 CFR [10-1-15 Edition] provision.

Report prepared by:

Sunny Zhou
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6/F, Block D, HuaHan Building, Longshan
Road, Nanshan District, Shenzhen, China.
Development Zone, Guangzhou, P. R.China.
Phone: (86 755) 8601 0695
Fax: (86 755) 8601 6751

Table of Contents

1.0	<u>General Description</u>	2
1.1	Product Description	2
1.2	Related Submittal(s) Grants	2
1.3	Test Methodology	2
1.4	Test Facility	2
2.0	<u>System Test Configuration</u>	4
2.1	Justification	4
2.2	EUT Exercising Software	4
2.3	Special Accessories	4
2.4	Equipment Modification	5
2.5	Measurement Uncertainty	5
2.6	Support Equipment List and Description	5
3.0	<u>Emission Results</u>	7
3.1	Field Strength Calculation	8
3.1	Field Strength Calculation (cont'd)	8
3.2	Radiated Emission Configuration Photograph	10
3.3	Radiated Emission Data	11
4.0	<u>Equipment Photographs</u>	14
5.0	<u>Product Labelling</u>	16
6.0	<u>Technical Specifications</u>	18
7.0	<u>Instruction Manual</u>	20
8.0	<u>Miscellaneous Information</u>	21
8.1	Measured Bandwidth	23
8.2	Discussion of Pulse Desensitization	24
8.3	Calculation of Average Factor	25
8.4	Emission Test Procedures	26
9.0	<u>Test Equipment List</u>	29

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Timing	Timing	Timing.pdf
Operation Description	Technical Description	descri.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
Test Report	Bandwidth Plot	bw.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Test Report	Average Factor	af.pdf
Cover Letter	Letter of Agency	agency.pdf
Cover Letter	Request for confidentiality	request.pdf



EXHIBIT 1

GENERAL DESCRIPTION

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a transmitter for Electric Scooter operating at 315MHz. The EUT is powered by one 3.0V Button Cell. For more detailed features description, please refer to the user's manual.

The transmitter activated automatically cease transmission within 5 seconds after activation.

The time domain features is saved with file name: Timing.pdf.

Antenna Type: Integral antenna

Modulation Type: ASK

The brief circuit description is saved with file name: descri.pdf

1.2 Related Submittal(s) Grants

This is an application for certification of a transmitter. The receiver, associated with this transmitter, has FCC ID: 2AH3K3K1 and has been filed at the same time.

1.3 Test Methodology

Radiated emission measurement was performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Justification Section"** of this Application.

1.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **EMTEK (Shenzhen) Co., Ltd.** and located at Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052, China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 406365).

EXHIBIT 2
SYSTEM TEST CONFIGURATION

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was power by one new 3.0V Button Cell during testing.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the centre of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.



2.4 Equipment Modification

Any modifications installed previous to testing by SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Kejiyuan Branch.

2.5 Measurement Uncertainty

When determining the test conclusion, the measurement uncertainty of test has been considered.

2.6 Support Equipment List and Description

N/A



EXHIBIT 3

EMISSION RESULTS

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1

3.0 Emission Results

Data is included worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$



3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission

315.0 MHz

For electronic filing, the worst case radiated emission configuration photograph is saved with filename: radiated photos.pdf

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 9.8 dB

TEST PERSONNEL:

Sunny Zhou Project Engineer
Typed/Printed Name

November 21, 2016
Date

Applicant: SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD

Date of Test: November 21, 2016

Mode: TX Transmit

Sample: 1/1

Table 1

Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	315.000	80.7	20.0	15.6	10.5	65.8	75.6	-9.8
Horizontal	630.000	51.7	20.0	24.0	10.5	45.2	55.6	-10.4
Horizontal	945.000	47.1	20.0	24.5	10.5	41.1	55.6	-14.5
Horizontal	1260.000	41.5	20.0	27.2	10.5	38.2	55.6	-17.4
Horizontal	*1575.000	42.5	20.0	29.0	10.5	41.0	54.0	-13.0
Horizontal	1890.000	39.9	20.0	29.8	10.5	39.2	55.6	-16.4
Horizontal	*2205.000	40.6	20.0	31.1	10.5	41.2	54.0	-12.8

Notes: 1. Average Detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3 meter distance were measured at 0.3 meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3 meter.
3. Negative value in the margin column shows emission below limit.
4. All emissions below the Average limit.
5. “*” Emission within restricted band fulfils the requirement of section 15.205.

Test Engineer: Sunny Zhou

EXHIBIT 4
EQUIPMENT PHOTOGRAPHS



4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf



EXHIBIT 5

PRODUCT LABELLING

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1



5.0 Product Labelling

For electronic filing, the FCC ID label artwork and the label location are saved with filename: label.pdf



EXHIBIT 6

TECHNICAL SPECIFICATIONS

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1



6.0 Technical Specifications

For electronic filing, the block diagram and schematics are saved with filename: block.pdf and circuit.pdf



EXHIBIT 7
INSTRUCTION MANUAL

TRF no.: FCC 15C_TX_b
FCC ID: 2AH3K2K1



7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8
MISCELLANEOUS INFORMATION

8.0 Miscellaneous Information

This miscellaneous information includes details of the measured bandwidth, the test procedure and calculation of factors such as pulse desensitization and averaging factor.

8.1 Measured Bandwidth

For electronic filing, the plot shows the fundamental emission when modulated is saved with filename: bw.pdf. From the plot, the 20dB bandwidth is 8.25 KHz and less than the limit of 787.5 KHz. It fulfils the requirement of 15.231(C).

Figure 8.1 Bandwidth

8.2 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

The effective period (T_{eff}) was approximately 290 μ s for a digital "1" bit, as shown in the plots of Exhibit 8.3. With a resolution bandwidth (3 dB) of 100 kHz, the pulse desensitivity factor was 0 dB.

8.3 Calculation of Average Factor

Averaging factor in dB = $20 \log (\text{duty cycle})$

The specification for output field strengths in accordance with the FCC rules specifies measurements with an average detector. During testing, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation. The duty cycle is measured by placing the spectrum analyzer in zero scan (receiver mode) and linear mode at maximum bandwidth (3 MHz at 3 dB down) and viewing the resulting time domain signal output from the analyzer on a Tektronix oscilloscope. The oscilloscope is used because of its superior time base and triggering facilities.

A plot of the worst-case duty cycle as detected in this manner are saved with filename: af.pdf

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 51.014 ms

Effective period of the cycle = $1.014 \text{ ms} \times 11 + 0.290 \text{ ms} \times 14 = 15.214 \text{ ms}$

DC = $15.214 \text{ ms} / 51.014 \text{ ms} = 0.298$ or 29.8%

Therefore, the averaging factor is found by $20 \log_{10} 0.298 = -10.5 \text{ dB}$

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter, up to 1GHz 0.8m and above 1GHz 1.5m in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjust through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where transmissions of short enough pulse duration warrant, a greater bandwidth pulsed is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.2). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.



EXHIBIT 9
TEST EQUIPMENT LIST

9.0 Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
EMI Receiver	R&S	ESU	1302.6005.26	28-May-2016	28-May-2017
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	28-May-2016	28-May-2017
Horn Antenna	Schwarzbeck	BBHA 9120	D143	28-May-2016	28-May-2017
Active Loop Antenna	ARA	PLA-1030/B	1029	28-May-2016	28-May-2017
Bilog Antenna	Schwarzbeck	VULB9163	142	28-May-2016	28-May-2017
Spectrum Analyzer	R&S	FSP 30	101148	28-May-2016	28-May-2017
Spectrum Analyzer	R&S	FSV 40	101506	28-May-2016	28-May-2017
Preamplifier	HP	8447D	2944A07999	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX1	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX2	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX3	28-May-2016	28-May-2017
Notch Filter	Micro-Tronics	BRM50702-02	--	28-May-2016	28-May-2017