

SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD

Application
For
Certification

FCC ID: 2AH3K3K1

Receiver

Sample Description: Electric Scooter

Report No.: 160824016SZN-002

Model: K1-01

We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, mention 47 CFR [10-1-15]

Prepared and Checked by:

Sign on file
Sunny Zhou
Project Engineer

Approved by:

Kidd Yang
Senior Project Engineer
Date: November 27, 2016

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF No.: FCC 15C_RX_b

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	General Description
<i>EXHIBIT 2:</i>	System Test Configuration
<i>EXHIBIT 3:</i>	Emission Results
<i>EXHIBIT 4:</i>	Equipment Photographs
<i>EXHIBIT 5:</i>	Product Labelling
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Instruction Manual
<i>EXHIBIT 8:</i>	Miscellaneous Information
<i>EXHIBIT 9:</i>	Confidentiality Request
<i>EXHIBIT 10:</i>	Test Equipment List

MEASUREMENT/TECHNICAL REPORT

SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD
FCC ID: 2AHJZ-A243M

This report concerns (check one) Original Grant Class II Change _____

Equipment Type: CYY – Communications Receiver used w/Pt 15 Transmitter

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued
on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart B for unintentional radiator - the new 47 CFR
[10-1-15 Edition] provision.

Report prepared by:

Sunny Zhou
Intertek Testing Services Shenzhen Ltd.
Kejiyuan Branch
6/F, Block D, HuaHan Building, Longshan
Road, Nanshan District, Shenzhen, China.
Phone: (86 755) 8614 0695
Fax: (86 755) 8601 6751

Table of Contents

1.0	<u>General Description</u>	2
1.1	Product Description	2
1.2	Related Submittal(s) Grants	2
1.3	Test Methodology	2
1.4	Test Facility	2
2.0	<u>System Test Configuration</u>	4
2.1	Justification	4
2.2	EUT Exercising Software	4
2.3	Special Accessories	4
2.4	Equipment Modification	5
2.5	Measurement Uncertainty	5
2.6	Support Equipment List and Description	5
3.0	<u>Emission Results</u>	6
3.1	Field Strength Calculation	8
3.2	Radiated Emission Configuration Photograph	9
3.3	Radiated Emission Data	10
4.0	<u>Equipment Photographs</u>	12
5.0	<u>Product Labelling</u>	15
6.0	<u>Technical Specifications</u>	17
7.0	<u>Instruction Manual</u>	18
8.0	<u>Miscellaneous Information</u>	20
8.1	Emissions Test Procedures	21
9.0	<u>Test Equipment List</u>	24

List of attached file

Exhibit type	File Description	filename
Test Report	Test Report	report.pdf
Test Setup Photo	Radiated Emission	radiated photos.pdf
External Photo	External Photo	external photos.pdf
Internal Photo	Internal Photo	internal photos.pdf
Block Diagram	Block Diagram	block.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
Cover Letter	Letter of Agency	agency.pdf

EXHIBIT 1

GENERAL DESCRIPTION

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a receiver for Electric Scooter operating at 315MHz. The EUT is powered by DC 36 V from internal rechargeable battery and can be Charged by AC/DC adapter AOI-08420155DD1 with the following ratings: Input: AC100-240V 50/60Hz 1.5A Output: DC42V 1550mA. When the product was charged by adapter, the receiver function will be stopped automatically. For more detailed features description, please refer to the user's manual.

Antenna Type: Integral antenna

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a receiver. The transmitter, associated with this receiver, has FCC ID: 2AH3K2K1 and has been filed at the same time. For Bluetooth function was tested and demonstrated in report 160824016SZN-004.

1.3 Test Methodology

Radiated emission measurements were performed according to the procedures in ANSI C63.4 (2014). Radiated emission measurement was performed in Semi-anechoic chamber, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the **"Justification Section"** of this Application.

1.4 Test Facility

The Semi-anechoic chamber used to collect the radiated data is **EMTEK (Shenzhen) Co., Ltd.** and located at Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052, China. This test facility and site measurement data have been fully placed on file with the FCC (Registration Number: 406365).

EXHIBIT 2
SYSTEM TEST CONFIGURATION

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by one fully DC 36 V from internal rechargeable battery during testing.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the centre of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was placed on a turn table, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it received continuously.

2.3 Special Accessories

N/A

2.4 Equipment Modification

Any modifications installed previous to testing by SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd Kejiyuan Branch.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

N/A

EXHIBIT 3

EMISSION RESULTS

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

where

FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RA = Receiver Amplitude (including preamplifier) in $\text{dB}\mu\text{V}$

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

FS = Field Strength in $\text{dB}\mu\text{V}/\text{m}$

RR = RA - AG in $\text{dB}\mu\text{V}$

LF = CF + AF in dB

Assume a receiver reading of 52.0 $\text{dB}\mu\text{V}$ is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 $\text{dB}\mu\text{V}/\text{m}$. This value in $\text{dB}\mu\text{V}/\text{m}$ was converted to its corresponding level in $\mu\text{V}/\text{m}$.

$$RA = 52.0 \text{ dB}\mu\text{V}/\text{m}$$

$$AF = 7.4 \text{ dB}$$

$$RR = 23.0 \text{ dB}\mu\text{V}$$

$$CF = 1.6 \text{ dB}$$

$$LF = 9.0 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 23 + 9 = 32 \text{ dB}\mu\text{V}/\text{m}$$

$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

3.2 Radiated Emission Configuration Photograph

Worst Case Radiated Emission
at
947.620 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.doc.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 10.8 dB

TEST PERSONNEL:

Sunny Zhou, Engineer

Typed/Printed Name

November 21, 2016

Date

Applicant: SHENZHEN VOKUL SPORTS EQUIPMENT CO.,LTD

Date of Test: November 21, 2016

Test Mode: Receive

Table 1

FCC Class B Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	30.000	25.3	20.0	17.8	23.1	40.0	-16.9
Horizontal	491.700	26.3	20.0	21.7	28.0	46.0	-18.0
Horizontal	947.620	25.4	20.0	29.8	35.2	46.0	-10.8
Vertical	38.245	29.7	20.0	13.0	22.7	40.0	-17.3
Vertical	193.569	38.3	20.0	12.3	30.6	43.5	-12.9
Vertical	426.245	28.7	20.0	20.2	28.9	46.0	-17.1

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
Horizontal	1302.571	42.7	36.8	24.6	30.5	54.0	-23.5
Horizontal	1816.326	39.8	36.8	28.2	31.2	54.0	-22.8

NOTES: 1. Quasi-Peak detector is used for frequency up to 1GHz and Peak detector is used for frequency from 1-2GHz.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. All emissions up to 1000MHz are below the QP limit and all emissions above 1000MHz are below the average limit.

Test Engineer: Sunny Zhou

EXHIBIT 4
EQUIPMENT PHOTOGRAPHS

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.doc and internal photos.doc.

EXHIBIT 5
PRODUCT LABELLING

5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6
TECHNICAL SPECIFICATIONS

6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7
INSTRUCTION MANUAL

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8
MISCELLANEOUS INFORMATION

8.0 Miscellaneous Information

This miscellaneous information includes emission measuring procedure.

8.1 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of Superheterodyne Receiver operating under Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 – 2014.

The Superheterodyne Receiver equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 12mm in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The antenna height and polarization are varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions are in QP mode from the frequency band 30MHz to 1GHz with RBW setting 120kHz and in PK & AV mode from frequency band 1GHz to 2GHz with RBW setting 1MHz.

For radiated emission, the frequency range scanned is 30MHz to 2GHz.

8.1 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2014.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Receiver measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

EXHIBIT 9

TEST EQUIPMENT LIST

9.0 Test Equipment List

Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
EMI Receiver	R&S	ESU	1302.6005.26	28-May-2016	28-May-2017
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	28-May-2016	28-May-2017
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	17-May-2016	17-May-2017
Active Loop Antenna	ARA	PLA-1030/B	1029	28-May-2016	28-May-2017
Bilog Antenna	Schwarzbeck	VULB9163	142	28-May-2016	28-May-2017
Spectrum Analyzer	R&S	FSP 30	101148	28-May-2016	28-May-2017
Spectrum Analyzer	R&S	FSV 40	101506	28-May-2016	28-May-2017
Preamplifier	HP	8447D	2944A07999	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX1	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX2	28-May-2016	28-May-2017
RF Cable	Schwarzbeck	AK9513	ACRX3	28-May-2016	28-May-2017
Notch Filter	Micro-Tronics	BRM50702-02	--	28-May-2016	28-May-2017