



深圳市科信无线技术有限公司
Shenzhen Kexin Wireless Technology Co., Ltd
Building H, Shabeili Hongyongli Industrial Zone, Longxin
Community, Baolong Street, Shenzhen, Guangdong, China

Product Number: AN2458-1395L120
Product Name: WIFI 2.4/5.8GHZ 高增益天线
Index: ANT0 and ANT1

- 1. Specification
- 2. Characteristics and Reliability Test
- 3. Antenna - S Parameter Test Data
- 4. Mechanical and Packing Drawing
- 5. Material Description and RoHS Test Report

1. Specification

A. Electrical Characteristics	
Frequency 天线频率	2400-2500MHZ / 4900-5900MHZ
S.W.R. 驻波比	< 1.5
Antenna Gain 天线增益	5dBi
Polarization 极化方式	Linear 线性极化

Test Items		Test Condition and Procedure	Requirements
C1	S.W.R.	Set DUT on Network Analyzer; make individual calibration to test	Directive DUT specification
C2	Antenna Gain	Set DUT on Antenna Chamber; make individual calibration to test	Directive DUT specification
M1	Vibration	GB / T2423 . 48-1997 Amplitude: 0.03 inch (1.5mm); Freq: 20 to 80 to 20 Hz 3 directions; 2 hours for each direction	1. No Visual Damage 2. Frequency Tol.<= 5%
M2	Random Drop	GB / T2423.8-1995 Height: 1.0 Meter; 3 directions; 1 time for each direction	1. No parts separated 2. Frequency Tol.<= 5%
M3	Solderability	GB 2423 . 28- 82 Solder iron: 260±5°C; Duration: 5 seconds	1. Mounted on PCB 2. No Visual Damage
M4	Terminal-	Holding with individual specification; force applied	1. Directive DUT specification

Product Number: AN2458-1395L120

Product Name: WIFI 2.4/5.8GHZ 高增益天线

Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Material of Radiator 材质	FR-4
Cable Type 线材类型	RG-1.13
Connector Type 天线接口	1 代 IPEX
Cable length 天线长度	从焊点算 12CM
C. Environmental	
Operation Temperature	- 40 °C ~ + 65 °C
Storage Temperature	- 40 °C ~ + 80 °C
Antenna Color Storage life	< 2 year

2. Characteristics and Reliability Test

	Pull Test	to axis of terminal	2. Frequency Tol.<= 5%
M5	Terminal-Torque Test	Holding with individual specification; applied clockwise and counterclockwise to the axis of terminal	1. Directive DUT specification 2. Frequency Tol.<= 5%
M6	Dimension	Inspection of dimension, color, material, package, surface process	Directive DUT specification
E1	Salt Spray	GB / T 2423 . 17- 93 Temp: 35°C; RH: >= 95%; NaCl solution: >= 5%; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E2	Humidity	GB / T 2423 . 4 - 93 Temp: 80°C / 12 H; -40°C / 12H RH: >= 90%; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
E3	Thermal Shock	GB / T 2423 . 22 - 87 1 Cycle: - 40°C (30 minutes) to + 80°C (30 minutes) Cycles: 24	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%




Product Number: AN2458-1395L120

Product Name: WIFI 2.4/5.8GHZ 高增益天线


E4	Life (High Temp.)	GB /T 2423 . 2 - 89 Temp: 80°C; Time: 24 hours	After 2 Hours Recovery 1. No Visual Damage 2. Frequency Tol.<= 5%
R1	RoHS	With Reference to IEC 62321:2008 with flow chart	Directive RoHS 2002/95/EC
R2	PFOS	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC
R3	PFOA	With Reference to USA EPA 3540C:1996 by LC/MS	Directive RoHS 2006/122/EC

3. Antenna - S Parameter Test Data



Product Number: AN2458-1395L120

Product Name: WIFI 2.4/5.8GHZ 高增益天线



Product Number: AN2458-1395L120

Product Name: WIFI 2.4/5.8GHZ 高增益天线

