



# TEST REPORT

Report No.: SHATBL2504007W05

**Applicant** : Rapsodo Pte Ltd

**Product Name** : PRO2.0™

**Brand Name** : RAPSODO

**Model Name** : PRO 2.0

**FCC ID** : 2AH3O-PRO20

**Test Standard** : FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of Test** : 2025.02.28~2025.04.11

**Report Prepared by** :

Chris Xu

(Chris Xu)

**Report Approved by** :

Guozheng Li

(Guozheng Li)

**Authorized Signatory** :

Terry Yang

(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards, or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Tel:+86(0)21-51298625

Web:www.atbl-lab.com

Email:atbl@atbl-lab.com

**TABLE OF CONTENTS**

REVISION HISTORY .....	3
DECLARATION OF REPORT .....	4
1. GENERAL DESCRIPTION .....	5
1.1. Applicant .....	5
1.2. Manufacturer .....	5
1.3. Factory .....	5
1.4. General Information of EUT .....	6
1.5. Laboratory Information .....	7
2. FCC 47CFR §2.1091 Requirement .....	8
2.1. Test Standards .....	8
2.2. Limit .....	8
2.3. MPE Calculation Method .....	9
2.4. Antenna Information .....	9
2.5. Manufacturing Tolerance .....	9
2.6. Test Result .....	10

**REVISION HISTORY**

Rev.	Issue Date	Revisions	Revised by
A0	2025.04.16	Initial Release	Terry Yang

## DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1091. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '□' indicates that EUT does not support content after '□', and '☒' indicates that it supports content after '☒'

## 1. GENERAL DESCRIPTION

### 1.1. Applicant

Name : Rapsodo Pte Ltd

Address : Blk 20 Ayer Rajah Crescent, #08-05 singapore, 139964 Singapore

### 1.2. Manufacturer

Name : Rapsodo Pte Ltd

Address : Blk 20 Ayer Rajah Crescent, #08-05 singapore, 139964 Singapore

### 1.3. Factory

Name : PCA Technology (M) Sdn. Bhd.

Address : 12, Jalan Bayu, Kawasan Perindustrian Tampoi Jaya, 81200 Johor Bahru, Johor Darul Ta'zim, Malaysia

**1.4. General Information of EUT**

<b>General Information</b>			
Equipment Name	PRO2.0™		
Brand Name	RAPSODO		
Model Name	PRO 2.0		
Series Model	N/A		
Model Difference	N/A		
Operation Frequency	Bluetooth&WiFi 2.4GHz:2400MHz - 2483.5MHz WiFi 5GHz:5150MHz - 5850MHz		
Modulation Type	Bluetooth BR&EDR:GFSK, $\pi/4$ -DQPSK,8-DPSK Bluetooth LE:GFSK		
	WiFi 2.4GHz 802.11b: DSSS (DBPSK/DQPSK/CCK) 802.11g/n(HT): OFDM (BPSK/QPSK/16QAM/64QAM)		
	WiFi 5GHz 802.11a/n(HT): OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac(VHT): OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)		
Antenna Information	<input checked="" type="checkbox"/> SISO	Antenna Type:	IPEX
		Antenna 0 Gain:	5dBi
		Antenna 1 Gain:	5dBi
Antenna Designation	IPEX Antenna		
Battery	Rated Voltage: 7.4V Charge Limit Voltage: 8.4V Capacity: 6600mAh		
Hardware Version	D-2		
Software Version	36.2		

**1.5. Laboratory Information**

Company Name	: Shanghai ATBL Technology Co., Ltd.
Address	: Building 8, No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	: +86(0)21-51298625

## 2. FCC 47CFR §2.1091 Requirement

### 2.1. Test Standards

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

### 2.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 2.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

### 2.4. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	5.00	IPEX
Chain 1	5.00	IPEX

### 2.5. Manufacturing Tolerance

Function	Target (dBm)	Tolerance $\pm$ (dB)
SISO Transmit		
Bluetooth	10.57	1.00
WiFi 2.4GHz	20.37	1.00
WiFi 5GHz	21.20	1.00
24.175 GHz	15.90	1.00
MIMO Transmit		
WiFi 2.4GHz	21.17	1.00
WiFi 5GHz	23.71	1.00

Note:

1. The target power has included the maximum transmission power and tolerance values.
2. other technical (Radar) MPE calculation refered to FCC ID:UXS-IP937.
3. WIFI Output power (EIRP) including turn-up tolerance.
4.  $dBm = dB\mu V/m - 95.2 = 111.1 dB\mu V/m - 95.2 = 15.90 dBm$ .

## 2.6. Test Result

As declared by the Applicant, the EUT is a wireless device used in a Mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna is refer to section 4, the RF power density can be obtained.

Modulation Type	Output power (Target)		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	dBm	mW				
SISO Transmit						
Bluetooth	11.57	14.355	5	3.1622	0.009	1.0000
WiFi 2.4GHz	21.37	137.088	5	3.1622	0.086	1.0000
WiFi 5GHz	22.20	165.959	5	3.1622	0.104	1.0000
24.175 GHz for Radar module 1	16.90	48.978	15	31.62	0.308	1.0000
24.175 GHz for Radar module 2	16.90	48.978	15	31.62	0.308	1.0000
MIMO Transmit						
WiFi 2.4GHz	22.17	164.816	5	3.1622	0.104	1.0000
WiFi 5GHz	24.71	295.801	5	3.1622	0.186	1.0000

Simultaneous Transmitting:

$$\text{WiFi 5GHz+Bluetooth+Radar} = 0.104/1 + 0.009/1 + (0.308/1)^2 = 0.729 < 1$$

Note:

1. If nothing else, the report will only record the worst power.
2. The Maximum power is less than the limit, complies with the exemption requirements.
3. WIFI Output power (EIRP) including turn-up tolerance.
4. Bluetooth Output power (PK) including turn-up tolerance.
5. The calculated distance is 20 cm.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*