

Test report No:  
NIE: 59776RAN.002

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1093 ISED RSS -102 Issue 5:2015

|                                             |                                                                                                                                                                                                                           |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| (*) Identification of item under evaluation | Connected watch                                                                                                                                                                                                           |
| (*) Trademark                               | Tissot SA                                                                                                                                                                                                                 |
| (*) Model and /or type reference            | T-Touch Connect T121420 A                                                                                                                                                                                                 |
| Other identification of the product         | SW version: 1.0.0<br>HW version: T121420 A<br>FCC ID: 2AH93T121420A<br>IC: 25567-T121420A                                                                                                                                 |
| (*) Features                                | ---                                                                                                                                                                                                                       |
| Manufacturer                                | TISSOT SA<br>Chemin des Tourelles 17<br>CH-2400 Le Locle<br>Switzerland                                                                                                                                                   |
| Test method requested, standard             | FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices.<br><br>ISED RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) |
| Summary                                     | IN COMPLIANCE                                                                                                                                                                                                             |
| Approved by (name / position & signature)   | Miguel Lacave<br>Antennas Lab Manager                                                                                                                                                                                     |
| Date of issue                               | 2020-02-04                                                                                                                                                                                                                |
| Report template No                          | FAN24_02<br>(*) "Data provided by the client"                                                                                                                                                                             |

# Index

Competences and guarantees .....3

General conditions .....3

Data provided by the client.....3

Identification of the client.....3

Document history .....4

General description of the device under evaluation .....4

Assessment summary .....4

Evaluation Results .....5

Appendix A: FCC RF Exposure information .....6

    FCC SAR test exclusion considerations for portable devices .....7

Appendix B: ISED RF Exposure information .....9

    ISED SAR test exclusion considerations .....10

## Competences and guarantees

---

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

---

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

## Data provided by the client

---

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. Maximum output power and maximum antenna gain information.
3. The sample consists of an analog-digital connected watch with typical Swiss watchmaking design. The product is equipped with features such as notifications, pedometer, altimeter, and navigation. The product can be recharged by light and by inductive recharging.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

---

ETA SA, MANUFACTURE HORLOGERE SUISSE  
Schmelzstrasse 16  
2540 Grenchen  
Switzerland

## Document history

| Report number | Date       | Description   |
|---------------|------------|---------------|
| 59776RAN.002  | 2020-02-04 | First release |

## General description of the device under evaluation

The device under evaluation consists of a watch, which supports Bluetooth Low Energy as radio transmitter.

The equipment specifications declared by the manufacturer for Bluetooth Low Energy are:

| Technology / Mode | Band | Frequency (MHz) | Maximum Conducted Output Power (dBm) | Antenna peak gain (dBi) | Maximum E.I.R.P. (dBm) | Maximum E.I.R.P. (mW) |
|-------------------|------|-----------------|--------------------------------------|-------------------------|------------------------|-----------------------|
| BTLE              | ISM  | 2400 - 2483.5   | 0.00                                 | -5.83                   | -5.83                  | 0.26                  |

**Table 1:** Equipment specifications

## Assessment summary

| Radiofrequency radiation exposure limits             |      |                 |         |
|------------------------------------------------------|------|-----------------|---------|
| FCC 47 CFR § 2.1093 & ISED RSS-102 Issue 5 (2015-03) |      |                 |         |
| Technology / Mode                                    | Band | Frequency (MHz) | Verdict |
| BTLE                                                 | ISM  | 2400 - 2483.5   | Pass    |

**Table 2:** Assessment summary

## Evaluation Results

### FCC evaluation:

The evaluation according to the minimum intended use distance of **0** mm (5mm applied for the evaluation according to KDB 447498 D01 General RF Exposure Guidance, see Appendix A for additional information) will be as follow:

| Technology / Mode | Band | Frequency (MHz) | Max Output Power (dBm) | Distance (cm) | Result | Limit 1-g SAR | SAR Test Exclusion |
|-------------------|------|-----------------|------------------------|---------------|--------|---------------|--------------------|
| BTLE              | ISM  | 2400            | 0.00                   | 0.50          | 0.31   | 3.00          | <b>Pass</b>        |
| BTLE              | ISM  | 2440            | 0.00                   | 0.50          | 0.31   | 3.00          | <b>Pass</b>        |
| BTLE              | ISM  | 2483.5          | 0.00                   | 0.50          | 0.32   | 3.00          | <b>Pass</b>        |

**Table 3: FCC Evaluation Result**

The computed 0.32 is < 3.0, so according to KDB 447498 D01 – General RF Exposure Guidance, this mode qualifies for Standalone SAR test exclusion for 1-g SAR and 10-g Extremity SAR.

### ISED evaluation:

Exemption limits for the applicable separation distance have been calculated by linear interpolation for the applicable operating frequencies according to According to paragraph “RSS-102 Issue 5 (2015-03), 2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation”.

The device has a transmitting antenna with a negative gain; therefore the maximum conducted output power has been used for the evaluation as a worst case condition.

For an intended use distance of 0 mm (5mm applied for the evaluation), the evaluation for the applicable output power levels and exemption limits for each operating frequency will be as follow:

| Technology / Mode | Band | Frequency (MHz) | Distance (cm) | Maximum Conducted Output Power (mW) | SAR Low-power exclusion level (mW) | SAR Test Exclusion |
|-------------------|------|-----------------|---------------|-------------------------------------|------------------------------------|--------------------|
| BTLE              | ISM  | 2400            | 0.50          | 1.00                                | 4.27                               | <b>Pass</b>        |
| BTLE              | ISM  | 2440            | 0.50          | 1.00                                | 4.05                               | <b>Pass</b>        |
| BTLE              | ISM  | 2483.5          | 0.50          | 1.00                                | 3.94                               | <b>Pass</b>        |

**Table 4: ISED Evaluation Result**

As all operating frequencies comply with ISED Exemption Limits, according to the standard “ISED RSS-102 Issue 5 (2015-03)”, SAR testing is not required. See Appendix A/B for additional information.

## Appendix A: FCC RF Exposure information

## FCC SAR test exclusion considerations for portable devices

As stated by the FCC (47 CFR §2.1093), human exposure to RF emissions from portable devices, which are defined as transmitting devices to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user, must be evaluated with respect to the FCC-adopted limits for SAR.

According to FCC OET KDB 447498 D01 General RF Exposure Guidance:

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition is satisfied.

### - For distances ≤ 50 mm

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table:

| MHz  | 5  | 10 | 15  | 20  | 25  | 30  | 35  | 40  | 45  | 50  | mm                                         |
|------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|--------------------------------------------|
| 150  | 39 | 77 | 116 | 155 | 194 | 232 | 271 | 310 | 349 | 387 | SAR Test<br>Exclusion<br>Threshold<br>(mW) |
| 300  | 27 | 55 | 82  | 110 | 137 | 164 | 192 | 219 | 246 | 274 |                                            |
| 450  | 22 | 45 | 67  | 89  | 112 | 134 | 157 | 179 | 201 | 224 |                                            |
| 835  | 16 | 33 | 49  | 66  | 82  | 98  | 115 | 131 | 148 | 164 |                                            |
| 900  | 16 | 32 | 47  | 63  | 79  | 95  | 111 | 126 | 142 | 158 |                                            |
| 1500 | 12 | 24 | 37  | 49  | 61  | 73  | 86  | 98  | 110 | 122 |                                            |
| 1900 | 11 | 22 | 33  | 44  | 54  | 65  | 76  | 87  | 98  | 109 |                                            |
| 2450 | 10 | 19 | 29  | 38  | 48  | 57  | 67  | 77  | 86  | 96  |                                            |
| 3600 | 8  | 16 | 24  | 32  | 40  | 47  | 55  | 63  | 71  | 79  |                                            |
| 5200 | 7  | 13 | 20  | 26  | 33  | 39  | 46  | 53  | 59  | 66  |                                            |
| 5400 | 6  | 13 | 19  | 26  | 32  | 39  | 45  | 52  | 58  | 65  |                                            |
| 5800 | 6  | 12 | 19  | 25  | 31  | 37  | 44  | 50  | 56  | 62  |                                            |

**Table 5:** SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

#### - For distances > 50 mm

For 100 MHz to 6 GHz frequencies and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:

- 1) [Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- 2) [Power allowed at numeric threshold for 50 mm in table 1) + (test separation distance - 50 mm)·10] mW, at > 1500 MHz and ≤ 6 GHz

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table

| MHz  | 50  | 60  | 70  | 80  | 90  | 100 | 110 | 120 | 130 | 140  | 150  | 160  | 170  | 180  | 190  | mm                                |
|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|-----------------------------------|
| 100  | 474 | 481 | 487 | 494 | 501 | 507 | 514 | 521 | 527 | 534  | 541  | 547  | 554  | 561  | 567  | SAR Test Exclusion Threshold (mW) |
| 150  | 387 | 397 | 407 | 417 | 427 | 437 | 447 | 457 | 467 | 477  | 487  | 497  | 507  | 517  | 527  |                                   |
| 300  | 274 | 294 | 314 | 334 | 354 | 374 | 394 | 414 | 434 | 454  | 474  | 494  | 514  | 534  | 554  |                                   |
| 450  | 224 | 254 | 284 | 314 | 344 | 374 | 404 | 434 | 464 | 494  | 524  | 554  | 584  | 614  | 644  |                                   |
| 835  | 164 | 220 | 275 | 331 | 387 | 442 | 498 | 554 | 609 | 665  | 721  | 776  | 832  | 888  | 943  |                                   |
| 900  | 158 | 218 | 278 | 338 | 398 | 458 | 518 | 578 | 638 | 698  | 758  | 818  | 878  | 938  | 998  |                                   |
| 1500 | 122 | 222 | 322 | 422 | 522 | 622 | 722 | 822 | 922 | 1022 | 1122 | 1222 | 1322 | 1422 | 1522 |                                   |
| 1900 | 109 | 209 | 309 | 409 | 509 | 609 | 709 | 809 | 909 | 1009 | 1109 | 1209 | 1309 | 1409 | 1509 |                                   |
| 2450 | 96  | 196 | 296 | 396 | 496 | 596 | 696 | 796 | 896 | 996  | 1096 | 1196 | 1296 | 1396 | 1496 |                                   |
| 3600 | 79  | 179 | 279 | 379 | 479 | 579 | 679 | 779 | 879 | 979  | 1079 | 1179 | 1279 | 1379 | 1479 |                                   |
| 5200 | 66  | 166 | 266 | 366 | 466 | 566 | 666 | 766 | 866 | 966  | 1066 | 1166 | 1266 | 1366 | 1466 |                                   |
| 5400 | 65  | 165 | 265 | 365 | 465 | 565 | 665 | 765 | 865 | 965  | 1065 | 1165 | 1265 | 1365 | 1465 |                                   |
| 5800 | 62  | 162 | 262 | 362 | 462 | 562 | 662 | 762 | 862 | 962  | 1062 | 1162 | 1262 | 1362 | 1462 |                                   |

**Table 6:** SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm

#### - For frequencies below 100 MHz

The following may be considered for SAR test exclusion:

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table

| MHz  | < 50 | 50   | 60   | 70   | 80   | 90   | 100  | 110  | 120  | 130  | 140  | 150  | 160  | 170  | 180  | 190  | mm |
|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|
| 100  | 237  | 474  | 481  | 487  | 494  | 501  | 507  | 514  | 521  | 527  | 534  | 541  | 547  | 554  | 561  | 567  | mW |
| 50   | 308  | 617  | 625  | 634  | 643  | 651  | 660  | 669  | 677  | 686  | 695  | 703  | 712  | 721  | 729  | 738  |    |
| 10   | 474  | 948  | 961  | 975  | 988  | 1001 | 1015 | 1028 | 1041 | 1055 | 1068 | 1081 | 1095 | 1108 | 1121 | 1135 |    |
| 1    | 711  | 1422 | 1442 | 1462 | 1482 | 1502 | 1522 | 1542 | 1562 | 1582 | 1602 | 1622 | 1642 | 1662 | 1682 | 1702 |    |
| 0.1  | 948  | 1896 | 1923 | 1949 | 1976 | 2003 | 2029 | 2056 | 2083 | 2109 | 2136 | 2163 | 2189 | 2216 | 2243 | 2269 |    |
| 0.05 | 1019 | 2039 | 2067 | 2096 | 2125 | 2153 | 2182 | 2211 | 2239 | 2268 | 2297 | 2325 | 2354 | 2383 | 2411 | 2440 |    |
| 0.01 | 1185 | 2370 | 2403 | 2437 | 2470 | 2503 | 2537 | 2570 | 2603 | 2637 | 2670 | 2703 | 2737 | 2770 | 2803 | 2837 |    |

**Table 7:** SAR Test Exclusion Thresholds for frequencies < 100 MHz



## Appendix B: ISED RF Exposure information

## ISED SAR test exclusion considerations

According to “RSS-102 Issue 5 (2015-03) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)”, paragraph “2.5.1 Exemption Limits for Routine Evaluation – SAR Evaluation”, the device operates below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1:

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                 |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|
|                 | At separation distance of ≤5 mm | At separation distance of 10 mm | At separation distance of 15 mm | At separation distance of 20 mm | At separation distance of 25 mm |
| ≤300            | 71 mW                           | 101 mW                          | 132 mW                          | 162 mW                          | 193 mW                          |
| 450             | 52 mW                           | 70 mW                           | 88 mW                           | 106 mW                          | 123 mW                          |
| 835             | 17 mW                           | 30 mW                           | 42 mW                           | 55 mW                           | 67 mW                           |
| 1900            | 7 mW                            | 10 mW                           | 18 mW                           | 34 mW                           | 60 mW                           |
| 2450            | 4 mW                            | 7 mW                            | 15 mW                           | 30 mW                           | 52 mW                           |
| 3500            | 2 mW                            | 6 mW                            | 16 mW                           | 32 mW                           | 55 mW                           |
| 5800            | 1 mW                            | 6 mW                            | 15 mW                           | 27 mW                           | 41 mW                           |

| Frequency (MHz) | Exemption Limits (mW)           |                                 |                                 |                                 |                                  |
|-----------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
|                 | At separation distance of 30 mm | At separation distance of 35 mm | At separation distance of 40 mm | At separation distance of 45 mm | At separation distance of ≥50 mm |
| ≤300            | 223 mW                          | 254 mW                          | 284 mW                          | 315 mW                          | 345 mW                           |
| 450             | 141 mW                          | 159 mW                          | 177 mW                          | 195 mW                          | 213 mW                           |
| 835             | 80 mW                           | 92 mW                           | 105 mW                          | 117 mW                          | 130 mW                           |
| 1900            | 99 mW                           | 153 mW                          | 225 mW                          | 316 mW                          | 431 mW                           |
| 2450            | 83 mW                           | 123 mW                          | 173 mW                          | 235 mW                          | 309 mW                           |
| 3500            | 86 mW                           | 124 mW                          | 170 mW                          | 225 mW                          | 290 mW                           |
| 5800            | 56 mW                           | 71 mW                           | 85 mW                           | 97 mW                           | 106 mW                           |

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power. For controlled use devices where the 8 W/kg for 1 gram of tissue applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5. If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance. For test separation distance less than 5 mm, the exemption limits for a separation distance of 5 mm can be applied to determine if a routine evaluation is required.