

RF EXPOSURE EVALUATION

MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 v01 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34 | 1,920 R^2 . |
| 1.34-30 | 3,450 R^2/f^2 . |
| 30-300 | 3.83 R^2 . |
| 300-1,500 | 0.0128 R^2f . |
| 1,500-100,000 | 19.2 R^2 . |

R is the minimum separation distance in meters

f = frequency in MHz

Result

| Mode | Frequency (MHz) | Tune up conducted power [#] (dBm) | Antenna Gain [#] | | ERP | | Evaluation Distance (m) | ERP Limit (W) |
|------------|-----------------|--|---------------------------|-------|-------|-------|-------------------------|---------------|
| | | | (dBi) | (dBd) | (dBm) | (W) | | |
| 2.4G Wi-Fi | 2412-2462 | 23.00 | 2.97 | 0.82 | 23.82 | 0.241 | 0.2 | 0.768 |

Note: 1. The tune up conducted power[#] and antenna gain[#] were declared by the applicant.

2. The 2.4G and 5G Wi-Fi cannot transmit at same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant