

RF Exposure Report

Report No.: SA170505C03

FCC ID: 2AHBN-AP21

Test Model: AP21

Received Date: May 05, 2017

Test Date: May 09 ~ Jun. 28, 2017

Issued Date: Jul. 13, 2017

Applicant: Mist Systems, Inc.

Address: 1601 South De Anza Blvd. Suite 248 Cupertino California United States

95014

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA170505C03 Page No. 1 / 7 Report Format Version: 6.1.1



Table of Contents

R	ease Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
	Limits for Maximum Permissible Exposure (MPE)	5
3	Calculation Result Of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA170505C03	Original release.	Jul. 13, 2017



1 Certificate of Conformity

Product: Wi-Fi & BLE Array AP

Brand: Mist

Test Model: AP21

Sample Status: Engineering sample

Applicant: Mist Systems, Inc.

Test Date: May 09 ~ Jun. 28, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , Date: Jul. 13, 2017

Polly Chien / Specialist

Approved by: , Date: Jul. 13, 2017

Ken Liu / Senior Manager



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)			
Limits For General Population / Uncontrolled Exposure							
300-1500			F/1500	30			
1500-100,000			1.0	30			

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA170505C03 Page No. 5 / 7 Report Format Version: 6.1.1



Calculation Result Of Maximum Conducted Power

CDD mode:

ODD mode.							
Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain	Distance	Power Density (mW/cm ²)	Limit (mW/cm ²)	
(IVITZ)		(ubiii)	(dBi)	(cm)	(IIIVV/CIII)	(IIIVV/CIII)	
Radio 1							
2412-2462	1TX	22.82	3.63	20	0.088	1	
2412-2402	2TX	25.39	6.54	20	0.310	1	
Radio 2							
5480 5 340	1TX	21.13	4.93	20	0.080	1	
5180-5240	2TX	23.46	7.87	20	0.270	1	
5745-5825	1TX	23.03	4.96	20	0.125	1	
3743-3623	2TX	24.29	7.97	20	0.335	1	
Radio 3							
BT LE	-	5.22	4.98	20	0.002	1	

Beamiorning wode							
Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)	
Radio 1							
2412-2462	2TX	19.55	6.54	20	0.081	1	
Radio 2							
5180-5240	2TX	23.26	7.87	20	0.258	1	
5745-5825	2TX	23.98	7.97	20	0.312	1	

Note:

2412-2462MHz:

1TX: Max. antenna gian: 3.63dBi 2TX: Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2/N$] = 6.54dBi

5180-5240MHz:

1TX: Max. antenna gian: 4.93dBi 2TX: Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2/N$] = 7.87dBi

5745-5825MHz:

1TX: Max. antenna gian: 4.96dBi 2TX: Directional gain = 10 log[$(10^{G1/20} + 10^{G2/20} + ... + 10^{GN/20})^2/N$] = 7.97dBi



	MAX POW	TOTAL POWER	POWER LIMIT	
	Radio 1: WLAN	Radio 3: BT	(dBm)	(dBm)
2.4GHz	25.39	5.22	25.43	30

CONCULSION:

Both of the WLAN 2.4G & WLAN 5G & BT can transmit simultaneously, the formula of calculated the MPE is: $CPD1 / LPD2 + CPD2 / LPD2 + \dots etc. < 1$

CPD = Calculation power density

LPD = Limit of power density

Radio 1: 2.4G + Radio 2: 5G + Radio 3: BT = 0.310 +0.335 + 0.002 = 0.647 < 1

---END---