

RF Exposure Report

Report No.: SA151230E03O

FCC ID: 2AHBN-AP41

Test Model: AP41

Series Model: AP41E

Received Date: Jun. 26, 2019

Test Date: Jul. 02 ~ Aug. 05, 2019

Issued Date: Aug. 13, 2019

Applicant: Mist Systems, Inc.

Address: 1601 South De Anza Blvd. Suite 248 Cupertino California United States

95014

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, TAIWAN (R.O.C.)

FCC Registration / 788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA151230E03O Page No. 1 / 8 Report Format Version: 6.1.1 Reference No.: 190626C17



Table of Contents

Rele	Release Control Record				
1	Certificate of Conformity	4			
2	RF Exposure	5			
2.2	Limits for Maximum Permissible Exposure (MPE)	5			
3	Calculation Result of Maximum Conducted Power	6			



Release Control Record

Issue No.	Description	Date Issued
SA151230E03O	Original release	Aug. 13, 2019

Report No.: SA151230E03O Page No. 3 / 8 Report Format Version: 6.1.1 Reference No.: 190626C17



1 Certificate of Conformity

Product: Premium Wi-Fi & BLE Array AP

Brand: Mist

Test Model: AP41

Series Model: AP41E

Sample Status: Engineering sample

Applicant: Mist Systems, Inc.

Test Date: Jul. 02 ~ Aug. 05, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : , **Date:** Aug. 13, 2019

Pettie Chen / Senior Specialist

Approved by : , Date: Aug. 13, 2019

Bruce Chen / Senior Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Average Time (minutes)				
Limits For General Population / Uncontrolled Exposure								
0.3-1.34	614	1.63	(100)*	30				
1.34-30	824/f	2.19/f	(180/f ²)*	30				
30-300	27.5	0.073	0.2	30				
300-1500			f/1500	30				
1500-100,000			1.0	30				

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 35cm away from the body of the user. So, this device is classified as Mobile Device.

Report No.: SA151230E03O Pag Reference No.: 190626C17



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	
CDD Mode							
	1TX	19.57	8	35	0.037	1	
2412-2462	2TX	23.04	11.01	35	0.165	1	
2412-2402	3TX	25.02	12.77	35	0.391	1	
	4TX	26.20	14.02	35	0.683	1	
	1TX	17.04	8	35	0.021	1	
5180-5240	2TX	20.47	11.01	35	0.091	1	
3180-3240	3TX	22.60	12.77	35	0.224	1	
	4TX	23.73	14.02	35	0.387	1	
	1TX	10.88	8	35	0.005	1	
5260-5320	2TX	14.38	11.01	35	0.022	1	
3200-3320	3TX	16.34	12.77	35	0.053	1	
	4TX	17.49	14.02	35	0.092	1	
	1TX	11.45	8	35	0.006	1	
5500-5700	2TX	14.73	11.01	35	0.024	1	
3300-3700	3TX	16.64	12.77	35	0.057	1	
	4TX	17.72	14.02	35	0.097	1	
	1TX	21.62	8	35	0.060	1	
5745-5825	2TX	24.48	11.01	35	0.230	1	
3740-0020	3TX	26.65	12.77	35	0.568	1	
	4TX	27.80	14.02	35	0.988	1	



Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	
Beamforming Mode							
	2TX	18.65	11.01	35	0.060	1	
2412-2462	3TX	20.65	12.77	35	0.143	1	
	4TX	21.87	14.02	35	0.252	1	
	2TX	18.52	11.01	35	0.058	1	
5180-5240	3TX	20.61	12.77	35	0.141	1	
	4TX	21.75	14.02	35	0.245	1	
	2TX	12.88	11.01	35	0.016	1	
5260-5320	3TX	14.81	12.77	35	0.037	1	
	4TX	15.97	14.02	35	0.065	1	
	2TX	12.88	11.01	35	0.016	1	
5500-5700	3TX	14.75	12.77	35	0.037	1	
	4TX	15.86	14.02	35	0.063	1	
	2TX	18.74	11.01	35	0.061	1	
5745-5825	3TX	20.76	12.77	35	0.146	1	
	4TX	21.86	14.02	35	0.252	1	

Frequency Band (MHz)	TX Function	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm ²)
Radio 3						
BT EDR	-	10.90	11.05	35	0.010	1
BT LE	-	6.13	11.05	35	0.003	1

Note: WLAN:

2TX: Directional gain = 8 dBi + 10 log(2)= 11.01dBi 3TX: Directional gain = 8 dBi + 10 log(3)= 12.77dBi 4TX: Directional gain = 8 dBi + 10 log(4)= 14.02dBi

BT EDR/BT LE: Directional gain = 5.03dBi + 10log(4) = 11.05dBi



	MAX POW	/ER (dBm)	TOTAL POWER	POWER LIMIT (dBm)
	Radio 1: WLAN	Radio 3: BT	(dBm)	
2.4GHz	26.20	10.90	26.33	30

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

CONCULSION:

2.4G & 5G & BT cannot transmit simultaneously.

The simultaneous operation mode was determined by client as below:

1. Radio 1: 2.4G + Radio 3: BT

2. Radio 1: 5G + Radio 3: BT

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

Radio 1: 2.4G + Radio 3: BT = 0.683/1 + 0.010/1 = 0.693Radio 1: 5G + Radio 3: BT = 0.988/1 + 0.010/1 = 0.998

Therefore, the maximum calculation of this situation is 0.998, which is less than the "1" limit.

---END---