

# FCC Part 15C

## Measurement and Test Report

For

**HuiZhou WanZhao Electronics Co.,Ltd.**

**Tongqiao Road, Tongqiao Industrial Park, High-tech Development**

**Zone, HuiZhou City, Guangdong China**

**FCC ID: 2AHBSV-MP02-G**

<b>FCC Rule(s):</b>	<u>FCC Part 15.247</u>
<b>Product Description:</b>	<u>Levitating Bluetooth Speaker</u>
<b>Tested Model:</b>	<u>V-MP02-G</u>
<b>Report No.:</b>	<u>STR16018233I</u>
<b>Tested Date:</b>	<u>2016-01-20 to 2016-01-28</u>
<b>Issued Date:</b>	<u>2016-01-28</u>
<b>Tested By:</b>	<u>Leo Lee/ Engineer</u>
<b>Reviewed By:</b>	<u>Silin Chen/ EMC Manager</u>
<b>Approved &amp; Authorized By:</b>	<u>Jandy so / PSQ Manager</u>
<b>Prepared By:</b>	<u>Shenzhen SEM.Test Technology Co., Ltd.</u> 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: <a href="http://www.semtest.com.cn">www.semtest.com.cn</a>

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permission by Shenzhen SEM.Test Technology Co., Ltd.

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY.....	5
1.4 TEST FACILITY .....	5
1.5 EUT SETUP AND TEST MODE.....	6
1.6 TEST EQUIPMENT LIST AND DETAILS .....	7
<b>2. SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>3. RF EXPOSURE .....</b>	<b>9</b>
3.1 STANDARD APPLICABLE.....	9
3.2 TEST RESULT.....	9
<b>4. ANTENNA REQUIREMENT .....</b>	<b>10</b>
4.1 STANDARD APPLICABLE.....	10
4.2 EVALUATION INFORMATION .....	10
<b>5. FREQUENCY HOPPING SYSTEM REQUIREMENTS .....</b>	<b>11</b>
5.1 STANDARD APPLICABLE.....	11
5.2 FREQUENCY HOPPING SYSTEM.....	11
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....	12
<b>6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION .....</b>	<b>13</b>
6.1 STANDARD APPLICABLE.....	13
6.2 TEST PROCEDURE.....	13
6.3 ENVIRONMENTAL CONDITIONS .....	13
6.4 SUMMARY OF TEST RESULTS/PLOTS .....	14
<b>7. DWELL TIME OF HOPPING CHANNEL.....</b>	<b>18</b>
7.1 STANDARD APPLICABLE.....	18
7.2 TEST PROCEDURE.....	18
7.3 ENVIRONMENTAL CONDITIONS .....	18
7.4 SUMMARY OF TEST RESULTS/PLOTS .....	19
<b>8. 20DB BANDWIDTH .....</b>	<b>29</b>
8.1 STANDARD APPLICABLE.....	29
8.2 TEST PROCEDURE.....	29
8.3 ENVIRONMENTAL CONDITIONS .....	29
8.4 SUMMARY OF TEST RESULTS/PLOTS .....	29
<b>9. RF OUTPUT POWER .....</b>	<b>33</b>
9.1 STANDARD APPLICABLE.....	33
9.2 TEST PROCEDURE.....	33
9.3 ENVIRONMENTAL CONDITIONS .....	33
9.4 SUMMARY OF TEST RESULTS/PLOTS .....	33
<b>10. FIELD STRENGTH OF SPURIOUS EMISSIONS .....</b>	<b>35</b>
10.1 MEASUREMENT UNCERTAINTY .....	35
10.2 STANDARD APPLICABLE.....	35
10.3 TEST PROCEDURE.....	35
10.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	37
10.5 ENVIRONMENTAL CONDITIONS .....	37
10.6 SUMMARY OF TEST RESULTS/PLOTS .....	37
<b>11. OUT OF BAND EMISSIONS.....</b>	<b>47</b>
11.1 STANDARD APPLICABLE.....	47
11.2 TEST PROCEDURE.....	47
11.3 ENVIRONMENTAL CONDITIONS .....	48
11.4 SUMMARY OF TEST RESULTS/PLOTS .....	48
<b>12. CONDUCTED EMISSIONS .....</b>	<b>52</b>
12.1 MEASUREMENT UNCERTAINTY .....	52

12.2 TEST PROCEDURE.....	52
12.3 BASIC TEST SETUP BLOCK DIAGRAM.....	52
12.4 ENVIRONMENTAL CONDITIONS .....	52
12.5 TEST RECEIVER SETUP .....	53
12.6 SUMMARY OF TEST RESULTS/PLOTS .....	53
12.7 CONDUCTED EMISSIONS TEST DATA.....	53

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: HuiZhou WanZhao Electronics Co.,Ltd.  
Address of applicant: Tongqiao Road, Tongqiao Industrial Park, High-tech Development Zone, HuiZhou City, Guangdong China

Manufacturer: HuiZhou WanZhao Electronics Co.,Ltd.  
Address of manufacturer: Tongqiao Road, Tongqiao Industrial Park, High-tech Development Zone, HuiZhou City, Guangdong China

<b>General Description of EUT</b>	
Product Name:	Levitating Bluetooth Speaker
Trade Name:	LVV
Model No.:	V-MP02-G
Rated Voltage:	Battery: 7.4V
Power Adapter Model:	BX-1201500 I/P: AC 100~240V,50/60Hz; O/P: DC12V
<i>Note: The test data is gathered from a production sample provided by the manufacturer.</i>	

<b>Technical Characteristics of EUT</b>	
Bluetooth Version:	Bluetooth V4.0 (only Bluetooth V3.0 used)
Frequency Range:	2402-2480MHz
RF Output Power:	-6.90 dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	-1dBi
Lowest Internal Frequency of EUT:	26MHz

## 1.2 Test Standards

The following report is prepared on behalf of the HuiZhou WanZhao Electronics Co.,Ltd in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide DA 00-705 for frequency hopping spread spectrum systems shall be performed also.

## 1.4 Test Facility

### **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

### **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2<sup>nd</sup> Road, Bao'an District, Shenzhen, P.R.C (518101).

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List			
Test Mode	Description		Remark
TM1	Low Channel		2402MHz
TM2	Middle Channel		2441MHz
TM3	High Channel		2480MHz
TM4	Hopping		2402-2480MHz
TM5	Charge base and Bluetooth Playing		Worst mode
TM6	Levitating base and Bluetooth Playing		/
TM7	Bluetooth Playing		/

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	379
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021

Normal mode: the Bluetooth has been tested on the modulation of GFSK, (Pi/4)DQPSK and 8DPSK, compliance test and record the worst case.

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC cable	1.9	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Phone	Apple	5S	/

## 1.6 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal Date	Due Date
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16
Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

## 2. SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

### 3. RF Exposure

---

#### 3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### 3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

## 4. Antenna Requirement

---

### 4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

### 4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

## 5. Frequency Hopping System Requirements

---

### 5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

### 5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

### 5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 6. Quantity of Hopping Channels and Channel Separation

### 6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 6.2 Test Procedure

According to the DA 00-705, the number of hopping frequencies test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = the frequency band of operation (2400MHz to 2483.5MHz)

RBW = 100kHz, VBW = 100kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize, observed the band of 2400MHz to 2483.5MHz, than count it out the number of channels for comparing with the FCC rules.

The channel spacing test method as follows:

Set span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span

Video (or Average) Bandwidth (VBW)  $\geq$  RBW

Sweep = auto; Detector function = peak; Trace = max hold


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

### 6.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar


## 6.4 Summary of Test Results/Plots

No. of Channel = 79




For GFSK mode


Channel Spacing (Low CH=1MHz)



## Channel Spacing (Middle CH=1MHz)




## Channel Spacing (High CH=1MHz)




For Pi/4 DQPSK mode


Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



### Channel Spacing (High CH=1MHz)



## 7. Dwell Time of Hopping Channel

---

### 7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 7.2 Test Procedure

According to the DA 00-705, the dwell time of a hopping channel test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Use the marker-delta function to determine the dwell time

### 7.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 7.4 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length). Test data is corrected with the worse case, which the packet length is DH1, DH3, and DH5.



The test period:  $T = 0.4 \text{ Second} * 79 \text{ Channel} = 31.6 \text{ s}$


Dwell time = time slot length \* (Hopping rate / Number of hopping channels) \* Period

Modulation	Test Channel	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
GFSK	2402MHz	DH1	0.36	115.20	400
		DH3	1.62	259.20	400
		DH5	2.87	306.13	400
	2441MHz	DH1	0.37	118.40	400
		DH3	1.61	257.60	400
		DH5	2.86	305.07	400
	2480MHz	DH1	0.36	115.20	400
		DH3	1.62	259.20	400
		DH5	2.86	305.07	400
8DPSK	2402MHz	3DH1	0.37	118.40	400
		3DH3	1.61	257.60	400
		3DH5	2.86	305.07	400
	2441MHz	3DH1	0.38	121.60	400
		3DH3	1.62	259.20	400
		3DH5	2.86	305.07	400
	2480MHz	3DH1	0.37	118.40	400
		3DH3	1.62	259.20	400
		3DH5	2.86	305.07	400


*Please refer to the test plots as below:*



## DH1 time slot (Low, Middle, High Channels)








DH3 time slot (Low, Middle, High Channels)








## DH5 time slot (Low, Middle, High Channels)








3DH1 time slot (Low, Middle, High Channels)








## 3DH3 time slot (Low, Middle, High Channels)





3DH5 time slot (Low, Middle, High Channels)





## 8. 20dB Bandwidth

### 8.1 Standard Applicable

According to 15.247(a) and 15.215(c). 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 8.2 Test Procedure

According to the DA 00-705, the 20dB bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto; Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down bandwidth of the emission.

### 8.3 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

### 8.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
GFSK	2402	841.381	867.7476	Pass
	2441	812.968	847.9281	Pass
	2480	1014	938.6378	Pass
8DPSK	2402	1277	1223.7	Pass
	2441	1260	1193.0	Pass
	2480	1276	1224.5	Pass

For GFSK


Low Channel:



Middle Channel:




High Channel:




For 8DPSK


Low Channel:



Middle Channel:



High Channel:



## 9. RF Output Power

---

### 9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

### 9.2 Test Procedure

According to the DA 00-705, the peak output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, the indicated level is the peak output power (the external attenuation and cable loss shall be considered).

### 9.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	55%
ATM Pressure:	1011 mbar

### 9.4 Summary of Test Results/Plots

For GFSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-7.52	0.18	1000
Middle Channel	2441	-8.37	0.15	1000
High Channel	2480	-8.48	0.14	1000

For Pi/4 QDPSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-7.04	0.20	1000
Middle Channel	2441	-7.90	0.16	1000
High Channel	2480	-8.40	0.14	1000

For 8DPSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-6.90	0.20	1000
Middle Channel	2441	-7.63	0.17	1000
High Channel	2480	-8.12	0.15	1000

*Note: the antenna gain of -1dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.*

## 10. Field Strength of Spurious Emissions

---

### 10.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.10$  dB.

### 10.2 Standard Applicable



According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

### 10.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.



Frequency :9kHz-30MHz  
 RBW=10KHz,  
 VBW =30KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak

Frequency :30MHz-1GHz  
 RBW=120KHz,  
 VBW=300KHz  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, QP

Frequency :Above 1GHz  
 RBW=1MHz,  
 VBW=3MHz(Peak), 10Hz(AV)  
 Sweep time= Auto  
 Trace = max hold  
 Detector function = peak, AV

## 10.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

## 10.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar


## 10.6 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*


### Plot of Radiated Emissions Test Data (30MHz to 1GHz)

**EUT:** Levitating Bluetooth Speaker  
**Tested Model:** V-MP02-G  
**Operating Condition:** Charge base and Bluetooth Playing (worst mode)  
**Comment:** AC 120V/60Hz; Adapter DC 12V  
**Test Specification:** Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	109.7960	31.65	-11.16	20.49	43.50	-23.01	254	100	peak
2	147.4036	40.46	-12.46	28.00	43.50	-15.50	183	100	peak
3	242.5253	34.16	-8.16	26.00	46.00	-20.00	169	100	peak
4	265.6757	32.19	-6.71	25.48	46.00	-20.52	244	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	35.4993	44.03	-8.90	35.13	40.00	-4.87	132	100	peak
2	44.5868	40.28	-7.97	32.31	40.00	-7.69	269	100	peak
3	109.4116	52.20	-11.15	41.05	43.50	-2.45	311	100	peak
4	146.8877	44.61	-12.47	32.14	43.50	-11.36	247	100	peak


*Operating Condition:* Transmitting low Channel (2402MHz)  
*Comment:* DC 7.4V

*Test Specification:* Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.4165	17.52	4.81	22.33	40.00	-17.67	124	100	peak
2	53.3179	13.93	5.30	19.23	40.00	-20.77	168	100	peak
3	101.6443	14.38	5.11	19.49	43.50	-24.01	139	100	peak
4	393.4724	14.17	12.83	27.00	46.00	-19.00	214	100	peak
5	599.3213	13.66	19.19	32.85	46.00	-13.15	154	100	peak
6	755.3873	15.00	18.86	33.86	46.00	-12.14	136	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.2855	16.58	4.79	21.37	40.00	-18.63	158	100	peak
2	112.1305	14.73	5.06	19.79	43.50	-23.71	137	100	peak
3	406.0880	16.54	12.91	29.45	46.00	-16.55	245	100	peak
4	599.3213	16.08	19.19	35.27	46.00	-10.73	269	100	peak
5	677.5798	16.20	19.13	35.33	46.00	-10.67	124	100	peak
6	1000.0000	16.54	18.91	35.45	54.00	-18.55	136	100	peak


*Operating Condition:* Transmitting Middle Channel (2441MHz)  
*Comment:* DC 7.4V

*Test Specification:* Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.4165	17.46	4.81	22.27	40.00	-17.73	168	100	peak
2	46.9948	15.54	5.26	20.80	40.00	-19.20	254	100	peak
3	99.1797	15.61	5.01	20.62	43.50	-22.88	136	100	peak
4	210.0482	13.89	5.90	19.79	43.50	-23.71	199	100	peak
5	390.7226	16.44	12.70	29.14	46.00	-16.86	127	100	peak
6	679.9600	16.08	19.26	35.34	46.00	-10.66	169	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	38.2120	17.00	4.94	21.94	40.00	-18.06	249	100	peak
2	52.7600	15.25	5.30	20.55	40.00	-19.45	273	100	peak
3	104.9033	15.76	5.10	20.86	43.50	-22.64	164	100	peak
4	321.0608	14.98	12.26	27.24	46.00	-18.76	159	100	peak
5	601.4265	14.99	19.22	34.21	46.00	-11.79	127	100	peak
6	755.3873	16.19	18.86	35.05	46.00	-10.95	136	100	peak


*Operating Condition:* Transmitting High Channel (2480MHz)  
*Comment:* DC 7.4V

*Test Specification:* Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	36.3814	16.95	4.64	21.59	40.00	-18.41	257	100	peak
2	52.5753	15.63	5.30	20.93	40.00	-19.07	314	100	peak
3	113.7143	15.29	5.05	20.34	43.50	-23.16	126	100	peak
4	333.6867	15.78	11.90	27.68	46.00	-18.32	142	100	peak
5	605.6592	15.20	18.92	34.12	46.00	-11.88	174	100	peak
6	744.8661	17.73	19.33	37.06	46.00	-8.94	138	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	37.4165	17.42	4.81	22.23	40.00	-17.77	164	100	peak
2	56.9912	15.35	5.34	20.69	40.00	-19.31	137	100	peak
3	112.9196	14.84	5.06	19.90	43.50	-23.60	156	100	peak
4	322.1886	15.09	12.23	27.32	46.00	-18.68	147	100	peak
5	684.7454	15.08	18.91	33.99	46.00	-12.01	169	100	peak
6	744.8661	16.09	19.33	35.42	46.00	-10.58	254	100	peak

*Spurious Emissions Above 1GHz*

Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2402MHz							
4804	48.3	-3.59	44.71	74	-29.29	H	PK
4804	51.97	-3.59	48.38	54	-5.62	H	AV
7206	46.13	-0.52	45.61	74	-28.39	H	PK
7206	47.25	-0.52	46.73	54	-7.27	H	AV
4804	50.23	-3.59	46.64	74	-27.36	V	PK
4804	51.78	-3.59	48.19	54	-5.81	V	AV
7206	56.14	-0.52	55.62	74	-18.38	V	PK
7206	49.56	-0.52	49.04	54	-4.96	V	AV
Middle Channel-2441MHz							
4882	62.18	-3.49	58.69	74	-15.31	H	PK
4882	51.64	-3.49	48.15	54	-5.85	H	AV
7323	51.23	-0.47	50.76	74	-23.24	H	PK
7323	47.92	-0.47	47.45	54	-6.55	H	AV
4882	54.79	-3.49	51.30	74	-22.70	V	PK
4882	53.51	-3.49	50.02	54	-3.98	V	AV
7323	51.63	-0.47	51.16	74	-22.84	V	PK
7323	44.89	-0.47	44.42	54	-9.58	V	AV
High Channel-2480MHz							
4960	51.23	-3.41	47.82	74	-26.18	H	PK
4960	49.36	-3.41	45.95	54	-8.05	H	AV
7440	52.37	-0.42	51.95	74	-22.05	H	PK
7440	46.98	-0.42	46.56	54	-7.44	H	AV
4960	53.47	-3.41	50.06	74	-23.94	V	PK
4960	44.69	-3.41	41.28	54	-12.72	V	AV
7440	52.37	-0.42	51.95	74	-22.05	V	PK
7440	43.36	-0.42	42.94	54	-11.06	V	AV

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*

*The measurements greater than 20dB below the limit from 9kHz to 30MHz..*

## 11. Out of Band Emissions

---

### 11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

### 11.2 Test Procedure

According to the DA 00-705, the band-edge radiated test method as follows.

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the DA 00-705, the band-edge conducted test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2380MHz to 2410MHz for low bandedge, 2470MHz to 2500MHz for the high bandedge)

RBW = 100kHz, VBW = 300kHz

Sweep = auto; Detector function = peak; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the limit specified in this section (at least 20dB attenuation).

### 11.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

### 11.4 Summary of Test Results/Plots

Bandedge (Radiated)


Lowest Bandedge

Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	32.10	-3.69	28.41	54.00	-25.59	Average Detector
	2310.000	46.54	-3.69	42.85	74.00	-31.15	Peak Detector
2	2390.000	32.67	-3.49	29.18	54.00	-24.82	Average Detector
	2390.000	47.53	-3.49	44.04	74.00	-29.96	Peak Detector


Highest Bandedge  
Horizontal (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.000	62.50	-3.25	59.25	/	/	Average Detector
	2480.000	79.93	-3.25	76.68	/	/	Peak Detector
2	2483.500	Delta = 43.66dBc	-3.25	36.29	54.00	-17.71	Average Detector
	2483.500			45.59	74.00	-28.41	Peak Detector
3	2500.000	32.20	-3.20	29.00	54.00	-25.00	Average Detector
	2500.000	45.59	-3.20	42.39	74.00	-31.61	Peak Detector

### Bandedge (Conducted)(specific frequency)

## Lowest Bandedge




## Highest Bandedge




## Bandedge (Conducted) ( Frequency Hopping)

Lowest Bandedge



Highest Bandedge



## 12. Conducted Emissions

### 12.1 Measurement Uncertainty


Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

### 12.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

### 12.3 Basic Test Setup Block Diagram



### 12.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

## 12.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth .....	9 kHz
Quasi-Peak Adapter Mode .....	Normal

## 12.6 Summary of Test Results/Plots


According to the data in section 12.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:

**-3.05 dB at 3.7580 MHz in the Line mode, AVG detector, 0.15-30MHz**

## 12.7 Conducted Emissions Test Data


### Plot of Conducted Emissions Test Data

**EUT:** Resin Decor with Speaker  
**Tested Model:** HS 180057 Elephant  
**Operating Condition:** Charging and Bluetooth Playing  
**Comment:** AC 120V/60Hz; Adapter DC 12V  
  
**Test Specification:** Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	3.7380	32.92	12.16	45.08	56.00	-10.92	peak
2	3.7380	28.60	12.16	40.76	46.00	-5.24	AVG
3	4.8100	35.01	12.87	47.88	56.00	-8.12	peak
4	4.8100	31.27	12.87	44.14	46.00	-1.86	AVG
5	5.8780	36.53	12.65	49.18	60.00	-10.82	peak
6	5.8780	32.24	12.65	44.89	50.00	-5.11	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	3.7580	33.09	12.17	45.26	56.00	-10.74	peak
2	3.7580	30.78	12.17	42.95	46.00	-3.05	AVG
3	4.8340	33.69	12.89	46.58	56.00	-9.42	peak
4	4.8340	29.71	12.89	42.60	46.00	-3.40	AVG
5	5.9060	35.39	12.64	48.03	60.00	-11.97	peak
6	5.9060	28.61	12.64	41.25	50.00	-8.75	AVG

\*\*\*\*\* END OF REPORT \*\*\*\*\*