

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.....: MWR160118104

FCC ID.....: 2AHBY-ET1

Compiled by

(position+printed name+signature)..:

File administrators Martin Ao

Supervised by

(position+printed name+signature)... Test Engineer Yuchao Wang

Approved by

Manager Dixon Hao (position+printed name+signature)..:

Date of issue....: Jan. 25, 2016

Representative Laboratory Name .: Maxwell International Co., Ltd.

Room 509, Hongfa center building, Baoan District, Shenzhen, Address:

Guangdong, China

Testing Laboratory Name Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road, Address:

Nanshan District, Shenzhen, China 518055

yuchao.wang

Applicant's name..... ALPHA EXPORT AND IMPORT CO.,LTD

4D HUASHANG BUILDING, NORTH PORT RD, SHENZHEN Address:

CHINA

Test specification:

FCC Part 15.247: Operation within the bands 902-928 MHz, Standard:

2400-2483.5 MHz and 5725-5850 MHz

TRF Originator.....: Maxwell International Co., Ltd.

Maxwell International Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Maxwell International Co., Ltd. as copyright owner and source of the material. Maxwell International Co., Ltd. takess no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Mobile Phone

Trade Mark: **ALPHARD**

Manufacturer..... ALPHA EXPORT AND IMPORT CO.,LTD

Model/Type reference....: ET1

Listed Models: ET2, ET3, ET4, ET5, ET6, ET7, ET8, ET9, ET10, ET11, ET12

Modulation Type: **GFSK**

Operation Frequency...... From 2402MHz to 2480MHz

DC 3.70V Rating:

Hardware version V178_MB_V2.0

Software version: V2.0

Result..... PASS

Page 2 of 35 Report No.: MWR160118104

TEST REPORT

Test Report No. :	MWR160118104	Jan. 25, 2016
	1919 91 10 10 10 4	Date of issue

Equipment under Test : Mobile Phone

Model /Type : ET1

Listed Models : ET2, ET3, ET4, ET5, ET6, ET7, ET8, ET9, ET10, ET11,

ET12

Applicant : ALPHA EXPORT AND IMPORT CO.,LTD

Address : 4D HUASHANG BUILDING, NORTH PORT RD,

SHENZHEN CHINA

Manufacturer : ALPHA EXPORT AND IMPORT CO.,LTD

Address : 4D HUASHANG BUILDING, NORTH PORT RD,

SHENZHEN CHINA

Test Result:	PASS

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Report No.: MWR160118104

Contents

SUMMARY	<u>5</u>
General Remarks	5
Product Description	5
Equipment Under Test Description of the test mode	6 6
Short description of the Equipment under Test (EUT)	6
Test Environments	7
EUT operation mode	7
EUT configuration	7
Internal Identification of AE used during the test	7
Related Submittal(s) / Grant (s)	7
Modifications	7
TEST ENVIRONMENT	8
Address of the test laboratory	8
Test Facility	8
Environmental conditions	8
Test Description	8
Summary of measurement results	9
Test Conditions	9
Equipments Used during the Test	10
TEST CONDITIONS AND RESULTS	11
AC Power Conducted Emission	11
Radiated Emissions and Band Edge	14
Maximum Peak Output Power	22
Power Spectral Density	23
Spurious RF Conducted Emission	26
6dB Bandwidth	31
Antenna Requirement	34
TEST SETUP PHOTOS OF THE EUT	35
EXTERNAL PHOTOS OF THE EUT	2.5

Page 4 of 35 Report No.: MWR160118104

1 TEST STANDARDS

The tests were performed according to following standards:

<u>FCC Rules Part 15.247:</u> Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

<u>ANSI C63.10:2013</u>: American National Standard for Testing Unlicensed Wireless Devices

<u>KDB558074 D01 V03:</u> Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Jan. 11, 2016
Testing commenced on	:	Jan. 12, 2016
Testing concluded on	:	Jan. 25, 2016

2.2 Product Description

The **ALPHA EXPORT AND IMPORT CO.,LTD**'s Model: ET1 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

[
Name of EUT	Mobile Phone			
Model Number	ET1			
Modilation Type	GMSK for GSM/GPRS, 8-PSK for EDGE,QPSK for UMTS			
Antenna Type	Internal			
UMTS Operation Frequency Band	Device supported UMTS FDD Band V			
	IEEE 802.11b:2412-2462MHz			
WLAN FCC Operation frequency	IEEE 802.11g:2412-2462MHz			
WEART CO Operation frequency	IEEE 802.11n HT20:2412-2462MHz			
	IEEE 802.11n HT40:2422-2452MHz			
BT FCC Operation frequency	2402MHz-2480MHz			
HSDPA Release Version	Release 10			
HSUPA Release Version	Release 6			
DC-HSUPA Release Version	Not Supported			
WCDMA Release Version	R99			
	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)			
MI AN ECC Modulation Type	IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)			
WLAN FCC Modulation Type	IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)			
	IEEE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)			
BT Modulation Type	GFSK,8DPSK,π/4DQPSK(BT 3.0+EDR)			
Hardware version	V178_MB_V2.0			
Software version	V2.0			
Android version	Android 4.4.2			
GPS function	Supported			
WLAN	Supported 802.11b/802.11g/802.11n			
Bluetooth	Supported BT 4.0/BT 3.0+EDR			
GSM/EDGE/GPRS	Supported GSM/GPRS/EDGE			
GSM/EDGE/GPRS Power Class	GSM850:Power Class 4/ PCS1900:Power Class 1			
GSM/EDGE/GPRS Operation	CCM050 :024 2MH = 040 0MH = /DCC4000:4050 2MH = 4000 0MH =			
Frequency	GSM850 :824.2MHz-848.8MHz/PCS1900:1850.2MHz-1909.8MHz			
GSM/EDGE/GPRS Operation	CCM0E0/DCC4000/CDDC0E0/CDDC4000/CDCC0E0/CDCC4000			
Frequency Band	GSM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900			
GSM Release Version	R99			
GPRS/EDGE Multislot Class	GPRS/EDGE: Multi-slot Class 12			
Extreme temp. Tolerance	-30°C to +50°C			
Extreme vol. Limits	3.40VDC to 4.20VDC (nominal: 3.70VDC)			
GPRS operation mode	Class B			

Page 6 of 35 Report No.: MWR160118104

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	0	120V / 60 Hz	0	115V / 60Hz
		0	12 V DC	0	24 V DC
		•	Other (specified in blank bel	ow)

DC 3.70V

2.4 Description of the test mode

The application provider specific test software to control sample in continuous TX and RX (Duty Cycle >98%)

For testing meet KDB558074 test requirement.

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 40 channels of EUT, and the test carried out at the lowest channel, middle channel and highest channel

Channel	Frequency(MHz)	Channel	Frequency(MHz)
00	2402	20	2442
01	2404	21	2444
02	2406	22	2446
03	2408	23	2448
04	2410	24	2450
05	2412	25	2452
06	2414	26	2454
07	2416	27	2456
08	2418	28	2458
09	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

2.5 Short description of the Equipment under Test (EUT)

2.5.1 General Description

ET1 is subscriber equipment in the WCDMA/GSM system. The HSPA/UMTS frequency band is Band I and Band V; The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only Band V and GSM850 and PCS1900 bands test data included in this report. The Mobile Phone implements such functions as RF signal receiving/transmitting, HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and SIM card interface. It also provides Bluetooth module to synchronize data between a PC and the phone, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

Note: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Page 7 of 35 Report No.: MWR160118104

2.5.2 Customized Configurations

#EUT Conf.	Signal Description	Operating Frequency
TM1_ Ch00	GFSK modulation	Ch No. 00/2402MHz
TM1_ Ch19	GFSK modulation	Ch No. 19/ 2440MHz
TM1 Ch39	GFSK modulation	Ch No. 39/ 2480MHz

2.6 Test Environments

NOTE: The values used in the test report maybe stringent than the declared.

Environment Parameter	Selected Values During Tests			
NTNV	Temperature	Voltage	Relative Humidity	
	Ambient	3.70VDC	Ambient	

2.7 EUT operation mode

The EUT has been tested under typical operating condition. The Applicant provides command

to control the EUT for staying in continuous transmitting (Duty Cycle >98%) and receiving mode for testing.

2.8 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- O supplied by the lab

0	Power Cable	Length (m):	1
		Shield :	1
		Detachable :	1
0	Multimeter	Manufacturer:	1
		Model No.:	1

2.9 Internal Identification of AE used during the test

AE ID*	Description
AE1	Charger and USB cable

AE1

Model: GR ∧ ND

INPUT: AC180-240V~ 50/60Hz 0.15A

OUTPUT: DC 5.0V 1A

2.10 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AHBY-ET1** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.11 Modifications

No modifications were implemented to meet testing criteria.

^{*}AE ID: is used to identify the test sample in the lab internally.

Page 8 of 35 Report No.: MWR160118104

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4, CISPR 22/EN 55022 and CISPR16-4-1 SVSWR requirements.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

3.4 Test Description

Test Item	FCC Part No.	Requirements	Verdict
DTS (6 dB) Bandwidth	15.247(a)(2)	≥ 500 kHz.	PASS
Maximum Peak Conducted Output Power	15.247(b)(3)	For directional gain:< 30dBm – (G[dBi] –6 [dB]),peak; Otherwise:< 30dBm, peak.	PASS
Maximum Power Spectral Density Level	15.247(e)	For directional gain :< 8dBm/3 kHz – (G[dBi] –6[dB]), peak. Otherwise :< 8dBm/3 kHz, peak.	PASS
Band Edges Compliance	15.247(d)	< -20dBr/100 kHz if total peak power ≤power limit.	PASS
Unwanted Emissions into Non- Restricted Frequency Bands	15.247(d)	< -20dBr/100 kHz if total peak power ≤power limit.	PASS
Unwanted Emissions into Restricted Frequency Bands (Conducted)	15.247(d) 15.209	< -20dBr/100 kHz if total peak power ≤power limit.	PASS
Unwanted Emissions into Restricted Frequency Bands (Radiated)	15.247(d) 15.209	FCC Part 15.209 field strength limit;	PASS
AC Power Line Conducted Emissions	15.207	FCC Part 15.207 conducted limit;	PASS

Remark: The measurement uncertainty is not included in the test result.

3.5 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Reco In Re		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	GFSK	 Lowest Middle Highest	GFSK		\boxtimes				complies
§15.247(e)	Power spectral density	GFSK	 Lowest Middle Highest	GFSK	☑ Lowest☑ Middle☑ Highest	\boxtimes				complies
§15.247(a)(1)	Spectrum bandwidth - 6 dB bandwidth	GFSK	☑ Lowest☑ Middle☑ Highest	GFSK	 Lowest Middle Highest	\boxtimes				complies
§15.247(b)(1)	Maximum output power	GFSK	 Lowest Middle Highest	GFSK		\boxtimes				complies
§15.247(d)	Band edge compliance conducted	GFSK		GFSK		\boxtimes				complies
§15.205	Band edge compliance radiated	GFSK		GFSK	⊠ Lowest ⊠ Highest					complies
§15.247(d)	TX spurious emissions conducted	GFSK		GFSK		\boxtimes				complies
§15.247(d)	TX spurious emissions radiated	GFSK		GFSK		\boxtimes				complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	\boxtimes				complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	GFSK	-/-	GFSK	-/-	\boxtimes				complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	GFSK	-/-	GFSK	-/-	\boxtimes				complies

Remark:

- The measurement uncertainty is not included in the test result. NA = Not Applicable; NP = Not Performed 1.
- 2.

Test Conditions 3.6

Test Case	Test Conditions			
rest Case	Configuration	Description		
DTC (6 dD)	Measurement Method	FCC KDB 558074 §8.2 Option 2		
DTS (6 dB) Bandwidth	Test Environment	NTNV		
Dariuwiuiii	EUT Configuration	TM1_ Ch00, TM1_ Ch19, TM1_ Ch39		
Maximum Peak Conducted Output	Measurement Method	FCC KDB 558074§9.1.2		
Power	Test Environment	NTNV		
rowei	EUT Configuration	TM1_ Ch00, TM1_ Ch19, TM1_ Ch39		
Maximum Power Spectral Density	Measurement Method	FCC KDB 558074 §10.2 (peak PSD).		
Level	Test Environment	NTNV		
Level	EUT Configuration	TM1_ Ch00, TM1_ Ch19, TM1_ Ch39		
Unwanted Emissions into Non-	Measurement Method	FCC KDB 558074§11.0		
Restricted Frequency Bands	Test Environment	NTNV		
Restricted Frequency Barids	EUT Configuration	T TM1_ Ch00, TM1_ Ch19, TM1_ Ch39		
Unwanted Emissions into Restricted	Measurement Method	FCC KDB 558074§12.2, Conducted		
Frequency Bands (Conducted)		(antenna-port).		
	Test Environment	NTNV		
	EUT Configuration	TM1_ Ch00, TM1_ Ch19, TM1_ Ch39		

Page 10 of 35

Unwanted Emissions into Restricted	Measurement Method	FCC KDB 558074§12.1,Radiated(cabinet/case emissions with Impedance matching for antenna-port).
	EUT Configuration	TM1 Ch00, TM1 Ch19, TM1 Ch39

Report No.: MWR160118104

Test Case	Test Conditions				
rest case	Configuration	Description			
AC Dower Line Conducted	Measurement Method	AC mains conducted.			
AC Power Line Conducted Emissions	Test Environment	NTNV			
EIIIISSIOIIS	EUT Configuration	TM1_ Ch19 (Worst Conf.).			

Note: For Radiated Emissions, By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.


3.7 Equipments Used during the Test

• •	•				
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2015/06/02	2016/06/01
LISN	R&S	ESH2-Z5	860014/010	2015/06/02	2016/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	N9020A	MY49100067	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Temperature/ Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19
High-Pass Filter	K&L	9SH10- 2700/X12750-O/O	N/A	2015/05/20	2016/05/19
High-Pass Filter	K&L	41H10- 1375/U12750-O/O	N/A	2015/05/20	2016/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	2015/06/02	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	2016/06/01
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2015/06/02	2016/06/01
RF Cable	Megalon	RF-A303	N/A	2015/06/02	2016/06/01
Power Sensor	R&S	NRP-Z4	823.3618.03	2015.06.02	2016.06.01
Power Meter	R&S	NRVS	1020.1809.02	2015.06.02	2016.06.01

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2. Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4. The EUT received DC5V power from the adapter, the adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5. All support equipments received AC power from a second LISN, if any.
- 6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

Eroguanav	Maximum RF Line Voltage (dBμV)						
Frequency (MHz)	CLA	SS A	CLASS B				
	Q.P.	Ave.	Q.P.	Ave.			
0.15 - 0.50	79	66	66-56*	56-46*			
0.50 - 5.00	73	60	56	46			
5.00 - 30.0	73	60	60	50			


^{*} Decreasing linearly with the logarithm of the frequency

TEST RESULTS

The AC Power Conducted Emission measurement is performed at both TX and RX (Idle) mode, recorded worst case at TX mode..

L:

SCAN TABLE: "Voltage (9K-30M)FIN" Short Description: 150K-30M Voltage




MEASUREMENT RESULT: "CTL160121205_fin"

1/21/2016 8:	56PM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dΒμV	dB			
	-						
0.174000	40.40	12.3	65	24.4	QP	L1	GND
0.406000	32.10	10.6	58	25.6	QP	L1	GND
8.610000	32.90	10.7	60	27.1	QP	L1	GND
9.362000	32.00	10.7	60	28.0	QP	L1	GND
10.394000	32.70	10.7	60	27.3	QP	L1	GND
24.242000	22.90	11.1	60	37.1	QP	L1	GND

MEASUREMENT RESULT: "CTL160121205_fin2"

1/21/2016 8 Frequency MHz	Level	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.406000	31.00	10.6	48	16.7	AV	L1	GND
0.462000	31.30	10.4	47	15.4	AV	L1	GND
0.522000	29.30	10.3	46	16.7	AV	L1	GND
0.634000	28.30	10.4	46	17.7	AV	L1	GND
1.386000	27.60	10.5	46	18.4	AV	L1	GND
23.866000	34.30	11.1	50	15.7	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M)FIN" Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "CTL160121204 fin"

1/21/2016 8:	:53PM						
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.174000	40.90	12.3	65	23.9	QP	N	GND
0.406000	32.90	10.6	58	24.8	QP	N	GND
0.462000	31.20	10.4	57	25.5	QP	N	GND
9.430000	31.60	10.7	60	28.4	QP	N	GND
26.682000	26.30	11.2	60	33.7	QΡ	N	GND
27.898000	23.80	11.2	60	36.2	QP	N	GND

MEASUREMENT RESULT: "CTL160121204 fin2"


1/21/2016 8:	53PM						
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dΒμV	dB	dΒμV	dB			
0.406000	30.70	10.6	48	17.0	AV	N	GND
0.462000	29.60	10.4	47	17.1	AV	N	GND
0.522000	28.30	10.3	46	17.7	AV	N	GND
0.634000	27.50	10.4	46	18.5	AV	N	GND
2.370000	27.50	10.5	46	18.5	AV	N	GND
23.866000	33.00	11.1	50	17.0	AV	N	GND

Page 14 of 35 Report No.: MWR160118104


4.2 Radiated Emissions and Band Edge

TEST CONFIGURATION


Frequency range 9 KHz - 30MHz



Frequency range 30MHz - 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

- 1. The EUT was placed on a turn table which is 0.8m above ground plane for below 1GHz and 1.50m above ground plane for above 1GHz.
- 2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0℃ to 360℃ to acquire the highest emissions from EUT.
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measurements have been completed.
- 5. The EUT minimum operation frequency was 32.768 KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9 KHz to 25GHz.
- 6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3

18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector	
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP	
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP	
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP	
	Peak Value: RBW=1MHz/VBW=3MHz,	Peak	
1GHz-40GHz	Sweep time=Auto	reak	
13112-403112	Average Value: RBW=1MHz/VBW=10Hz,	Peak	
	Sweep time=Auto	reak	

More procudre as follows;

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Premeasurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna height is 1.0 meter.
- --- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- --- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- --- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QP detector.
- --- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Premeasurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height changes from 1 to 4 meter.
- --- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter.
- --- The final measurement will be done with QP detector with an EMI receiver.

Page 16 of 35 Report No.: MWR160118104

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 3 meter.
- --- The EUT was set into operation.

Premeasurement:

- --- The turntable rotates from 0° to 315° using 45° steps.
- --- The antenna is polarized vertical and horizontal.
- --- The antenna height scan range is 1 meter to 2.5 meter.
- --- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- --- The final measurement will be performed with minimum the six highest peaks.
- --- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position (± 45°) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- --- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- --- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- --- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- --- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- --- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- --- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- --- The measurement distance is 1 meter.
- --- The EUT was set into operation.

Premeasurement:

--- The antenna is moved spherical over the EUT in different polarizations of the antenna. Final measurement:

- --- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- --- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Report No.: MWR160118104

For example

Frequency	FS	RA	AF	CL	AG	Transd
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dB)	(dB)
300.00	40	58.1	12.2	1.6	31.90	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	300	20log(2400/F(KHz))+80	2400/F(KHz)
0.49-1.705	30	20log(24000/F(KHz))+40	24000/F(KHz)
1.705-30	30	20log(30)+40	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

- 1. The radiated measurement are performed the each channel (low/mid/high), the datum recorded below (the middle channel) is the worst case for all test channels.
- 2. ULTRA-BROADBAND ANTENNA for the radiation emission test below 1G.
- 3. HORN ANTENNA for the radiation emission test above 1G.
- 4. We tested both battery powered and powered by adapter charging mode at three orientations, recorded worst case at powered by adapter charging mode.
- 5. "---" means not recorded as emission levels lower than limit.
- 6. Margin= Limit Level

For 9KHz to 30MHz

Frequency (MHz)	Corrected Reading (dBµV/m)@3m	FCC Limit (dBµV/m) @3m	Margin (dB)	Detector	Result
12.74	46.25	69.54	23.29	QP	PASS
22.66	48.69	69.54	20.85	QP	PASS

For 30MHz to 1000MHz



For 1GHz to 25GHz

	Frequency	(MHz):		240	12		Polarity:		HORIZONTAL		
No.	Frequency (MHz)	Emissi Leve (dBuV/	l	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)	
1	2402.00	81.54	PK			48.14	28.78	4.61	0.00	33.40	
1	2402.00	73.25	ΑV			39.85	28.78	4.61	0.00	33.40	
2	2390.00	36.98	PK	74	37.02	3.66	28.72	4.60	0.00	33.32	
2	2390.00		ΑV	54							
3	2400.00	38.41	PK	74	35.59	5.02	28.78	4.61	0.00	33.39	
3	2400.00		ΑV	54							
4	4804.00	47.22	PK	74	26.78	42.71	33.49	6.91	35.89	4.51	
4	4804.00		ΑV	54							
5	5025.75	44.35	PK	74	29.65	37.47	34.07	7.05	34.24	6.88	
5	5025.75	ı	ΑV	54							
6	7206.00	45.98	PK	74	28.02	34.87	36.95	9.18	35.03	11.11	
6	7206.00	1	ΑV	54							

	Frequency(MHz):		240)2	Polarity:			VERTICAL	
No.	Frequency (MHz)	Emissi Leve (dBuV/	l	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	81.98	PK			48.58	28.78	4.61	0.00	33.40
1	2402.00	73.74	ΑV			40.34	28.78	4.61	0.00	33.40
2	2390.00	37.00	PK	74	37.00	3.68	28.72	4.60	0.00	33.32
2	2390.00		ΑV	54						
3	2400.00	38.96	PK	74	35.04	5.57	28.78	4.61	0.00	33.39
3	2400.00		ΑV	54						
4	4804.00	47.54	PK	74	26.46	43.03	33.49	6.91	35.89	4.51
4	4804.00		ΑV	54						
5	5211.50	44.42	PK	74	29.58	37.03	34.55	7.15	34.31	7.39
5	5211.50		ΑV	54						
6	7206.00	45.40	PK	74	28.6	34.29	36.95	9.18	35.03	11.11
6	7206.00		ΑV	54						

REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)

- Emission level (dBuV/m) = Raw Value (dBuV)+Correction Factor (dB/m)
 Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
 Margin value = Limit value- Emission level.
 -- Mean the PK detector measured value is below average limit.
 The other emission levels were very low against the limit.
 RBW=1MHz VBW=3MHz Peak detector is for PK value; RBW=1MHz VBW=10Hz Peak detector is for AV value.

Report No.: MWR160118104

	Frequency(MHz):		244	10		Polarity:		HORIZONTAL	
No.	Frequency (MHz)	Emissi Leve (dBuV/	l	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	81.32	PK			47.81	28.85	4.65	0.00	33.51
1	2440.00	72.25	ΑV			38.74	28.85	4.65	0.00	33.51
2	4175.50	40.24	PK	74	33.76	35.62	32.82	6.51	34.70	4.62
2	4175.50		ΑV	54						
3	4880.00	48.36	PK	74	25.64	42.11	33.60	6.95	34.30	6.25
3	4880.00		ΑV	54				-		
4	5210.25	45.64	PK	74	28.36	38.05	34.55	7.15	34.11	7.59
4	5210.25		ΑV	54						
5	7320.00	46.25	PK	74	27.75	34.56	37.46	9.23	35.00	11.69
5	7320.00		ΑV	54						

	Frequency	(MHz):		244	10		Polarity:		VERTICAL	
No.	Frequency (MHz)	Emissi Leve (dBuV/	1	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	80.55	PK			47.04	28.85	4.65	0.00	33.51
1	2440.00	72.62	ΑV			39.11	28.85	4.65	0.00	33.51
2	4225.75	40.54	PK	74	33.46	35.85	32.82	6.54	34.67	4.69
2	4225.75		ΑV	54						
3	4880.00	46.59	PK	74	27.41	40.34	33.60	6.95	34.30	6.25
3	4880.00		ΑV	54						
4	5200.50	45.62	PK	74	28.38	38.05	34.54	7.14	34.12	7.57
4	5200.50		ΑV	54						
5	7320.00	45.21	PK	74	28.79	33.52	37.46	9.23	35.00	11.69
5	7320.00		ΑV	54						

REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- 3. Margin value = Limit value- Emission level.
- 4. -- Mean the PK detector measured value is below average limit.
- 5. The other emission levels were very low against the limit.
- 6. RBW=1MHz VBW=3MHz Peak detector is for PK value; RBW=1MHz VBW=10Hz Peak detector is for AV value.

Report No.: MWR160118104

	Frequency((MHz):		248	30	Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emissi Leve (dBuV/		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	80.41	PK			46.79	28.92	4.70	0.00	33.62
1	2480.00	72.69	ΑV			39.07	28.92	4.70	0.00	33.62
2	2483.50	38.55	PK	74	35.45	4.92	28.93	4.70	0.00	33.63
2	2483.50		ΑV	54						
3	2500.00	36.52	PK	74	37.48	2.84	28.96	4.72	0.00	33.68
3	2500.00		ΑV	54						
4	4960.00	48.70	PK	74	25.3	43.78	33.84	7.00	35.92	4.92
4	4960.00		ΑV	54						
5	5125.50	43.36	PK	74	30.64	36.15	34.38	7.10	34.28	7.21
5	5125.50		ΑV	54						
6	7440.00	42.30	PK	74	31.7	30.35	37.64	9.28	34.97	11.95
6	7440.00		ΑV	54						


	Frequency	(MHz):		248	30	l	Polarity:		VERTIO	CAL
No.	Frequency (MHz)	Emissi Leve (dBuV/	l	Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	80.58	PK			46.96	28.92	4.70	0.00	33.62
1	2480.00	72.63	ΑV			39.01	28.92	4.70	0.00	33.62
2	2483.50	38.74	PK	74	35.26	5.11	28.93	4.70	0.00	33.63
2	2483.50		ΑV	54						
3	2500.00	35.25	PK	74	38.75	1.57	28.96	4.72	0.00	33.68
3	2500.00	1	ΑV	54	1	-				
4	4960.00	48.44	PK	74	25.56	43.52	33.84	7.00	35.92	4.92
4	4960.00		ΑV	54						
5	5315.50	43.26	PK	74	30.74	35.74	34.66	7.21	34.34	7.52
5	5315.50		ΑV	54						
6	7440.00	42.44	PK	74	31.56	30.49	37.64	9.28	34.97	11.95
6	7440.00	1	ΑV	54						

REMARKS:

- 1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
- 2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
- Margin value = Limit value- Emission level.
 -- Mean the PK detector measured value is below average limit.
 The other emission levels were very low against the limit.
- 6. RBW=1MHz VBW=3MHz Peak detector is for PK value; RBW=1MHz VBW=10Hz Peak detector is for AV value.

4.3 Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Mea Guidance v03r02 9.1.2 PKPM1 Peak power meter method "The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector."

<u>LIMIT</u>

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS

A. Test Verdict

Channel	Frequency (MHz)	Measured Output Peak Power (dBm)	Limits (dBm)	Verdict
00	2402	-3.25	30	PASS
19	2440	-2.78	30	PASS
39	2480	-3.26	30	PASS

Note:

1. The test results including the cable lose.

4.4 Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 V03 Method PKPSD (peak PSD) this procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4. Set the VBW \geq 3 RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS

A. Test Verdict

Channel	Frequency (MHz)	Report PSD (dBm/100kHz)	Refer to Plot	Limits (dBm/3KHz)	Verdict
00	2402	-3.874	Plot 4.4.1 A	8	PASS
19	2440	-3.504	Plot 4.4.1 B	8	PASS
39	2480	-3.948	Plot 4.4.1 C	8	PASS

Note

- 1. The test results including the cable lose.
- B. Test Plots



(Plot 4.4.1 A: Channel 00: 2402 MHz @ GFSK)



(Plot 4.4.1 B: Channel 19: 2440 MHz @ GFSK)



(Plot 4.4.1 C: Channel 39: 2480 MHz @ GFSK

#VBW 300 kHz

Span 1.042 MHz Sweep 1.000 ms (1001 pts)

STATUS RF Alignment Failure

Center 2.4800000 GHz #Res BW 100 kHz

1 of 2

4.5 Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-20139 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100 kHz and VBW= 300 KHz to measure the peak field strength, and measure frequency range from 9 KHz to 26.5GHz.

LIMIT

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST RESULTS

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

TEST RESULTS

Remark: The measurement frequency range is from 9 KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

A. Test Verdict

Channel	Frequency (MHz)	Frequency Range	Refer to Plot	Limit (dBc)	Verdict
00	2402	30MHz-3 GHz	Plot 4.5.1 A1	-20	PASS
00		3GHz-25GHz	Plot 4.5.1 A2	-20	PASS
19	2440	30MHz-3 GHz	Plot 4.5.1 B1	-20	PASS
		3GHz-25GHz	Plot 4.5.1 B2	-20	PASS
39	2480	30MHz-3 GHz	Plot 4.5.1 C1	-20	PASS
		3GHz-25GHz	Plot 4.5.1 C2	-20	PASS

Conducted	Left Band edge	Plot 4.5.1 D1	-20	PASS
bandedge	Right Band edge	Plot 4.5.1 D2	-20	PASS

Note.

- 1. The test results including the cable lose.
- 2. For 9KHz -30MHz, Because there was only background, So We did not recorded data.
- B. Test Plots



(Plot 4.5.1 A1: Channel 00: 2402MHz @ GFSK)




(Plot 4.5.1 A2: Channel 00: 2402MHz @ GFSK)



(Plot 4.5.1 B1: Channel 19: 2440MHz @ GFSK)



(Plot 4.5.1 B2: Channel 19: 2440MHz @ GFSK)



(Plot 4.5.1 C1: Channel 39: 2480MHz @ GFSK)




(Plot 4.5.1 C2: Channel 39: 2480MHz @ GFSK)

<mark>Љ<mark>ѕтат∪ѕ</mark> **⊗**RF Alignment Failure</mark>

1 of 2


(Plot 4.5.1 D1: Left Band edge @ GFSK)



(Plot 4.5.1 D2: Right Band edge @ GFSK)

4.6 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW =100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 V03 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) ≥ 3 RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

LIMIT

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST RESULTS

A. Test Verdict

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Refer to Plot	Limits (kHz)	Verdict
00	2402	0.6820	Plot 4.6.1 A	≥500	PASS
19	2440	0.6932	Plot 4.6.1 B	≥500	PASS
39	2480	0.6949	Plot 4.6.1 C	≥500	PASS

Note

- 1. The test results including the cable lose.
- B. Test Plots



(Plot 4.6.1 A: Channel 00: 2402MHz @ GFSK)



(Plot 4.6.1 B: Channel 19: 2440MHz @ GFSK)



(Plot 4.6.1 C: Channel 39: 2480MHz @ GFSK)

4.7 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refer ANSI C63.10 :2013 Output power test procedure for DTS devices Radiated power refer to ANSI C63.10 :2013 Radiated emissions tests.

Measurement parameters

Measurement parameter		
Detector:	Peak	
Sweep time:	Auto	
Resolution bandwidth:	1MHz	
Video bandwidth:	3MHz	
Trace-Mode:	Max hold	

Limits

FCC	IC		
Antenna Gain			
6 dBi			

Results

T _{nom}	V _{nom}	Lowest Channel 2402 MHz	Middle Channel 2440 MHz	Highest Channel 2480 MHz
	oower [dBm] GFSK modulation	-3.28	-2.71	-3.32
Radiated power [dBm] Measured with GFSK modulation		-4.12	-3.11	-3.66
Gain [dBi] Calculated		-0.84	-0.40	-0.34
Measuremer	nt uncertainty	± 0.6 dB (cond.) / ± 2.56 dB (rad.)		

5 Test Setup Photos of the EUT

Please refer to separated files for Test Setup Photos of the EUT.

6 External Photos of the EUT

Please refer to separated files for External Photos of the EUT.

7 Internal Photos of the EUT

End of Report	
Please refer to separated files for Internal Photos of the EUT.	