

**Produkte** Products

Prüfbericht - Nr.:

14045200 001

Seite 1 von 18 Page 1 of 18

Test Report No.:

Auftraggeber:

Sensibo LTD.

Client:

3 Ahuzat Bait, Tel Aviv

Israel, 6514302

Gegenstand der Prüfung:

Test Item:

WIFI module for air conditioner

Bezeichnung:

Identification:

SEN-CINS-01

Serien-Nr.: Serial No.:

**Engineering sample** 

Wareneingangs-Nr.:

A000410287 (002-004)

Eingangsdatum:

16.08.2016

Receipt No.:

Date of Receipt:

Prüfort:

TÜV Rheinland Hong Kong Ltd.

Testing Location:

8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

**Hong Kong Productivity Council** 

HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Zustand des Prüfgegenstandes bei Anlieferung:

Condition of test item at delivery:

Test samples are not damaged and suitable for

testing.

Prüfgrundlage:

Test Specification:

FCC Part 15 Subpart B

FCC Part 15 Subpart C ANSI C63.4-2014 ANSI C63.10-2013

Prüfergebnis:

Test Results:

Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben

genannter Prüfgrundlage.

The above mentioned product was tested and **passed**.

Prüflaboratorium:

**TÜV Rheinland Hong Kong Ltd.** 

Testing Laboratory:

8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay,

Kowloon, Hong Kong

geprüft/ tested by:

kontrolliert/ reviewed by:

Joey Leung

Name/Position

=

Project Manager Name/Stellung

Unterschrift Signature

14.10.2016 Datum

Date

Sharon Li

Name/Position

Department Manager Name/Stellung

Unterschrift Signature

Sonstiges:

14.10.2016

Datum

Date

FCC ID: 2AHCD-INS-V01

Other Aspects

P(ass) Abkürzungen:

N/T

entspricht Prüfgrundlage

entspricht nicht Prüfgrundlage

Abbreviations:

P(ass) passed


failed F(ail) not applicable N/A not tested

F(ail) N/A nicht anwendbar

nicht getestet

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.




# **Table of Content**

	P	age
Cover Page		1
Table of Content		2
Product information		4
Manufacturers declarations		4
Product function and intended use		4
Submitted documents		4
Independent Operation Modes		4
Related Submittal(s) Grants		4
Remark		4
Test Set-up and Operation Mode		5
Principle of Configuration Selection		5
Test Operation and Test Software		5
Special Accessories and Auxiliary Equipment		5
Countermeasures to achieve EMC Compliance		5
Test Methodology		6
Radiated Emission		6
Field Strength Calculation		
Test Setup Diagram		7
List of Test and Measurement Instruments		9
Measurement Uncertainty		.10
Results FCC Part 15 – Subpart B		.11
FCC 15.107 – Conducted Emission on AC Mains N/A		11
FCC 15.109 – Radiated EmissionsPass		11
Results FCC Part 15 – Subpart C		.12
FCC 15.203 – Antenna Requirement 1Pass		
FCC 15.204 – Antenna Requirement 2 N/A		. 12
FCC 15.207 – Conducted Emission on AC Mains N/A		. 12
FCC 15.247 (a)(2) – 6dB Bandwidth Measurement		12
FCC 15.247(b)(3) – Maximum Conducted (Average) Output PowerPass		13
FCC 15.247(e) – Power Spectral DensityPass		14

Date: 14.10.2016





FCC 15.247(d) – Spurious Conducted Emissions	Pass 15
FCC 15.205 – Radiated Emissions in Restricted Frequency Bands	Pass 16
Appendix 1 – Test protocols	38 pages
Appendix 2 – Test setup	4 pages
Appendix 3 – EUT External Photos	4 pages
Appendix 4 – EUT Internal Photos	3 pages
Annendix 5 – RF exposure information	2 nages

Date: 14.10.2016



## **Product information**

#### **Manufacturers declarations**

	Transceiver
Operating frequency range	2412 - 2462 MHz
Type of modulation	802.11b: DSSS (DBPSK/DQPSK/CCK)
	802.11n: OFDM (BPSK/QPSK/16QAM/64QAM)
Number of channels	11
Channel separation	5 MHz
Type of antenna	PCB Antenna
Antenna gain (dBi)	3 dBi
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V <sub>nor</sub> : 5 VDC
Independent Operation Modes	Transmitting

## Product function and intended use

The Equipment Under Test (EUT) is a WIFI module which is powered by 5VDC from air conditioner. It supports IEEE 802.11 b/g/n (2.4GHz) wireless communication function.

### FCC ID: 2AHCD-INS-V01

Models	Product description
SEN-CINS-01	WIFI module for air conditioner

#### **Submitted documents**

Circuit Diagram Block Diagram Bill of material User manual Label

## **Independent Operation Modes**

The basic operation mode is transmitting mode. For further information refer to User Manual

## Related Submittal(s) Grants

This is a single application for certification of the transmitter.

### Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Report No.: 14045200 001 Date: 14.10.2016 Page 4 of 18



# **Test Set-up and Operation Mode**

# **Principle of Configuration Selection**

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation

level. The test modes were adapted accordingly in reference to the instructions for use.

### **Test Operation and Test Software**

Test operation should refer to test methodology.

For Part 15B

Client provides a test software and connection board to simulate the data transfer scenario. A
 Faraday's bag was also provide by client to eliminate the emission from the connection board during
 testing.

#### For part 15C

- Client provides a test mode sample which programmed with the maximum RF output power and worst case data-rate setting. The test mode sample also programmed to change the modulation and transmitting channel by pressing a button on the EUT. The setting of the RF output power expected by the customer shall be fixed on the firmware of the final end product.
- Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.

### **Special Accessories and Auxiliary Equipment**

The following adaptor provided by client was used as power supply for the EUT.

- Brand: Belline - Model: #390211

Input: 100-240VAC, 0..25AOutput: 5.0VDC, 1500mA

## Countermeasures to achieve EMC Compliance

- none

Test Report No.: 14045200 001 Date: 14.10.2016 Page 5 of 18



# **Test Methodology**

#### **Radiated Emission**

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013. The radiated emission measurements of the data transfer part were performed according to the procedures in ANSI C63.4-2014.

For measurement below 1GHz, the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz, the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

## **Field Strength Calculation**

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.


FA and PA are only be used for the measuring frequency above 1 GHz.

Test Report No.: 14045200 001 Date: 14.10.2016 Page 6 of 18




# **Test Setup Diagram**

**Diagram of Measurement Configuration for Radiation Test** 



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.


Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)




Test Report No.: 14045200 001 Date: 14.10.2016 Page 7 of 18



# Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)



Test Report No.: 14045200 001 Date: 14.10.2016 Page 8 of 18



# **List of Test and Measurement Instruments**

Hong Kong Productivity Council (Registration number: 90656)

### **Radiated Emission**


Equipment	Manufacturer	Туре	S/N	Cal. Date	Due Date
Semi-anechoic Chamber	Frankonia	Nil	Nil	25 Apr 2016	25 Apr 2017
Cable	Hubersuhner	SUCOFLEX 104	72799 /6	31 Mar 2016	31 Mar 2018
Test Receiver	R&S	ESU26	100190	07 Dec 2015	07 Dec 2016
Bi-conical Antenna	R&S	HK116	100241	01 Sep 2015	01 Sep 2017
Log Periodic Antenna	R&S	HL223	841516/017	01 Sep 2015	01 Sep 2017
Coaxial cable	Harbour	LL335	N/A	10 Jun 2016	10 Jun 2018
Microwave amplifer 0.5- 26.5GHz, 25dB gain	НР	83017A	3950M00241	18 Jul 2016	18 Jul 2018
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28 Oct 2015	28 Oct 2017
Horn Antenna	EMCO	3115	9002-3347	26 Aug 2015	26 Aug 2017
Active Loop Antenna	EMCO	6502	9107-2651	15 Aug 2015	15 Nov 2016

# **TÜV Rheinland Hong Kong Ltd**

### **Radio Test**

Equipment	Manufacturer	Туре	S/N	Cal. Date	Due Date
Spectrum Analyzer	R&S	FSP30	100610	19 Jan 2016	19 Jan 2017

Test Report No.: 14045200 001 Date: 14.10.2016 Page 9 of 18



# **Measurement Uncertainty**

The estimated combined standard uncertainty for power-line conducted emissions measurements is  $\pm 3.43$ dB.

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 5.10$ dB (30MHz to 200MHz) and  $\pm 5.08$ dB (200MHz to 1000MHz) and is  $\pm 5.10$ dB (30MHz to 200MHz) and  $\pm 5.08$ dB (above 1GHz).

The estimated combined standard uncertainty for antenna conducted emission is ±1.56dB

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for the level of confidence is approximately 95%.

Test Report No.: 14045200 001 Date: 14.10.2016 Page 10 of 18



# Results FCC Part 15 – Subpart B

### FCC 15.107 - Conducted Emission on AC Mains

N/A

There is no AC power input or output ports on the EUT.

#### FCC 15.109 - Radiated Emissions

**Pass** 

Test Specification: ANSI C63.4-2014 Mode of operation: Data transfer mode

Port of testing : Enclosure Detector : Quasi-Peak

RBW/VBW : 120 kHz for f < 1 GHz
Supply voltage : 5VDC by external power supply

Frequency range : 30MHz - 1GHz

Temperature : 23°C : 50% Humidity

Requirement: The field strength of radiated emissions from unintentional radiators at a distance of 3

meters shall not exceed the radiated limits shown in §15.109(a).

Results: **Pass** 

'	Vei	rtical	Po	lar	iza	tioı	n

Freq	Level	Limit
MHz	dBuV/m	dBuV/m
No peak found		40.0
	Horizontal Polarization	

#### Horizontal Polarization

Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
95.952	40.4	43.5
399.809	39.0	46.0

Test Report No.: 14045200 001 Date: 14.10.2016 Page 11 of 18



# Results FCC Part 15 - Subpart C

FCC 15.203 - Antenna Requirement 1

**Pass** 

FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the

device

Results: a) Antenna type: Integral PCB antenna

b) Manufacturer and model no: N/A
c) Peak Gain: N/A
3 dBi

Verdict: Pass

FCC 15.204 - Antenna Requirement 2

N/A

FCC Requirement: An intentional radiator may be operated only with the antenna with which it is

authorized. If an antenna is marketed with the intentional radiator, it shall be of a type

which is authorized with the intentional radiator.

**Results:** Only one integral antenna can be used.

Verdict: N/A

FCC 15.207 - Conducted Emission on AC Mains

N/A

There is no AC power input or output ports on the EUT.

FCC 15.247 (a)(2) – 6dB Bandwidth Measurement

**Pass** 

FCC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz,

2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall

be at least 500kHz.

Test Specification: KDB 558074 D01 v03r05 (Clause 8.1)

Port of testing : Temporary antenna port

Mode of operation: TX mode Detector: Peak

RBW/VBW : 100KHz/ 300KHz

Supply voltage : 5VDC by external power supply

Temperature : 23°C Humidity : 50%

**Results:** For test protocols please refer to Appendix 1

#### 802.11B

Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (MHz)
2412	2406.850	2416.850	10.00
2437	2431.850	2441.850	10.00
2462	2456.850	2466.850	10.00

Test Report No.: 14045200 001 Date: 14.10.2016 Page 12 of 18



802.11G			
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (MHz)
2412	2404.350	2419.550	15.20
2437	2429.350	2444.550	15.20
2462	2454.350	2469.550	15.20
802.11N			
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (kHz)
2412	2404.350	2419.550	15.20
2437	2429.300	2444.550	15.25
2462	2454.350	2469.550	15.20

FCC 13.247(D)(3)	C 15.247(b)(3) – Maximum Conducted (Average) Output Power	Pass
------------------	---	------

FCC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-

5850MHz bands: 1 Watt (30dBm)

Test Specification: KDB 558074 D01 v03r05 (Clause 9.2.2.6)

Port of testing : Temporary antenna port

Mode of operation: TX mode Detector: RMS

Supply voltage : 5VDC by external power supply

Duty Cycle : 56% - 69%

Temperature : 23°C Humidity : 50%

**Results:** For test protocols please refer to Appendix 1

### 802.11B

Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict
2412	11.63	1 / 30.0	Pass
2437	12.94	1 / 30.0	Pass
2462	13.32	1 / 30.0	Pass

### 802.11G

Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict
2412	10.95	1 / 30.0	Pass
2437	13.70	1 / 30.0	Pass
2462	12.27	1 / 30.0	Pass

### 802.11N

Frequency (MHz)	Measured Output Power (dBm)	Limit (W/dBm)	Verdict
2412	9.90	1 / 30.0	Pass
2437	12.74	1 / 30.0	Pass
2462	11.28	1 / 30.0	Pass

Test Report No.: 14045200 001 Date: 14.10.2016 Page 13 of 18



### FCC 15.247(e) - Power Spectral Density

**Pass** 

**FCC Requirement:** For digitally modulated systems, the power spectral density conducted from the

intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band

during any time interval of continuous transmission.

Test Specification: KDB 558074 D01 v03r05 (Clause 10.7)

Port of testing : Temporary antenna port

Mode of operation: TX mode Detector: RMS

RBW/VBW : 100 KHz / ≥3xRBW

Span : ≥1.5 x OBW

Supply voltage : 5VDC by external power supply

Temperature : 23°C Humidity : 50%

**Results:** For test protocols please refer to Appendix 1.

#### 802.11B

Operating Frequency (MHz)	Measured Power Density (dBm)	Limit (dBm)	Verdict
2412	-2.13	8.0	Pass
2437	-0.82	8.0	Pass
2462	-0.53	8.0	Pass

## 802.11G

Operating Frequency (MHz)	Measured Power Density (dBm)	Limit (dBm)	Verdict
2412	-3.67	8.0	Pass
2437	-0.82	8.0	Pass
2462	-2.29	8.0	Pass

# 802.11N

Operating Frequency (MHz)	Measured Power Density (dBm)	Limit (dBm)	Verdict
2412	-5.62	8.0	Pass
2437	-3.24	8.0	Pass
2462	-3.97	8.0	Pass

Test Report No.: 14045200 001 Date: 14.10.2016 Page 14 of 18



### FCC 15.247(d) - Spurious Conducted Emissions

**Pass** 

Test Specification: KDB 558074 D01 v03r05 (Clause 11.0)

Mode of operation: TX mode

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : 100 kHz / 300 kHz

Supply voltage : 5VDC by external power supply

Temperature : 23 °C Humidity : 50 %

FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or

digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based

on either an RF conducted or a radiated measurement.

**Results:** Pre-scan has been conducted to determine the worst-case mode from all possible

combinations between available modulations and data rate.

Only the worst cases is shown below. For test protocols refer to Appendix 1

#### 802.11B

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2412	2396.400	-42.51	-1.78	40.73	Pass
2437	9280.000	-49.06	-0.41	48.65	Pass
2462	2487.500	-48.60	-0.01	48.59	Pass

## 802.11G

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2412	2400.000	-35.95	-3.67	32.28	Pass
2437	7440.000	-49.74	-0.64	49.10	Pass
2462	2484.300	-46.16	-2.13	44.03	Pass

#### 802.11N

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2412	2400.000	-35.48	-3.87	31.61	Pass
2437	9260.000	-49.92	-0.76	49.16	Pass
2462	2483.600	-45.90	-2.14	43.76	Pass

Test Report No.: 14045200 001 Date: 14.10.2016 Page 15 of 18



Limit/ Detector

dBuV/m

74.0 / P

54.0 / A

FCC 15.205 - Radia	ated Emissions	in Restricted Frequency Bands	Pass
Detector : RBW/VBW : Supply voltage : Temperature :	TX mode Enclosure Peak 100 kHz / 300 1 MHz / 3 MHz 5VDC by exter 23°C	kHz for f < 1 GHz	
Humidity :	50%		
FCC Requirement:	level of the des bands, as defin	bandwidth outside the frequency ba sired power. In addition, radiated em ned in section15.205(a), must also co in section 15.205(c).	issions which fall in the restricted
Results:	combinations by All three transm	peen conducted to determine the wo between available modulations and c mit frequency modes comply with the s no spurious found below 30MHz.	lata rate.
Mode: 802.11B 2412	2MHz TX	Vertical Polarization	
Freq MHz		Level dBuV/m	Limit/ Detector dBuV/m
4019.55	51	63.11	74.0 / P
4020.67	73	43.76	54.0 / A
2389.87		48.97	74.0 / P
2333.20	)5	33.98	54.0 / A
Mode: 802.11B 2412	2MHz TX	Horizontal Polarization	
Freq MHz		Level dBuV/m	Limit/ Detector dBuV/m
4020.27		57.04	74.0 / P
4020.83		40.93	54.0 / A
2379.10		53.03	74.0 / P
2333.20	)5	35.56	54.0 / A
Mode: 802.11B 2437	7 MHz TX	Vertical Polarization	
Freq MHz		Level dBuV/m	Limit/ Detector dBuV/m
4063.14		62.76	74.0 / P
4060.73	37	43.53	54.0 / A
Mode: 802.11B 243	7 MHz TX	Horizontal Polarization	
_			

Test Report No.: 14045200 001 Date: 14.10.2016 Page 16 of 18

Level

dBuV/m

56.33

40.39

Freq MHz

4060.497

4062.179



Mode: 802.11B 2462MHz TX	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4104.920	59.91	74.0 / P
4104.119	42.30	54.0 / A
2487.731	47.85	74.0 / P
2487.863	32.18	54.0 / A
Mode: 802.11B 2462 MHz TX	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4101.795	56.12	74.0 / P
4102.436	40.22	54.0 / A
2485.351	51.53	74.0 / P
2486.990	35.37	54.0 / A
Mode: 802.11G 2412MHz TX	Vertical Polarization	0.10774
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4021.074	62.38	74.0 / P
4021.234	41.14	54.0 / A
2390.000	53.61	74.0 / P
2390.000	34.53	54.0 / A
		J 34.0 / A
Mode: 802.11G 2412MHz TX	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4019.391	55.06	74.0 / P
4018.109	39.13	54.0 / A
2390.000	60.17	74.0 / P
2390.000	39.67	54.0 / A
Mode: 802.11G 2437 MHz TX	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4058.974	61.54	74.0 / P
4030.374		/4.U / F
4060.176	40.87	54.0 / A
4060.176 Mode: 802.11G 2437 MHz TX	40.87 Horizontal Polarization	54.0 / A
4060.176 Mode: 802.11G 2437 MHz TX <b>Freq</b>	40.87 Horizontal Polarization Level	54.0 / A  Limit/ Detector
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz	40.87 Horizontal Polarization Level dBuV/m	54.0 / A  Limit/ Detector dBuV/m
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz 4065.785	40.87 Horizontal Polarization Level dBuV/m 55.59	Limit/ Detector dBuV/m 74.0 / P
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz	40.87 Horizontal Polarization Level dBuV/m	54.0 / A  Limit/ Detector dBuV/m
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz  4065.785 4060.096  Mode: 802.11G 2462MHz TX	40.87  Horizontal Polarization  Level dBuV/m  55.59 39.40  Vertical Polarization	54.0 / A  Limit/ Detector dBuV/m 74.0 / P 54.0 / A
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz  4065.785 4060.096  Mode: 802.11G 2462MHz TX  Freq	40.87  Horizontal Polarization  Level dBuV/m 55.59 39.40  Vertical Polarization  Level	Limit/ Detector dBuV/m 74.0 / P 54.0 / A
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz  4065.785 4060.096  Mode: 802.11G 2462MHz TX  Freq MHz	40.87 Horizontal Polarization  Level dBuV/m 55.59 39.40  Vertical Polarization  Level dBuV/m	Limit/ Detector dBuV/m 74.0 / P 54.0 / A  Limit/ Detector dBuV/m
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz  4065.785 4060.096  Mode: 802.11G 2462MHz TX  Freq MHz  4104.215	40.87 Horizontal Polarization  Level dBuV/m 55.59 39.40  Vertical Polarization  Level dBuV/m 60.20	54.0 / A  Limit/ Detector dBuV/m 74.0 / P 54.0 / A  Limit/ Detector dBuV/m 74.0 / P
4060.176  Mode: 802.11G 2437 MHz TX  Freq MHz  4065.785 4060.096  Mode: 802.11G 2462MHz TX  Freq MHz	40.87 Horizontal Polarization  Level dBuV/m 55.59 39.40  Vertical Polarization  Level dBuV/m	Limit/ Detector dBuV/m 74.0 / P 54.0 / A  Limit/ Detector dBuV/m

Test Report No.: 14045200 001 Date: 14.10.2016 Page 17 of 18



Eroa	Loval	Limit/ Detector
Freq MHz	Level dBuV/m	dBuV/m
4102.612	55.01	74.0 / P
4101.811	39.05	54.0 / A
2483.500	63.53	74.0 / P
2483.660	39.73	54.0 / A
Mode: 802.11N 2412MHz TX	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4021.362	60.99	74.0 / P
4020.962	40.80	54.0 / A
2390.000	55.77	74.0 / P
2390.000	33.05	54.0 / A
Mode: 802.11N 2412MHz TX	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4021.282	54.35	74.0 / P
4021.042	39.01	54.0 / A
2390.000	57.26	74.0 / P
2390.000	38.93	54.0 / A
Mode: 802.11N 2437 MHz TX	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4063.157	60.34	74.0 / P
4062.837	40.65	54.0 / A
Mode: 802.11N 2437 MHz TX	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4059.471	54.47	74.0 / P
4060.353	39.07	54.0 / A
Mode: 802.11N 2462MHz TX	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBuV/m	dBuV/m
4101.138	60.55	74.0 / P
4104.423	40.45	54.0 / A
2483.500	59.43	74.0 / P
2483.500	35.08	74.0 / P 54.0 / A
2403.300	ან.06	54.U / A
Mada, 000 44N 0400 MIL TV	Horizontal Polarization	
IVIOUE: 8U2. I IIN 2462 IVIHZ I X		Limit/ Detector
Freq	Level	
Freq MHz	Level dBuV/m	dBuV/m
Freq		<b>dBuV/m</b> 74.0 / P
MHz	dBuV/m	L
Freq MHz 4099.696	<b>dBuV/m</b> 53.36	74.0 / P

Test Report No.: 14045200 001 Date: 14.10.2016 Page 18 of 18