

FCC PART 15.247 TEST REPORT

For

AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II, Xiamen, China

FCC ID: 2AHCR-C312X

Report Type: Original Report	Product Type: Indoor Monitor
Test Engineer: Chao Gao <i>Chao Gao</i>	
Report Number: RXM200318050-00B	
Report Date: 2020-05-03	
Reviewed By: Oscar Ye EMC Manager <i>Oscar Ye</i>	
Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliant Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	14
FCC §15.203 – ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
CORRECTED FACTOR & OVER LIMIT CALCULATION.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	26
APPLICABLE STANDARD	26
EUT SETUP	26
EMI TEST RECEIVER SETUP.....	27
TEST PROCEDURE	27
CORRECTED AMPLITUDE & MARGIN CALCULATION	27
TEST RESULTS SUMMARY	27
TEST DATA	28
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	48
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	54

APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST DATA	54
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST DATA	57
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	73
APPLICABLE STANDARD	73
TEST PROCEDURE	73
TEST DATA	73
FCC §15.247(d) - BAND EDGES TESTING	80
APPLICABLE STANDARD	80
TEST PROCEDURE	80
TEST DATA	80

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	AKUVOX (XIAMEN) NETWORKS CO., LTD.
Tested Model:	C312A
Series Model:	C312W
Model Difference:	See Declaration of Similarity
Product Type:	Indoor Monitor
Power Supply:	12V === 1.0A or 48V === 0.25A (Powered by PoE adapter)
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480 MHz
Channel Number:	79
Channel Separation:	1 MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type:	PCB Antenna
Maximum Antenna Gain:	2.0 dBi

**All measurement and test data in this report was gathered from production sample serial number: 20200318050. (Assigned by the BACL. The EUT supplied by the applicant was received on 2020-03-18).*

Objective

This test report is prepared on behalf of *AKUVOX (XIAMEN) NETWORKS CO., LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2AHCR-C312X.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

Function	Test Item	Model	Power Supply Mode	Page
BT	CE	C312A	DC source	P17-P18
			POE	P19-P20
		C312W	DC source	P21-P22
			POE	P23-P24
	RSE(Below 1GHz)	C312A	DC source	P27
			POE	P28
		C312W	DC source	P29
			POE	P30
	RSE(Above 1GHz)	C312A	DC source	P31-P35
	RF Conducted	C312A	DC source	P36-P85

EUT Exercise Software

RF test software: Secure CRT

GFSK, $\pi/4$ -DQPSK, 8DPSK Power setting: Default.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZHAOXIN	DC Power Supply	RXN-605D	DC002
RUCKUS	Adapter	PA1024-4HUB	/
RUCKUS	POE	NPE-5818	136287121
VAKADA	Door bell	B08	N/A
AnYong	Load	RXLG	N/A
Schneider Electric	Relay	RXM2LB2BD	N/A
DELL	Notebook	E6410	3094742521

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.0	DC Source/Adapter	AC Source
RJ45 Cable	1.5	EUT	POE
Power Cable	1.2	POE	POE Adapter
RJ45 cable	5.0	EUT	Notebook
Signal Cable	5.0	EUT	Door bell
Signal Cable	5.0	EUT	Relay
Power supply cable	5.0	EUT	Load

Block Diagram of Test Setup


For Conducted Emissions (Powered by DC Source):




For Radiated Emissions(Below 1GHz):




For Radiated Emissions(Above 1GHz):




For Conducted Emissions (Powered by POE):



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §1.1310 & §2.1091	MAXIMUM PERMISSIBLE EXPOSURE (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Spurious Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2019-05-30	2020-05-29
ETS-LINDGREN	Horn Antenna	3115	6229	2019-01-11	2022-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-10-18	2022-10-17
A.H.Systems, inc	Amplifier	PAM-0118P	512	2019-05-11	2020-05-10
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2019-09-21	2020-09-20
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2019-12-14	2020-12-13
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-07-23	2020-07-22
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
NETWORKS	RF Cable	NETWORKS C01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2019-07-11	2020-07-10
Audix	Test Software	e3	V9	--	--
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2019-08-10	2020-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Tune up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412~2462	2.0	1.58	21.50	141.25	20	0.0444	1.0
802.11g		2.0	1.58	22.50	177.83	20	0.0561	1.0
802.11n-HT20		2.0	1.58	21.50	141.25	20	0.0444	1.0
BLE	2402~2480	2.0	1.58	6.00	3.98	20	0.0013	1.0
BT	2402~2480	2.0	1.58	6.50	4.47	20	0.0014	1.0

Note:

1. The tune up conducted power was declared by the manufacturer.
2. Wi-Fi and BT/BLE can't transmit simultaneously.

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB antenna and the antenna gain is 2.0 dBi; fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the DC Source or adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Over Limit Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.


Test Data

Environmental Conditions

Temperature:	23.2~23.4 °C
Relative Humidity:	49~50%
ATM Pressure:	101.1~101.2kPa


The testing was performed by Chao Gao from 2020-04-10 to 2020-04-15.

EUT operation mode: Transmitting in low channel of GFSK


Model: C312A**Powered by DC Source****AC 120V/60 Hz, Line**

		Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.167	-13.30	19.83	6.53	55.12	-48.59	Average
2	0.167	-0.10	19.83	19.73	65.12	-45.39	QP
3	0.217	-14.50	19.82	5.32	52.92	-47.60	Average
4	0.217	-0.50	19.82	19.32	62.92	-43.60	QP
5	0.325	-9.60	19.82	10.22	49.57	-39.35	Average
6	0.325	-0.90	19.82	18.92	59.57	-40.65	QP
7	0.426	-15.90	19.75	3.85	47.33	-43.48	Average
8	0.426	-3.30	19.75	16.45	57.33	-40.88	QP
9	3.123	-4.20	19.46	15.26	46.00	-30.74	Average
10	3.123	5.70	19.46	25.16	56.00	-30.84	QP
11	6.841	2.80	19.52	22.32	50.00	-27.68	Average
12	6.841	11.00	19.52	30.52	60.00	-29.48	QP

AC 120V/60 Hz, Neutral




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.213	-12.80	19.82	7.02	53.10	-46.08	Average
2	0.213	-0.90	19.82	18.92	63.10	-44.18	QP
3	0.413	-13.80	19.74	5.94	47.59	-41.65	Average
4	0.413	-2.20	19.74	17.54	57.59	-40.05	QP
5	0.647	-15.20	19.75	4.55	46.00	-41.45	Average
6	0.647	-5.60	19.75	14.15	56.00	-41.85	QP
7	2.066	-5.70	19.78	14.08	46.00	-31.92	Average
8	2.066	2.70	19.78	22.48	56.00	-33.52	QP
9	3.074	0.40	19.46	19.86	46.00	-26.14	Average
10	3.074	11.00	19.46	30.46	56.00	-25.54	QP
11	6.805	1.90	19.52	21.42	50.00	-28.58	Average
12	6.805	10.10	19.52	29.62	60.00	-30.38	QP


Powered by POE**AC 120V/60 Hz, Line**

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.154	14.80	19.82	34.62	55.78	-21.16	Average
2	0.154	29.40	19.82	49.22	65.78	-16.56	QP
3	0.274	14.00	19.82	33.82	50.98	-17.16	Average
4	0.274	21.00	19.82	40.82	60.98	-20.16	QP
5	0.492	22.40	19.76	42.16	46.14	-3.98	Average
6	0.492	28.60	19.76	48.36	56.14	-7.78	QP
7	1.276	14.70	19.82	34.52	46.00	-11.48	Average
8	1.276	20.40	19.82	40.22	56.00	-15.78	QP
9	3.860	12.70	19.47	32.17	46.00	-13.83	Average
10	3.860	19.50	19.47	38.97	56.00	-17.03	QP
11	10.790	18.90	19.57	38.47	50.00	-11.53	Average
12	10.790	24.50	19.57	44.07	60.00	-15.93	QP

AC 120V/60 Hz, Neutral




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.152	17.40	19.82	37.22	55.87	-18.65	Average
2	0.152	30.40	19.82	50.22	65.87	-15.65	QP
3	0.206	13.80	19.82	33.62	53.36	-19.74	Average
4	0.206	23.70	19.82	43.52	63.36	-19.84	QP
5	0.497	22.40	19.76	42.16	46.05	-3.89	Average
6	0.497	28.50	19.76	48.26	56.05	-7.79	QP
7	1.242	18.01	19.81	37.82	46.00	-8.18	Average
8	1.242	23.31	19.81	43.12	56.00	-12.88	QP
9	2.066	18.20	19.78	37.98	46.00	-8.02	Average
10	2.066	24.10	19.78	43.88	56.00	-12.12	QP
11	10.564	25.50	19.56	45.06	50.00	-4.94	Average
12	10.564	30.80	19.56	50.36	60.00	-9.64	QP

Model: C312W**Powered by DC Source****AC 120V/60 Hz, Line**


	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.158	-12.50	19.82	7.32	55.56	-48.24	Average
2	0.158	-0.30	19.82	19.52	65.56	-46.04	QP
3	0.299	-14.10	19.83	5.73	50.28	-44.55	Average
4	0.299	-1.20	19.83	18.63	60.28	-41.65	QP
5	0.375	-15.60	19.77	4.17	48.39	-44.22	Average
6	0.375	-2.10	19.77	17.67	58.39	-40.72	QP
7	0.767	-12.60	19.72	7.12	46.00	-38.88	Average
8	0.767	-6.60	19.72	13.12	56.00	-42.88	QP
9	3.074	-3.80	19.46	15.66	46.00	-30.34	Average
10	3.074	6.30	19.46	25.76	56.00	-30.24	QP
11	7.252	2.00	19.52	21.52	50.00	-28.48	Average
12	7.252	9.40	19.52	28.92	60.00	-31.08	QP

AC 120V/60 Hz, Neutral

Date: 2020-04-10




	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.160	-12.70	19.83	7.13	55.47	-48.34 Average
2	0.160	0.20	19.83	20.03	65.47	-45.44 QP
3	0.249	-13.80	19.82	6.02	51.78	-45.76 Average
4	0.249	-0.70	19.82	19.12	61.78	-42.66 QP
5	0.356	-14.50	19.80	5.30	48.83	-43.53 Average
6	0.356	-1.90	19.80	17.90	58.83	-40.93 QP
7	0.727	-14.80	19.74	4.94	46.00	-41.06 Average
8	0.727	-7.00	19.74	12.74	56.00	-43.26 QP
9	3.074	-0.60	19.46	18.86	46.00	-27.14 Average
10	3.074	8.40	19.46	27.86	56.00	-28.14 QP
11	7.137	-0.60	19.52	18.92	50.00	-31.08 Average
12	7.137	8.50	19.52	28.02	60.00	-31.98 QP

Powered by POE**AC 120V/60 Hz, Line**

		Read		Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.167	11.70	19.83	31.53	55.12	-23.59 Average
2	0.167	23.20	19.83	43.03	65.12	-22.09 QP
3	0.502	23.20	19.76	42.96	46.00	-3.04 Average
4	0.502	29.50	19.76	49.26	56.00	-6.74 QP
5	1.242	15.21	19.81	35.02	46.00	-10.98 Average
6	1.242	20.81	19.81	40.62	56.00	-15.38 QP
7	1.970	15.80	19.83	35.63	46.00	-10.37 Average
8	1.970	21.70	19.83	41.53	56.00	-14.47 QP
9	4.315	13.91	19.47	33.38	46.00	-12.62 Average
10	4.315	21.11	19.47	40.58	56.00	-15.42 QP
11	10.019	18.90	19.56	38.46	50.00	-11.54 Average
12	10.019	24.40	19.56	43.96	60.00	-16.04 QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.166	11.40	19.83	31.23	55.16	-23.93	Average
2	0.166	23.80	19.83	43.63	65.16	-21.53	QP
3	0.207	13.10	19.82	32.92	53.32	-20.40	Average
4	0.207	22.80	19.82	42.62	63.32	-20.70	QP
5	0.494	22.30	19.76	42.06	46.10	-4.04	Average
6	0.494	28.40	19.76	48.16	56.10	-7.94	QP
7	1.338	17.81	19.82	37.63	46.00	-8.37	Average
8	1.338	23.41	19.82	43.23	56.00	-12.77	QP
9	2.055	18.20	19.79	37.99	46.00	-8.01	Average
10	2.055	24.20	19.79	43.99	56.00	-12.01	QP
11	10.288	25.60	19.56	45.16	50.00	-4.84	Average
12	10.288	31.20	19.56	50.76	60.00	-9.24	QP



Note:

1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**

Temperature:	23.3~24.6 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.1~101.3 kPa

The testing was performed by Chao Gao from 2020-04-16 to 2020-04-22.

EUT operation mode: Transmitting


Spurious Emission Test:

Model: C312A

Powered by DC Source

30MHz-1GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the **low channel of GFSK Mode in Z-axis of orientation** was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
41.78	22.23	100	V	277	-11.9	40.00	17.77
68.98	24.59	100	V	282	-17.3	40.00	15.41
249.99	25.63	100	V	147	-12.1	46.00	20.37
450.01	38.54	100	H	58	-7.4	46.00	7.46
550.00	41.42	200	H	348	-5.6	46.00	4.58
749.99	39.16	100	V	28	-2.5	46.00	6.84

Powered by POE
30MHz-1GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the low channel of GFSK Mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	Quasi-peak (dB μ V/m)	Height (cm)	Polar (H/V)				
34.68	29.45	100	V	348	-7.1	40.00	10.55
77.20	31.14	100	V	84	-17.6	40.00	8.86
105.01	35.81	100	V	109	-14.0	43.50	7.69
250.02	38.14	100	V	95	-12.1	46.00	7.86
450.01	38.24	200	V	328	-7.4	46.00	7.76
750.02	43.45	200	H	330	-2.5	46.00	2.55

Model: C312W**Powered by DC Source****30MHz-1GHz:**


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the low channel of GFSK Mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
39.24	28.03	100	V	225	-10.2	40.00	11.97
150.02	21.86	200	H	284	-12.3	43.50	21.64
249.98	31.27	100	V	1	-12.1	46.00	14.73
449.98	44.17	100	H	2	-7.4	46.00	1.83
549.99	44.18	200	H	0	-5.6	46.00	1.82
750.00	40.16	100	H	198	-2.5	46.00	5.84

Powered by POE
30MHz-1GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the low channel of GFSK Mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	Quasi-peak (dB μ V/m)	Height (cm)	Polar (H/V)				
34.73	29.65	100	V	12	-7.1	40.00	10.35
77.19	31.49	100	V	48	-17.6	40.00	8.51
104.77	35.33	100	V	114	-14	43.50	8.17
250.01	37.33	100	H	60	-12.1	46.00	8.67
450.00	37.03	100	H	18	-7.4	46.00	8.97
750.02	42.34	100	H	188	-2.5	46.00	3.66

1GHz-18GHz:


*Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the **low channel of GFSK Mode in Z-axis of orientation** was recorded*

Note:

1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1061.20	---	26.09	150	V	0	-18.7	54.00	27.91
1061.20	38.40	---	150	V	0	-18.7	74.00	35.60
1595.00	---	27.71	150	V	286	-16.0	54.00	26.29
1595.00	40.09	---	150	V	286	-16.0	74.00	33.91
2249.50	---	35.54	200	H	179	-13.4	54.00	18.46
2249.50	41.72	---	200	H	179	-13.4	74.00	32.28
3925.70	---	30.91	150	H	97	-7.3	54.00	23.09
3925.70	40.56	---	150	H	97	-7.3	74.00	33.44
11111.60	---	41.26	150	V	303	2.9	54.00	12.74
11111.60	50.08	---	150	V	303	2.9	74.00	23.92
17877.60	---	45.52	200	H	143	8.8	54.00	8.48
17877.60	55.04	---	200	H	143	8.8	74.00	18.96

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1124.10	---	28.30	200	V	359	-18.4	54.00	25.70
1124.10	34.06	---	200	V	359	-18.4	74.00	39.94
1498.10	---	30.15	150	V	328	-16.4	54.00	23.85
1498.10	38.71	---	150	V	328	-16.4	74.00	35.29
2249.50	---	36.79	200	H	186	-13.4	54.00	17.21
2249.50	43.49	---	200	H	186	-13.4	74.00	30.51
5251.70	---	33.67	150	V	18	-4.5	54.00	20.33
5251.70	42.72	---	150	V	18	-4.5	74.00	31.28
13117.60	---	42.29	200	V	210	5.3	54.00	11.71
13117.60	51.40	---	200	V	210	5.3	74.00	22.60
17928.60	---	46.99	150	V	280	8.8	54.00	7.01
17928.60	55.08	---	150	V	280	8.8	74.00	18.92

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1499.80	---	29.76	150	V	295	-16.4	54.00	24.24
1499.80	39.06	---	150	V	295	-16.4	74.00	34.94
2249.50	---	34.22	150	V	231	-13.4	54.00	19.78
2249.50	41.33	---	150	V	231	-13.4	74.00	32.67
3070.60	---	33.07	200	H	190	-9.9	54.00	20.93
3070.60	38.99	---	200	H	190	-9.9	74.00	35.01
4430.60	---	32.51	200	V	295	-6.3	54.00	21.49
4430.60	41.80	---	200	V	295	-6.3	74.00	32.20
8177.40	---	40.55	150	H	155	1.6	54.00	13.45
8177.40	49.80	---	150	H	155	1.6	74.00	24.20
17972.80	---	47.92	200	V	174	8.8	54.00	6.08
17972.80	56.14	---	200	V	174	8.8	74.00	17.86

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the low channel of GFSK Mode in Z-axis of orientation was recorded



Date: 22.APR.2020 10:40:38



Date: 22.APR.2020 10:55:02

Fundamental Test & Restricted Bands Emissions:

*Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case is the **low channel of GFSK Mode in Z-axis of orientation** was recorded*



Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	---	40.17	150.0	H	145.0	-2.9	54.00	13.83
2390.00	47.39	---	150.0	H	145.0	-2.9	74.00	26.61
High Channel: 2480MHz								
2483.50	---	40.95	150.0	H	139.0	-2.5	54.00	13.05
2483.50	47.45	---	150.0	H	139.0	-2.5	74.00	26.55

Conducted Spurious Emissions at Antenna Port**BDR (GFSK): Low Channel****BDR (GFSK): Middle Channel**


BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data

Environmental Conditions

Temperature:	23.3 °C
Relative Humidity:	51 %
ATM Pressure:	101.3 kPa

The testing was performed by Chao Gao on 2020-04-20.


EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.003	0.693	Pass
	Adjacent	2403			
	Middle	2441	0.999	0.693	Pass
	Adjacent	2442			
	High	2480	0.999	0.697	Pass
	Adjacent	2479			
EDR ($\pi/4$ -DQPSK)	Low	2402	1.003	0.906	Pass
	Adjacent	2403			
	Middle	2441	1.003	0.902	Pass
	Adjacent	2442			
	High	2480	0.999	0.906	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	0.999	0.882	Pass
	Adjacent	2403			
	Middle	2441	0.999	0.882	Pass
	Adjacent	2442			
	High	2480	0.999	0.886	Pass
	Adjacent	2479			

For BDR and EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




Date: 20.APR.2020 15:43:49


BDR (GFSK): High Channel




Date: 20.APR.2020 15:45:37

EDR ($\pi/4$ -DQPSK): Low Channel


Date: 20 APR 2020 15:34:15

EDR ($\pi/4$ -DQPSK): Middle Channel

Date: 20 APR 2020 15:41:55


EDR ($\pi/4$ -DQPSK): High Channel

Date: 20 APR 2020 15:47:42


EDR (8DPSK): Low Channel

Date: 20 APR 2020 15:35:30

EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	23.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Chao Gao on 2020-04-16.



EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.040
	Middle	2441	1.040
	High	2480	1.046
EDR ($\pi/4$ -DQPSK)	Low	2402	1.359
	Middle	2441	1.353
	High	2480	1.359
EDR (8DPSK)	Low	2402	1.323
	Middle	2441	1.323
	High	2480	1.329

BDR (GFSK): Low Channel






BDR (GFSK): Middle Channel**BDR (GFSK): High Channel**

EDR ($\pi/4$ -DQPSK): Low Channel



EDR($\pi/4$ -DQPSK): Middle Channel



EDR ($\pi/4$ -DQPSK): High Channel**EDR (8DPSK): Low Channel**

Delta 1 [T1] 0.82 dB RBW 30 kHz RF Att 20 dB
 Ref Lvl 20 dBm 20 dBm 1.32264529 MHz SWT 8.5 ms Unit dBm

11 dB Offset

▼1 [T1] -18.00 dBm
 ▲1 [T1] 0.82 dB
 1.32264529 MHz

1MAX
 D1 2.18 dBm
 D2 -17.82 dBm

Center 2.441 GHz 300 kHz/ Span 3 MHz

Date: 16. APR. 2020 13:33:16

Delta 1 [T1] 0.46 dB
 RBW 30 kHz RF Att 20 dB
 Ref Lvl 20 dBm 1.32865731 MHz
 VBW 100 kHz
 SWT 8.5 ms Unit dBm

11 dB Offset
 -19.94 dBm
 2.47923347 GHz
 0.46 dB
 1.32865731 MHz

D1 0.44 dBm
 D2 -19.56 dBm

1MAX
 1

Center 2.48 GHz 300 kHz/ Span 3 MHz

Date: 16. APR. 2020 13:36:00

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**

Temperature:	23.2 °C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa


The testing was performed by Chao Gao on 2020-04-16.

EUT operation mode: Hopping


Test Result: Compliant.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	23.3 °C
Relative Humidity:	50 %
ATM Pressure:	102.0 kPa

The testing was performed by Chao Gao on 2020-04-16.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.411	0.132	0.4	Pass
		Middle	0.411	0.132	0.4	Pass
		High	0.409	0.131	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.698	0.272	0.4	Pass
		Middle	1.686	0.270	0.4	Pass
		High	1.674	0.268	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.934	0.313	0.4	Pass
		Middle	2.958	0.316	0.4	Pass
		High	2.934	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.417	0.133	0.4	Pass
		Middle	0.415	0.133	0.4	Pass
		High	0.413	0.132	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.686	0.270	0.4	Pass
		Middle	1.686	0.270	0.4	Pass
		High	1.698	0.272	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.926	0.312	0.4	Pass
		Middle	2.934	0.313	0.4	Pass
		High	2.926	0.312	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.417	0.133	0.4	Pass
		Middle	0.415	0.133	0.4	Pass
		High	0.413	0.132	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.698	0.272	0.4	Pass
		Middle	1.698	0.272	0.4	Pass
		High	1.686	0.270	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.942	0.314	0.4	Pass
		Middle	2.958	0.316	0.4	Pass
		High	2.958	0.316	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




BDR (GFSK): Pulse time, Middle Channel, DH1




BDR (GFSK): Pulse time, High Channel, DH1




BDR (GFSK): Pulse time, Low Channel, DH3




BDR (GFSK): Pulse time, Middle Channel, DH3




BDR (GFSK): Pulse time, High Channel, DH3




BDR (GFSK): Pulse time, Low Channel, DH5




BDR (GFSK): Pulse time, Middle Channel, DH5





BDR (GFSK): Pulse time, High Channel, DH5




EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1






EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1**



EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3




EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3**EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5**



EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5**

EDR (8DPSK): Pulse time, Low Channel, 3DH1




EDR (8DPSK): Pulse time, Middle Channel, 3DH1




EDR (8DPSK): Pulse time, High Channel, 3DH1**EDR (8DPSK): Pulse time, Low Channel, 3DH3**


EDR (8DPSK): Pulse time, Middle Channel, 3DH3




EDR (8DPSK): Pulse time, High Channel, 3DH3




EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions

Temperature:	23.3 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Chao Gao on 2020-04-16.

EUT operation mode: Transmitting


Test Result: Compliant.

Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	6.49	4.46	125
	2441	5.35	3.43	125
	2480	4.12	2.58	125
EDR ($\pi/4$-DQPSK)	2402	5.85	3.85	125
	2441	5.35	3.43	125
	2480	3.87	2.44	125
EDR (8DPSK)	2402	6.36	4.33	125
	2441	5.72	3.73	125
	2480	4.25	2.66	125


BDR (GFSK): 2402MHz




BDR (GFSK): 2441MHz




BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




EDR($\pi/4$ -DQPSK): 2441MHz




EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	22.8~23.2 °C
Relative Humidity:	48~50 %
ATM Pressure:	101.1~101.3 kPa

The testing was performed by Chao Gao from 2020-04-16 to 2020-04-22.

EUT operation mode: Transmitting & Hopping

Test Result: Compliant.


BDR (GFSK): Left Side - Transmitting




BDR (GFSK): Right Side - Transmitting




EDR ($\pi/4$ -DQPSK): Left Side - Transmitting




EDR ($\pi/4$ -DQPSK): Right Side - Transmitting




EDR (8DPSK): Left Side - Transmitting



EDR (8DPSK): Right Side - Transmitting




BDR (GFSK): Left Side - Hopping




Date: 20 APR 2020 13:49:01


BDR (GFSK): Right Side- Hopping



Date: 22 APR 2020 11:45:11

EDR ($\pi/4$ -DQPSK): Left Side- Hopping

Date: 20 APR 2020 15:10:56

EDR ($\pi/4$ -DQPSK): Right Side- Hopping

Date: 20 APR 2020 15:15:06

Spectrum

Ref Level 20.00 dBm **Offset** 11.00 dB **RBW** 100 kHz
Att 20 dB **SWT** 37.9 μs **VBW** 300 kHz **Mode** Auto FFT

1Pk Max

10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm

D1 2.960 dBm
D2 -17.040 dBm
M1
M1[1] -57.17 dBm
2.3997970 GHz

CF 2.4 GHz 691 pts Span 10.0 MHz

Spectrum

Ref Level 20.00 dBm Offset 11.00 dB RBW 100 kHz
 Att 20 dB SWT 38 μ s VBW 300 kHz Mode Auto FFT

1Pk Max

M1[1] -56.62 dBm
 2.4846810 GHz

D1 2.520 dBm
 D2 -17.490 dBm

CF 2.4835 GHz 691 pts Span 12.0 MHz

***** END OF REPORT *****