

FCC PART 15.247 TEST REPORT

For

AKUVOX (XIAMEN) NETWORKS CO., LTD.

10/F, No.56, Software Park II, Xiamen, China

FCC ID: 2AHCR-R29CL

Report Type: Original Report	Product Type: Door phone
Test Engineer:	Stone Zhang <i>Stone Zhang</i>
Report Number:	RXM200703051-00C
Report Date:	2020-08-27
Reviewed By:	Oscar Ye EMC Manager <i>Oscar Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS.....	10
TEST EQUIPMENT LIST	11
FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
FCC §15.203 - ANTENNA REQUIREMENT.....	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
FACTOR & OVER LIMIT CALCULATION.....	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER SETUP.....	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	22
TEST RESULTS SUMMARY	22
TEST DATA	23
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40

TEST DATA	40
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	46
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	65
APPLICABLE STANDARD	65
TEST PROCEDURE	65
TEST DATA	65
FCC §15.247(d) - BAND EDGES TESTING	71
APPLICABLE STANDARD	71
TEST PROCEDURE	71
TEST DATA	71

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	AKUVOX (XIAMEN) NETWORKS CO., LTD.
Tested Model	R29C-L
Product Type	Door phone
Power Supply	DC 12V
RF Function	Classic BT
Operating Band/Frequency	2402-2480 MHz
Channel Number	79
Channel Separation	1 MHz
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type	FPC antenna
Maximum Antenna Gain	-2.3 dBi

**All measurement and test data in this report was gathered from production sample serial number: 20200703051.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-07-03)*

Objective

This test report is prepared on behalf of *AKUVOX (XIAMEN) NETWORKS CO., LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS Submittal with FCC ID: 2AHCR-R29CL
FCC Part 15.225 DXX Submittal with FCC ID: 2AHCR-R29CL

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISSED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

RF test software: Cmdr

GFSK, $\pi/4$ -DQPSK, 8DPSK Power level: Default

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ORIENTAL HERO ELE.FTY.	Adapter	OH-1015E1201000U3	/
DELL	Notebook	E6410	3094742521
TP-LINK	Router	EC26CA652860	1153145002998
Schneider Electric	Relay	RXM2LB2BD	/
WeiShi	Entrance guard	Q3	/
AnYong	Load	RXLG	/
FuShi	Switch	AR22PR-310B	/
/	Socket	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Power Cable	1.2	EUT	Adapter
RJ45 Cable	10.0	EUT	Router
RJ45 Cable	1.0	Router	Notebook
Signal Cable	5.0	EUT	Switch
Signal Cable	5.0	EUT	Relay
Signal Cable	5.0	EUT	Entrance Guard
Power supply Cable	5.0	EUT	Load

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrument	Pre-amplifier	310N	171205	2019-08-14	2020-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2019-08-15	2020-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2017-07-15	2020-07-14
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2019-08-05	2020-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2019-08-15	2020-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2019-08-15	2020-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/0009	2019-12-14	2020-12-13
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2019-08-05	2020-08-04
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2019-08-15	2020-08-14
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
AKUVOX (XIAMEN) NETWORKS CO., LTD.	RF Cable	AKUVOX (XIAMEN) NETWORKS CO., LTD. C01	C01	Each Time	/

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K0 3-101746-zn	2019-08-05	2020-08-04
Rohde & Schwarz	LISN	ENV216	101115	2019-12-14	2020-12-13
Audix	Test Software	e3	V9	/	/
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2020-03-01	2021-02-28
MICRO-COAX	Coaxial Cable	Cable-15	015	2019-08-15	2020-08-14

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data (worst case):

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
Wi-Fi 802.11b	2412-2462	-2.3	0.59	19.50	89.13	20	0.0105	1.00
Wi-Fi 802.11g		-2.3	0.59	23.00	199.53	20	0.0234	1.00
Wi-Fi 802.11n-HT20		-2.3	0.59	22.00	158.49	20	0.0186	1.00
BLE	2402-2480	-2.3	0.59	7.00	5.01	20	0.0006	1.00
BT 3.0	2402-2480	-2.3	0.59	7.00	5.01	20	0.0006	1.00
GSM850	824-849	2.0	1.58	26.00	398.11	20	0.1255	0.55
GSM1900	1850-1910	2.0	1.58	23.00	199.53	20	0.0629	1.00
WCDMA Band II	1850-1910	2.0	1.58	25.00	316.23	20	0.0997	1.00
WCDMA Band IV	1710-1755	2.0	1.58	25.00	316.23	20	0.0997	1.00
WCDMA Band V	824-849	2.0	1.58	25.00	316.23	20	0.0997	0.55
LTE Band2	1850-1910	2.0	1.58	25.00	316.23	20	0.0997	1.00
LTE Band4	1710-1755	2.0	1.58	25.00	316.23	20	0.0997	1.00
LTE Band5	824-849	2.0	1.58	25.00	316.23	20	0.0997	0.55
LTE Band7	2500-2570	2.0	1.58	25.00	316.23	20	0.0997	1.00
LTE Band12	699-716	2.0	1.58	25.00	316.23	20	0.0997	0.47
LTE Band13	777-787	2.0	1.58	25.00	316.23	20	0.0997	0.52
LTE Band25	1850-1915	2.0	1.58	25.00	316.23	20	0.0997	1.00
LTE Band26 (814-824)	814-824	2.0	1.58	25.00	316.23	20	0.0997	0.54
LTE Band26 (824-849)	824-849	2.0	1.58	25.00	316.23	20	0.0997	0.55
LTE Band38	2570-2620	2.0	1.58	25.00	316.23	20	0.0997	1.00
LTE Band41	2496-2690	2.0	1.58	25.00	316.23	20	0.0997	1.00

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up EIRP		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
NFC	13.56	0	1.00	-8.50	0.14	20	0.000028	0.98

Note:

- (1) Tune-up conducted power was declared by the Manufacturer.
- (2) The LTE module FCC ID: XMR201903EG25G (Grant: 2019-03-29).
- (3) For NFC ERP=84.27 dBμV/m -95.2=-10.93dBm
EIRP=ERP+2.15=-8.78 dBm
Tune up EIRP=-8.5dBm
- (4) 2.4G Wi-Fi/BT/BLE and GSM/WCDMA/LTE and NFC can transmit simultaneously; the worst condition as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0234/1.00 + 0.1255/0.55 + 0.000028/0.98 = 0.2516 < 1.0$$

Conclusion: The device meets MPE at distance 20cm.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an FPC antenna with IPEX connector for BT3.0, and the antenna gain is -2.3 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa

The testing was performed by Stone Zhang on 2020-07-13.


EUT operation mode: Transmitting in low channel of BDR (GFSK) mode (worst case)

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.155	18.10	19.82	37.92	55.74	-17.82	Average
2	0.155	30.00	19.82	49.82	65.74	-15.92	QP
3	0.402	21.00	19.74	40.74	47.81	-7.07	Average
4	0.402	27.70	19.74	47.44	57.81	-10.37	QP
5	1.707	11.00	19.84	30.84	46.00	-15.16	Average
6	1.707	21.80	19.84	41.64	56.00	-14.36	QP
7	3.528	15.60	19.47	35.07	46.00	-10.93	Average
8	3.528	26.70	19.47	46.17	56.00	-9.83	QP
9	6.024	15.29	19.51	34.80	50.00	-15.20	Average
10	6.024	24.09	19.51	43.60	60.00	-16.40	QP
11	11.807	17.30	19.58	36.88	50.00	-13.12	Average
12	11.807	26.10	19.58	45.68	60.00	-14.32	QP

AC 120V/60 Hz, Neutral





	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.157	12.30	19.82	32.12	55.60	-23.48	Average
2	0.157	29.50	19.82	49.32	65.60	-16.28	QP
3	0.402	18.10	19.74	37.84	47.81	-9.97	Average
4	0.402	26.60	19.74	46.34	57.81	-11.47	QP
5	0.894	11.70	19.73	31.43	46.00	-14.57	Average
6	0.894	17.70	19.73	37.43	56.00	-18.57	QP
7	1.680	8.40	19.84	28.24	46.00	-17.76	Average
8	1.680	16.40	19.84	36.24	56.00	-19.76	QP
9	3.943	13.50	19.47	32.97	46.00	-13.03	Average
10	3.943	21.30	19.47	40.77	56.00	-15.23	QP
11	10.019	20.40	19.56	39.96	50.00	-10.04	Average
12	10.019	24.80	19.56	44.36	60.00	-15.64	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V /m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data**Environmental Conditions**


Temperature:	24.1~26.5 °C
Relative Humidity:	50~51 %
ATM Pressure:	101.2~101.4 kPa

The testing was performed by Stone Zhang from 2020-07-13 to 2020-07-17.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case low channel of BDR(GFSK) mode in Z-axis of orientation was recorded



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
40.862600	22.05	100.0	V	36.0	-11.8	40.00	17.95
108.490750	31.76	200.0	H	62.0	-13.8	43.50	11.74
135.604250	32.39	100.0	V	41.0	-12.2	43.50	11.11
162.743800	31.99	100.0	V	83.0	-13.3	43.50	11.51
528.007400	39.23	100.0	V	47.0	-5.9	46.00	6.77
648.000450	42.30	100.0	V	325.0	-4.3	46.00	3.70

1GHz-18GHz:


Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) Mode in Z-axis of orientation was recorded

Note:

1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1187.00	---	25.97	150.0	V	67.0	-18.1	54.00	28.03
1187.00	36.68	---	150.0	V	67.0	-18.1	74.00	37.32
1591.60	---	27.60	200.0	V	274.0	-16.0	54.00	26.40
1591.60	33.45	---	200.0	V	274.0	-16.0	74.00	40.55
4826.70	---	33.53	150.0	H	215.0	-5.5	54.00	20.47
4826.70	38.96	---	150.0	H	215.0	-5.5	74.00	35.04
7206.00	---	39.20	200.0	V	2.0	0.4	54.00	14.80
7206.00	45.09	---	200.0	V	2.0	0.4	74.00	28.91
10664.50	---	40.70	150.0	V	81.0	2.5	54.00	13.30
10664.50	46.00	---	150.0	V	81.0	2.5	74.00	28.00
17658.30	---	48.63	200.0	H	11.0	8.9	54.00	5.37
17658.30	52.98	---	200.0	H	11.0	8.9	74.00	21.02

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1187.00	---	24.31	150.0	H	117.0	-18.1	54.00	29.69
1187.00	35.75	---	150.0	H	117.0	-18.1	74.00	38.25
3539.80	---	31.53	200.0	V	146.0	-8.7	54.00	22.47
3539.80	37.33	---	200.0	V	146.0	-8.7	74.00	36.67
4882.00	---	31.39	200.0	V	176.0	-5.4	54.00	22.61
4882.00	39.65	---	200.0	V	176.0	-5.4	74.00	34.35
7708.20	---	39.34	150.0	H	295.0	1.4	54.00	14.66
7708.20	44.56	---	150.0	H	295.0	1.4	74.00	29.44
9879.10	---	39.87	150.0	H	221.0	2.0	54.00	14.13
9879.10	44.83	---	150.0	H	221.0	2.0	74.00	29.17
17683.80	---	47.94	150.0	H	357.0	8.9	54.00	6.06
17683.80	54.23	---	150.0	H	357.0	8.9	74.00	19.77

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1192.10	---	23.00	200.0	V	112.0	-18.0	54.00	31.00
1192.10	34.30	---	200.0	V	112.0	-18.0	74.00	39.70
1982.60	---	24.95	200.0	H	313.0	-14.5	54.00	29.05
1982.60	35.44	---	200.0	H	313.0	-14.5	74.00	38.56
4960.00	---	33.39	200.0	V	65.0	-5.3	54.00	20.61
4960.00	41.11	---	200.0	V	65.0	-5.3	74.00	32.89
6638.90	---	37.54	150.0	V	10.0	-0.9	54.00	16.46
6638.90	42.37	---	150.0	V	10.0	-0.9	74.00	31.63
9838.30	---	40.20	150.0	H	95.0	2.0	54.00	13.80
9838.30	45.13	---	150.0	H	95.0	2.0	74.00	28.87
17694.00	---	46.20	200.0	H	357.0	8.9	54.00	7.80
17694.00	55.09	---	200.0	H	357.0	8.9	74.00	18.91

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation,, the worst case low channel of BDR(GFSK) mode in Z-axis of orientation was recorded



Date: 17.JUL.2020 04:29:56



Date: 10.JUL.2020 21:36:53



Restricted Bands Emissions:



Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case BDR(GFSK) mode in Z-axis of orientation was recorded



Note:

- Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.000000	44.76	---	150.0	V	60.0	-2.9	74.00	29.24
2390.000000	---	36.75	150.0	V	60.0	-2.9	54.00	17.25
High Channel: 2480MHz								
2483.500000	---	38.18	150.0	H	136.0	-2.5	54.00	15.82
2483.500000	46.12	---	150.0	V	136.0	-2.5	74.00	27.88

Conducted Spurious Emissions at Antenna Port**BDR (GFSK): Low Channel****BDR (GFSK): Middle Channel**


BDR (GFSK): High Channel**EDR ($\pi/4$ -DQPSK): Low Channel**

EDR ($\pi/4$ -DQPSK): Middle ChannelEDR ($\pi/4$ -DQPSK): High Channel


EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data**Environmental Conditions**

Temperature:	25.7°C
Relative Humidity:	49 %
ATM Pressure:	101.1 kPa

The testing was performed by Stone Zhang on 2020-07-12.


EUT operation mode: Transmitting

Test Result: Compliant.


Note: For BDR and EDR mode, Limit = 20 dB bandwidth*2/3

Delta 1 [T1]
 Ref Lvl 0.13 dB
 20 dBm 1.01603206 MHz
 RBW 30 kHz RF Att 20 dB
 VBW 100 kHz Unit dBm
 SWT 8.5 ms
 10.5 dB Offset
 1 [T1]
 1 [T1]
 1 [T1]
 6.99 dBm
 2.40196794 GHz
 0.13 dB
 1.01603206 MHz
 1MAX
 1MA
 Center 2.4025 GHz 300 kHz/
 Span 3 MHz
 Date: 12. JUL. 2020 14:52:29


BDR (GFSK): Middle Channel




BDR (GFSK): High Channel




EDR ($\pi/4$ -DQPSK): Low Channel




EDR ($\pi/4$ -DQPSK): Middle Channel




EDR ($\pi/4$ -DQPSK): High Channel




EDR (8DPSK): Low Channel



EDR (8DPSK): Middle Channel



EDR (8DPSK): High Channel



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.3 kPa


The testing was performed by Stone Zhang on 2020-07-12.

EUT operation mode: Transmitting


Test Result: Compliant.

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	1.052
	Middle	2441	1.058
	High	2480	1.058
EDR ($\pi/4$-DQPSK)	Low	2402	1.353
	Middle	2441	1.353
	High	2480	1.359
EDR (8DPSK)	Low	2402	1.329
	Middle	2441	1.335
	High	2480	1.341


BDR (GFSK): Low Channel




BDR (GFSK): Middle Channel




BDR (GFSK): High Channel



EDR ($\pi/4$ -DQPSK): Low Channel



EDR($\pi/4$ -DQPSK): Middle Channel



Delta 1 [T1] 1.04 dB

RBW 30 kHz RF Att 20 dB

Ref Lvl 20 dBm

SWT 8.5 ms Unit dBm

10.5 dB Offset

D1 1.35 dBm

D2 -18.65 dBm

1MAX

1 [T1] -19.34 dBm

2.47929359 GHz

1.04 dB

1.35871743 MHz

Center 2.48 GHz

300 kHz/

Span 3 MHz

Date: 12. JUL. 2020 09:59:31

Delta 1 [T1] 0.18 dB
 Ref Lvl 20 dBm
 1.32865731 MHz
 RBW 30 kHz
 VBW 100 kHz
 SWT 8.5 ms
 RF Att 20 dB
 Unit dBm

10.5 dB Offset
 -D1 1.23 dBm
 1MAX
 -D2 -18.77 dBm
 1
 1
 -18.99 dBm
 2.40130561 GHz
 0.18 dB
 1.32865731 MHz
 1MA

Center 2.402 GHz
 300 kHz/
 Span 3 MHz

Date: 12. JUL. 2020 10:04:54

Delta 1 [T1] 0.62 dB
 RBW 30 kHz RF Att 20 dB
 Ref Lvl 20 dBm Unit dBm
 20 dBm 1.33466934 MHz

10.5 dB Offset
 -D1 1.2 dBm
 1MAX
 D2 -18.8 dBm
 1
 1
 -19.66 dBm
 2.44029960 GHz
 0.62 dB
 1.33466934 MHz
 1MA

Center 2.441 GHz 300 kHz/
 Span 3 MHz

Date: 12. JUL. 2020 10:02:18

Delta 1 [T1] -0.29 dB

RBW 30 kHz RF Att 20 dB

Ref Lvl 20 dBm Unit dBm

1.34068136 MHz

SWT 8.5 ms

10.5 dB Offset

▼1 [T1] -19.05 dBm

▲1 [T1] -0.29 dB

1.34068136 MHz

D1 1.35 dBm

1MAX

D2 -18.65 dBm

1

1MA

Center 2.48 GHz

300 kHz/

Span 3 MHz

Date: 12. JUL. 2020 10:00:44

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**

Temperature:	25.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.5 kPa


The testing was performed by Stone Zhang on 2020-07-12.

EUT operation mode: Hopping


Test Result: Compliant.

Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15


BDR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	25.4~25.9 °C
Relative Humidity:	51~52 %
ATM Pressure:	101.2~102.9 kPa

The testing was performed by Stone Zhang from 2020-07-12 to 2020-08-27.


EUT operation mode: Hopping

Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.435	0.139	0.4	Pass
		Middle	0.437	0.140	0.4	Pass
		High	0.433	0.139	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.693	0.271	0.4	Pass
		Middle	1.711	0.274	0.4	Pass
		High	1.687	0.270	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.936	0.313	0.4	Pass
		Middle	2.966	0.316	0.4	Pass
		High	3.006	0.321	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.437	0.140	0.4	Pass
		Middle	0.437	0.140	0.4	Pass
		High	0.441	0.141	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.754	0.281	0.4	Pass
		Middle	1.711	0.274	0.4	Pass
		High	1.693	0.271	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.966	0.316	0.4	Pass
		Middle	2.986	0.319	0.4	Pass
		High	2.986	0.319	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.445	0.142	0.4	Pass
		Middle	0.447	0.143	0.4	Pass
		High	0.459	0.147	0.4	Pass
		Note: 3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.693	0.271	0.4	Pass
		Middle	1.687	0.270	0.4	Pass
		High	1.717	0.275	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.996	0.320	0.4	Pass
		Middle	2.976	0.317	0.4	Pass
		High	3.016	0.322	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK): Pulse time, Low Channel, DH1




BDR (GFSK): Pulse time, Middle Channel, DH1





BDR (GFSK): Pulse time, High Channel, DH1




BDR (GFSK): Pulse time, Low Channel, DH3




BDR (GFSK): Pulse time, Middle Channel, DH3**BDR (GFSK): Pulse time, High Channel, DH3**


BDR (GFSK): Pulse time, Low Channel, DH5




BDR (GFSK): Pulse time, Middle Channel, DH5







BDR (GFSK): Pulse time, High Channel, DH5




EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1




EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1**



EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3



EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3



EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5



EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5**EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5**

EDR (8DPSK): Pulse time, Low Channel, 3DH1**EDR (8DPSK): Pulse time, Middle Channel, 3DH1**

Delta 1 [T1] -0.59 dB
 458.916633 μ s
 10.5 dB Offset
 Ref Lvl 20 dBm
 RBW 500 kHz
 VBW 2 MHz
 SWT 1 ms
 RF Att 20 dB
 Unit dBm


-62.66 dBm
 -48.696192 μ s
 -0.59 dB
 458.916633 μ s

Center 2.48 GHz
 100 μ s/


Date: 12. JUL. 2020 17:24:18

Delta 1 [T1]
 Ref Lvl -1.00 dB
 20 dBm 1.693386 ms
 RBW 500 kHz
 VBW 2 MHz
 SWT 3 ms
 RF Att Unit dBm
 10.5 dB Offset
 -58.28 dBm
 -42.684168 μs
 -1.00 dB
 1.693386 ms
 TR
 Center 2.402 GHz
 300 μs/
 Date: 12. JUL. 2020 17:20:50


EDR (8DPSK): Pulse time, Middle Channel, 3DH3




EDR (8DPSK): Pulse time, High Channel, 3DH3




EDR (8DPSK): Pulse time, Low Channel, 3DH5



EDR (8DPSK): Pulse time, Middle Channel, 3DH5



EDR (8DPSK): Pulse time, High Channel, 3DH5



FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data

Environmental Conditions


Temperature:	25.1 °C
Relative Humidity:	50 %
ATM Pressure:	101.2 kPa

The testing was performed by Stone Zhang on 2020-07-12.


EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	6.69	4.67	125
	2441	6.10	4.07	125
	2480	5.61	3.64	125
EDR ($\pi/4$-DQPSK)	2402	4.63	2.90	125
	2441	4.63	2.90	125
	2480	4.25	2.66	125
EDR (8DPSK)	2402	5.12	3.25	125
	2441	5.01	3.17	125
	2480	4.50	2.82	125

BDR (GFSK): 2402MHz


BDR (GFSK): 2441MHz




BDR (GFSK): 2480MHz




EDR($\pi/4$ -DQPSK): 2402MHz




EDR($\pi/4$ -DQPSK): 2441MHz




EDR($\pi/4$ -DQPSK): 2480MHz




EDR(8DPSK): 2402MHz



EDR(8DPSK): 2441MHz



EDR(8DPSK): 2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	26.2 °C
Relative Humidity:	50 %
ATM Pressure:	101.6 kPa


The testing was performed by Stone Zhang on 2020-07-12.

EUT operation mode: Transmitting & Hopping


Test Result: Compliant.

Band Edge


BDR (GFSK): Left Side




BDR (GFSK): Right Side




EDR ($\pi/4$ -DQPSK): Left Side




EDR ($\pi/4$ -DQPSK): Right Side




EDR (8DPSK): Left Side




EDR (8DPSK): Right Side




BDR (GFSK): Left Side - Hopping




BDR (GFSK): Right Side- Hopping




EDR ($\pi/4$ -DQPSK): Left Side- Hopping




EDR ($\pi/4$ -DQPSK): Right Side- Hopping



EDR (8DPSK): Left Side- Hopping



EDR (8DPSK): Right Side- Hopping



Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******