

588 West Jindu Road, Xingiao, Songjiang, 201612 Shanghai, China

ee.shanghai@sgs.com

TEST REPORT

 Application No.:
 SHEM1803002204CR

 FCC ID:
 2AHEA-WF12096

 IC:
 21124- WF12096

Applicant: Shanghai Mobvoi Information Technology Company Limited

Address of Applicant: Building 2-106, 1690 Cailun Road, China (Shanghai) free trade area, China

Manufacturer: Shanghai Mobvoi Information Technology Company Limited

Address of Manufacturer: Building 2-106, 1690 Cailun Road, China (Shanghai) free trade area, China

Factory: Compal Display Electronics (Kunshan) Co., Ltd.

Address of Factory: No.1881 Liji Road Shipai Bacheng Town, Kunshan, Jiangsu, P.R.China

Equipment Under Test (EUT):

EUT Name: TicWatch Pro Smartwatch

Model No.: WF12096
Trade mark: TicWatch

Standard(s): 47 CFR Part 15, Subpart C 15.247

RSS-247 Issue 2, February 2017 RSS-Gen Issue 4, November 2014

Date of Receipt: 2018-03-26

Date of Test: 2018-04-02 to 2018-04-17

Date of Issue: 2018-04-18

Test Result: Pass*



Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful of fenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM180300220403

Page: 2 of 26

Revision Record							
Version Description Date Remark							
00	Original	2018-04-18	/				

Authorized for issue by:		
	Vincent Zhu	
	Vincent Zhu / Project Engineer	
	Darlam Zhan	
	Parlam Zhan / Reviewer	



Report No.: SHEM180300220403

Page: 3 of 26

2 Test Summary

Radio Spectrum Technical Requirement						
Item	Standard	Method	Requirement	Result		
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass		

Radio Spectrum Matter Part						
Item	Standard	Method	Requirement	Result		
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass		
Conducted Peak Output Power			47 CFR Part 15, Subpart C 15.247(b)(3)	Pass		
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass		
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass		
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass		
99% Bandwidth	RSS-247 Issue 2, February 2017	ANSI C63.10 Section 6.9.3	RSS-Gen Section 6.6	Pass		



Report No.: SHEM180300220403

Page: 4 of 26

3 Contents

			Page
1	COVE	R PAGE	1
2	TEST	SUMMARY	3
3	CONT	ENTS	4
4		RAL INFORMATION	
		DETAILS OF E.U.T.	
		DESCRIPTION OF SUPPORT UNITS	
		MEASUREMENT UNCERTAINTY	
		FEST LOCATION	
		FEST FACILITY	
		ABNORMALITIES FROM STANDARD CONDITIONS	
5		PMENT LIST	
5	EQUIP	THEN LIST	9
6	RADIO	O SPECTRUM TECHNICAL REQUIREMENT	10
	6.1 A	ANTENNA REQUIREMENT	10
	6.1.1	Test Requirement:	10
	6.1.2	Conclusion	10
7	RADIO	O SPECTRUM MATTER TEST RESULTS	11
	7.1 N	AINIMUM 6DB BANDWIDTH	11
	7.1.1	E.U.T. Operation	11
	7.1.2	Test Setup Diagram	11
	7.1.3	Measurement Procedure and Data	
		CONDUCTED PEAK OUTPUT POWER	
	7.2.1	E.U.T. Operation	
	7.2.2	Test Setup Diagram	
	7.2.3 7.3 F	Measurement Procedure and Data	
	7.3 F	Power Spectrum Density	
	7.3.1	Test Setup Diagram	
	7.3.3	Measurement Procedure and Data	
		CONDUCTED BAND EDGES MEASUREMENT	
	7.4.1	E.U.T. Operation	14
	7.4.2	Test Setup Diagram	14
	7.4.3	Measurement Procedure and Data	
		CONDUCTED SPURIOUS EMISSIONS	
	7.5.1	E.U.T. Operation	
	7.5.2	Test Setup Diagram	
	7.5.3	Measurement Procedure and Data	
		RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	
	7.6.1 7.6.2	E.U.T. Operation Test Setup Diagram	
	7.6.2 7.6.3	Measurement Procedure and Data	
		RADIATED Spurious Emissions	
	7.7.1	E.U.T. Operation	
	7.7.2	Test Setup Diagram	
	7.7.3	Measurement Procedure and Data	



Report No.: SHEM180300220403

Page: 5 of 26

7.8	99% BANDWIDTH	25
7.8	8.1 E.U.T. Operation	25
	8.2 Test Setup Diagram	
	8.3 Measurement Procedure and Data	
8 TE	EST SETUP PHOTOGRAPHS	26
9 El	UT CONSTRUCTIONAL DETAILS	26



Report No.: SHEM180300220403

Page: 6 of 26

4 General Information

4.1 Details of E.U.T.

Power supply: Battery:3.8V 415mAh

Charging Dock:

name:TicWatch Dock Model:WF20028 INPUT:DC 5V 1A

OUTPUT:DC 5V 0.8A

Cable: DC Cable 80mm for TicWatch Dock

Antenna Gain -1 dBi

Antenna Type PIFA Antenna

Channel Spacing 2MHz
Modulation Type GFSK
Number of Channels 40

Operation Frequency 2402MHz to 2480MHz

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	/
Serial port adapter plate	/	Test Plate 3	/



Report No.: SHEM180300220403

Page: 7 of 26

4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Timeout	2s
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	RF power density	2.84dB
7	Conducted Spurious emissions	0.75dB
0	DE Dadiated naver	4.5dB (Below 1GHz)
8	RF Radiated power	4.8dB (Above 1GHz)
		4.2dB (Below 30MHz)
9	Dadiated Churique emission test	4.4dB (30MHz-1GHz)
9	Radiated Spurious emission test	4.6dB (1GHz-18GHz)
		5.2dB (Above 18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



Report No.: SHEM180300220403

Page: 8 of 26

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666 Fax: +86 21 6191 5678

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L0599)

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• NVLAP (Certificate No. 201034-0)

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

• FCC -Designation Number: CN5033

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

• Industry Canada (IC) - IC Assigned Code: 8617A

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

VCCI (Member No.: 3061)

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-12221,G-10830 respectively.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Report No.: SHEM180300220403

Page: 9 of 26

5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Conducted Emission at AC		inouoi ito	inventory ite	oui buto	our but but
EMI test receiver	R&S	ESR7	SHEM162-1	2017-12-20	2018-12-19
LISN	Schwarzbeck	NSLK8127	SHEM061-1	2017-12-20	2018-12-19
LISN	EMCO	3816/2	SHEM019-1	2017-12-20	2018-12-19
Pulse limiter	R&S	ESH3-Z2	SHEM029-1	2017-12-20	2018-12-19
CE test Cable	/		/	2017-12-20	
0 = 1001 0 11010	/	CE01	/	2017-12-26	2018-12-25
Conducted Test	Dec	ECD 20	CUEMOO2 4	2017 12 20	2040 40 40
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2017-12-20	2018-12-19
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2017-09-26	2018-09-25
Power meter	R&S	NRP	SHEM057-1	2017-12-26	2018-12-25
Power Sensor	R&S	NRP-Z22	SHEM136-1	2017-07-22	2018-07-21
Power Sensor	R&S	NRP-Z91	SHEM057-2	2017-12-26	2018-12-25
Signal Generator	R&S	SMR40	SHEM058-1	2017-07-03	2018-07-02
Signal Generator	Agilent	N5182A	SHEM182-1	2017-09-26	2018-09-25
Communication Tester	R&S	CMW270	SHEM183-1	2017-10-22	2018-10-21
Switcher	Tonscend	JS0806	SHEM184-1	2017-09-26	2018-09-25
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2017-09-26	2018-09-25
AC Power Stabilizer	WOCEN	6100	SHEM045-1	2017-12-26	2018-12-25
DC Power Supply	QJE	QJ30003SII	SHEM046-1	2017-12-26	2018-12-25
Conducted test Cable	/	RF01, RF 02	/	2017-12-26	2018-12-25
Radiated Test					
EMI test receiver	R&S	ESU40	SHEM051-1	2017-12-20	2018-12-19
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2017-12-20	2018-12-19
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2017-04-10	2020-04-09
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2017-02-28	2020-02-27
Antenna (25MHz-3GHz)	Schwarzbeck	HL562	SHEM010-1	2017-02-28	2020-02-27
Horn Antenna (1-8GHz)	Schwarzbeck	HF906	SHEM009-1	2017-10-24	2020-10-23
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2017-01-14	2020-01-13
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2017-12-03	2020-12-02
Pre-amplifier (9KHz-2GHz)	LAVIIO	LNA-0001-412010	SHEM164-1	2017-08-22	2018-08-21
Pre-amplifier (1-18GHz)	CLAVIIO	BDLNA-0118-352810	SHEM050-2	2017-08-22	2018-08-21
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2017-12-20	2018-12-19
Band filter	LORCH	9BRX-875/X150-SR	SHEM156-1	/	/
Band filter	LORCH	13BRX-1950/X500-SR	SHEM083-2	/	/
Band filter	LORCH	5BRX-2400/X200-SR	SHEM155-1	/	/
Band filter	LORCH	5BRX-5500/X1000-SR	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G-100SS	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700-3SS	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2020-07-21
RE test Cable	/	RE01, RE02, RE06	/	2017-12-26	2018-12-25



Report No.: SHEM180300220403

Page: 10 of 26

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PIFA antenna and no consideration of replacement. The best case gain of the antenna is -1dBi.





Report No.: SHEM180300220403

Page: 11 of 26

7 Radio Spectrum Matter Test Results

7.1 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit: ≥500 kHz

7.1.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar Test mode c:Engineering mode Using test software to control EUT working in continuous

c:Engineering mode_Using test software to control EUT working in continuous transmitting, and select channel and modulation type.

7.1.2 Test Setup Diagram

Spectrum Analyzer



Ground Reference Plane

7.1.3 Measurement Procedure and Data



Report No.: SHEM180300220403

Page: 12 of 26

7.2 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)	
	1 for ≥50 hopping channels	
902-928	0.25 for 25≤ hopping channels <50	
	1 for digital modulation	
	1 for ≥75 non-overlapping hopping channels	
2400-2483.5	0.125 for all other frequency hopping systems	
	1 for digital modulation	
5725-5850	1 for frequency hopping systems and digital modulation	

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.2.2 Test Setup Diagram



Ground Reference Plane

7.2.3 Measurement Procedure and Data



Report No.: SHEM180300220403

Page: 13 of 26

7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit: ≤8dBm in any 3 kHz band during any time interval of continuous

transmission


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.3.2 Test Setup Diagram



Ground Reference Plane

7.3.3 Measurement Procedure and Data



Report No.: SHEM180300220403

Page: 14 of 26

7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in

§15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.4.2 Test Setup Diagram



Ground Reference Plane

7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEM180300220403

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sqs.com/en/Terms-and-Conditions.rems-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Condi



Report No.: SHEM180300220403

Page: 15 of 26

7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.11

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread

spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition,

radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in

§15.209(a) (see §15.205(c)

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.5.2 Test Setup Diagram



Ground Reference Plane

7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix B for SHEM180300220403

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sqs.com/en/Terms-and-Conditions.rems-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Condi



Report No.: SHEM180300220403

Page: 16 of 26

7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.6.1 E.U.T. Operation


Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar


Test mode c:Engineering mode Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.6.2 Test Setup Diagram







This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sqs.com/en/Terms-and-Conditions.rems-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Condi



Report No.: SHEM180300220403

Page: 17 of 26

7.6.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Report No.: SHEM180300220403

Page: 18 of 26

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:Low



Antenna Polarity :HORIZONTAL

		Read	Antenna	Cable	Preamp	Emission	Limit	0ver	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	2376.23	43.27	26.01	6.45	37.36	38.37	74.00	-35.63	Peak
2	2390.00	41.08	26.03	6.47	37.36	36.22	74.00	-37.78	Peak
3	2401.84	94.78	26.05	6.50	37.35	89.98	74.00	15.98	Peak


Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Report No.: SHEM180300220403

Page: 19 of 26

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low



Antenna Polarity : VERTICAL

		Read	Antenna	Cable	Preamp	Emission	Limit	0ver	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	2363.47	44.28	26.00	6.42	37.36	39.34	74.00	-34.66	Peak
2	2390.00	41.23	26.03	6.47	37.36	36.37	74.00	-37.63	Peak
3	2402.15	94.82	26.05	6.50	37.35	90.02	74.00	16.02	Peak


Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Report No.: SHEM180300220403

Page: 20 of 26

Mode:c; Polarization:Horizontal; Modulation:GFSK; ; Channel:High



Antenna Polarity : HORIZONTAL

		Read	Antenna	Cable	Preamp	Emission	Limit	0ver	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	2480.03	91.55	26.17	6.74	37.49	86.97	74.00	12.97	Peak
2	2483.50	52.86	26.18	6.80	37.51	48.33	74.00	-25.67	Peak
3	2496.82	42.29	26.20	6.80	37.53	37.76	74.00	-36.24	Peak


Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Report No.: SHEM180300220403

Page: 21 of 26

Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High



Antenna Polarity : VERTICAL

		Read	Antenna	Cable	Preamp	Emission	Limit	0ver	
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	2479.66	92.18	26.17	6.74	37.49	87.60	74.00	13.60	Peak
2	2483.50	53.77	26.18	6.80	37.51	49.24	74.00	-24.76	Peak
3	2487.67	42.87	26.18	6.80	37.51	38.34	74.00	-35.66	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor



Report No.: SHEM180300220403

Page: 22 of 26

7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation


Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar


Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.7.2 Test Setup Diagram







This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Report No.: SHEM180300220403

Page: 23 of 26

7.7.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown



Report No.: SHEM180300220403

Page: 24 of 26

Mode:c; Pola	arization:H	orizontal; N	/lodulation:G	FSK; ; Cha	annel:Low							
Frequency	RX_R	Factor	Emission	Limit	Marg	jin Detector						
MHz	dBuV	dB	dBuV/m	dBuV/m	dB							
4804	40.19	6.18	46.37	54	-7.6	3 peak						
7206	35.06	10.63	45.69	54	-8.3	1 peak						
9608	36.22	14.38	50.6	54	-3.4	l peak						
Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:Low												
Frequency	RX_R	Factor	Emission		iei.Low Marg	in Detector						
MHz	dBuV	dB	dBuV/m		•							
4804	37.66	6.18		ови v/m	ı ив -10.1							
			43.84			•						
7206	35.31	10.63	45.94	54	-8.0	•						
9608	36.76	14.38	51.14	54	-2.8	6 peak						
Mode:c; Pola	arization:H	orizontal; N	/lodulation:G	FSK; ; Cha	annel:mido	lle						
Frequency	RX_R	Factor	Emission	Limit	Marg	in Detector						
MHz	dBuV	dB	dBuV/m	dBuV/m	ı dB							
4880	39.18	6.97	46.15	54	-7.8	5 peak						
7320	34.27	11.12	45.39	54	-8.6	1 peak						
9760	33.8	14.35	48.15	54	-5.8	5 peak						
Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:middle Frequency RX_R Factor Emission Limit Margin Detector												
MHz	dBuV	dB	dBuV/m		•							
4880	37.03	6.97	44	54	-10							
7320	37.42	11.12	48.54	54	-5.4	•						
9760	32.87	14.35	47.22	54	-6.7	•						
0700	02.07	14.00	71.22	04	0.7	o pour						
Mode:c; Pola	arization:H	orizontal; N	/lodulation:G	FSK; ; Cha	annel:High							
Frequency	RX_R	Factor	Emission	Limit	Margin	Detector						
MHz	dBuV	dB	dBuV/m	dBuV/m	dB							
4960	37.68	7.49	45.17	54	-8.83	peak						
7440	36.6	11.65	48.25	54	-5.75	peak						
9920	33.76	14.4	48.16	54	-5.84	peak						
Mode:c; Polarization:Vertical; Modulation:GFSK; ; Channel:High												
Frequency	RX_R	Factor	Emission	Limit	Margin	Detector						
MHz	dBuV	dB	dBuV/m	dBuV/m	dB							
4960	37.27	7.49	44.76	54	-9.24	peak						
7440												
7 770	39.45	11.65	51.1	54	-2.9	peak						



Report No.: SHEM180300220403

Page: 25 of 26

7.8 99% Bandwidth

Test Requirement RSS-Gen Section 6.6
Test Method: ANSI C63.10 Section 6.9.3

7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode c:Engineering mode_Using test software to control EUT working in continuous

transmitting, and select channel and modulation type.

7.8.2 Test Setup Diagram



Ground Reference Plane

7.8.3 Measurement Procedure and Data



Report No.: SHEM180300220403

Page: 26 of 26

8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

- End of the Report -