



## Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V05  
Report Template Revision Date: 2021-11-03

# Test Report

**Report No.:** CQASZ20250500987E-01

**Applicant:** Shenzhen DO Intelligent Technology Co., Ltd

**Address of Applicant:** 11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China

**Equipment Under Test (EUT):**

**Product:** Smart Watch

**Model No.:** GTS1 E

**Test Model No.:** GTS1 E

**Brand Name:** IDO

**FCC ID:** 2AHFT8021

**Standards:** 47 CFR Part 15, Subpart C

KDB558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10:2013

**Date of Receipt:** 2025-05-06

**Date of Test:** 2025-05-06 to 2025-05-19

**Date of Issue:** 2025-06-13

**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above.

**Tested By:**

lewis zhou

( Lewis Zhou )

**Reviewed By:**

Timo Lei

( Timo Lei )

**Approved By:**

Jack Ai

( Jack Ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20250500987E-01	Rev.01	Initial report	2025-06-13

#### Note:

The differences between Product 1# and 2# products lie in the FLASH, speaker, screen and microphone, including the difference in suppliers. The main differences are in appearance and model. These changes do not affect RF performance.

## 2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

### 3 Contents

	Page
<b>1 VERSION</b> .....	2
<b>2 TEST SUMMARY</b> .....	3
<b>3 CONTENTS</b> .....	4
<b>4 GENERAL INFORMATION</b> .....	5
4.1 CLIENT INFORMATION .....	5
4.2 GENERAL DESCRIPTION OF EUT .....	5
4.3 ADDITIONAL INSTRUCTIONS .....	7
4.4 TEST ENVIRONMENT .....	8
4.5 DESCRIPTION OF SUPPORT UNITS .....	8
4.6 TEST CONFIGURATION .....	8
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	9
4.8 TEST LOCATION .....	10
4.9 TEST FACILITY .....	10
4.10 DEVIATION FROM STANDARDS .....	10
4.11 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	10
4.12 EQUIPMENT LIST .....	11
<b>5 TEST RESULTS AND MEASUREMENT DATA</b> .....	12
5.1 ANTENNA REQUIREMENT .....	12
5.2 CONDUCTED EMISSIONS .....	13
5.3 CONDUCTED PEAK OUTPUT POWER .....	19
5.4 6dB OCCUPY BANDWIDTH .....	24
5.5 POWER SPECTRAL DENSITY .....	27
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS .....	30
5.7 SPURIOUS RF CONDUCTED EMISSIONS .....	32
5.8 RADIATED SPURIOUS EMISSION & RESTRICTED BANDS .....	37
5.8.1 <i>Spurious Emissions</i> .....	37
<b>6 PHOTOGRAPHS - EUT TEST SETUP</b> .....	45
6.1 RADIATED SPURIOUS EMISSION .....	45
6.2 CONDUCTED EMISSIONS TEST SETUP .....	46
6.3 RF CONDUCTED MEASUREMENT .....	47
<b>7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS</b> .....	48

## 4 General Information

### 4.1 Client Information

Applicant:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Applicant:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Manufacturer:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Manufacturer:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China
Factory:	Shenzhen DO Intelligent Technology Co., Ltd
Address of Factory:	11th Floor, 3# Building, Guole Tech Park, Lirong Road, Dalang, Longhua District, Shenzhen, China

### 4.2 General Description of EUT

Product Name:	Smart Watch
Model No.:	GTS1 E
Test Model No.:	GTS1 E
Trade Mark:	IDO
Software Version:	V1.00.18
Hardware Version:	V1.2
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.3
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	SiFli_RF_Tool_v1.1.6
Antenna Type:	FPC antenna
Antenna Gain:	-2.24dBi
EUT Power Supply:	Li-ion battery DC 3.85V 350mAh
Simultaneous Transmission	<input type="checkbox"/> Simultaneous TX is supported and evaluated in this report. <input checked="" type="checkbox"/> Simultaneous TX is not supported.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz


Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

### 4.3 Additional Instructions

<b>EUT Test Software Settings:</b>	
Mode:	<input checked="" type="checkbox"/> Special software is used. <input type="checkbox"/> Through engineering command into the engineering mode. engineering command: *###3646633#*#*
EUT Power level:	Class2 (Power level is built-in set parameters and cannot be changed and selected)
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Mode	Channel
	CH0
	CH19
	CH39
GFSK	Frequency(MHz)
	2402
	2440
	2480

**Run Software:**


## 4.4 Test Environment

<b>Operating Environment:</b>	
Temperature:	24.5°C
Humidity:	59% RH
Atmospheric Pressure:	1009mbar
Test Mode:	Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.

## 4.5 Description of Support Units

The EUT has been tested with associated equipment below.


### 1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
Adapter	HUAWEI	HW-0502000C01	/	CQA

### 2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

## 4.6 Test configuration



## 4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty
1	Radiated Emission (Below 1GHz)	5.12dB
2	Radiated Emission (Above 1GHz)	4.60dB
3	Conducted Disturbance (0.15~30MHz)	3.34dB
4	Radio Frequency	$3 \times 10^{-8}$
5	Duty cycle	0.6 %
6	Occupied Bandwidth	1.1%
7	RF conducted power	0.86dB
8	RF power density	0.74
9	Conducted Spurious emissions	0.86dB
10	Temperature test	0.8°C
11	Humidity test	2.0%
12	Supply voltages	0.5 %
13	Frequency Error	5.5 Hz

## **4.8 Test Location**

All tests were performed at:

Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

## **4.9 Test Facility**

- A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

- FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

## **4.10 Deviation from Standards**

None.

## **4.11 Other Information Requested by the Customer**

None.

## 4.12 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2024/9/2	2025/9/1
Spectrum analyzer	R&S	FSU26	CQA-038	2024/9/2	2025/9/1
Spectrum analyzer	R&S	FSU40	CQA-075	2024/9/2	2025/9/1
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2024/9/2	2025/9/1
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2024/9/2	2025/9/1
Preamplifier	EMCI	EMC184055SE	CQA-089	2024/9/2	2025/9/1
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2024/9/2	2025/9/1
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2024/9/2	2025/9/1
Antenna Connector	CQA	RFC-01	CQA-080	2024/9/2	2025/9/1
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2024/9/2	2025/9/1
Power meter	R&S	NRVD	CQA-029	2024/9/2	2025/9/1
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2024/9/2	2025/9/1
EMI Test Receiver	R&S	ESR7	CQA-005	2024/9/2	2025/9/1
LISN	R&S	ENV216	CQA-003	2024/9/2	2025/9/1
Coaxial cable	CQA	N/A	CQA-C009	2024/9/2	2025/9/1
DC power	KEYSIGHT	E3631A	CQA-028	2024/9/2	2025/9/1

Test software:

	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

Note:

The temporary antenna connector is soldered on the pcb board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

## 5 Test results and Measurement Data

### 5.1 Antenna Requirement


<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
<b>EUT Antenna:</b>	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment. This is either permanently attachment or a unique coupling that satisfies the requirement.	

## 5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)		Limit (dBuV)
			Quasi-peak
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50

\* Decreases with the logarithm of the frequency.


| Test Procedure: | - 1) The mains terminal disturbance voltage test was conducted in a shielded room. - 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. - 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, - 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. - 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. |  |  |

Test Setup:	
Test Mode:	Through Pre-scan, find the transmitting mode at the lowest channel is the worst case.
Test Voltage:	AC 120V/60Hz
Test Results:	Pass

1#

**Measurement Data**

Live line:




Freq	Read			Limit	Over	Pol/Phase	
	MHz	Level	Factor				
1	0.150	13.27	9.70	22.97	56.00	-33.03	Average Line
2	0.150	25.01	9.70	34.71	66.00	-31.29	QP Line
3	0.240	11.85	9.56	21.41	52.10	-30.69	Average Line
4	0.240	19.07	9.56	28.63	62.10	-33.47	QP Line
5	0.410	9.98	9.62	19.60	47.65	-28.05	Average Line
6	0.410	19.04	9.62	28.66	57.65	-28.99	QP Line
7	0.870	9.60	9.79	19.39	46.00	-26.61	Average Line
8	0.870	19.30	9.79	29.09	56.00	-26.91	QP Line
9 PP	1.135	10.33	10.06	20.39	46.00	-25.61	Average Line
10 QP	1.135	19.83	10.06	29.89	56.00	-26.11	QP Line
11	1.490	9.38	10.81	20.19	46.00	-25.81	Average Line
12	1.490	17.89	10.81	28.70	56.00	-27.30	QP Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:



Freq	Read		Limit	Over	Remark	Pol/Phase	
	Freq	Level					
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.150	12.62	9.70	22.32	56.00	-33.68	Average
2	0.150	27.15	9.70	36.85	66.00	-29.15	QP
3	0.275	10.92	9.51	20.43	50.97	-30.54	Average
4	0.275	18.51	9.51	28.02	60.97	-32.95	QP
5	0.500	9.69	9.70	19.39	46.00	-26.61	Average
6	0.500	17.14	9.70	26.84	56.00	-29.16	QP
7	0.725	8.85	9.88	18.73	46.00	-27.27	Average
8	0.725	16.53	9.88	26.41	56.00	-29.59	QP
9	0.905	8.87	9.76	18.63	46.00	-27.37	Average
10	0.905	17.05	9.76	26.81	56.00	-29.19	QP
11	PP	1.245	10.15	9.71	19.86	46.00	-26.14
12	QP	1.245	18.22	9.71	27.93	56.00	-28.07


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

2#

**Measurement Data**

Live line:




Freq	Read		Level	Limit	Over	Remark	Pol/Phase	
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.405	9.37	9.61	18.98	47.75	-28.77	Average	Line
2	0.405	18.19	9.61	27.80	57.75	-29.95	QP	Line
3	0.555	8.40	9.76	18.16	46.00	-27.84	Average	Line
4	0.555	17.69	9.76	27.45	56.00	-28.55	QP	Line
5	0.765	9.15	9.86	19.01	46.00	-26.99	Average	Line
6	0.765	17.95	9.86	27.81	56.00	-28.19	QP	Line
7	1.040	9.72	9.81	19.53	46.00	-26.47	Average	Line
8	1.040	19.08	9.81	28.89	56.00	-27.11	QP	Line
9 PP	1.110	10.19	10.00	20.19	46.00	-25.81	Average	Line
10 QP	1.110	19.75	10.00	29.75	56.00	-26.25	QP	Line
11	1.375	9.22	10.59	19.81	46.00	-26.19	Average	Line
12	1.375	18.65	10.59	29.24	56.00	-26.76	QP	Line

**Remark:**

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




Freq	Read		Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.250	10.68	9.54	20.22	51.76	-31.54	Average
2	0.250	17.76	9.54	27.30	61.76	-34.46	QP
3	0.285	14.02	9.50	23.52	50.67	-27.15	Average
4 PP	0.285	31.09	9.50	40.59	60.67	-20.08	QP
5	0.590	8.22	9.79	18.01	46.00	-27.99	Average
6	0.590	15.67	9.79	25.46	56.00	-30.54	QP
7	0.860	8.66	9.79	18.45	46.00	-27.55	Average
8	0.860	15.97	9.79	25.76	56.00	-30.24	QP
9 AV	1.310	10.20	9.72	19.92	46.00	-26.08	Average
10	1.310	17.44	9.72	27.16	56.00	-28.84	QP
11	1.370	9.15	9.72	18.87	46.00	-27.13	Average
12	1.370	16.48	9.72	26.20	56.00	-29.80	QP

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

### 5.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)		
Test Method:	ANSI C63.10 2013		
Test Setup:			
	<i>Remark: Offset=Cable loss+ attenuation factor.</i>		
Limit:	30dBm		
Test Mode:	Transmitting with GFSK modulation.		
Test Results:	Pass		


#### Operated Mode for Worst Duty Cycle:

Test Mode	On time [Ton] (ms)	Period [Ttotal] ms)	Duty Cycle(%)	Average correction factor(dB)
GFSK 1Mbps	2.19	2.50	87.60	0.57

#### Remark:


- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor =  $10 * \log(1/ \text{Duty cycle})$ ;


Test Graph\_GFSK 1Mbps Duty Cycle:




**Measurement Data**

GFSK mode (1Mbps)			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	9.53	30.00	Pass
Middle	9.63	30.00	Pass
Highest	10.12	30.00	Pass







## 5.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)	
Test Method:	ANSI C63.10 2013	
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>	
Limit:	$\geq 500$ kHz	
Instruments Used:	Refer to section 4.11 for details.	
Test Results:	Pass	


### Measurement Data

GFSK mode (1Mbps)			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	0.66	$\geq 500$	Pass
Middle	0.67	$\geq 500$	Pass
Highest	0.67	$\geq 500$	Pass






## 5.5 Power Spectral Density


Test Requirement:	47 CFR Part 15C Section 15.247 (e)	
Test Method:	ANSI C63.10 2013	
Test Setup:	 <i>Remark: Offset=Cable loss+ attenuation factor.</i>	
Limit:	$\leq 8.00 \text{dBm}/3\text{kHz}$	
Test Mode:	Transmitting with GFSK modulation.	
Test Results:	Pass	

### Measurement Data


GFSK mode (1Mbps)			
Test channel	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
Lowest	-1.33	$\leq 8.00$	Pass
Middle	-0.90	$\leq 8.00$	Pass
Highest	-0.46	$\leq 8.00$	Pass

Test plot as follows:







## 5.6 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p><i>Remark: Offset=Cable loss+ attenuation factor.</i></p>
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass


TestMode	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Low	2402	9.30	-33.13	≤-10.7	PASS
	High	2480	9.91	-35.76	≤-10.09	PASS


**Test plot as follows:**



## 5.7 Spurious RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	
<i>Remark: Offset=Cable loss+ attenuation factor.</i>	
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Mode:	Transmitting with GFSK modulation.
Test Results:	Pass

Test plot as follows:








**Remark:**



Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

## 5.8 Radiated Spurious Emission & Restricted bands

### 5.8.1 Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.



Test Procedure:	<p>a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>Note: For the radiated emission test above 1GHz:</p> <p>Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both</p>
-----------------	--


	<p>horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <ul style="list-style-type: none"> <li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>g. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)</li> <li>h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.</li> <li>i. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Exploratory Test Mode:	<p>Transmitting with GFSK modulation.</p> <p>Transmitting mode.</p>
Final Test Mode:	<p>Through Pre-scan, find the 1Mbps of data type and GFSK modulation is the worst case.</p> <p>For below 1GHz part, through pre-scan, the worst case is the highest channel.</p> <p>Only the worst case is recorded in the report.</p>
Test Results:	Pass

Radiated Emission below 1GHz

30MHz~1GHz, the worst case

Test mode:	Transmitting mode	Horizontal
------------	-------------------	------------


1#



Freq	Read			Limit	Over	APOS	TPOS			
	Freq	Level	Factor					Pol/Phase		
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg	
1	51.12	9.71	13.78	23.49	40.00	-16.51	Peak	HORIZONTAL	100	326
2	435.59	11.70	19.96	31.66	46.00	-14.34	Peak	HORIZONTAL	100	271
3	501.18	12.93	21.84	34.77	46.00	-11.23	Peak	HORIZONTAL	100	50
4	711.67	11.24	24.49	35.73	46.00	-10.27	Peak	HORIZONTAL	100	360
5 pp	881.41	9.70	29.52	39.22	46.00	-6.78	Peak	HORIZONTAL	100	274
6	972.34	10.70	28.91	39.61	54.00	-14.39	Peak	HORIZONTAL	100	212


30MHz~1GHz, the worst case

Test mode:	Transmitting mode	Vertical
------------	-------------------	----------



Read	Freq	Level	Factor	Level	Limit	Over	Limit	Remark	APOS		TPOS	
									MHz	dBuV	dB/m	dBuV/m
1	46.50	10.60	13.17	23.77	40.00	-16.23	Peak		VERTICAL	100	250	
2	115.32	10.25	11.93	22.18	43.50	-21.32	Peak		VERTICAL	100	30	
3	284.98	10.79	17.34	28.13	46.00	-17.87	Peak		VERTICAL	100	331	
4	572.61	9.94	22.76	32.70	46.00	-13.30	Peak		VERTICAL	100	254	
5 pp	897.00	9.96	29.56	39.52	46.00	-6.48	Peak		VERTICAL	100	179	
6	965.54	10.57	28.85	39.42	54.00	-14.58	Peak		VERTICAL	100	330	


2#



Freq	Read			Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos	
	MHz	dBuV	dB/m							
1	50.59	9.44	13.78	23.22	40.00	-16.78	Peak	HORIZONTAL	100	151
2	98.83	9.01	12.79	21.80	43.50	-21.70	Peak	HORIZONTAL	100	256
3	501.18	11.82	21.84	33.66	46.00	-12.34	Peak	HORIZONTAL	100	325
4	807.43	11.10	27.39	38.49	46.00	-7.51	Peak	HORIZONTAL	100	285
5 pp	875.25	9.78	29.43	39.21	46.00	-6.79	Peak	HORIZONTAL	100	359
6	989.54	10.13	29.10	39.23	54.00	-14.77	Peak	HORIZONTAL	100	12

30MHz~1GHz, the worst case

Test mode:	Transmitting mode	Vertical
------------	-------------------	----------



Freq	Read			Limit Line	Over Limit	Remark	Pol/Phase	APos	TPos
	Level	Factor	Level						
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	50.06	9.09	13.77	22.86	40.00	-17.14 Peak	VERTICAL	100	152
2	209.31	10.72	13.27	23.99	43.50	-19.51 Peak	VERTICAL	100	186
3	511.84	10.23	21.94	32.17	46.00	-13.83 Peak	VERTICAL	100	221
4	603.54	11.44	22.84	34.28	46.00	-11.72 Peak	VERTICAL	100	271
5	729.36	11.23	24.70	35.93	46.00	-10.07 Peak	VERTICAL	100	329
6 pp	884.50	10.00	29.58	39.58	46.00	-6.42 Peak	VERTICAL	100	31

**Transmitter Emission above 1GHz**

Worse case mode:		GFSK(1Mbps)		Test channel:		Lowest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits	Over (dB)	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V	(m)	(Degree)
2390	53.93	-9.2	44.73	74	-29.27	Peak	H	1.5	79
2400	56.37	-9.39	46.98	74	-27.02	Peak	H	1.5	181
4804	53.57	-4.33	49.24	74	-24.76	Peak	H	1.5	243
7206	50.90	1.01	51.91	74	-22.09	Peak	H	1.5	257
2390	52.71	-9.2	43.51	74	-30.49	Peak	V	1.5	28
2400	51.19	-9.39	41.80	74	-32.20	Peak	V	1.5	235
4804	53.57	-4.33	49.24	74	-24.76	Peak	V	1.5	301
7206	50.05	1.01	51.06	74	-22.94	Peak	V	1.5	210

Worse case mode:		GFSK(1Mbps)		Test channel:		Middle			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits	Over (dB)	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V	(m)	(Degree)
4880	51.25	-4.11	47.14	74	-26.86	peak	H	1.5	184
7320	50.59	1.51	52.10	74	-21.90	peak	H	1.5	279
4880	53.73	-4.11	49.62	74	-24.38	peak	V	1.5	146
7320	48.41	1.51	49.92	74	-24.08	peak	V	1.5	108

Worse case mode:		GFSK(1Mbps)		Test channel:		Highest			
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits	Over (dB)	Detect or Type	Ant. Pol.	Antenna Height (m)	Table Angle (Degree)
							H/V	(m)	(Degree)
2483.5	55.77	-9.29	46.48	74	-27.52	Peak	H	1.5	100
4960	52.70	-4.04	48.66	74	-25.34	Peak	H	1.5	229
7440	50.78	1.57	52.35	74	-21.65	Peak	H	1.5	259
2483.5	55.37	-9.29	46.08	74	-27.92	Peak	V	1.5	142
4960	51.80	-4.04	47.76	74	-26.24	Peak	V	1.5	103
7440	51.04	1.57	52.61	74	-21.39	Peak	V	1.5	105

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## 6 Photographs - EUT Test Setup

### 6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:




Above 1GHz:



## 6.2 Conducted Emissions Test Setup




### 6.3 RF Conducted measurement




## 7 Photographs - EUT Constructional Details



1#
































2#















\*\*\* END OF REPORT \*\*\*