

FCC PART 15B, CLASS B TEST REPORT

For

JM Manufacturing Limited

Justen Centre, 1-3/F, 46-52 Wai Ching Street, Jordan Road, Kowloon, Hong Kong

FCC ID: 2AHGJJMS9803-T49

Report Type: Product Type:

Original Report MINI CAN R/C CAR

Report Number: RSZ161212832-00

Report Date: 2016-12-19

Jesse Huang

Reviewed By: Manager

Prepared By: Bay Area Compliance Laboratories Corp. (Kunshan)

No.248 Chenghu Road, Kunshan, Jiangsu province,

Jesse. Humf

China

Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
External I/O Cable	
BLOCK DIAGRAM OF TEST SETUP	e
SUMMARY OF TEST RESULTS	
TEST EQUIPMENT LIST	
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
Test Data	

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *JM Manufacturing Limited's* product, model number: *JMS-YZ9803-T (FCC ID: 2AHGJJMS9803-T49)* or the "EUT" in this report was a *MINI CAN R/C CAR*, which was measured approximately: 7.1 cm (L) \times 3.1 cm (W) \times 2.3 cm (H), rated with input voltage: DC 1.2V lithium battery. The highest operational frequency is 49 MHz.

Report No.: RSZ161212832-00

*All measurement and test data in this report was gathered from production sample serial number: 161212. (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2016-12-12.

Objective

This test report is prepared on behalf of *JM Manufacturing Limited in accordance* with Part 2-Subpart J, Part 15-Subparts A, B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC PART 15.235 DXX submissions with FCC ID: 2AHGJJMS9803-T491.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

	Item	Uncertainty		
AC Power Line	s Conducted Emissions	±3.26 dB		
Radiated emission	30MHz~1GHz	±5.91dB		
	Above 1G	±4.92dB		

FCC Part 15B, Class B Page 3 of 11

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Report No.: RSZ161212832-00

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15B, Class B Page 4 of 11

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Receiving & Running

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	
Nanfu	battery	AA	/	

Report No.: RSZ161212832-00


External I/O Cable

Cable Description	Length (m)	From/Port	То	
/	/	/	/	

FCC Part 15B, Class B Page 5 of 11

Block Diagram of Test Setup

For radiated emissions



Report No.: RSZ161212832-00

FCC Part 15B, Class B Page 6 of 11

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Not Applicable*
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ161212832-00

FCC Part 15B, Class B Page 7 of 11

^{*}Note: The EUT is powered by the batteries.

TEST EQUIPMENT LIST

Manufacturer	Description Model		Serial Number	Calibration Date	Calibration Due Date			
	Radiated Emission Test							
Sonoma Instrunent Amplifier 330 171377 2016-10-21 2016-10-21								
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-11-25	2016-11-25			
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08			
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR			
haojintech	Coaxial Cable	Cable-1	001	2016-09-08	2017-09-07			
haojintech	Coaxial Cable	Cable-2	002	2016-09-08	2017-09-07			
haojintech	Coaxial Cable	Cable-3	003	2016-09-08	2017-09-07			

Report No.: RSZ161212832-00

FCC Part 15B, Class B Page 8 of 11

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI)


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109

EUT Setup

Below 1GHz:



Report No.: RSZ161212832-00

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP	

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz.

FCC Part 15B, Class B Page 9 of 11

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RSZ161212832-00

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_{m} is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Layne Li on 2016-12-15.

FCC Part 15B, Class B Page 10 of 11

EUT Operation Mode: Receiving & Running

30 MHz – 1GHz:

Frequency (MHz) Reading (dBμV) (PK/QP/Ave.)	Turntable	Rx Antenna		Corrected	Corrected	FCC Part 15.109			
	8		Degree	Height (m)	Polar (H/V)	Factor (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.06	25.84	QP	109	1.5	V	-4.98	20.86	40	19.14
473.83	29.38	QP	45	1.8	Н	-7.21	22.17	46	23.83
542.18	29.86	QP	103	1.5	V	-5.36	24.50	46	21.50
700.38	29.79	QP	60	1.5	Н	-2.45	27.34	46	18.66
836.06	34.18	QP	298	1.9	Н	-1.59	32.59	46	13.41
849.25	35.26	QP	144	2.9	V	-1.59	33.67	46	12.33

Report No.: RSZ161212832-00

Note:

Corrected Amplitude = Corrected Factor + Reading
Corrected Factor=Antenna factor(RX)+cable loss - amplifier factor
Margin = Limit- Corr. Amplitude
All signals exceeding 20 microvolts/meter at 3 meters have been recorded.

***** END OF REPORT *****

FCC Part 15B, Class B Page 11 of 11