



FCC PART 15B, CLASS B **TEST REPORT**

For

JM Manufacturing Limited

Justen Centre, 1-3/F, 46-52 Wai Ching Street, Jordan Road, Kowloon, Hong Kong

FCC ID: 2AHGJJMSYZ621-49

Report Type: **Product Type:** Original Report RC BUMPER CAR

Report Number: RSZ170816832-00

Report Date: 2017-08-22

Hill He

Reviewed By: EMC Engineer

Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone,

HYM HR

Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	
TEST METHODOLOGY	
Measurement Uncertainty	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT Exercise Software	5
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	
EXTERNAL I/O CABLE	5
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	9
APPLICABLE STANDARD	9
EUT Setup	9
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	

Report No.: RSZ170816832-00

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *JM Manufacturing Limited's* product, model number: *JMSYZ300621 (FCC ID: 2AHGJJMSYZ621-49, UPC Number: 400028858469)* or the "EUT" in this report was a *RC BUMPER CAR*, which was measured approximately: 160 mm (L) x 110 mm (W) x 110 mm (H), rated with input voltage: DC 1.5V*3 batteries. The highest operating frequency is 49.865 MHz.

Report No.: RSZ170816832-00

* All measurement and test data in this report was gathered from production sample serial number: 20170818. (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-08-18.

Objective

This test report is prepared on behalf of *JM Manufacturing Limited* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC PART 15.235 DXX submissions with FCC ID: 2AHGJJMSYZ621-491

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Item			Expanded Measurement uncertainty
	30MHz~200MHz	Horizontal	4.58 dB (k=2, 95% level of confidence)
Radiated emission	30MHZ~200MHZ	Vertical	4.59 dB (k=2, 95% level of confidence)
	200MHz~1 GHz	Horizontal	4.83 dB (k=2, 95% level of confidence)
		Vertical	5.85 dB (k=2, 95% level of confidence)

FCC Part 15B, Class B Page 3 of 11

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Report No.: RSZ170816832-00

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS (Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP (Lab code: 200707-0), the FCC Designation No.CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

FCC Part 15B, Class B Page 4 of 11

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT Exercise Software

No exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Nanfu	Battery	5	N/A
JM	Remote control	JMSYZ300621	N/A

Report No.: RSZ170816832-00


External I/O Cable

Cable Description	Length (m)	From/Port	То	
/	/	/	/	

FCC Part 15B, Class B Page 5 of 11

Report No.: RSZ170816832-00

Block Diagram of Test Setup



FCC Part 15B, Class B Page 6 of 11

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Not Applicable*
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ170816832-00

Note:

Not Applicable*: The EUT is powered by battery.

FCC Part 15B, Class B Page 7 of 11

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Sunol Sciences	Bi-log Antenna	ЈВ1	A040904-2	2014-12-17	2017-12-17
TDK	Chamber	Chamber A	2#	2016-12-05	2019-12-05
НР	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
R&S	Auto test Software	EMC32	V9.10	NCR	NCR

Report No.: RSZ170816832-00

FCC Part 15B, Class B Page 8 of 11

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109

EUT Setup

Below 1GHz:



Report No.: RSZ170816832-00

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 1 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP	

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz.

FCC Part 15B, Class B Page 9 of 11

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: RSZ170816832-00

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Joson Xiao on 2017-08-21.

EUT Operation Mode: Receiving & Running (Receiving 49.865MHz Singal from Remote control)

FCC Part 15B, Class B Page 10 of 11

30 MHz – 1GHz:

Frequency Receiver	Turntable	Rx Antenna		Corrected		FCC Part 15B			
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree He	Height (m)	Polar (H/V)	Factor (dB/m)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
412.338750	30.61	QP	251.0	1.00	Н	0.1	30.71	46.00	15.29
443.572875	33.38	QP	285.0	1.18	Н	0.2	33.58	46.00	12.42
451.177875	33.01	QP	95.0	1.07	Н	0.3	33.31	46.00	12.69
505.399875	34.63	QP	308.0	2.00	Н	3.2	37.83	46.00	8.17
516.646125	30.20	QP	255.0	1.90	Н	3.6	33.80	46.00	12.20
695.437625	22.39	QP	30.0	1.19	V	6.5	28.89	46.00	17.11

Report No.: RSZ170816832-00

- Corrected Amplitude = Correction Factor + Reading
 Margin = Limit Corrected Amplitude

**** END OF REPORT ****

Page 11 of 11 FCC Part 15B, Class B