



# TEST REPORT

## FCC PART 15 SUBPART C 15.247

Test report  
On Behalf of  
**THUMBS UP (UK) LTD**  
For  
**Audiowave Neck Speaker**

**Model No.: SW-06WAVEGY**

**FCC ID: 2AHHESW-06WAVEBK**

**Prepared for :** **THUMBS UP (UK) LTD**  
**Unit L, Braintree Ind Est, Braintree Road, Ruislip, Middlesex. HA4 0EJ, UK**

**Prepared By :** **Shenzhen HUAK Testing Technology Co., Ltd.**  
**1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping  
Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China**

**Date of Test:** **Jan. 26, 2019 to Jan. 31, 2019**

**Date of Report:** **Feb. 15, 2019**

**Report Number:** **HK1902150247E**



## TEST RESULT CERTIFICATION

**Applicant's name** ..... THUMBS UP (UK) LTD

Address ..... Unit L, Braintree Ind Est, Braintree Road, Ruislip, Middlesex. HA4 0EJ, UK

**Manufacture's Name** ..... THUMBS UP (UK) LTD

Address ..... Unit L, Braintree Ind Est, Braintree Road, Ruislip, Middlesex. HA4 0EJ, UK

**Factory's Name** ..... THUMBS UP (UK) LTD

Address ..... Unit L, Braintree Ind Est, Braintree Road, Ruislip, Middlesex. HA4 0EJ, UK

### Product description

Trade Mark: N/A

Product name ..... Audiowave Neck Speaker

Model and/or type reference ... SW-06WAVEGY, SW-06WAVEBK

Difference description All the same except for the model name and appearance color

**Standards** ..... **47 CFR FCC Part 15 Subpart C 15.247**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :

Date (s) of performance of tests ..... : Jan. 26, 2019 to Jan. 31, 2019

Date of Issue ..... : Feb. 15, 2019

Test Result ..... : **Pass**

Testing Engineer : 

(Gary Qian)

Technical Manager : 

(Eden Hu)

Authorized Signatory : 

(Jason Zhou)



## TABLE OF CONTENTS

<b>1. SUMMARY .....</b>	<b>4</b>
1.1. TEST STANDARDS .....	4
1.2. TEST DESCRIPTION .....	4
TEST FACILITY .....	5
1.3. STATEMENT OF THE MEASUREMENT UNCERTAINTY .....	5
<b>2. GENERAL INFORMATION .....</b>	<b>6</b>
2.1. ENVIRONMENTAL CONDITIONS .....	6
2.2. GENERAL DESCRIPTION OF EUT .....	6
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY .....	6
2.4. RELATED SUBMITTAL(S) / GRANT(S) .....	8
2.5. MODIFICATIONS .....	8
2.6. RECEIVER INPUT BANDWIDTH .....	8
2.7. EXAMPLE OF A HOPPING SEQUENCE IN DATA MODE .....	8
2.8. EQUALLY AVERAGE USE OF FREQUENCIES AND BEHAVIOUR .....	8
2.9. EQUIPMENT USED .....	9
<b>3. PEAK OUTPUT POWER .....</b>	<b>10</b>
3.1. MEASUREMENT PROCEDURE .....	10
3.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	10
3.3. LIMITS AND MEASUREMENT RESULT .....	11
<b>4. 20DB BANDWIDTH .....</b>	<b>15</b>
4.1. MEASUREMENT PROCEDURE .....	15
4.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	15
4.3. LIMITS AND MEASUREMENT RESULTS .....	16
<b>5. CONDUCTED SPURIOUS EMISSION .....</b>	<b>20</b>
5.1. MEASUREMENT PROCEDURE .....	20
5.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	20
5.3. LIMITS AND MEASUREMENT RESULT .....	20
<b>6. RADIATED EMISSION .....</b>	<b>28</b>
6.1. MEASUREMENT PROCEDURE .....	28
6.2. TEST SETUP .....	30
6.3. LIMITS AND MEASUREMENT RESULT .....	31
<b>7. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>41</b>
7.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....	41
7.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST .....	41
7.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	42
7.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	42
7.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST .....	43
<b>8. NUMBER OF HOPPING FREQUENCY .....</b>	<b>45</b>
8.1. MEASUREMENT PROCEDURE .....	45
8.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	45
8.3. LIMITS AND MEASUREMENT RESULT .....	45
<b>9. TIME OF OCCUPANCY (DWELL TIME) .....</b>	<b>46</b>
9.1. MEASUREMENT PROCEDURE .....	46
9.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	46
9.3. LIMITS AND MEASUREMENT RESULT .....	46
<b>10. FREQUENCY SEPARATION .....</b>	<b>50</b>
10.1. MEASUREMENT PROCEDURE .....	50
10.2. TEST SETUP (BLOCK DIAGRAM OF CONFIGURATION) .....	50
10.3. LIMITS AND MEASUREMENT RESULT .....	50
<b>11. TEST SETUP PHOTOS OF THE EUT .....</b>	<b>51</b>
<b>12. APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>53</b>



## 1. SUMMARY

### 1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10:2013](#) : American National Standard for Testing Unlicensed Wireless Devices

### 1.2. Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(1)(i)	20dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(b)	Pseudorandom Frequency Hopping Sequence	PASS
FCC Part 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
FCC Part 15.247(a)(1)	Frequency Separation	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS



## Test Facility

### 1.3.1 Address of the test laboratory

Shenzhen HUAK Testing Technology Co., Ltd.

Address: 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Heping Community, Fuhai Street, Bao'an District, Shenzhen, China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

### 1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### IC Registration No.: 21210

The 3m alternate test site of Shenzhen HUAK Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of with Registration No.: 21210 on May 24, 2016.

#### FCC Registration No.: CN1229

Test Firm Registration Number : 616276

### 1.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen HUAK Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for HUAK laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)
Conducted Disturbance 0.15~30MHz	±3.20dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



## 2. GENERAL INFORMATION

### 2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2. General Description of EUT

Product Name:	Audiowave Neck Speaker
Model/Type reference:	SW-06WAVEGY
Power supply:	DC 3.7V by battery
Version:	V5.0
Modulation:	GFSK, π/4DQPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	0dBi
Hardware Version:	GLD-BT649-V1.0
Software Version:	V5.0

Note: For more details, refer to the user's manual of the EUT.

### 2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing.

There are 79 channels provided to the EUT and Channel 00/39/78 was selected for testing.

#### Operation Frequency :

Channel	Frequency (MHz)
00	2402
01	2403
:	:
38	2440
39	2441
40	2442
:	:
77	2479
78	2480

Note: The line display in grey were the channel selected for testing



NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal Operating (BT)


Note:

- 1.Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacturer.

Conducted Emission Configure :



Radiated Emission Configure :



Item	Equipment	Model No.	ID or Specification	Remark
1	Adapter	NTR-S01	DC 5V	Support



## 2.4. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.5. Modifications

No modifications were implemented to meet testing criteria.

## 2.6. Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHZ, In every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection(e.g. single or multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

## 2.7. Example of a Hopping Sequence in Data Mode

Example of a 79 hopping sequence in data mode:

40,21,44,23,42,53,46,55,48,33,52,35,50,65,54,67  
56,37,60,39,58,69,62,71,64,25,68,27,66,57,70,59  
72,29,76,31,74,61,78,63,01,41,05,43,03,73,07,75  
09,45,13,47,11,77,15,00,64,49,66,53,68,02,70,06  
01,51,03,55,05,04

## 2.8. Equally Average Use of Frequencies and Behaviour

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock

The LAP(lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP(upper address part) are the 24MSB's of the 48BD\_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior zation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire LAP(24 bits), 4LSB's(4bits)(Input 1) and the 27MSB's of the clock(Input 2) are used. With this input values different mathematical procedures(permuations, additions, XOR-operations)are performed to generate teSequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:

The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer(and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always Differ from the first one.



## 2.9. Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	R&S	ENV216	HKE-002	Dec. 27, 2018	1 Year
2.	Receiver	R&S	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
3.	RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 27, 2018	1 Year
4.	Horn Antenna	Schwarzbeck	BBHA 9170	HKE-090	Dec. 27, 2018	1 Year
5.	Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 27, 2018	1 Year
6.	Preamplifier	Schwarzbeck	BBV 9743	HKE-006	Dec. 27, 2018	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI 7	HKE-010	Dec. 27, 2018	1 Year
8.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	HKE-012	Dec. 27, 2018	1 Year
9.	Loop Antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 27, 2018	1 Year
10.	Horn Antenna	Schwarzbeck	9120D	HKE-013	Dec. 27, 2018	1 Year
11.	Pre-amplifier	EMCI	EMC051845 SE	HKE-015	Dec. 27, 2018	1 Year
12.	Pre-amplifier	Agilent	83051A	HKE-016	Dec. 27, 2018	1 Year
13.	EMI Test Software EZ-EMC	Tonscend	JS1120-B Version	HKE-083	Dec. 27, 2018	N/A
14.	Shielded room	Shiel Hong	4*3*3	HKE-039	Dec. 27, 2018	3 Year

The calibration interval was one year

### 3. Peak Output Power


#### 3.1. Measurement Procedure

For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
3. RBW > 20 dB bandwidth of the emission being measured.
4. VBW  $\geq$  RBW.
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.


Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

#### 3.2. Test Set-Up (Block Diagram of Configuration)



### 3.3. Limits and Measurement Result

PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	4.176	30	Pass
2.441	4.065	30	Pass
2.480	3.809	30	Pass






CH39



CH78





**PEAK OUTPUT POWER MEASUREMENT RESULT  
FOR  $\Pi/4$ -DQPSK MODULATION**

Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	4.662	30	Pass
2.441	4.615	30	Pass
2.480	4.376	30	Pass





CH39



CH78




## 4. 20dB Bandwidth

### 4.1. Measurement Procedure

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel  
The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 4.2. Test Set-Up (Block Diagram of Configuration)






### 4.3. Limits and Measurement Results


MEASUREMENT RESULT FOR GFSK MODULATION			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	0.9474	PASS
	Middle Channel	0.9478	PASS
	High Channel	0.9462	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL





## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




**MEASUREMENT RESULT FOR  $\Pi/4$ -DQPSK MODULATION**

<b>Applicable Limits</b>	<b>Measurement Result</b>		
	<b>Test Data (MHz)</b>		<b>Criteria</b>
N/A	Low Channel	1.314	PASS
	Middle Channel	1.313	PASS
	High Channel	1.312	PASS

**TEST PLOT OF BANDWIDTH FOR LOW CHANNEL**



## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL





## 5. Conducted Spurious Emission

### 5.1. Measurement Procedure

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.  
RBW = 100 kHz; VBW= 300 kHz; Sweep = auto; Detector function = peak.
4. Set SPA Trace 1 Max hold, then View.

### 5.2. Test Set-Up (Block Diagram of Configuration)

The same as described in section 4.2


### 5.3. Limits and Measurement Result

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS




## TEST RESULT FOR ENTIRE FREQUENCY RANGE

### TEST PLOT OF OUT OF BAND EMISSIONS WITH THE WORST CASE OF GFSK MODULATION IN LOW CHANNEL





### TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN MIDDLE CHANNEL






### TEST PLOT OF OUT OF BAND EMISSIONS OF GFSK MODULATION IN HIGH CHANNEL




Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit. The GFSK modulation is the worst case and only those data recorded in the report.



# TEST RESULT FOR BAND EDGE GFSK MODULATION IN LOW CHANNEL Hopping off




## Hopping on






# GFSK MODULATION IN HIGH CHANNEL Hopping off




## Hopping on





# Π/4-DQPSK MODULATION IN LOW CHANNEL Hopping off



## Hopping on





## Π/4-DQPSK MODULATION IN HIGH CHANNEL Hopping off



## Hopping on





## 6. Radiated Emission

### 6.1. Measurement Procedure

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.




The following table is the setting of spectrum analyzer and receiver.

<b>Spectrum Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/10Hz for Average


<b>Receiver Parameter</b>	<b>Setting</b>
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

## 6.2. Test Setup


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





### 6.3. Limits and Measurement Result

15.209&RSS-GEN Limit in the below table has to be followed

<b>Frequencies (MHz)</b>	<b>Field Strength (micorvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.

**RADIATED EMISSION BELOW 30MHZ**

No emission found between lowest internal used/generated frequencies to 30MHz.

**RADIATED EMISSION BELOW 1GHZ**

<b>EUT</b>	Audiowave Neck Speaker	<b>Model Name</b>	SW-06WAVEGY
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 4	<b>Antenna</b>	Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		46.1667	1.20	19.87	21.07	40.00	-18.93	peak			
2		204.6000	8.53	16.33	24.86	43.50	-18.64	peak			
3		523.0833	2.19	25.44	27.63	46.00	-18.37	peak			
4		692.8333	2.89	28.06	30.95	46.00	-15.05	peak			
5		823.7833	2.71	30.72	33.43	46.00	-12.57	peak			
6	*	948.2667	3.54	32.12	35.66	46.00	-10.34	peak			

**RESULT: PASS**

<b>EUT</b>	Audiowave Neck Speaker	<b>Model Name</b>	SW-06WAVEGY
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 4	<b>Antenna</b>	Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7333	12.43	14.95	27.38	40.00	-12.62	peak			
2		177.1167	4.66	17.43	22.09	43.50	-21.41	peak			
3		469.7333	2.72	24.38	27.10	46.00	-18.90	peak			
4		626.5500	3.35	27.27	30.62	46.00	-15.38	peak			
5		783.3667	3.47	30.03	33.50	46.00	-12.50	peak			
6	*	924.0167	4.09	31.91	36.00	46.00	-10.00	peak			

### RESULT: PASS

**Note:** 1. Factor=Antenna Factor+ Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 4 is the worst case and recorded in the report.

**RADIATED EMISSION ABOVE 1GHZ**

<b>EUT</b>	Audiowave Neck Speaker	<b>Model Name</b>	SW-06WAVEGY
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4804.062	46.39	3.76	50.15	74.00	-23.85	peak
4804.062	44.56	3.76	48.32	54.00	-5.68	AVG
7206.093	34.98	8.17	43.15	74.00	-30.85	peak
7206.093	31.94	8.17	40.11	54.00	-13.89	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	Audiowave Neck Speaker	<b>Model Name</b>	SW-06WAVEGY
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4804.062	48.41	3.76	52.17	74.00	-21.83	peak
4804.062	44.39	3.76	48.15	54.00	-5.85	AVG
7206.093	36.88	8.17	45.05	74.00	-28.95	peak
7206.093	35.66	8.17	43.83	54.00	-10.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



<b>EUT</b>	Audiowave Neck Speaker		<b>Model Name</b>	SW-06WAVEGY	
<b>Temperature</b>	25°C		<b>Relative Humidity</b>	55.4%	
<b>Pressure</b>	960hPa		<b>Test Voltage</b>	Normal Voltage	
<b>Test Mode</b>	Mode 2		<b>Antenna</b>	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4882.062	48.19	3.78	51.97	74.00	-22.03	peak
4882.062	43.54	3.78	47.32	54.00	-6.68	AVG
7323.093	39.82	8.23	48.05	74.00	-25.95	peak
7323.093	37.99	8.23	46.22	54.00	-7.78	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	Audiowave Neck Speaker		<b>Model Name</b>	SW-06WAVEGY	
<b>Temperature</b>	25°C		<b>Relative Humidity</b>	55.4%	
<b>Pressure</b>	960hPa		<b>Test Voltage</b>	Normal Voltage	
<b>Test Mode</b>	Mode 2		<b>Antenna</b>	Vertical	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4882.062	46.32	3.78	50.10	74.00	-23.90	peak
4882.062	43.40	3.78	47.18	54.00	-6.82	AVG
7323.093	38.28	8.23	46.51	74.00	-27.49	peak
7323.093	34.85	8.23	43.08	54.00	-10.92	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



<b>EUT</b>	Audiowave Neck Speaker		<b>Model Name</b>	SW-06WAVEGY	
<b>Temperature</b>	25°C		<b>Relative Humidity</b>	55.4%	
<b>Pressure</b>	960hPa		<b>Test Voltage</b>	Normal Voltage	
<b>Test Mode</b>	Mode 3		<b>Antenna</b>	Horizontal	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4960.062	47.34	3.81	51.15	74.00	-22.85	peak
4960.062	44.94	3.81	48.75	54.00	-5.25	AVG
7440.093	39.63	8.27	47.90	74.00	-26.10	peak
7440.093	36.79	8.27	45.06	54.00	-8.94	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

<b>EUT</b>	Audiowave Neck Speaker		<b>Model Name</b>	SW-06WAVEGY	
<b>Temperature</b>	25°C		<b>Relative Humidity</b>	55.4%	
<b>Pressure</b>	960hPa		<b>Test Voltage</b>	Normal Voltage	
<b>Test Mode</b>	Mode 3		<b>Antenna</b>	Vertical	

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dB $\mu$ V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4960.062	46.70	3.81	50.51	74.00	-23.49	peak
4960.062	44.91	3.81	48.72	54.00	-5.28	AVG
7440.093	38.78	8.27	47.05	74.00	-26.95	peak
7440.093	37.71	8.27	45.98	54.00	-8.02	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

**RESULT: PASS****Note:**

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.


Factor=Antenna Factor+ Cable loss-Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

All test modes had been tested. The GFSK modulation is the worst case and recorded in the report.

**TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS**

<b>EUT</b>	Audiowave Neck Speaker	<b>Model Name</b>	SW-06WAVEGY
<b>Temperature</b>	25°C	<b>Relative Humidity</b>	55.4%
<b>Pressure</b>	960hPa	<b>Test Voltage</b>	Normal Voltage
<b>Test Mode</b>	Mode 1	<b>Antenna</b>	Horizontal

**PK**

**AV**

**RESULT: PASS**