



# RADIO TEST REPORT

## FCC ID: 2AHHW-BRILLIANCE323

**Product:** bluetooth speaker

**Trade Mark:** NEUS

**Model No.:** Brilliance323

**Serial Model:** N/A

**Report No.:** NTEK- 2015NT12313715F1

**Issue Date:** 13 Jun 2017

### Prepared for

Neusound Co.,Ltd.

A Zone Floor5th Building 4 JuHui Industrial Area TianLiao Town  
GuangMing District, Shenzhen City,China

### Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,  
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 6588

Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>

**TABLE OF CONTENTS**

<b>1</b>	<b>TEST RESULT CERTIFICATION .....</b>	<b>3</b>
<b>2</b>	<b>SUMMARY OF TEST RESULTS.....</b>	<b>4</b>
<b>3</b>	<b>FACILITIES AND ACCREDITATIONS .....</b>	<b>5</b>
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS .....	5
3.3	MEASUREMENT UNCERTAINTY .....	5
<b>4</b>	<b>GENERAL DESCRIPTION OF EUT .....</b>	<b>6</b>
<b>5</b>	<b>DESCRIPTION OF TEST MODES .....</b>	<b>8</b>
<b>6</b>	<b>SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
<b>7</b>	<b>TEST REQUIREMENTS .....</b>	<b>13</b>
7.1	CONDUCTED EMISSIONS TEST .....	13
7.2	RADIATED SPURIOUS EMISSION .....	18
7.3	NUMBER OF HOPPING CHANNEL.....	27
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT .....	29
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	35
7.6	20DB BANDWIDTH TEST .....	42
7.7	PEAK OUTPUT POWER .....	48
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	54
7.9	ANTENNA APPLICATION .....	62

## 1 TEST RESULT CERTIFICATION

Applicant's name .....	Neusound Co.,Ltd.
Address .....	A Zone Floor5th Building 4 JuHui Industrial Area TianLiao Town GuangMing District, Shenzhen City,China
Manufacturer's Name .....	Neusound Co.,Ltd.
Address .....	A Zone Floor5th Building 4 JuHui Industrial Area TianLiao Town GuangMing District, Shenzhen City,China
Product description	
Product name .....	bluetooth speaker
Model and/or type reference .....	Brilliance323
Serial Model .....	N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2016 FCC 47 CFR Part 15, Subpart C:2016 KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013 DA 00-705	Complied


This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 31 May. 2017 ~ 13 Jun. 2017

Testing Engineer :   
(Susan Su)

Technical Manager :   
(Jason Chen)

Authorized Signatory :   
(Sam Chen)

**2 SUMMARY OF TEST RESULTS****FCC Part15 (15.247), Subpart C**

Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

## Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

### 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

##### Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)  
The Certificate Registration Number is L5516.

FCC- Accredited Test Firm Registration Number: 463705.  
Designation Number: CN1184

A2LA-Lab. The Certificate Registration Number is 4298.01  
This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009)

Accredited by Industry Canada, August 29, 2012  
The Certificate Registration Number is 9270A-1.

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd  
Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

#### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$

**4 GENERAL DESCRIPTION OF EUT**

Product Feature and Specification	
Equipment	bluetooth speaker
Trade Mark	NEUS
FCC ID	2AHHW-BRILLIANCE323
Model No.	Brilliance323
Serial Model	N/A
Model Difference	N/A
Operating Frequency	2402MHz~2480MHz
Modulation	GFSK,π/4-DQPSK, 8DPSK
Number of Channels	79 Channels
Antenna Type	PCB Antenna
Antenna Gain	1 dBi
Power supply	<input checked="" type="checkbox"/> Adapter supply: Model: PSED150150U W Input: 100-240V~, 50/60Hz, 0.6A Output: 15V---1.5A
HW Version	N/A
SW Version	N/A

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

## Revision History

## 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for  $\pi/4$ -DQPSK modulation; 3Mbps for 8DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note:  $f_c = 2402\text{MHz} + k \times 1\text{MHz}$   $k=0 to 78$

The following summary table is showing all test modes to demonstrate in compliance with the standard.

### For AC Conducted Emission

Final Test Mode	Description
Mode 1	Normal link

Note: AC power line Conducted Emission was tested under maximum output power.

### For Radiated Test Cases

Final Test Mode	Description
Mode 1	Normal link
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

### For Conducted Test Cases


Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

## 6 SETUP OF EQUIPMENT UNDER TEST

### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



## 6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	bluetooth speaker	NEUS	Brilliance323	2AHHW-BRILLIAN CE323	EUT
E-2	Adapter	N/A	PSED150150U W	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Adapter line	NO	NO	1.2m
C-2	RF Cable	NO	NO	0.5m

### Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

**6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS**

## Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.04.09	2018.04.08	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2016.11.10	2017.11.09	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2017.04.09	2018.04.08	1 year
4	Test Receiver	R&S	ESPI	101318	2017.04.09	2018.04.08	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2017.04.09	2018.04.08	1 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2017.04.09	2018.04.08	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.04.09	2018.04.08	1 year
9	Amplifier	EMC	EMC051835 SE	980246	2016.08.09	2017.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35-HG	177156	2017.04.09	2018.04.08	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2017.04.09	2018.04.08	1 year
12	Power Meter	DARE	RPR3006W	15I00041SN O84	2016.08.09	2017.08.08	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

## Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.04.09	2018.04.08	1 year
2	LISN	R&S	ENV216	101313	2017.04.19	2018.04.18	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2017.04.09	2018.04.08	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2017.04.09	2018.04.08	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

1	Filter	TRILTHIC	2400MHz	29	2017.04.19	2018.04.18	1 year
---	--------	----------	---------	----	------------	------------	--------

Note: Each piece of equipment is scheduled for calibration once a year.

## 7 TEST REQUIREMENTS

### 7.1.1 CONDUCTED EMISSIONS TEST

#### 7.1.2 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.3 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. \*Decreases with the logarithm of the frequency  
 2. The lower limit shall apply at the transition frequencies  
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.4 Test Configuration



#### 7.1.5 Test Procedure


According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 7.1.6 Test Results

Pass


### 7.1.7 Test Results



Site: **L1** Temperature: 26  
Limit: FCC Part 15B (0.15-30MHz) Main QP Power: AC 120V/60Hz Humidity: 56 %  
Mode: Normal link

Note:

No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1		0.3140	34.18	10.12	44.30	59.86	-15.56	QP	
2		0.3140	21.61	10.12	31.73	49.86	-18.13	AVG	
3		0.6540	32.19	9.81	42.00	56.00	-14.00	QP	
4	*	0.6540	26.49	9.81	36.30	46.00	-9.70	AVG	
5		1.3020	30.97	9.83	40.80	56.00	-15.20	QP	
6		1.3020	25.21	9.83	35.04	46.00	-10.96	AVG	
7		2.3380	29.96	9.74	39.70	56.00	-16.30	QP	
8		2.3380	20.37	9.74	30.11	46.00	-15.89	AVG	
9		8.7256	37.05	9.75	46.80	60.00	-13.20	QP	
10		8.7256	26.35	9.75	36.10	50.00	-13.90	AVG	
11		12.6457	38.32	9.78	48.10	60.00	-11.90	QP	
12		12.6457	26.13	9.78	35.91	50.00	-14.09	AVG	




Site Phase: **N** Temperature: 26

Limit: FCC Part 15B (0.15-30MHz) \_Main\_QP Power: AC 120V/60Hz

Mode: Normal link Humidity: 56 %

Note:

No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level dBuV	Factor dB	ment dBuV				
1		0.1660	41.05	10.06	51.11	65.15	-14.04	QP	
2		0.1660	26.03	10.06	36.09	55.15	-19.06	AVG	
3		0.4020	31.57	10.05	41.62	57.81	-16.19	QP	
4		0.4020	22.36	10.05	32.41	47.81	-15.40	AVG	
5		0.9778	18.83	9.87	28.70	56.00	-27.30	QP	
6		0.9778	11.42	9.87	21.29	46.00	-24.71	AVG	
7		4.4378	25.40	9.72	35.12	56.00	-20.88	QP	
8		4.4378	12.05	9.72	21.77	46.00	-24.23	AVG	
9		8.3817	35.25	9.75	45.00	60.00	-15.00	QP	
10 *		8.3817	30.87	9.75	40.62	50.00	-9.38	AVG	
11		11.4379	37.93	9.77	47.70	60.00	-12.30	QP	
12		11.4379	27.62	9.77	37.39	50.00	-12.61	AVG	




Site: Phase: **L1** Temperature: 26  
Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 240V/50Hz Humidity: 56 %

Mode: Normal link

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over Detector	Over	
								Comment	
1		0.3140	34.18	10.12	44.30	59.86	-15.56	QP	
2		0.3140	28.07	10.12	38.19	49.86	-11.67	AVG	
3		0.3996	30.33	10.05	40.38	57.86	-17.48	QP	
4	*	0.3996	28.33	10.05	38.38	47.86	-9.48	AVG	
5		0.9858	28.33	9.87	38.20	56.00	-17.80	QP	
6		0.9858	23.10	9.87	32.97	46.00	-13.03	AVG	
7		5.8578	35.07	9.73	44.80	60.00	-15.20	QP	
8		5.8578	23.94	9.73	33.67	50.00	-16.33	AVG	
9		8.7256	37.05	9.75	46.80	60.00	-13.20	QP	
10		8.7256	26.35	9.75	36.10	50.00	-13.90	AVG	
11		13.6819	36.91	9.79	46.70	60.00	-13.30	QP	
12		13.6819	14.91	9.79	24.70	50.00	-25.30	AVG	



Site: Phase: **N** Temperature: 26  
Limit: FCC Part 15B\_(0.15-30MHz) \_Main\_QP Power: AC 240V/50Hz Humidity: 56 %  
Mode: Normal link  
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dB	Over Detector	Comment	
								Over	Detector
1		0.1859	37.18	10.04	47.22	64.21	-16.99	QP	
2		0.1859	20.27	10.04	30.31	54.21	-23.90	AVG	
3		0.4259	28.91	9.99	38.90	57.33	-18.43	QP	
4		0.4259	23.01	9.99	33.00	47.33	-14.33	AVG	
5		1.4415	22.88	9.82	32.70	56.00	-23.30	QP	
6		1.4415	7.99	9.82	17.81	46.00	-28.19	AVG	
7		8.0975	35.55	9.75	45.30	60.00	-14.70	QP	
8		8.0975	26.58	9.75	36.33	50.00	-13.67	AVG	
9		11.3139	38.03	9.77	47.80	60.00	-12.20	QP	
10	*	11.3139	29.98	9.77	39.75	50.00	-10.25	AVG	
11		15.2939	35.59	9.81	45.40	60.00	-14.60	QP	
12		15.2939	29.54	9.81	39.35	50.00	-10.65	AVG	

### 7.1.8 RADIATED SPURIOUS EMISSION

#### 7.1.9 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

#### 7.1.10 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength ( $\text{dB}\mu\text{V/m}$ )	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490~1.705	2400/F(KHz)	20 log ( $\mu$ V/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

#### Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B ( $\text{dB}\mu\text{V/m}$ ) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in  $\text{dB}\mu\text{V/m}$ = $20 \log (\mu\text{V/m})$


2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})(\text{dB})$ ;
- Limit line= $\text{Specific limits}(\text{dB}\mu\text{V}) + \text{distance extrapolation factor}$ .

#### 7.1.11 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

### 7.1.12 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



### 7.1.13 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =  $10 \cdot \lg(100 \text{ [kHz]}/\text{narrower RBW [kHz]})$ . , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

**7.1.14 Test Results****■ Spurious Emission below 30MHz (9KHz to 30MHz)**

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--


Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $20\log(\text{Specific distance/ test distance})(\text{ dB})$ ;

Limit line=Specific limits(dBuV) + distance extrapolation factor

## ■ Spurious Emission below 1GHz (30MHz to 1GHz)

All the modulation modes have been tested, and the worst result was report as below:



Site

Polarization: **Vertical**

Temperature: 24

Limit: FCC\_PART15\_B\_03m\_QP


Power: AC 120V/60Hz

Humidity: 50 %

Mode: Normal link

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Degree
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1	!	34.0363	18.27	17.53	35.80	40.00	-4.20	QP		
2	!	36.8952	19.59	16.41	36.00	40.00	-4.00	QP		
3	*	51.4806	27.73	9.07	36.80	40.00	-3.20	QP		
4		125.8863	25.40	10.70	36.10	43.50	-7.40	QP		
5		134.0882	25.65	10.95	36.60	43.50	-6.90	QP		
6		241.6762	17.53	10.70	28.23	46.00	-17.77	QP		



Site

Polarization: *Horizontal*

Temperature: 24

Limit: FCC\_PART15\_B\_03m\_QP

Power: AC 120V/60Hz

Humidity: 50 %

Mode: Normal link

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	Degree
			Level	Factor	ment					
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	Comment
1		32.5197	13.20	18.51	31.71	40.00	-8.29	QP		
2		56.9911	19.35	6.44	25.79	40.00	-14.21	QP		
3	*	147.4036	24.50	11.48	35.98	43.50	-7.52	QP		
4		177.5091	21.97	12.11	34.08	43.50	-9.42	QP		
5		241.6762	19.68	10.70	30.38	46.00	-15.62	QP		
6		330.1949	17.40	13.65	31.05	46.00	-14.95	QP		

## ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Remark	Comment
Low Channel (2402 MHz)-Above 1G							
4804.186	56.68	-3.64	60.32	74.00	-13.68	Pk	Vertical
4804.186	43.57	-3.64	47.21	54.00	-6.79	AV	Vertical
7206.483	54.26	-0.95	55.21	74.00	-18.79	Pk	Vertical
7206.483	41.69	-0.95	42.64	54.00	-11.36	AV	Vertical
4804.238	60.62	-3.64	64.26	74.00	-9.74	Pk	Horizontal
4804.238	44.48	-3.64	48.12	54.00	-5.88	AV	Horizontal
7206.176	55.83	-0.95	56.78	74.00	-17.22	Pk	Horizontal
7206.176	38.83	-0.95	39.78	54.00	-14.22	AV	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.106	58.25	-3.68	61.93	74.00	-12.07	Pk	Vertical
4882.106	42.69	-3.68	46.37	54.00	-7.63	AV	Vertical
7323.231	55.34	-0.82	56.16	74.00	-17.84	Pk	Vertical
7323.231	43.69	-0.82	44.51	54.00	-9.49	AV	Vertical
4882.357	60.28	-3.68	63.96	74.00	-10.04	Pk	Horizontal
4882.357	41.41	-3.68	45.09	54.00	-8.91	AV	Horizontal
7323.152	57.58	-0.82	58.40	74.00	-15.60	Pk	Horizontal
7323.152	43.67	-0.82	44.49	54.00	-9.51	AV	Horizontal
High Channel (2480 MHz)- Above 1G							
4960.102	60.14	-3.59	63.73	74.00	-10.27	Pk	Vertical
4960.102	43.59	-3.59	47.18	54.00	-6.82	AV	Vertical
7440.374	54.92	-0.68	55.60	74.00	-18.40	Pk	Vertical
7440.374	39.12	-0.68	39.80	54.00	-14.20	AV	Vertical
4960.305	59.45	-3.59	63.04	74.00	-10.96	Pk	Horizontal
4960.305	41.56	-3.59	45.15	54.00	-8.85	AV	Horizontal
7440.214	54.87	-0.68	55.55	74.00	-18.45	Pk	Horizontal
7440.214	38.95	-0.68	39.63	54.00	-14.37	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3)All other emissions more than 20dB below the limit.

**■ Spurious Emission in Band edge**

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Susan Su

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	52.68	-13.06	39.62	74.00	-34.38	Pk	Vertical
2390	51.57	-13.06	38.51	74.00	-35.49	Pk	Horizontal
2483.5	56.17	-12.78	43.39	74.00	-30.61	Pk	Vertical
2483.5	57.68	-12.78	44.90	74.00	-29.10	Pk	Horizontal
1Mbps hopping							
2390	56.27	-13.06	43.21	74.00	-30.79	Pk	Vertical
2390	57.65	-13.06	44.59	74.00	-29.41	Pk	Horizontal
2483.5	58.46	-12.78	45.68	74.00	-28.32	Pk	Vertical
2483.5	57.15	-12.78	44.37	74.00	-29.63	Pk	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

## ■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
3260	30.56	-13.06	17.5	74	-56.5	Pk	Vertical
3260	57.73	-13.06	44.67	54	-9.33	AV	Vertical
3260	58.93	-13.06	45.87	74	-28.13	Pk	Horizontal
3260	52.26	-13.06	39.2	54	-14.8	AV	Horizontal
3332	63.37	-12.78	50.59	74	-23.41	Pk	Vertical
3332	49.62	-12.78	36.84	54	-17.16	AV	Vertical
3332	60.52	-12.78	47.74	74	-26.26	Pk	Horizontal
3332	50.4	-12.78	37.62	54	-16.38	AV	Horizontal
17789	63.82	-12.24	51.58	74	-22.42	Pk	Vertical
17789	53.5	-12.24	41.26	54	-12.74	AV	Vertical
17957	64.31	-12.24	52.07	74	-21.93	Pk	Horizontal
17957	54.26	-12.24	42.02	54	-11.98	AV	Horizontal
1Mbps hopping							
3260	60.81	-13.06	47.75	74	-26.25	Pk	Vertical
3260	50.39	-13.06	37.33	54	-16.67	AV	Vertical
3260	59.37	-13.06	46.31	74	-27.69	Pk	Horizontal
3260	50.06	-13.06	37	54	-17	AV	Horizontal
3332	61.16	-12.78	48.38	74	-25.62	Pk	Vertical
3332	48.29	-12.78	35.51	54	-18.49	AV	Vertical
3332	62.48	-12.78	49.7	74	-24.3	Pk	Horizontal
3332	50.45	-12.78	37.67	54	-16.33	AV	Horizontal
17781	63.19	-12.24	50.95	74	-23.05	Pk	Vertical
17781	53.42	-12.24	41.18	54	-12.82	AV	Vertical
17955	64.23	-12.24	51.99	74	-22.01	Pk	Horizontal
17955	54.22	-12.24	41.98	54	-12.02	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

**7.1.15 NUMBER OF HOPPING CHANNEL****7.1.16 Applicable Standard**

According to FCC Part 15.247(a)(1) (iii)and DA 00-705

**7.1.17 Conformance Limit**

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

**7.1.18 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.1.19 Test Setup**

Please refer to Section 6.1 of this test report.

**7.1.20 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto


Detector function = peak

Trace = max hold

**7.1.21 Test Results**

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Number of Hopping (Channel)	Adaptive Frequency hopping (Channel)	limit	Verdict
79	20	$\geq 15$	Pass



### 7.1.22 HOPPING CHANNEL SEPARATION MEASUREMENT

#### 7.1.23 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

#### 7.1.24 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

#### 7.1.25 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.1.26 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.1.27 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW  $\geq$  30KHz

VBW  $\geq$  3\*RBW

Sweep = auto

Detector function = peak

Trace = max hold


#### 7.1.28 Test Results

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	1.004	>878.349	20dB BW
	39	2441	1.000	>879.626	20dB BW
	78	2480	1.000	>873.188	20dB BW
$\pi/4$ -DQPSK	0	2402	1.000	>813.333	2/3 of 20dB BW
	39	2441	1.000	>812.000	2/3 of 20dB BW
	78	2480	1.000	>812.667	2/3 of 20dB BW
8DPSK	0	2402	1.000	>808.000	2/3 of 20dB BW
	39	2441	1.004	>807.333	2/3 of 20dB BW
	78	2480	1.004	>809.333	2/3 of 20dB BW


Channel Separation plot on channel 00-01


1Mbps



Channel Separation plot on channel 39-40


1Mbps






Channel Separation plot on channel 39-40

2Mbps




Channel Separation plot on channel 77-78

2Mbps




Channel Separation plot on channel 00-01


3Mbps



Channel Separation plot on channel 39-40

3Mbps





**7.1.29 AVERAGE TIME OF OCCUPANCY (DWELL TIME)****7.1.30 Applicable Standard**

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

**7.1.31 Conformance Limit**

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

**7.1.32 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.1.33 Test Setup**

Please refer to Section 6.1 of this test report.

**7.1.34 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW  $\geq$  1MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

Set the EUT for DH5, DH3 and DH1 packet transmitting.

Measure the maximum time duration of one single pulse.

### 7.1.35 Test Results

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Modulation Mode	Channel Number	Packet type	Mode	Hops Over Occupancy Time (ms)	Pulse width (ms)	dwell time (ms)	Limit (ms)	Verdict
GFSK	39	DH1	Normal	320.00	0.435	139.200	<400	PASS
	39		AFH	160.00	0.435	69.600	<400	PASS
	39	DH3	Normal	160.00	0.898	143.680	<400	PASS
	39		AFH	80.00	0.898	71.840	<400	PASS
	39	DH5	Normal	106.67	2.965	316.277	<400	PASS
	39		AFH	53.33	2.965	158.123	<400	PASS
$\pi/4$ -DQPSK	39	2DH1	Normal	320.00	0.449	143.680	<400	PASS
	39		AFH	160.00	0.449	71.840	<400	PASS
	39	2DH3	Normal	160.00	1.714	274.240	<400	PASS
	39		AFH	80.00	1.714	137.120	<400	PASS
	39	2DH5	Normal	106.67	2.951	314.783	<400	PASS
	39		AFH	53.33	2.951	157.377	<400	PASS
8DPSK	39	3DH1	Normal	320.00	0.462	147.840	<400	PASS
	39		AFH	160.00	0.462	73.920	<400	PASS
	39	3DH3	Normal	160.00	1.700	272.000	<400	PASS
	39		AFH	80.00	1.700	136.000	<400	PASS
	39	3DH5	Normal	106.67	2.951	314.783	<400	PASS
	39		AFH	53.33	2.951	157.377	<400	PASS

Note:

A Period Time = (channel number)\*0.4


DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)


DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)


DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)


For Example:


1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time











**7.1.36 20DB BANDWIDTH TEST****7.1.37 Applicable Standard**

According to FCC Part 15.247(a)(1) and DA 00-705

**7.1.38 Conformance Limit**

No limit requirement.

**7.1.39 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.1.40 Test Setup**

Please refer to Section 6.1 of this test report.

**7.1.41 Test Procedure**

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

**7.1.42 Test Results**

EUT:	bluetooth speaker	Model No.:	Brilliance323	
Temperature:	20 °C	Relative Humidity:	48%	
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su	


Test Channel	Frequency (MHz)	Measurement Bandwidth (KHz)	Limit (kHz)	Verdict
<b>1Mbps</b>				
00	2402	878.349	N/A	PASS
39	2441	879.626	N/A	PASS
78	2480	873.188	N/A	PASS
<b>2Mbps</b>				
00	2402	1220.000	N/A	PASS
39	2441	1218.000	N/A	PASS
78	2480	1219.000	N/A	PASS
<b>3Mbps</b>				
00	2402	1212.000	N/A	PASS
39	2441	1211.000	N/A	PASS
78	2480	1214.000	N/A	PASS

Note: N/A (Not Applicable)




## 20dB Bandwidth plot on channel 78

1Mbps





## 20dB Bandwidth plot on channel 00

2Mbps









**7.1.43 PEAK OUTPUT POWER****7.1.44 Applicable Standard**

According to FCC Part 15.247(b)(1) and DA 00-705

**7.1.45 Conformance Limit**

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

**7.1.46 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.1.47 Test Setup**

Please refer to Section 6.1 of this test report.

**7.1.48 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  the 20 dB bandwidth of the emission being measured

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold


**7.1.49 Test Results**

EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict
<b>1Mbps</b>					
00	2402	Default	2.16	30	PASS
39	2441	Default	3.93	30	PASS
78	2480	Default	3.97	30	PASS
<b>2Mbps</b>					
00	2402	Default	2.30	20.97	PASS
39	2441	Default	2.30	20.97	PASS
78	2480	Default	2.87	20.97	PASS
<b>3Mbps</b>					
00	2402	Default	2.62	20.97	PASS
39	2441	Default	2.67	20.97	PASS
78	2480	Default	3.17	20.97	PASS


Peak output Power plot on channel 00


1Mbps




Peak output Power plot on channel 39

1Mbps








Peak output Power plot on channel 00


3Mbps



Peak output Power plot on channel 39

3Mbps





**7.1.50 CONDUCTED BAND EDGE MEASUREMENT****7.1.51 Applicable Standard**

According to FCC Part 15.247(d) and DA 00-705

**7.1.52 Conformance Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**7.1.53 Measuring Instruments**

The Measuring equipment is listed in the section 6.3 of this test report.

**7.1.54 Test Setup**

Please refer to Section 6.1 of this test report.

**7.1.55 Test Procedure**

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.


Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.


Repeat above procedures until all measured frequencies were complete.



**7.1.56 Test Results**


EUT:	bluetooth speaker	Model No.:	Brilliance323
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Susan Su


Note: Hopping enabled and disabled have evaluated, and the worst data was reported













## EDR mode (8DPSK): Band Edge- High Channel



**7.1.57 ANTENNA APPLICATION****7.1.58 Antenna Requirement**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

**7.1.59 Result**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.