

TEST REPORT

Applicant Name : Shenzhen Freetalker Industry Co., Ltd.
Address : 6/F, Building A, Xinghong Science Park, No.111 of Shuiku Rd.,
Fenghuanggang, Xixiang, Bao'an, Shenzhen, China
Report Number : SZNS220915-41905E-RF-00
FCC ID: 2AHJLQ81

Test Standard (s)

FCC PART 95

Sample Description

Product Type: Walkie Talkie
Model No.: Q81
Multiple Model(s) No.: TQ81,T168,RD633,T821,T319
Trade Mark: FREETALKER
Date Received: 2022/09/15
Report Date: 2022/10/17

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Nick Fang
EMC Engineer

Approved By:



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk ★.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk **. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS.....	7
TEST EQUIPMENT LIST	8
\$2.1093 - RF EXPOSURE INFORMATION	9
APPLICABLE STANDARD	9
RESULT	9
FCC §2.1046 & §95.567 - RF OUTPUT POWER.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST DATA	10
FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC.....	11
APPLICABLE STANDARD	11
TEST PROCEDURE	11
TEST DATA	11
FCC §2.1049 & §95.573 & §95.579 - AUTHOURIZED BANDWIDTH AND EMISSION MASK.....	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
FCC §2.1055 (D) & §95.565 - FREQUENCY STABILITY	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28
§95.587 – FRS ADDITIONAL REQUIREMENTS	30
APPLICABLE STANDARD	30
RESULT	30

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

Product	Walkie Talkie
Tested Model	Q81
Multiple Models	TQ81,T168, RD633,T821,T319 (model difference see product declaration letter of similarity)
Frequency Range	462.5625~462.7125MHz 467.5625~467.6125MHz
Transmit Power (ERP)	462.5625~462.7125MHz: 2.65dBm 467.5625~467.6125MHz: 1.84dBm
Channel Spacing	12.5kHz
Modulation Technique	FM
Antenna Specification*	0dBi(It is provided by the applicant)
Voltage Range	DC 3*1.2V AAA Ni-MH rechargeable batteries or DC 3*1.5V AAA alkaline batteries or DC 5V from USB port
Sample serial number	SZNS220915-41905E-RF-S1 (Assigned by ATC)
Sample/EUT Status	Good condition
Extreme condition*	L.V.: Low Voltage 2.9V N.V.: Normal Voltage 3.6V H.V.: High Voltage 4.5V(provided by the applicant)

Objective

This test report is in accordance with Part 2 and Part 95, Subpart A & Subpart B of the Federal Communication Commissions rules.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart A, Subpart B of the Federal Communication Commissions rules with TIA-603-E, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards and ANSI C63.26-2015 American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	5%	
RF output power, conducted	0.73dB	
Unwanted Emission, conducted	1.6dB	
Emissions, Radiated	30MHz - 1GHz 1GHz - 18GHz	4.28dB 4.98dB
Temperature	1°C	
Humidity	6%	
Supply voltages	0.4%	

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Channel List

Channel No.	Channel Frequency (MHz)
1	462.5625
2	462.5875
3	462.6125
4	462.6375
5	462.6625
6	462.6875
7	462.7125
8	467.5625
9	467.5875
0	467.6125

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§2.1093	RF Exposure	Compliant
§2.1046, §95.567	RF Output Power	Compliant
§2.1047, §95.575	Modulation Characteristic	Compliant
§2.1049, §95.573, §95.579	Authorized Bandwidth & Emission Mask	Compliant
§2.1053, §95.579	Radiated Spurious Emission	Compliant
§2.1055(d), §95.565	Frequency Stability	Compliant
§95.587	FRS additional requirements	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2020/01/05	2023/01/04
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Agilent	Signal Generator	N5183A	MY51040755	2021/12/13	2022/12/12
RF Conducted Test					
SPECTRUM ANALYZER	Rohde & Schwarz	FSU26	200982	2022/07/04	2023/07/03
HP Agilent	RF Communication test set	8920B	3325U00859	2021/12/14	2022/12/13
WEINSCHEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
REALE	Temp. & Humid. Chamber	RHP-800BT	R20170318310	2021/12/14	2022/12/13
Fluke	Multi Meter	45	7664009	2021/12/14	2022/12/13
Manson	DC Power Source	KPS-6604	ATCS-205	NCR	NCR
Unknown	RF Cable	Unknown	Unknown	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

§2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

SAR-Based Exemption:

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum timeaveraged power or maximum time-averaged ERP, whichever is greater.

Per §1.1307(b)(3)(i)(B), for single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Result

Frequency (MHz)	P _{th}		Maximum tune-up ERP (dBm)	Maximum tune-up conducted power (dBm)	Exemption
	(mW)	(dBm)			
462.5625-462.7125	21.17	13.26	3.0	5.15	Compliant
467.5625-467.6125	20.86	13.19	2.0	4.15	Compliant

Note: 1. The tune up ERP was declared by the applicant.
 2. The antenna gain is 0dBi(-2.15dBd), so the Conducted power was used for evaluation
 3. To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 0.5cm from nearby persons.

Result: Compliant.

FCC §2.1046 & §95.567 - RF OUTPUT POWER

Applicable Standard

Per FCC §2.1046, and §95.567, Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

Test Data

Environmental Conditions

Temperature:	26°C
Relative Humidity:	63%
ATM Pressure:	101.0 kPa

The testing was performed by Zeki Ma on 2022-09-24.

Test Mode: Transmitting

Frequency (MHz)	Receiver Reading (dBm)	Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)				
462.6125MHz								
462.6125	-25.15	101	2.2	H	9.1	-16.05	33	49.05
462.6125	-2.35	26	1.3	V	5.0	2.65	33	30.35
467.6125MHz								
467.6125	-23.68	55	1.5	H	8.3	-15.38	27	42.38
467.6125	-3.56	308	1.3	V	5.4	1.84	27	25.16

Note:

Absolute Level = Reading Level + Substituted Factor

Substituted Factor contains: SG Level - Cable loss+ Antenna Gain

Margin = Limit -Absolute Level

Test Result: Compliant.

FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC

Applicable Standard

Per FCC §2.1047 and §95.575: Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

Test Procedure

Test Method: TIA/EIA-603-E/ANSI C63.26-2015

Test Data

Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-10-16.


Please refer to the following tables and plots.

Test Mode: Transmitting

MODULATION LIMITING


Carrier Frequency: 462.6125MHz

Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	1.501	0.065	1.418	0.058	2.500
400	1.603	0.081	1.435	0.079	2.500
500	1.657	0.100	1.578	0.097	2.500
600	1.691	0.112	1.571	0.109	2.500
700	1.702	0.131	1.650	0.129	2.500
800	1.742	0.141	1.743	0.140	2.500
900	1.871	0.146	1.906	0.141	2.500
1000	2.015	0.198	1.995	0.179	2.500
1200	1.919	0.226	1.864	0.212	2.500
1400	1.985	0.250	2.028	0.243	2.500
1600	1.866	0.281	1.830	0.269	2.500
1800	1.737	0.312	1.717	0.310	2.500
2000	1.617	0.330	1.509	0.322	2.500
2100	1.528	0.335	1.485	0.324	2.500
2200	1.466	0.352	1.499	0.349	2.500
2300	1.332	0.374	1.230	0.366	2.500
2400	1.156	0.381	1.128	0.370	2.500
2500	0.945	0.386	0.846	0.381	2.500
2600	0.898	0.396	0.826	0.396	2.500
2700	0.851	0.408	0.722	0.403	2.500
2800	0.785	0.415	0.850	0.411	2.500
2900	0.768	0.417	0.767	0.413	2.500
3000	0.746	0.380	0.735	0.364	2.500



Carrier Frequency: 467.6125MHz


Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	1.501	0.056	1.615	0.068	2.500
400	1.482	0.041	1.710	0.070	2.500
500	1.650	0.095	1.579	0.125	2.500
600	1.673	0.132	1.722	0.132	2.500
700	1.689	0.133	1.755	0.138	2.500
800	1.720	0.129	1.776	0.135	2.500
900	1.937	0.181	1.896	0.120	2.500
1000	1.978	0.190	2.024	0.190	2.500
1200	2.002	0.238	1.854	0.249	2.500
1400	1.981	0.218	1.944	0.229	2.500
1600	1.816	0.267	1.933	0.270	2.500
1800	1.755	0.270	1.769	0.319	2.500
2000	1.593	0.331	1.661	0.294	2.500
2100	1.636	0.311	1.352	0.369	2.500
2200	1.457	0.326	1.535	0.305	2.500
2300	1.331	0.357	1.378	0.408	2.500
2400	1.170	0.415	1.197	0.374	2.500
2500	0.963	0.351	0.917	0.387	2.500
2600	0.995	0.408	0.902	0.384	2.500
2700	0.871	0.445	0.751	0.383	2.500
2800	0.885	0.455	0.946	0.423	2.500
2900	0.922	0.409	0.623	0.426	2.500
3000	0.841	0.388	0.727	0.377	2.500



Audio Frequency Response


Carrier Frequency: 462.6125MHz

Audio Frequency (Hz)	Response Attenuation (dB)
300	-9.79
400	-7.33
500	-5.85
600	-3.90
700	-2.64
800	-1.72
900	-0.99
1000	0
1200	1.80
1400	3.36
1600	4.22
1800	4.55
2000	4.88
2100	5.78
2200	6.32
2300	6.44
2400	6.79
2500	7.21
2600	7.26
2700	7.24
2800	7.04
2900	6.62
3000	6.35



Carrier Frequency: 467.6125MHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-10.40
400	-8.05
500	-6.34
600	-3.72
700	-3.17
800	-1.62
900	-0.69
1000	0.00
1200	1.92
1400	3.46
1600	4.10
1800	4.73
2000	4.67
2100	5.95
2200	6.48
2300	6.52
2400	6.88
2500	7.38
2600	7.21
2700	7.14
2800	7.07
2900	6.49
3000	6.38



Audio frequency lows pass filter response


Carrier Frequency: 462.6125MHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-15.57	0.0
4.0	-74.17	-12.5
5.0	-85.32	-22.2
6.0	-86.56	-30.1
7.0	-85.01	-36.8
8.0	-88.88	-42.6
9.0	-85.87	-47.7
10.0	-85.13	-52.3
12.0	-87.72	-60.2
14.0	-88.43	-66.9
16.0	-88.50	-72.7
18.0	-88.90	-77.8
20.0	-86.40	-82.4



Carrier Frequency: 467.6125MHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-16.44	0.0
4.0	-72.70	-12.5
5.0	-82.58	-22.2
6.0	-85.17	-30.1
7.0	-83.70	-36.8
8.0	-85.69	-42.6
9.0	-85.74	-47.7
10.0	-83.08	-52.3
12.0	-84.69	-60.2
14.0	-82.33	-66.9
16.0	-84.16	-72.7
18.0	-84.31	-77.8
20.0	-86.24	-82.4



FCC §2.1049 & §95.573 & §95.579 - AUTHOURIZED BANDWIDTH AND EMISSION MASK

Applicable Standard

According to §95.573. Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) Attenuation requirements. The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.

(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3) $43 + 10 \log (P)$ dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) Measurement bandwidths. The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

Test Procedure

TIA-603-E, section 2.2.11

Test Data

Environmental Conditions

Temperature:	27.4 °C
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-10-16.

Test Mode: Transmitting


Mode	Channel Separation (kHz)	Frequency (MHz)	99% Occupied Bandwidth (kHz)	Limit (kHz)
Analog	12.5	462.6125	9.936	12.5
		467.6125	9.936	12.5

Emission Designator Per CFR 47 §2.201& §2.202&, $B_n = 2M + 2D$:

Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$


F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

OBW, 462.6125MHz




Date: 16.OCT.2022 15:19:48

Emission Mask, 462.6125MHz




Date: 16.OCT.2022 15:35:46

OBW, 467.6125 MHz



Date: 16.OCT.2022 17:13:22

Emission Mask, 467.6125MHz



Date: 16.OCT.2022 15:34:51

FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION

Applicable Standard

FCC §2.1053 and §95.579. Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

- (1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.
- (2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.
- (3) $43 + 10 \log (P)$ dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

Test Procedure

The transmitter was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \log_{10} (\text{TXpwr in Watts} / 0.001)$ - the absolute level
Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	26°C
Relative Humidity:	63%
ATM Pressure:	101.0 kPa

The testing was performed by Zeki Ma on 2022-09-24.

Test Mode: Transmitting

Frequency (MHz)	Receiver Reading (dBm)	Turntable Degree	Rx Antenna		Substituted Factor (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)				
462.6125 MHz								
925.23	-72.1	359	1.1	H	9.3	-62.8	-13	49.8
925.23	-72.7	249	1	V	11.5	-61.2	-13	48.2
1387.84	-54.9	134	1.8	H	6	-48.9	-13	35.9
1387.84	-58.1	142	1.3	V	5.8	-52.3	-13	39.3
1850.45	-47.8	161	1.3	H	4.4	-43.4	-13	30.4
1850.45	-53.4	63	1.1	V	3.6	-49.8	-13	36.8
2313.06	-53.5	262	2	H	7.2	-46.3	-13	33.3
2313.06	-54.3	300	1.5	V	6.7	-47.6	-13	34.6
2775.68	-56.8	300	2.1	H	6.7	-50.1	-13	37.1
2775.68	-55.9	145	1.8	V	6.3	-49.6	-13	36.6
3238.29	-53.4	56	1.6	H	7	-46.4	-13	33.4
3238.29	-52.9	275	1.9	V	6.3	-46.6	-13	33.6
467.6125 MHz								
935.23	-76.8	60	1.8	H	9.3	-67.5	-13	54.5
935.23	-72.1	279	1.3	V	11.5	-60.6	-13	47.6
1402.84	-57.7	291	2.1	H	5.9	-51.8	-13	38.8
1402.84	-61.3	78	1.9	V	5.8	-55.5	-13	42.5
1870.45	-52.3	22	1.4	H	4.2	-48.1	-13	35.1
1870.45	-54	243	1.2	V	3.4	-50.6	-13	37.6
2338.06	-58.8	7	1	H	7.3	-51.5	-13	38.5
2338.06	-57.9	159	1.1	V	6.5	-51.4	-13	38.4
2805.68	-57.4	235	1.6	H	6.8	-50.6	-13	37.6
2805.68	-56.7	196	1.5	V	6.7	-50	-13	37
3273.29	-54.1	322	2.2	H	6.7	-47.4	-13	34.4
3273.29	-54.1	213	1.8	V	5.9	-48.2	-13	35.2

Note:

Absolute Level = Reading Level + Substituted Factor

Substituted Factor contains: SG Level - Cable loss+ Antenna Gain

Margin = Limit - Absolute Level

FCC §2.1055 (d) & §95.565 - FREQUENCY STABILITY

Applicable Standard

According to FCC §2.1055(a) (1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$, and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.565, Each FRS transmitter type must be designed such that the carrier frequencies remain within ± 2.5 parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage (item 1 or item 2 will be chosen according to different condition) :

1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

Test Data

Environmental Conditions

Temperature:	27.4°C
Relative Humidity:	53 %
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-10-16.

Test Mode: Transmitting

Reference Frequency:462.6125MHz, Limit:2.5 ppm, 12.5kHz			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	NV	462.611944	-1.202
40	NV	462.611942	-1.206
30	NV	462.611949	-1.191
20	NV	462.611950	-1.189
10	NV	462.611945	-1.200
0	NV	462.611942	-1.206
-10	NV	462.611947	-1.195
-20	NV	462.611943	-1.204
-30	NV	462.611948	-1.193
Frequency Stability versus Input Voltage			
20	LV	462.611959	-1.169
20	HV	462.611965	-1.156

Reference Frequency:467.6125 MHz, Limit:2.5 ppm, 12.5kHz			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability versus Input Temperature			
50	NV	467.611951	-1.174
40	NV	467.611959	-1.157
30	NV	467.611954	-1.168
20	NV	467.611957	-1.161
10	NV	467.611948	-1.180
0	NV	467.611948	-1.180
-10	NV	467.611949	-1.178
-20	NV	467.611955	-1.165
-30	NV	467.611950	-1.176
Frequency Stability versus Input Voltage			
20	LV	467.611947	-1.183
20	HV	467.611949	-1.178

§95.587 – FRS ADDITIONAL REQUIREMENTS

Applicable Standard

According to FCC §95.587

Each FRS transmitter type must be designed to meet the following additional requirements.

(a) Transmit frequency capability. FRS transmitter types must not be capable of transmitting on any frequency or channel other than those listed in § 95.563.

(b) Antenna. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

(2) The gain of the antenna must not exceed that of a half-wave dipole antenna.

(3) The antenna must be designed such that the electric field of the emitted waves is vertically polarized when the unit is operated in the normal orientation.

(c) Digital data transmissions. FRS transmitter types having the capability to transmit digital data must be designed to meet the following requirements.

(1) FRS units may transmit digital data containing location information, or requesting location information from one or more other FRS or GMRS units, or containing a brief text message to another specific FRS or GMRS unit or units.

(2) Digital data transmissions may be initiated by a manual action or command of the operator or on an automatic or periodic basis, and FRS units may be designed to automatically respond with location data upon receiving an interrogation request from another.

(3) Digital data transmissions must not exceed one second in duration.

(4) Digital data transmissions must not be sent more frequently than one digital data transmission within a thirty-second period, except that an FRS unit may automatically respond to more than one interrogation request received within a thirty-second period.

(d) Packet mode. FRS transmitter types must not be capable of transmitting data in the store-and-forward packet operation mode.

(e) Effective September 30, 2019, no person shall manufacture or import hand-held portable radio equipment capable of operating under this subpart (FRS) and other licensed or licensed-by-rule services in this chapter (part 15 unlicensed equipment authorizations are permitted if consistent with part 15 rules).

Result

(a) Compliant, please refer to the channel list.

(b) Compliant, EUT has a non-removable integral vertically polarized antenna arrangement and the antenna gain is 0dBi(-2.15dBd), fulfill the requirement of this section. Please refer to the EUT photos.

(c) Not Applicable, EUT not support this function.

(d) Not Applicable, EUT not support this function.

(e) Compliant, EUT only with FRS function operating under FCC part 95B, not support other function.

******* END OF REPORT *******