RF TESTREPORT

ISSUED BY Shenzhen BALUN Technology Co., Ltd.



FOR

K2 Dual Core System

ISSUED TO System Level Solutions Inc.

14100 Murphy Ave., San Martin, CA - 95046, United States.





Report No.: EUT Type: Model Name: Brand Name: Test Standard:

BL-SZ1680264-602 K2 Dual Core System PI1WLDD000101 K2DC

47 CFR Part 15 Subpart C

RSS-Gen (Issue 4, November 2014)

RSS-247 (Issue 1, May 2015)

FCC ID: 2AHK5-PI1WLD101 ISED Number: 21180-PI1WLD101

Test conclusion:

Test Date:

Pass

Aug. 20, 2016 ~ Aug. 26, 2016

Date of Issue: Mar. 13, 2017

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.



Revision History

VersionIssue DateRevisions ContentRev. 01Mar. 03, 2017Initial Issue

Rev. 02 Mar. 13, 2017 Change the antenna connector photo.

TABLE OF CONTENTS

1	ADMIN	ISTRATIVE DATA (GENERAL INFORMATION)	5
	1.1	Identification of the Testing Laboratory	5
	1.2	Identification of the Responsible Testing Location	5
	1.3	aboratory Condition	5
	1.4	Announce	5
2	PRODU	JCT INFORMATION	6
	2.1	Applicant Information	6
	2.2	Manufacturer Information	6
	2.3	Factory Information	6
	2.4	General Description for Equipment under Test (EUT)	6
	2.5	Ancillary Equipment	6
	2.6	Technical Information	7
	2.7	Additional Instructions	7
3	SUMM	ARY OF TEST RESULTS	8
	3.1	Test Standards	8
	3.2	Verdict	9
4	GENEF	RAL TEST CONFIGURATIONS	.10
	4.1	Test Environments	.10
	4.2	Test Equipment List	.10
	4.3	MEASUREMENT UNCERTAINTY	.11
	4.4	Description of Test Setup	.11
	4.4.1	For Antenna Port Test	.11
	4.4.2	For AC Power Supply Port Test	.12
	4.4.3	For Radiated Test (Below 30 MHz)	.12



	4.4.4	For Radiated Test (30 MHz-1 GHz)	13
	4.4.5	For Radiated Test (Above 1 GHz)	13
4	4.5	Measurement Results Explanation Example	14
	4.5.1	For conducted test items:	14
	4.5.2	For radiated band edges and spurious emission test:	14
5	TEST I	TEMS	15
Ę	5.1	Antenna Requirements	15
	5.1.1	Standard Applicable	15
	5.1.2	Antenna Anti-Replacement Construction	15
	5.1.3	Antenna Gain	16
Ę	5.2	Output Power	17
	5.2.1	Test Limit	17
	5.2.2	Test Setup	17
	5.2.3	Test Procedure	17
	5.2.4	Test Result	18
Ę	5.3	Occupied Bandwidth	19
	5.3.1	Limit	19
	5.3.2	Test Setup	19
	5.3.3	Test Procedure	19
	5.3.4	Test Result	19
Ę	5.4	Conducted Spurious Emission	20
	5.4.1	Limit	20
	5.4.2	Test Setup	20
	5.4.3	Test Procedure	20
	5.4.4	Test Result	21
Ę	5.5	Band Edge (Authorized-band band-edge)	22
	5.5.1	Limit	22
	5.5.2	Test Setup	22
	5.5.3	Test Procedure	22
	5.5.4	Test Result	23
Ę	5.6	Conducted Emission	24
	5.6.1	Limit	24



5.6.2	Test Setup	24
5.6.3	Test Procedure	24
5.6.4	Test Result	24
5.7	Radiated Spurious Emission	25
5.7.1	Limit	25
5.7.2	Test Setup	25
5.7.3	Test Procedure	25
5.7.4	Test Result	26
5.8	Band Edge (Restricted-band band-edge)	27
5.8.1	Limit	27
1.1.1	Test Setup	27
1.1.2	Test Procedure	27
5.8.2	Test Result	27
5.9	Power Spectral density (PSD)	28
5.9.1	Limit	28
5.9.2	Test Setup	28
5.9.3	Test Procedure	28
5.9.4	Test Result	28
ANNEX A	TEST RESULT	29
A.1	Output Power	29
A.2	Occupied Bandwidth	30
A.3	Conducted Spurious Emissions	32
A.4	Band Edge (Authorized-band band-edge)	35
A.5	Conducted Emissions	37
A.6	Radiated Spurious Emission	39
A.7	Band Edge (Restricted-band band-edge)	43
A.8	Power Spectral Density (PSD)	44
ANNEX B	TEST SETUP PHOTOS	45
ANNEX C	EUT EXTERNAL PHOTOS	45
ANNEX D	EUT INTERNAL PHOTOS	45



1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
A dalaga a	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.	
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road,	
Address	Nanshan District, Shenzhen, Guangdong Province, P. R. China	
	The laboratory has been listed by Industry Canada to perform	
	electromagnetic emission measurements. The recognition numbers of test	
	site are 11524A-1.	
Approditation	The laboratory has been listed by US Federal Communications	
Accreditation	Commission to perform electromagnetic emission measurements. The	
Certificate	recognition numbers of test site are 832625.	
	The laboratory is a testing organization accredited by China National	
	Accreditation Service for Conformity Assessment (CNAS) according to	
	ISO/IEC 17025. The accreditation certificate number is L6791.	
	All measurement facilities used to collect the measurement data are	
Description	located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi	
Description	Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China	
	518055	

1.3 aboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.5.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.



2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	System Level Solutions Inc.
Address	14100 Murphy Ave., San Martin, CA - 95046, United States.

2.2 Manufacturer Information

Manufacturer System Level Solutions (India) Pvt. Ltd	
Addroso	Plot#32, Zone-D/4, Phase-1, GIDC Estate, V.U. Nagar - 388 121,
Address	Gujarat, India.

2.3 Factory Information

Factory	Pronology Services (China) Inc.
A daluaca	The Second Industrial Zone, Lou Village, Gongming Town, Guangming
Address	Dist., 518106, Shenzhen, Guangdong, China.

2.4 General Description for Equipment under Test (EUT)

EUT Type	K2 Dual Core System
Model Name	PI1WLDD000101
Series Model Name	N/A
Description of Model	N/A
name differentiation	IV/A
Hardware Version	1B-01
Software Version	2.3.0
Dimensions (Approx.)	144mm x 55mm x 23 mm
Weight (Approx.)	0.098Kg
Network and Wireless	Bluetooth 3.0, Bluetooth 4.0 Low Energy (BLE),
connectivity	WIFI 802.11b, 802.11g and 802.11n (HT20)

2.5 Ancillary Equipment

4	Ancillary Equipment 1	HDMI Cable	
		Length (Approx.)	30 cm
	Ancillary Equipment 2	USB Cable	
		Length (Approx.)	103 cm
	Ancillary Equipment 3	Ycable	
		Length (Approx.)	104 cm



2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS	
Modulation Type	GFSK	
Transfer Rate	1 Mbps	
Eroguanov Panga	The frequency range used is 2402 MHz – 2480 MHz;	
Frequency Range	The frequency block is 2400 MHz to 2483.5 MHz.	
Number of channel	40 (at intervals of 2 MHz)	
Tested Channel	0 (2402 MHz), 19 (2440 MHz), 39 (2480 MHz).	
Antenna Type	Dipole Antenna	
Antenna Gain	3 dBi(All involve the antenna gain test item, has been included in the	
Antenna Gam	final results)	
	The equipment is K2 Dual Core System, it contains Bluetooth module	
About the Product	operating at 2.4 GHz ISM band. Only the Bluetooth 4.0 Low Energy	
	(BLE) was tested in this report.	


2.7 Additional Instructions

EUT Software Settings:

	Special software is used.
Modo	The software provided by client to enable the EUT under
Mode	transmission condition continuously at specific channel frequencies
	individually.

Power level setup in software						
Test Software Version	Ampak RFTestTool					
Mode	Channel	Channel Frequency (MHz) Soft Set				
	CH0	2402	TX LEVEL is built-in set			
GFSK	CH19	2440	parameters and cannot be			
	CH39	2480	changed and selected.			

Run Software





3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
	47 CFR Part 15,	
1	Subpart C	Miscellaneous Wireless Communications Services
	(10-1-15 Edition)	
2	KDB Publication	Guidance for Performing Compliance Measurements on
2 558074 D01v03r05		Digital Transmission Systems (DTS) Operating Under §15.247
2	RSS-Gen	Conoral Deguirements for Compliance of Radio Apparatus
3 General Requirements for Compliance		General Requirements for Compliance of Radio Apparatus
1	RSS-247	Digital Transmission Systems (DTSs), Frequency Hopping Systems(FHSs)
4	(Issue 1, May 2015)	and Licence-Exemp Local Area Network (LE-LAN) Devices
5	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices



3.2 Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	RSS-247, 5.4 (6)	N/A		Pass ^{Note1}
2	Output Power	15.247(b)	RSS-247, 5.4 (4)	Low/Middle/ High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	RSS-GEN, 6.6; RSS-247, 5.2 (1)	Low/Middle/ High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.3	Pass
5	Band Edge(Authorize d-band band- edge)	15.247(d)	RSS-247, 5.5;	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/ High	ANNEX A.5	Pass
7	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.6	Pass
8	Band Edge(Restricted -band band- edge)	15.209 15.247(d)	RSS-247, 5.5	Low/Middle/ High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	RSS-247, 5.2 (2)	Low/Middle/ High	ANNEX A.8	Pass
10	Receiver Spurious Emissions		RSS-Gen, 7.1.2		N/A	N/A ^{Note2}

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.



4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa -102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2016.07.13	2017.07.12
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2016.07.13	2017.07.12
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2016.07.13	2017.07.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2016.07.13	2017.07.12
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2015.10.15	2016.10.14
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2016.07.05	2017.07.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.05	2017.07.04
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2016.07.13	2017.07.12
Power Splitter	KMW	DCPD-LDC	1305003215	2016.07.13	2017.07.12
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2016.07.13	2017.07.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091		
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189		
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2016.07.13	2017.07.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2015.08.07	2016.08.06
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna- Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna- Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703		
Power Amplifier	OPHIR RF	5225F	1037	2017.02.17	2018.02.16
Power Amplifier	OPHIR RF	5273F	1016	2017.02.17	2018.02.16



4.3 MEASUREMENT UNCERTAINTY


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%


4.4 Description of Test Setup

4.4.1 For Antenna Port Test






4.4.2 For AC Power Supply Port Test



(Diagram 2)


4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)




4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)



4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

E = EIRP - 20log D + 104.8

where:

E = electric field strength in $dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP= Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)



5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.


If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
Compliance with 15.203, use of a	
standard antenna jack or electrical	The antenna is the unique connector with a dipole antenna.
connector is prohibited.	





5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (4)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW ≥ DTS bandwidth.

Set VBW ≥ 3 x RBW.

Set span ≥ 3 x RBW

Sweep time = auto couple.

Detector = peak.

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.

Set VBW ≥ RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of



sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \le 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.



5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1(Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.



5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to \geq 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement



Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.



5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

This Method apply to the equipment is using FHSS.

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation

RBW ≥ 1% of the span

VBW ≥ RBW

Sweep = auto

Detector function = peak /AV

Trace = max hold

Allow the trace to stabilize.

E [dBµV/m] = UR + AT + AFactor [dB]; AT = LCable loss [dB] - Gpreamp [dB]

AT: Total correction Factor except Antenna

UR: Receiver Reading

Gpreamp: Preamplifier Gain

AFactor: Antenna Factor at 3m

This Method apply to the equipment is using wide band modulations other than FHSS.

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle \geq 98%). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than \pm 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.



Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW ≥ $3 \times RBW$.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) \pm 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission \pm 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.



5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a $50 \, \mu H/50 \Omega$ line impedance stabilization network (LISN).

Fraguency range (MHz)	Conducted Limit (dBµV)		
Frequency range (MHz)	Quai-peak	Average	
0.15 - 0.50	66 to 56	56 to 46	
0.50 - 5	56	46	
0.50 - 30	60	50	

5.6.2 Test Setup

See section 4.4.2 (Diagram 2) for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.



5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (µV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

- 1. Field Strength ($dB\mu V/m$) = 20*log[Field Strength ($\mu V/m$)].
- 2. In the emission tables above, the tighter limit applies at the band edges.
- For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
- For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3, 4.4.4, 4.4.5 (Diagram 3, 4, 5) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for f < 1 GHz



VBW ≥ RBW Sweep = auto Detector function = peak Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.7.4 Test Result

Please refer to ANNEX A.6.



5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

1.1.1 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

1.1.2 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.8.2 Test Result

Please refer to ANNEX A.7.



5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW ≥ 3 RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.



ANNEX A TEST RESULT


A.1 Output Power

Peak Power Test Data


Channal	Measured Output Peak Power		Limit		Vordict
Channel	dBm	mW	dBm	mW	Verdict
Low	6.88	4.88			Pass
Middle	7.65	5.82	30	1000	Pass
High	8.20	6.61			Pass

Peak Power Test Plots


LOW CHANNEL



MIDDLE CHANNEL



HIGH CHANNEL






A.2 Occupied Bandwidth

Test Data


Channel	6 dB Bandwidth (KHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low Channel	681.567	1.061	≥500
Middle Channel	674.792	1.062	≥500
High Channel	665.526	1.061	≥500

Test plots (6 dB Bandwidth)

LOW CHANNEL Measure Ch Freq 2.402 GHz Meas Off Trig Free Occupied Bandwidth Channel Power #Atten 30 dB Occupied BW ACP Multi Carrier Power 2.402 000 GHz #VBW 300 kHz Power Stat CCDF Occ BW % Pwr x dB Occupied Bandwidth 99.00 % -6.00 dB 1.0885 MHz More 1 of 2 Transmit Freq Error x dB Bandwidth 94.794 kHz 681.567 kHz Copyright 2000-2012 Agilent Tech



HIGH CHANNEL



Test plots (99% Bandwidth)



LOW CHANNEL

MIDDLE CHANNEL





HIGH CHANNEL Sweep Time Trig Free Ch Freq 2.48 GHz 3.200 ms Man Occupied Bandwidth Sweep Single Ref 15 dBm #Peak #Atten 30 dB Time Ассу <u>Norm</u> Center 2.480 000 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 3.2 ms (601 pts) **Points** Occupied Bandwidth Occ BW % Pwr -6.00 dB 1.0611 MHz Transmit Freq Error x dB Bandwidth 121.020 kHz 570.562 kHz




A.3 Conducted Spurious Emissions

Test Data

Channel	Measured Max. Out of	Limit	(dBm)	
Channel	Band Emission (dBm)	Carrier Level	Calculated	Verdict
			20 dBc Limit	
Low Channel	-54.69	6.17	-13.83	Pass
Middle Channel	-53.15	6.81	-13.19	Pass
High Channel	-51.73	7.28	-12.72	Pass


Test Plots


LOW CHANNEL CARRIER LEVEL



LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz


LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz









MIDDLE CHANNEL CARRIER LEVEL




MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz

MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz






HIGH CHANNEL CARRIER LEVEL






HIGH CHANNEL, SPURIOUS 30 MHz ~ 3GHz

HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz








A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Channal	Measured Max. Band	Limit	(dBm)		
Channel	Edge Emission (dBm)	Carrier Level	Calculated 20 dBc Limit	Verdict	
Low Channel	-42.02	6.17	-13.83	Pass	
High Channel	-42.54	7.28	-12.72	Pass	


Test Plots

LOW CHANNEL, Carrier level




LOW CHANNEL, Reference level

LOW CHANNEL, Band Edge





High CHANNEL, Carrier level




HIGH CHANNEL, Reference level

Copyright 2000-2012 Agilent Technologies

Freq/Channel Mkr1 2.483 500 GHz -52.07 dBm Center Freq 2.48350000 GHz Ref 15 dBm #Peak #Atten 30 dB Start Freq 2.47850000 GHz **Stop Freq** 2.48850000 GHz **CF Step** 1.00000000 MHz <u>Auto</u> Man Center 2.483 500 GHz #Res BW 100 kHz Span 10 MHz Sweep 1 ms (601 pts) Freq Offset 0.00000000 Hz *VBW 300 kHz Trace (1) X Axis 2.483 500 GHz Amplitude -52.07 dBm Signal Track

HIGH CHANNEL, Band Edge






A.5 Conducted Emissions

Note 1: The EUT is working in the Normal link mode.


Test Data and Test Plots



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	(dB)			
1	0.19	55.9	11.00	64.8	8.90	Peak	L Line	Pass
1**	0.19	40.4	11.00	54.8	14.40	AV	L Line	Pass
2	0.28	47.3	11.00	62.3	15.00	Peak	L Line	Pass
2**	0.28	29.3	11.00	52.3	23.00	AV	L Line	Pass
3	0.38	41.1	11.00	59.5	18.40	Peak	L Line	Pass
3**	0.38	28.4	11.00	49.5	21.10	AV	L Line	Pass
4	0.49	39.5	11.00	56.3	16.80	Peak	L Line	Pass
4**	0.49	24.3	11.00	46.3	22.00	AV	L Line	Pass
5	1.05	36.6	11.00	56.0	19.40	Peak	L Line	Pass
5**	1.05	22.8	11.00	46.0	23.20	AV	L Line	Pass
6	2.12	36.6	11.00	56.0	19.40	Peak	L Line	Pass
6**	2.12	22.3	11.00	46.0	23.70	AV	L Line	Pass

PHASE N





No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Line	Verdict
	(MHz)	(dBuV)		(dBuV)	(dB)			
1	0.16	54.9	11.00	65.7	10.80	Peak	N Line	Pass
1**	0.16	37.4	11.00	55.7	18.30	AV	N Line	Pass
2	0.18	58.4	11.00	65.1	6.70	Peak	N Line	Pass
2**	0.18	48.0	11.00	55.1	7.10	AV	N Line	Pass
3	0.19	57.3	11.00	64.9	7.60	Peak	N Line	Pass
3**	0.19	46.6	11.00	54.9	8.30	AV	N Line	Pass
4	0.43	42.3	11.00	57.9	15.60	Peak	N Line	Pass
4**	0.43	33.1	11.00	47.9	14.80	AV	N Line	Pass
5	0.98	38.8	11.00	56.0	17.20	Peak	N Line	Pass
5**	0.98	23.9	11.00	46.0	22.10	AV	N Line	Pass
6	4.54	36.6	11.00	56.0	19.40	Peak	N Line	Pass
6**	4.54	26.1	11.00	46.0	19.90	AV	N Line	Pass



A.6 Radiated Spurious Emission

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The EUT is working in the Normal link mode below 1 GHz.

Test Data and Plots






No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	124.79	37.91	-22.47	43.5	5.59	Peak	136.20	100	Vertical	Pass
2	167.95	27.39	-22.82	43.5	16.11	Peak	1.70	100	Vertical	Pass
3	374.75	30.01	-15.82	46.0	15.99	Peak	302.70	100	Vertical	Pass
4	624.95	41.11	-10.27	46.0	4.89	Peak	331.30	100	Vertical	Pass
5	749.80	39.69	-8.59	46.0	6.31	Peak	57.50	100	Vertical	Pass
6	874.90	38.90	-6.24	46.0	7.10	Peak	61.50	100	Vertical	Pass

30 MHz to 1 GHz, ANT H





No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	124.79	32.10	-22.47	43.5	11.40	Peak	59.60	100	Horizontal	Pass
2	239.95	31.88	-19.10	46.0	14.12	Peak	18.40	100	Horizontal	Pass
3	374.75	39.03	-15.82	46.0	6.97	Peak	176.10	100	Horizontal	Pass
4	624.95	38.96	-10.27	46.0	7.04	Peak	251.90	100	Horizontal	Pass
5	749.80	38.55	-8.59	46.0	7.45	Peak	192.60	100	Horizontal	Pass
6	874.90	42.65	-6.24	46.0	3.35	Peak	51.30	100	Horizontal	Pass



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	2077.66	53.07	-1.71	74	20.93	Peak	3.6	150	Vertical	Pass
2	2402.68	105.38	-0.34	74	-31.38	Peak	282.9	150	Vertical	N/A
3	4806.03	51.62	13.74	74	22.38	Peak	163	150	Vertical	Pass
4	7336.52	47.38	20.04	74	26.63	Peak	324.9	150	Vertical	Pass
5	13301.17	48.84	10.55	74	25.16	Peak	26	150	Vertical	Pass
6	19139.77	50.85	9.77	74	23.15	Peak	163.3	150	Vertical	Pass

GFSK Low Channel 1 GHz to 25 GHz, ANT H

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	2127.83	53.93	-1.05	74	20.07	Peak	238.7	150	Horizontal	Pass
2	2402.23	100.84	-0.34	74	-26.84	Peak	83.4	150	Horizontal	N/A
3	5953.99	52.80	15.90	74	21.20	Peak	282.1	150	Horizontal	Pass
4	8347.34	47.44	18.24	74	26.56	Peak	259.9	150	Horizontal	Pass
5	14611.48	45.04	9.03	74	28.96	Peak	346.8	150	Horizontal	Pass
6	22613.98	47.85	11.23	74	26.15	Peak	263.1	150	Horizontal	Pass

GESK Middle Channel 1 GHz to 25 GHz ANT \

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	1915.21	50.30	-2.58	74	23.70	Peak	26.1	150	Vertical	Pass
2	2440.12	104.39	-0.38	74	-30.39	Peak	233.7	150	Vertical	N/A
3	5942.67	50.78	15.81	74	23.22	Peak	49.5	150	Vertical	Pass
4	8706.74	45.30	18.28	74	28.70	Peak	323.1	150	Vertical	Pass
5	12457.99	45.11	8.86	74	28.89	Peak	341.5	150	Vertical	Pass
6	24201.33	48.21	11.63	74	25.79	Peak	347.8	150	Vertical	Pass

GFSK Middle Channel 1 GHz to 25 GHz, ANT F

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	2151.02	53.85	-1.11	74	20.15	Peak	96.9	150	Horizontal	Pass
2	2440.10	99.03	-0.41	74	-25.03	Peak	36.1	150	Horizontal	N/A
3	5985.30	52.32	15.76	74	21.68	Peak	284.3	150	Horizontal	Pass
4	8628.12	46.63	18.28	74	27.37	Peak	81.6	150	Horizontal	Pass
5	16972.13	45.59	20.48	74	28.41	Peak	313.2	150	Horizontal	Pass
6	19888.52	47.21	9.93	74	26.79	Peak	315.4	150	Horizontal	Pass

GFSK High Channel 1 GHz to 25 GHz, ANT V



No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	1779.48	51.67	-3.70	74	22.33	Peak	154.3	150	Vertical	Pass
2	2480.19	104.21	-0.56	74	-30.21	Peak	289.2	150	Vertical	N/A
3	2483.32	51.42	-0.61	74	22.58	Peak	169.2	150	Vertical	Pass
4	10559.90	41.78	15.63	74	32.22	Peak	325.6	150	Vertical	Pass
5	17700.08	44.19	9.64	74	29.81	Peak	146.9	150	Vertical	Pass
6	22993.34	46.64	9.63	74	27.36	Peak	329.7	150	Vertical	Pass

GFSK High Channel 1 GHz to 25 GHz, ANT H

No.	Frequency	Results	Factor (dB)	Limit	Margin	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(0)	(cm)		
1	2158.26	53.60	-0.98	74	20.40	Peak	201.4	150	Horizontal	Pass
2	2480.87	99.51	-0.56	74	-25.51	Peak	71.4	150	Horizontal	N/A
3	2736.98	51.70	1.76	74	22.30	Peak	18.3	150	Horizontal	Pass
4	7347.75	50.99	19.71	74	23.01	Peak	358.7	150	Horizontal	Pass
5	13498.75	45.77	9.02	74	28.23	Peak	153.5	150	Horizontal	Pass
6	18760.82	47.91	11.24	74	26.09	Peak	117	150	Horizontal	Pass



A.7 Band Edge (Restricted-band band-edge)


Test Data

Note 1: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note 2: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note 3: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390	48.27	74	25.73	PEAK	Pass
		2390		54		AVERAGE	Pass
GFSK	HIGH	2483.5	51.91	74	22.09	PEAK	Pass
		2483.5		54		AVERAGE	Pass







A.8 Power Spectral Density (PSD)


Test Data


Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-7.30	8	Pass
Middle Channel	-6.72	8	Pass
High Channel	-6.37	8	Pass

Test plots

LOW CHANNEL MIDDLE CHANNEL ★ Agilent Peak Search Ref 10 dBm #Peak #Atten 20 dB **Next Peak** Log 10 dB/ Offst 0.5 dB Next Pk Right Next Pk Left Min Search Pk-Pk Search Mkr → CF More 1 of 2 Center 2.402 000 0 GHz #Res BW 3 kHz Span 1.5 MHz Sweep 158.2 ms (601 pts) #VBW 10 kHz

#Atten 20 dB







ANNEX B TEST SETUP PHOTOS

Please refer the document "BL-SZ1680264-AR.PDF".

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document "BL-SZ1680264-AW.PDF".

ANNEX D EUT INTERNAL PHOTOS

Please refer the document "BL-SZ1680264-AI.PDF".

--END OF REPORT--