

RF EXPOSURE **EVALUATION REPORT**

APPLICANT

TechMille Ltd.

PRODUCT NAME

Vibration Mote

MODEL NAME

Model 1, Model 2

TRADE NAME

Petasense

BRAND NAME

Petasense

FCC ID

2AHKW-00061

47CFR 2.1091

STANDARD(S)

KDB 447498 D01 General RF Exposure

Guidance v06

ISSUE DATE

ECHNOLOGY Co., Ltd. SHENZHEN MORLAB CON

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555
Back 66-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	4
1.1. IDENTIFICATION OF APPLICANT	4
1.2. IDENTIFICATION OF MANUFACTURER	4
1.3. 1. PHOTOGRAPHS OF THE EUT	4
1.3.1. PHOTOGRAPHS OF THE EUT	5
1.3.2. IDENTIFICATION OF ALL USED EUT	6
1.4. APPLIED REFERENCE DOCUMENTS	6
2. DEVICE CATEGORY AND RF EXPOSURE LIMIT	MOR. OF M.
2. DEVICE CATEGORY AND RF EXPOSURE LIMIT	<u> </u>
3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER	8
4. RF EXPOSURE EVALUATION	8
ANNEX C GENERAL INFORMATION	<u>9</u>

Change History					
Issue	Issue Date Reason for change				
1.0	2016-07-11	First edition			
MORE	Me	3 RLAT MORE ME AB RLAT MORE			



TEST REPORT DECLARATION

Applicant	TechMille Ltd.		
Applicant Address	B609 Botai Int'l Plaza, No. 122 Guangshun North Street, Chaoyang District, Beijing		
Manufacturer	HONG KONG ZONGWELL INDUSTRIAL CO., LTD.		
Manufacturer Address	UNIT 04, 7/F, BRIGHT WAY TOWER, NO. 33 MONG KOK ROAD, KOWLOON, HK		
Product Name	Vibration Mote		
Model Name	Petasense		
Brand Name	Model 1,Model 2		
HW Version	C18		
SW Version	V2.0.0		
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06		
Issue Date	2016-07-11		
SAR Evaluation	Not Required		

Tested by	: Chen Sheng kui			
		Chen Shengkui		
Reviewed by		Liu Jun		
		Liu Jun		
Approved by	:	Zeno Dexin		
		Zeno Dexin		



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant


Company Name:	TechMille Ltd.
Address:	B609 Botai Int'l Plaza, No. 122 Guangshun North Street, Chaoyang
The Moken Mo.	District, Beijing

1.2. Identification of Manufacturer

Company Name:	HONG KONG ZONGWELL INDUSTRIAL CO., LTD.		
Address:	UNIT 04, 7/F, BRIGHT WAY TOWER, NO. 33 MONG KOK ROAD,		
E OFLAN MORE	KOWLOON, HK		

1.3. Equipment Under Test (EUT)

Model Name:	Model 1, Model 2				
Trade Name:	Petasense				
Brand Name:	Petasense				
Hardware Version:	C18				
Software Version:	V2.0.0				
Frequency Bands:	WIFI 802.11b/g/n20/n40; Bluetooth 4.0;				
Modulation Mode:	WIFI802.11b: DSSS;WIFI802.11g: OFDM;WIFI802.11n20: OFDM; WIFI802.11n40: OFDM; Bluetooth 4.0:GFSK;				
Antenna type:	BT4.0: Ceramic Antenna WIFI:PCB Antenna				
Antenna Gain:	BT4.0: 0.5 dBl WIFI:2.0 dBl				





1.3.1. Photographs of the EUT

EUT front view



2. EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Hardware Version		Software Version
1#	C18	V2.0.0

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title		
1 OPLAE	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile devices		
2	KDB 447498 D01v06	General RF Exposure Guidance		



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
(E	3) Limits for General	Population/Uncontro	lled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz



Plane-wave equivalent power density



3. MEASUREMENT OF CONDUCTED PEAK OUTPUT POWER

2.4G Wifi average output power

Donal	Frequenc		Output Power(dBm)		
Band	Channel	y (MHz)	802.11B	802.11G	802.11N 20
Wifi	1	2412	9.77	7.66	4.92
	6	2437	9.58	7.55	4.72
	11	2462	9.74	7.55	4.86

Bluetooth Conducted Average Output Power

Band	Channel	Frequency	Output Power(dBm)
Barra	(M	(MHz)	GFSK
B	0	2402	-8.18
BT	19	2440	-9.04
	39	2480	-10.24

4 RF EXPOSURE EVALUATION

Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Average Power (dBm)	Time-averaging EIRP (mW)	Power density (mW/cm²)	Limit for MPE (mW/cm²)
2.4GHz	2462	2.0	9.77	15.03	0.0001	1.0
ВТ	2402	0.5	-8.18	0.17	0.00003	1.0

MPE calculation method

Power Density = EIRP/ $4\pi R^2$

Where: EIRP = P·G

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)



ANNEX C GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.		
Department:	Morlab Laboratory		
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China		
Responsible Test Lab Manager:	Mr. Su Feng		
Telephone:	+86 755 36698555		
Facsimile:	+86 755 36698525		

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

***** END OF REPORT *****