Shenzhen Global Test Service Co., Ltd.



1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation

Report Reference No:	GTSR16020030-MPE
FCC ID::	2AHMXDOOGEEP1

Compiled by

(position+printed name+signature)..: File administrators Jimmy Wang

Supervised by

(position+printed name+signature)..: Test Engineer Peter Xiao

Approved by

(position+printed name+signature)..: Manager Sam Wang

Date of issue Mar. 21, 2016

Representative Laboratory Name: Shenzhen Global Test Service Co.,Ltd.

Shenzhen, Guangdong

Applicant's name...... Shenzhen DOOGEE TONG WEI Tech Co.,Ltd.

Sangda estate, Zhehua Road, Huaqiang North street, Futian Dis.

Shenzhen

Test specification....::

47CFR §1.1310

KDB447498 v05r02

TRF Originator...... Shenzhen Global Test Service Co.,Ltd.

Master TRF Dated 2014-12

Shenzhen Global Test Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Smart projector

Trade Mark.....

Manufacturer Shenzhen DOOGEE TONG WEI Tech Co.,Ltd.

Model/Type reference DOOGEE P1

Listed Models

Exposure category General population/uncontrolled environment

EUT Type Production Unit

Hardware Version L8-MAIN-PCB-V1.3

Software Version...... M806-V54

Output:DC5V,2A

Result..... PASS

Report No.: GTSR16020030-MPE Page 2 of 8

TEST REPORT

Test Report No. :	GTSR16020030-MPE	Mar. 21, 2016
	0101(10020030-WII E	Date of issue

Equipment under Test Smart projector

DOOGEE P1 Model /Type

/ Listed Models

Applicant Shenzhen DOOGEE TONG WEI Tech Co.,Ltd.

The Forth and Fifth floor of the western Room 412, plant

Address 405, Sangda estate, Zhehua Road, Huaqiang North

street, Futian Dis. Shenzhen

Manufacturer Shenzhen DOOGEE TONG WEI Tech Co.,Ltd.

The Forth and Fifth floor of the western Room 412, plant Address

405, Sangda estate, Zhehua Road, Huaqiang North

street, Futian Dis. Shenzhen

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>SUMMARY</u>	4
1.1.	EUT configuration	4
1.2.	Product Description	4
1.3.	Note	4
<u>2.</u>	TEST ENVIRONMENT	5_
2.1.	Address of the test laboratory	5
2.2.	Test Facility	
2.3.	Environmental conditions	5 5 5
2.4.	Statement of the measurement uncertainty	5
<u>3.</u>	METHOD OF MEASUREMENT	6
3.1.	Applicable Standard	6
3.2.	Requirement	6
3.3.	Conducted Power Results	6 7
<u>4.</u>	EVALUATION RESULT	8
<u>5.</u>	CONCLUSION	8

Report No.: GTSR16020030-MPE Page 4 of 8

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- $\ensuremath{\bigcirc}$ supplied by the lab

0	Power Cable	Length (m):	/
		Shield :	1
		Detachable :	/

1.2. Product Description

Name of EUT	Smart projector
Model Number	DOOGEE P1
Listed Models	/
FCC ID	2AHMXDOOGEEP1
Power Supply	DC 5V or Battery DC 3.8V
Adapter information:	Model: ASSA41i-050200 Input: 100-240V∼50/60Hz 0.5A Output:DC 5.0V 2.0A
Supported type:	802.11a/802.11b/802.11g/802.11n HT20
Operation bandwidth:	20MHz
Modulation:	802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11b: DSSS(CCK,DQPSK,DBPSK) 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
	802.11a: 5180MHz—5240MHz/5745MHz—5825MHz
	802.11b:2412-2462MHz
Operation frequency:	802.11g:2412-2462MHz
	802.11n HT20:2412-2462MHz/5180MHz—5240MHz/5745MHz—5825MHz
Antenna Type	Internal Antenna

1.3. Note

Function	Test Standards	Reference Report
WLAN-2.4	FCC Part 15 Subpart C	GTSR16020030-2.4WLAN
WLAN-5.8	FCC Part 15 Subpart E	GTSR16020030-5.8WLAN
EMF	FCC Per 47 CFR 2.1093(d)	GTSR16020030-MPE

Report No.: GTSR16020030-MPE Page 5 of 8

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 964637

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 964637, Jul 24, 2015.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C		
Humidity:	30-60 %		
Atmospheric pressure:	950-1050mbar		

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01" Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Report No.: GTSR16020030-MPE Page 6 of 8

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v05r02: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)
	Limits for Occ	cupational/Control	led Exposure	
0.3 - 3.0 3.0 - 30 30 - 300 300 - 1500 1500 - 100,000	614 1842/f 61.4 /	1.63 4.89/f 0.163 /	(100) * (900/f²)* 1.0 f/300 5	6 6 6 6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Limits for Maximum r emissible Exposure (Mr E)/Oncomfolied Exposure					
Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm²)	Averaging Time (minute)	
	Limits for Occ	cupational/Control	led Exposure		
0.3 - 3.0 3.0 - 30 30 - 300 300 - 1500 1500 - 100,000	614 824/f 27.5 /	1.63 2.19/f 0.073 /	(100) * (180/f²)* 0.2 f/1500 1.0	30 30 30 30 30	

F=frequency in MHz

^{*=}Plane-wave equivalent power density

3.4. Conducted Power Results

Mode		Frequency (MHz)	Worst case Data rate	Conducted Output Power (dBm)	
		(IVITIZ)	Data Tate	PK	Average
	01	2412	1Mbps	8.62	5.24
802.11b	06	2437	1Mbps	8.52	5.16
	11	2462	1Mbps	8.05	5.12
802.11g	01	2412	6Mbps	8.32	3.19
	06	2437	6Mbps	8.14	3.78
	11	2462	6Mbps	8.02	2.97
802.11n HT20	01	2412	6.5 Mbps	7.62	2.28
	06	2437	6.5 Mbps	7.54	2.06
	11	2462	6.5 Mbps	7.41	1.95

Mode	Channel	Frequency (MHz)	Worst case Data rate	Conducted Output Power (dBm)	
			Data rate	PK	Average
802.11a	36	5180	1Mbps	14.26	10.82
	40	5200	1Mbps	13.82	10.65
	48	5240	1Mbps	13.54	10.28
	149	5745	6Mbps	14.73	10.17
	157	5785	6Mbps	14.52	10.12
	165	5825	6Mbps	14.83	9.84
802.11n HT20	36	5180	6.5 Mbps	13.95	11.52
	40	5200	6.5 Mbps	13.84	11.35
	48	5240	6.5 Mbps	13.02	11.52
	149	5745	6.5 Mbps	14.17	10.54
	157	5785	6.5 Mbps	13.89	10.32
	165	5825	6.5 Mbps	13.02	9.89

Manufacturing tolerance

IEEE 802.11b (Average)							
Frequency	2412	2437	2462				
Target (dBm)	5.0	5.0	5.0				
Tolerance ±(dB)	1.0	1.0	1.0				
	IEEE 802.11g (Average)						
Frequency	2412	2437	2462				
Target (dBm)	3.0	3.0	3.0				
Tolerance ±(dB)	1.0	1.0	1.0				
IEEE 802.11n HT20 (Average)							
Frequency	2412	2437	2462				
Target (dBm)	2.0	2.0	2.0				
Tolerance ±(dB)	1.0	1.0	1.0				
		1a(Average)					
Frequency	5180	5200	5240				
Target (dBm)	10.0	10.0	10.0				
Tolerance ±(dB)	1.0	1.0	1.0				
	IEEE802.11a(Average)						
Frequency	5745	5785	5825				
Target (dBm)	10.0	10.0	10.0				
Tolerance ±(dB)	1.0	1.0	1.0				
IEEE802.11 n HT20 (Average)							
Frequency	5180	5200	5240				
Target (dBm)	11.0	11.0	11.0				
Tolerance ±(dB)	1.0	1.0	1.0				
IEEE802.11 n HT20 (Average)							
Frequency	5745	5785	5825				
Target (dBm)	10.0	10.0	10.0				
Tolerance ±(dB)	1.0	1.0	1.0				

Report No.: GTSR16020030-MPE Page 8 of 8

3.5. MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum soure-baed Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r =20cm, as well as the gain of the used antenna is 2.0dBi for WLAN, and the power drift from Turnup Procedure provide by manufacturer as following states, the RF power density can be obtained.

4. Evaluation Result

4.1. Standalone MPE

	Minimum Separation	Output Power (Turn-up Procedure)		Antenna Gain	Power Density	Power Density	Test
	Distance (cm)	dBm	mW	(Numeric)	At 20 cm (mW/cm ²)	Limit (mW/cm ²)	Results
2.4WLAN	20.00	6.0	3.9811	1.5849	0.0013	1.0000	PASS
5.8WLAN	20.00	12.0	15.8489	1.5849	0.0049	1.0000	PASS

4.2. Simultaneous transmission MPE Considerations

According to KDB447498 :For mobile exposure host platform to qualify for simultaneous transmission MPE test exclusion, all transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

 \sum of MPE ratios ≤ 1.0

5. Conclusion

This equipment complies with FCC radiatior	exposure limits	set forth for an	uncontrolled
environment.			

End	of	Report
-----	----	--------