

Bowhead Technology (Shanghai) Ltd.

3F, No.1237, Mid-Fuxing Rd., Shanghai PRC 200031

Declaration Letter

Date: April. 1, 2016

To: Federal Communications Commission Authorization and Evaluation Division 7435
Oakland Mills Road Columbia MD 21046

FCC ID: 2AHP2BWT1601A

To Whom It May Concern:

This letter is to ascertain that Bowhead Technology (Shanghai) Ltd.

Product Witreless Charger & Power Bank FCC ID : 2AHP2BWT1601A, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 Clause 5(2) all 6 conditions as stated below hence PBA is not required.

a	Power transfer frequency is less than 1 MHz →The power transfer frequency is 166kHz. Therefore the frequency specification is satisfied with the device.
b	Output power from each primary coil is less than 5 watts →The maximum output power of each coil is less than5 watts.
c	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils →The DUT(Device Under Test) includes only one coil in transmitter. A secondary coil is detected and coupled by transmitter.
d	Client device is inserted in or placed directly in contact with the transmitter →When the client device is placed directly in contact with transmitter, then charging is able to start.
e	The maximum coupling surface area of the transmit (charging) device is between 60 cm ² and 400 cm ² . → The maximum coupling surface area of the transmitter is 64 cm ² Maximum coupling surface area(8cm x 8 cm)
f	Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit. →The highest leakage filed is less than 30 % of the MPE(Maximum Permissible Exposure) limit.

If you have any question or concerns, pls. contact us. Sincerely Yours,

Name of Applicant:	Gary Zong
Title of Applicant:	Manager
Signature of Applicant:	