



FCC TEST REPORT (Part 15, Subpart C)

Applicant:	OCTO Telematics S.p:A				
Address:	Via Lamaro 51 Rome RM 00173 Italy				
Manufacturer or Supplier:	Gosuncn Technology Group Co., I	Ltd.			
Address:	6F, 2819 KaiChuang Blvd., Science Guangdong, China.	e Town, Huangpu District, Guangzhou City,			
Product:	OBU				
Brand Name:	осто				
Model Name:	AT41				
FCC ID:	2AHR8-AT41BT				
Date of tests:	Mar. 02, 2018 ~ Mar. 13, 2018				
The tests have been	en carried out according to the requi	rements of the following standard:			
	Subpart C, Section 15.247 2013				
CONCLUSION: TI	he submitted sample was found to	COMPLY with the test requirement			
	Prepared by Roger Li Engineer / Mobile Department Approved by Sam Tung Manager / Mobile Department				
Roger					

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/our-business/eps/about-us/eems-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Date: Mar. 27, 2018



TABLE OF CONTENTS

REL	EASE (CONTROL RECORD	4
1	SUMM	ARY OF TEST RESULTS	5
1.1	MEAS	SUREMENT UNCERTAINTY	5
2	GENE	RAL INFORMATION	6
2.1	GENI	ERAL DESCRIPTION OF EUT	6
2.2	DESC	CRIPTION OF TEST MODES	7
	2.2.1	CONFIGURATION OF SYSTEM UNDER TEST	8
	2.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	8
2.3	GENI	ERAL DESCRIPTION OF APPLIED STANDARDS	10
2.4	DESC	CRIPTION OF SUPPORT UNITS	10
3	TEST	TYPES AND RESULTS	11
3.1	CON	DUCTED EMISSION MEASUREMENT	11
	3.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	11
	3.1.2	TEST INSTRUMENTS	11
	3.1.3	TEST PROCEDURES	12
	3.1.4	DEVIATION FROM TEST STANDARD	12
	3.1.5	TEST SETUP	13
	3.1.6	EUT OPERATING CONDITIONS	13
	3.1.7	TEST RESULTS	14
3.2	RADI	ATED EMISSION MEASUREMENT	16
	3.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	16
	3.2.2	TEST INSTRUMENTS	17
	3.2.3	TEST PROCEDURES	18
	3.2.4	DEVIATION FROM TEST STANDARD	18
	3.2.5	TEST SETUP	19
	3.2.6	EUT OPERATING CONDITIONS	20
	3.2.7	TEST RESULTS	21
3.3	6 DB	BANDWIDTH MEASUREMENT	26
	3.3.1	LIMITS OF 6DB BANDWIDTH MEASUREMENT	26
	3.3.2	TEST INSTRUMENTS	26
	3.3.3	TEST PROCEDURE	26
	3.3.4	DEVIATION FROM TEST STANDARD	27
	3.3.5	TEST SETUP	27
	3.3.6	EUT OPERATING CONDITIONS	27



BUREAU Test Report No.: RF180302W004-2

RY T	ΉFΙΔΕ		35
5	APPEN	IDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE E	UT
4	РНОТС	GRAPHS OF THE TEST CONFIGURATION	37
	3.6.7	TEST RESULTS	. 34
	3.6.6	EUT OPERATING CONDITION	. 34
	3.6.5	DEVIATION FROM TEST STANDARD	. 34
	3.6.4	TEST PROCEDURE	. 33
	3.6.3	TEST INSTRUMENTS	. 33
	3.6.2	TEST SETUP	. 33
	3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	. 33
3.6	OUT	OF BAND EMISSION MEASUREMENT	. 33
	3.5.7	TEST RESULTS	. 32
	3.5.6	EUT OPERATING CONDITION	. 31
	3.5.5	DEVIATION FROM TEST STANDARD	. 31
	3.5.4	TEST PROCEDURE	
	3.5.3	TEST INSTRUMENTS	
	3.5.2	TEST SETUP	. 31
	3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	
3.5		ER SPECTRAL DENSITY MEASUREMENT	
		AVERAGE OUTPUT POWER (FOR REFERENCE)	
		MAXIMUM PEAK OUTPUT POWER	
	3.4.7	TEST RESULTS	
	3.4.6	EUT OPERATING CONDITIONS	
	3.4.5	DEVIATION FROM TEST STANDARD	
	3.4.4	TEST PROCEDURES	
	3.4.3	TEST INSTRUMENTS	
	3.4.2	TEST SETUP	
5.4	3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	
3 /		DUCTED OUTPUT POWER	
	3.3.7	TEST RESULTS	. 28



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF180302W004-2	Original release	Mar. 27, 2018

SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

Α	APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)								
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK						
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -16.65dB at 0.392000MHz.						
15.205 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -5.59dB at 57.16MHz.						
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.						
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.						
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.						
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.						
15.203	Antenna Requirement	PASS	No antenna connector is used						

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in ETSI TR 100 028-2001:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
	9KHz ~ 30MHz	2.68dB
Radiated emissions	30MHz ~ 1GMHz	3.26dB
Radiated emissions	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	ОВИ
BRAND NAME	осто
MODEL NAME	AT41
NOMINAL VOLTAGE	DC 12V 3.7Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	DTS
MODULATION TYPE	BT-LE(GFSK) for DTS
TRANSMISSION RATE	BT_LE: 1 Mbps
OPERATING FREQUENCY	2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	BT-LE: 0.87mW (Maximum)
ANTENNA TYPE	PIFA Antenna with 2.5dBi gain
HW VERSION	AT41_MB_B
SW VERSION	ME3631U1AV1.0B06
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

- 1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- 2. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION	
BT_LE	1TX /1RX	

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



BUREAU Test Report No.: RF180302W004-2

2.2 DESCRIPTION OF TEST MODES

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE		APPLIC	ABLE TO		MODE
MODE	RE<1G	RE≥1G	PLC	APCM	MODE
-	V	√	√	√	-

Where

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	19	DTS	GFSK	1.0

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☑Following channel(s) was (were) selected for the final test as listed below.

MODE	MODE AVAILABLE CHANNEL		MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	DTS	GFSK	1.0



POWER LINE CONDUCTED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE TESTED CHANNEL		MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
BT-LE	0 to 39	19	DTS	GFSK	1.0

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE	TESTED	MODULATION	MODULATION	DATA RATE
	CHANNEL	CHANNEL	TECHNOLOGY	TYPE	(Mbps)
BT-LE	0 to 39	0, 39	DTS	GFSK	1

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE	TESTED	MODULATION	MODULATION	DATA RATE
	CHANNEL	CHANNEL	TECHNOLOGY	TYPE	(Mbps)
BT-LE	0 to 39	0, 19, 39	DTS	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY	
RE<1G	22deg. C, 54%RH	DC 12V	Star Le	
RE≥1G	22deg. C, 54%RH	DC 12V	Star Le	
PLC	24deg. C, 55%RH	DC 12V	Jocan Guo	
APCM	25deg. C, 60%RH	DC 3.7V from battery	Wenliang Wu	

2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247
KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

Note:

- 1. All test items have been performed and recorded as per the above standards.
- 2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m

TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)			
	Quasi-peak	Average		
0.15 ~ 0.5	66 to 56	56 to 46		
0.5 ~ 5	56	46		
5 ~ 30	60	50		

NOTE: 1. The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Jun. 28,17	Jun. 27,18
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Sep. 18,17	Sep. 17,18

NOTE:

- 1. The test was performed in CE shielded room.
- 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:


Frequency Range	1150KH7 - 30M/H7		Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2018/03/07

Frequency (MHz)	QuasiPeak (dB¦ÌV)	CAverage (dB¦ÌV)	Limit (dB¦ÌV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000		29.84	56.00	-26.16	L1	ON	9.6
0.150000	46.63		66.00	-19.37	L1	ON	9.6
0.400000		25.17	47.85	-22.68	L1	ON	9.7
0.400000	39.83		57.85	-18.02	L1	ON	9.7
0.876000		14.65	46.00	-31.35	L1	ON	9.7
0.876000	22.12		56.00	-33.88	L1	ON	9.7
9.676000		24.16	50.00	-25.84	L1	ON	9.9
9.676000	28.50		60.00	-31.50	L1	ON	9.9
11.408000		25.73	50.00	-24.27	L1	ON	9.9
11.408000	31.34		60.00	-28.66	L1	ON	9.9
0.150000		29.84	56.00	-26.16	L1	ON	9.6
0.150000	46.63		66.00	-19.37	L1	ON	9.6

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.





Email: customerservice.dg@cn.bureauveritas.com




Frequency Range	150KHz ~ 30MHz		Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Jocan Guo	TEST DATE	2018/03/07

Frequency (MHz)	QuasiPeak (dB¦ÌV)	CAverage (dB¦ÌV)	Limit (dB¦ÌV)	Margin (dB)	Line	Filter	Corr. (dB)
0.158000		33.12	55.57	-22.45	N	ON	10.1
0.158000	44.58		65.57	-20.99	N	ON	10.1
0.392000		25.47	48.02	-22.55	N	ON	10.1
0.392000	41.37		58.02	-16.65	N	ON	10.1
7.560000		21.26	50.00	-28.74	N	ON	9.8
7.560000	26.71		60.00	-33.29	N	ON	9.8
9.880000		23.96	50.00	-26.04	N	ON	9.9
9.880000	28.14		60.00	-31.86	N	ON	9.9
12.860000		22.13	50.00	-27.87	N	ON	9.9
12.860000	29.85		60.00	-30.15	N	ON	9.9
17.964000		20.95	50.00	-29.05	N	ON	10.0
17.964000	25.57		60.00	-34.43	N	ON	10.0

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

- 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
- 3. The emission levels of other frequencies were very low against the limit.
- 4. Margin value = Emission level Limit value
- 5. Correction factor = Insertion loss + Cable loss
- 6. Emission Level = Correction Factor + Reading Value.



Email: customerservice.dg@cn.bureauveritas.com

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)		
0.009 ~ 0.490	2400/F(kHz)	300		
0.490 ~ 1.705	24000/F(kHz)	30		
1.705 ~ 30.0	30	30		
30 ~ 88	100	3		
88 ~ 216	150	3		
216 ~ 960	200	3		
Above 960	500	3		

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



BUREAU Test Report No.: RF180302W004-2

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn- CT0001143-1216	May 06,17	May 05,18
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-4 0-K-SG/QMS- 00361	15433	Dec. 16,16	Dec. 15,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SM A	1505	Jul. 24,17	Jul. 23,18
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 10,18	Mar. 09,19
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

- 2. The test was performed in 3m Chamber.
- 3. The FCC Site Registration No. is 525120.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) /
 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test.
 The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

9 KHz – 30 KHz data: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.


30 MHz - 1GHz data:

BT-LE (GFSK)

CHANNEL	TX Channel 19	DETECTOR	Ougai Dack (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	Α	NTENN	IA POLAF	RITY & TE	ST DISTA	NCE: H	ORIZONT	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
57.16	34.41	64.17	40	-5.59	6.43	1.15	37.34	100	0	QP
141.55	22.34	49.15	43.5	-21.16	8.19	1.83	36.83	100	0	QP
201.69	26.12	50.3	43.5	-17.38	10.18	2.18	36.54	100	0	QP
254.07	35.12	56.72	46	-10.88	12.45	2.47	36.52	100	0	QP
289.96	26.84	47.79	46	-19.16	12.88	2.67	36.5	100	0	QP
349.13	22.3	40.92	46	-23.7	15.06	2.93	36.61	100	0	QP

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value






CHANNEL	TX Channel 19	DETECTOR	Ougoi Book (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
47.46	30.1	59.03	40	-9.9	7.44	1.04	37.41	200	0	QP	
97.9	23.3	51.01	43.5	-20.2	7.77	1.52	37	200	0	QP	
131.85	19.31	46.76	43.5	-24.19	7.67	1.76	36.88	200	0	QP	
193.93	32.86	57.27	43.5	-10.64	10.04	2.14	36.59	200	0	QP	
233.7	23.61	46.13	46	-22.39	11.65	2.36	36.53	200	0	QP	
361.74	15.51	33.57	46	-30.49	15.59	2.99	36.64	200	0	QP	

REMARKS:

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



Email: customerservice.dg@cn.bureauveritas.com



ABOVE 1GHz TEST DATA:

Note: For higher frequency, the emission is too low to be detected.

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	Α	NTENN	A POLAF	RITY & TE	ST DISTA	NCE: H	ORIZONT	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.35	41.25	54	-17.65	32.87	8.15	45.92	200	159	Average
2390	47.66	52.56	74	-26.34	32.87	8.15	45.92	200	159	Peak
2402	97.35	102.22			32.88	8.17	45.92	200	159	Average
2402	100.46	105.33			32.88	8.17	45.92	200	159	Peak
2483.5	36.69	41.28	54	-17.31	32.98	8.32	45.89	200	159	Average
2483.5	47.16	51.75	74	-26.84	32.98	8.32	45.89	200	159	Peak
		ANTEN	NA POLA	ARITY & 1	TEST DIST	ANCE: V	VERTICA	L AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.75	41.23	54	-18.25	32.29	8.15	45.92	100	295	Average
2390	46.88	52.36	74	-27.12	32.29	8.15	45.92	100	295	Peak
2402	97.45	102.9			32.3	8.17	45.92	100	295	Average
2402	100.12	105.57			32.3	8.17	45.92	100	295	Peak
2483.5	37.63	42.82	54	-16.37	32.38	8.32	45.89	100	295	Average
2483.5	47.6	52.79	74	-26.4	32.38	8.32	45.89	100	295	Peak

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	Α	NTENN	A POLAF	RITY & TE	ST DISTA	NCE: H	ORIZONT	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.26	42.16	54	-16.74	32.87	8.15	45.92	100	305	Average
2390	48.59	53.49	74	-25.41	32.87	8.15	45.92	100	305	Peak
2440	96.52	101.26			32.93	8.24	45.91	100	305	Average
2440	101.94	106.68			32.93	8.24	45.91	100	305	Peak
2483.5	37.72	42.31	54	-16.28	32.98	8.32	45.89	100	305	Average
2483.5	49.79	54.38	74	-24.21	32.98	8.32	45.89	100	305	Peak
		ANTEN	NA POLA	ARITY & 1	TEST DIST	ANCE: V	VERTICA	L AT 3 M	-	
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	35.48	40.96	54	-18.52	32.29	8.15	45.92	100	265	Average
2390	46.83	52.31	74	-27.17	32.29	8.15	45.92	100	265	Peak
2440	97.39	102.72			32.34	8.24	45.91	100	265	Average
2440	101.32	106.65			32.34	8.24	45.91	100	265	Peak
2483.5	37.16	42.35	54	-16.84	32.38	8.32	45.89	100	265	Average
2483.5	47.39	52.58	74	-26.61	32.38	8.32	45.89	100	265	Peak

- 1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level Limit value.
- 2. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	Α	NTENN	A POLAF	RITY & TE	ST DISTA	NCE: H	ORIZONT	AL AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	37.47	42.37	54	-16.53	32.87	8.15	45.92	100	310	Average
2390	48.53	53.43	74	-25.47	32.87	8.15	45.92	100	310	Peak
2480	96.68	101.29			32.98	8.31	45.9	100	310	Average
2480	100.84	105.45			32.98	8.31	45.9	100	310	Peak
2483.5	36.69	41.28	54	-17.31	32.98	8.32	45.89	100	310	Average
2483.5	50.28	54.87	74	-23.72	32.98	8.32	45.89	100	310	Peak
		ANTEN	NA POL	ARITY & 1	TEST DIST	ANCE: V	VERTICA	L AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	36.72	41.62	54	-17.28	32.87	8.15	45.92	100	290	Average
2390	49.69	54.59	74	-24.31	32.87	8.15	45.92	100	290	Peak
2480	95.58	100.19			32.98	8.31	45.9	100	290	Average
2480	100.9	105.51			32.98	8.31	45.9	100	290	Peak
2483.5	36.89	41.48	54	-17.11	32.98	8.32	45.89	100	290	Average
2483.5	49.67	54.26	74	-24.33	32.98	8.32	45.89	100	290	Peak

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Emission level – Limit value.
- 2. 2480MHz: Fundamental frequency.

3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Mar. 01,18	Feb. 28,19
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510523	Mar. 01,18	Feb. 28,19
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,18	Feb. 28,19
Power Sensor	ANRITSU	MA2411B	1339352	Mar. 01,18	Feb. 28,19

NOTE:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
- 2. The test was performed in RF Oven room.

3.3.3 TEST PROCEDURE

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) ≥ 3 RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.




BUREAU Test Report No.: RF180302W004-2

3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.3.7 TEST RESULTS

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.66	0.5	PASS
19	2440	0.66	0.5	PASS
39	2480	0.66	0.5	PASS




CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



3.4.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER 3.4.7.1

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT(W)	PASS/FAIL
0	2402	-0.59	0.87	1	PASS
19	2440	-0.71	0.85	1	PASS
39	2480	-0.68	0.86	1	PASS

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

BT-LE (GFSK)


CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	PASS/FAIL	
0	2402	-1.92	N/A	
19	2440	-0.85	N/A	
39	2480	-1.31	N/A	

3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

- 1. Set the span to 1.5 times the DTS bandwidth
- 2. Set the RBW = 3 kHz, VBW $\geq 3 \text{ x RBW}$, Detector = peak.
- 3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.


3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS

BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-14.21	8	PASS
19	2440	-14.34	8	PASS
39	2480	-14.40	8	PASS




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Tel: +86 755 8869 6566

MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Set span to encompass the spectrum to be examined
- 4. Detector = peak.
- 5. Trace Mode = max hold.
- 6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BT-LE (GFSK)



Email: customerservice.dg@cn.bureauveritas.com



BUREAU Test Report No.: RF180302W004-2



Email: customerservice.dg@cn.bureauveritas.com

PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---