

#### Annex FREQUENCY STABILITY

#### 9.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/-0.02% of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees.

#### 9.2 TEST PROCEDURE

- 1. The EUT was placed inside the environmental test chamber and powered by nominal DC voltage.
- 2. Turn the EUT on and couple its output to spectrum analyzer.
- 3. Turn the EUT off and set the chamber to the highest temperature specified.
- 4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2,5, and 10 minutes.
- 5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- 6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

## 9.3 Test Equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Temperature& Humidity test chamber	Safety test	GDS-250	171200018	2018.03.09	2019.03.08
DC power supply	Agilent	MY40002025	E3642A	2018/10/13	2019/10/12



# 9.4 TEST RESULT Channel 36 (5180MHz)

Voltage vs. Frequency Stability

Voltage vs. Frequency	Measurement
Stability Voltage(V)	Frequency(MHz)
5.75	5180.0023
5	5180.0020
4.25	5180.0017
Max.Deviation(MHz)	0.0023
Max.Deviation(ppm)	0.44

Rated working voltage:DC 5V

Temperature vs. Frequency Stability

Tomporeture(°C)	Measurement	
Temperature(°C)	Frequency(MHz)	
-30	5180.0260	
-20	5180.0258	
-10	5180.0256	
0	5180.0257	
10	5180.0251	
20	5180.0251	
30	5180.0254	
40	5180.0259	
50	5180.0253	
Max.Deviation(MHz)	0.0260	
Max.Deviation(ppm)	5.02	



### Channel 157 (5785MHz)

### Voltage vs. Frequency Stability

Voltage vs. Frequency	Measurement
Stability Voltage(V)	Frequency(MHz)
5.75	5785.0025
5	5785.0022
4.25	5785.0024
Max.Deviation(MHz)	0.0025
Max.Deviation(ppm)	0.43

Rated working voltage:DC 5V

Temperature vs. Frequency Stability

Tomporeture(°C)	Measurement	
Temperature(°ℂ)	Frequency(MHz)	
-30	5785.0019	
-20	5785.0015	
-10	5785.0009	
0	5785.0014	
10	5785.0013	
20	5785.0012	
30	5785.0010	
40	5785.0019	
50	5785.0010	
Max.Deviation(MHz)	0.0019	
Max.Deviation(ppm)	0.33	