

RF EXPOSURE EVALUATION for My Smart Blinds Inc

My Smart Blinds Smart Switch Model No.: BC-015

Prepared for : My Smart Blinds Inc

Address : 2365 Mountain Vista Ln. Provo, Utah, 84606, United States

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road,

Nanshan District, Shenzhen, Guangdong, China

Tel: (86) 755-26066544 Fax: (86) 755-26014772

Report Number : R0116051116I-1
Date of Test : Jun. 01~ 16, 2016
Date of Report : Jun. 17, 2016



TABLE OF CONTENT

Description

Test Report	Page			
1. GENERAL INFORMATION				
1.1. Description of Device (EUT)		4		
2. FCC § 2.1093 - RADIOFREQUENCY RADIATION EXPOSI PORTABLE DEVICES				
2.1. RF Exposure				



TEST REPORT

Applicant : My Smart Blinds Inc

Manufacturer : Long Xing Long Metal & Plastic Products

EUT : My Smart Blinds Smart Switch

Model No. : BC-015

Serial No. : N.A.

Trade Mark : N.A.

Rating : DC 3.0V Battery

Measurement Procedure Used:

FCC PART 2 Subpart J 2015 paragraph 2.1093

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC §2.1093 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test:	Jun. 01~ 16, 2016			
Prepared by :	keloo zhang			
	(Tested Engineer / Kebo Zhang)			
Reviewer:	Amy Ding			
	(Project Manager / Amy Ding)			
Approved & Authorized Signer:	Ton Chen			
	(Manager / Tom Chen)			



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

: My Smart Blinds Smart Switch

Model Number : BC-015

Test Power Supply: DC 3V Battery

Frequency : 2402~2480MHz

Modulation : GFSK

Channel Spacing : 2MHz

Number of

Channels

: 40

Antenna Type : PCB Antenna

Antenna Gain : 1.3 dBi

Applicant : My Smart Blinds Inc

Address : 2365 Mountain Vista Ln. Provo, Utah, 84606, United States

Manufacturer : Long Xing Long Metal & Plastic Products

Address : #83 LangeBei Industrial Road, Tongle, LongGang District,

Shenzhen, 518116, China

Factory : Long Xing Long Metal & Plastic Products

Address : #83 LangeBei Industrial Road, Tongle, LongGang District,

Shenzhen, 518116, China

Date of receipt : Jun. 01, 2016

Date of Test : Jun. 01~ 16, 2016



1.2. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 752021

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 752021, July 10, 2013.

IC-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited., EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration 8058A, Jun. 13, 2016.

Test Location

All Emissions tests were performed at Shenzhen Anbotek Compliance Laboratory Limited. at 1/F., Building 1, SEC Industrial Park, No.0409 Qianhai Road, Nanshan District, Shenzhen, Guangdong, China



2. FCC § 2.1093 - RADIOFREQUENCY RADIATION EXPOSURE

EVALUATION: PORTABLE DEVICES.

2.1. RF Exposure

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b):

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f_{\text{(GHz)}}}] \le 3.0 \text{ for } 1\text{-g SAR and } \le 7.5 \text{ for } 10\text{-g extremity SAR,}^{16} \text{ where}$

- · f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

2.2. Test Results

Channel (MHz)	Maximum output power(dBm)	Tune up tolerance(dBm)	Max Tune Up Power (dBm)	Distance	Calculation results	Limit
2402	0.514	0.514±1	1.514	5	0.439	3
2440	0.306	0.306±1	1.306	5	0.422	3
2480	2.234	2.234±1	3.234	5	0.663	3

Test Results: PASS.