


尺寸: 45*100mm
材质: 120克书写纸

正面

 <p>Hornet S Remote Controller RD12</p> <p>Operation Manual www.JYU.com</p>	<p>PART DESCRIPTIONS</p>  <p>Hornet S Communication Indicator red: disconnected green: connected</p> <p>remote battery capacity indicator red: low battery green: battery capacity OK</p> <p>RGB mode</p> <p>left sticker</p> <p>power on/off</p> <p>return to home</p> <p>photo/video</p> <p>right sticker</p> <p>hook</p> <p>take off/land</p> <p>mode switch [3. professional mode] [2. normal mode] [1. beginner mode]</p> <p>phone access</p> <p>antenna</p> <p>gimbal up/down wheel</p> <p>CH+ (add channel)</p> <p>CH- (reduce channel)</p> <p>LED brightness wheel</p> <p>charging and live view port</p>	<p>LED INDICATOR</p>  <p>There are 3 Bicolor (red/green) LED indicators on the remote controller used to indicate the status of communications, GPS and battery capacity.</p> <p>1. Communication Indicator The communication indicator will show green when the remote controller is successfully connected to the Hornet S and the user can operate the remote controller normally. The communication indicator will show red when the remote controller is disconnected from the Hornet S due to long communication distance or electromagnetic interference.</p> <p>2. GPS Status Indicator (this function is not yet available)</p> <p>3. Battery Capacity Indicator (Attention) This battery capacity indicator is for the remote controller battery, not the intelligent flight battery in the Hornet S. The battery capacity indicator will show green when the remote controller battery is at a normal capacity level. The battery capacity indicator will flash red and the alarm will vibrate ON and OFF every 5 seconds when the remote controller battery is at a low capacity level.</p> <p>Charging Instructions Plug the charger into the Micro-USB port. Turn the remote controller power and the charger power ON. During charging the battery capacity indicator will be red. When charging is complete it will be green.</p>	<p>POWER AND FUNCTION BUTTONS</p> <p>The remote controller front panel has a Power Button, a 3 position Mode Switch and 4 function switches. Two additional function switches can be found on the rear panel.</p> <p>There are two ways to use the buttons; Short Press (<1.5 seconds) and Long Press (>1.5 seconds). If the button is pressed and held longer than 1.5 seconds the remote controller will vibrate to confirm the Long Press.</p> <p>1. On/Off Slide the switch to turn ON power to the remote controller. It will vibrate once to indicate it is in US / North America configuration (throttle on left stick).</p> <p>2. Flight Mode Switch Mode 1 (Beginner): The GPS and Barometer hold position and altitude stable. Flight speed is 1/2 of Mode 2 (Normal). Slower, stable flight is perfect for beginners. Mode 2 (Normal): The GPS and Barometer hold position and altitude stable. Flight speed is set by the user. This mode is a good choice for users familiar with operating drones. Mode 3 (Professional): The GPS and Barometer are not used to hold position and altitude stable so the aircraft can respond quickly to changes and perform acrobatics. It can also fly at very high speeds. This mode is suitable for skilled fliers.</p> <p>3. Return to Home 1) Set the current location as Home by Long Press of button. 2) When in Mode 1 or Mode 2 and GPS is Normal, a Short Press of button will make the Hornet S automatically return to the Home location.</p> <p>4. Take Off/Land 1) Short Press The Hornet S will automatically land in the current location. 2) Long Press The Hornet S will automatically take Off in the current location.</p> <p>5. Take Photo/Video 1) Short Press The Hornet S will take a photograph. 2) Long Press The Hornet S will start recording video when the button is first pushed. Recording will stop when the button is pushed again.</p> <p>6. LED Control Button 1) Short Press Change the LED mode. 2) Long Press Add another channel while in the Gimbal Setting Mode. 3) CH+ 1) Short Press Delete one of the exiting channels while in the Gimbal Setting Mode 2) Mode Switch The Mode switch can be set to one of these three levels: 1. Beginner Mode 2. Normal Mode 3. Professional Mode</p>	<p>FUNCTION</p> <p>1. On/Off Slide the switch to turn ON power to the remote controller. It will vibrate once to indicate it is in US / North America configuration (throttle on left stick).</p> <p>2. Flight Mode Switch Mode 1 (Beginner): The GPS and Barometer hold position and altitude stable. Flight speed is 1/2 of Mode 2 (Normal). Slower, stable flight is perfect for beginners. Mode 2 (Normal): The GPS and Barometer hold position and altitude stable. Flight speed is set by the user. This mode is a good choice for users familiar with operating drones. Mode 3 (Professional): The GPS and Barometer are not used to hold position and altitude stable so the aircraft can respond quickly to changes and perform acrobatics. It can also fly at very high speeds. This mode is suitable for skilled fliers.</p> <p>3. Return to Home 1) Set the current location as Home by Long Press of button. 2) When in Mode 1 or Mode 2 and GPS is Normal, a Short Press of button will make the Hornet S automatically return to the Home location.</p> <p>4. Take Off/Land 1) When in Mode 1 or Mode 2, the GPS is Normal and the Hornet S is locked and in standby, a Long Press of button will make the Hornet S automatically fly to an altitude of approximately 5 meters and then hover in that location. 2) When in Mode 1 or Mode 2 and the Hornet S is unlocked and flying, a Short Press of button will make the Hornet S automatically land and lock at the current location.</p> <p>5. Photo/Video If the Hornet S has a camera installed, a Short Press of the Photo/Video button will cause the Hornet S to take a picture. A long press of the button will cause the Hornet S to start recording a video. A second press of the button will stop the recording.</p> <p>6. LED Control</p>
---	---	--	---	--

背面

<p>6. LED Control A Short Press of the LED control button will switch the LED pattern to Breath Mode. Another press of the LED control button will switch the LED pattern back to Rotation Mode.</p> <p>7. Throttle Configuration The default throttle configuration is left stick (US/North America). To set the throttle to right stick, turn the Remote Controller OFF. Press and hold the LED Control and the Photo/Video buttons and turn the Remote Controller ON again.</p> <p>When the Remote Controller vibrates twice, release the buttons, it is now configured to have the throttle on the right stick (Japan). As long as the Remote Controller is in this configuration it will vibrate twice when power is turned ON.</p> <p>To return the Remote Controller to throttle on left stick (US/North America), turn power OFF. Press and hold the LED Control and Photo/Video buttons and turn the Remote Controller ON again.</p> <p>When the Remote Controller vibrates once, release the buttons, it is now configured to have the throttle on the left stick (US/North America). As long as the Remote Controller is in this configuration it will vibrate once when power is turned ON.</p> <p>8. Image Transmission System Radio Frequency The Hornet S supports wireless transmission of the video signal. Camera data is sent to the Remote Controller and displayed on an external device such as FPV goggles, FPV display, smart phone or smart watch.</p> <p>The images are transmitted at an open channel ISM band and can interrupt other signals that may be on that band (such as a WiFi router) or be interrupted by the signal of a higher power device.</p> <p>If the signal is interfering with another device, you can move the video signal to a clearer channel using the Channel buttons on the back side of the remote controller.</p> <p>There are 7 available channels you can use (CH1, CH2, CH3, CH4, CH5, CH6 and CH7).</p>	<p>A Short Press of the CH+ button will switch the channel to the next higher channel.</p> <p>A Short Press of the CH- button will switch the channel to the next lower channel.</p> <p>9. Charging the Battery To charge the Remote Controllers internal battery, plug the power adapter charging cable into the Micro USB port, then plug the AC cable of the power adapter into a wall outlet. The battery charge indicator LEDs will be red to indicate charging. The indicator LEDs will change to green when charging is complete.</p> <p>10. Remote Controller Analog Channel Calibration The Hornet S supports 13 channels, including 6 analog channels (for sticks and dial wheels). Each of the 6 channels can be calibrated by the user. To calibrate the analog channels you must connect the Remote Controller to a computer using the Micro USB port. Once connected, turn the Remote Controller power ON and open the Hornet S ground station software and open the Hornet S ground station software.</p> <p></p> <p>Picture 4-1 Ground station remote control settings interface</p>	<p>Use the Remote Control to select the channel you wish to calibrate, then click the Start button to begin the calibration procedure.</p> <p>ATTENTION! Do not move the Remote Control sticks or dial wheels before starting the calibration procedure.</p> <p>When the calibration process begins, the LED indicator will turn green and begin to flash. Do not press any button or switch at this time! When the LED indicator turns red and begins to flash, push each stick fully left and then fully right. Move each dial wheel from minimum to maximum.</p> <p>When calibration is complete the Remote Controller will return to normal function. If calibration is not successful (typically because one of the channels is accidentally omitted) then you will need to perform calibration once again.</p> <p>11. Binding A Hornet S to a Remote Controller The Hornet S and Remote Controller are bound together as a working pair when you receive them. However, you can bind additional Hornet S aircraft to the same remote controller in this way: 1. Turn the Hornet S and Remote Controller Power OFF. 2. Press and hold the Return to Home and Take Off/Land buttons. 3. Turn the Remote Controller power ON. 4. Turn the Hornet S power ON. 5. When the LED indicator on the Remote Controller turns Green, the Hornet S is successfully bound to the Remote Controller.</p> <p>12. Software Update You can use your computer and the Hornet S PC software to check for Remote Controller software updates that may be available from JYU. If a new software version is available, you may load it on to your Remote Controller in this way: 1. Connect the Remote Controller to your PC using the supplied Micro USB cable. 2. Open the Hornet S software on your PC. 3. Click on the Remote Controller Firmware update button. The LED indicator will flash yellow to indicate the software is being downloaded.</p>	<p></p> <p>PC software firmware update interface</p> <p>If the Ground Station Software won't update the Remote Controller for some reason, please try this second option: 1. Turn the Remote Controller OFF and unplug the Micro USB connector. 2. Press and Hold the LED indicator button. 3. Turn the Remote Controller Power ON. The LED indicator will flash yellow. 4. Connect the Remote Controller to the PC using the Micro USB cable. 5. Click on the Remote Controller Firmware update button.</p> <p>FCC Caution:</p> <p>This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</p> <p>Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: -Reorient or relocate the receiving antenna. -Increase the separation between the equipment and receiver. -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. -Consult the dealer or an experienced radio/TV technician for help.</p> <p>RF warning statement: The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.</p>
--	---	---	---