Shenzhen Toby Technology Co., Ltd.

Report No.: TB-MPE147369

Page: 1 of 3

RF Exposure Evaluation FCC ID: 2AHTUSB5-SLAVE

1. Client Information

Applicant : Digitech Asia Ltd

Address : Suite 61, 76 Macdonnell Road Hong Kong

Manufacturer : Xunlei Yuanda Technology (Shenzhen) Co., Limited

Address: 3rd Floor, Baicai Technology Park, Beihuan Road, Shiyan Street,

Baoan District, Shenzhen, PRC

2. General Description of EUT

EUT Name	ŀ	Baby Safety-slave unit			
Models No.	:	SB-5			
Model Difference	•	N/A			
Product Description		Operation Frequency: Bluetooth:2402~2480MHz			
		Number of Channel:	BLE:40 Channels		
		Max Peak Output Power:	GFSK:4.26 dBm		
		Antenna Gain:	1 dBi Integral Antenna		
		Modulation Type:	1Mbps(GFSK)		
Power Supply	1	DC power by battery			
Power Rating	1	DC 3V by 2*1.5V AAA Battery.			
Connecting I/O Port(S)	5	Please refer to the User's Manual			

Note:

More test information about the EUT please refer the RF Test Report.

TB-RF-074-1. 0

Tel: +86 75526509301 Fax: +86 75526509195



Report No.: TB-MPE147369

Page: 2 of 3

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance Sub clause 4.31: Standalone SAR test exclusion considerations
 - 1)The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance≤5 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{(GHz)}}$] \leq 3.0 for 1-g SAR

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{(GHz)}}$] \leq 7.5.0 for 10-g SAR



Report No.: TB-MPE147369

Page: 3 of 3

2.

Calculation:

BLE Mode (GFSK)								
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value			
2.402	4.26	±0.5	2.992	0.928	3.0			
2.442	4.09	±0.5	2.877	0.899	3.0			
2.480	4.10	±0.5	2.884	0.908	3.0			

So standalone SAR measurements are not required.