

#### **TEST REPORT**

Report No.: 16070371HKG-002

**Toy Shock International Limited** 

**Application** For Certification (Original Grant) (FCC ID: 2AHUVGWRS0001)

Transceiver

Prepared and Checked by: Approved by:

Signed On File Lok Chi Hang, Wil **Assistant Engineer** 

Wong Kwok Yeung, Kenneth Senior Lead Engineer

Date: August 31, 2016

Intertek's standard Terms and Conditions can be obtained at our website http://www.intertek.com/terms/.

The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. © 2016 Intertek

## **GENERAL INFORMATION**

Grantee:	Toy Shock International Limited
Grantee Address:	Unit 11, 10/F., Tower A, New Mandarin Plaza,
	14 Science Museum Road, Tsim Sha Tsui East,
	Kowloon, Hong Kong.
Contact Person:	CF LIM
Tel:	(852) 2732 2272
Fax:	(852) 2732 2272
e-mail:	N/A
Manufacturer:	Dongguan Midfield Plastic Products Limited
Manufacturer Address:	No.1, HouDa Road, BaiHuaDong Village,
	DaLingShan Town, DongGuan City
Brand Name:	TAIYO
Model:	160000A
Additional Model:	160001A, 160002A
Type of EUT:	Transceiver
Description of EUT:	Flame Runner (160000A),
	Flame Bullet (160001A),
	Red Flame (160002A)
Serial Number:	N/A
FCC ID:	2AHUVGWRS0001
Date of Sample Submitted:	July 07, 2016
Date of Test:	July 07, 2016 to August 04, 2016
Report No.:	16070371HKG-002
Report Date:	August 31, 2016
Environmental Conditions:	Temperature: +10 to 40°C
	Humidity: 10 to 90%

Report No.: 16070371HKG-002

#### **SUMMARY OF TEST RESULT**

TEST SPECIFICATION	REFERENCE	RESULTS
Radiated Emission Radiated Emission on the Bandedge	15.249	Pass
Radiated Emission in Restricted Bands	15.205	Pass

The equipment under test is found to be complying with the following standards: FCC Part 15, October 1, 2014 Edition

Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the pervisions of this section.

Report No.: 16070371HKG-002 ii

<sup>2.</sup> Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

## **Table of Contents**

1.0	General Description	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	System Test Configuration	2
2.1	Justification	2
2.2	EUT Exercising Software	2
2.3	Special Accessories	2
2.4	Measurement Uncertainty	2
2.5	Support Equipment List and Description	2
3.0	Emission Results	3
3.1	Field Strength Calculation	3
3.2	Radiated Emission Configuration Photograph	4
3.3	Radiated Emission Data	
4.0	Equipment Photographs	9
5.0	Product Labelling	9
6.0	<u>Technical Specifications</u>	
7.0	Instruction Manual	
8.0	Miscellaneous Information1	0
8.1	Radiated Emission on the Bandedge1	0
8.2	Discussion of Pulse Desensitization1	1
8.3	Calculation of Average Factor1	
8.4	Emissions Test Procedures1	
9.0	Equipment List 1	7

Report No.: 16070371HKG-002 FCC ID: 2AHUVGWRS0001

#### 1.0 **General Description**

#### 1.1 Product Description

The Equipment Under Test (EUT) is a portable 2.4GHz Transceiver (Car Unit) for a RC Controller from 2414MHz, 2423MHz, 2452MHz and 2467MHz of specified channels. The EUT is powered by 4 X 1.5V AA batteries. After switch on the EUT and paired with controller, the car can be controlled to move forward, backward, turning left/ right direction by the controller.

The Model: 160001A and 160002A are the same as the Model: 160000A in hardware aspect. The difference in model number serves as marketing strategy. The models are different in body and wheel only.

Antenna Type: Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

The Certification procedure of corresponding controller for this transceiver (with FCC ID: 2AHUVGWT0001) is being processed as the same time of this application.

#### 1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10 (2013). All radiated measurements were performed in an 3m Chamber. Preliminary scans were performed in the 3m Chamber only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

#### 1.4 Test Facility

The 3m Chamber used to collect the radiated data is located at Workshop No. 3, G/F., World-Wide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Sha Tin, N.T., Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

Report No.: 16070371HKG-002 1 of 17

#### 2.0 **System Test Configuration**

#### 2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The device was powered by new 4 x 1.5V AA batteries.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The unit was operated standalone and placed in the center of the turntable.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

#### 2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

#### 2.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

#### 2.5 Support Equipment List and Description

N/A.

Report No.: 16070371HKG-002 2 of 17

#### 3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CF - AG - AV

where  $FS = Field Strength in dB\mu V/m$ 

RA = Receiver Amplitude (including preamplifier) in dBµV

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB AG = Amplifier Gain in dB AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

FS = RR + LF

where  $FS = Field Strength in dB\mu V/m$ 

RR = RA - AG - AV in  $dB\mu V$ 

LF = CF + AF in dB

Assume a receiver reading of 52.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

 $RA = 52.0 dB\mu V/m$ 

AF = 7.4 dB  $RR = 18.0 \text{ dB}\mu\text{V}$  CF = 1.6 dB LF = 9.0 dB

AG = 29.0 dB AV = 5.0 dB FS = RR + LF

 $FS = 18 + 9 = 27 \, dB\mu V/m$ 

Level in  $\mu$ V/m = Common Antilogarithm [(27 dB $\mu$ V/m)/20] = 22.4  $\mu$ V/m

Report No.: 16070371HKG-002 3 of 17

#### 3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 4932.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

#### 3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 16.1 dB

Report No.: 16070371HKG-002 4 of 17

Applicant: Toy Shock International Limited Date of Test: August 04, 2016

Model: 160000A

Worst-Case Operating Mode: Transmitting

# Table 1 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Lowest Channel

	on an in ion								
			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	2413.000	80.4	33	29.4	76.8	19.5	57.3	94.0	-36.7
V	2400.000	51.5	33	29.4	47.9	19.5	28.4	54.0	-25.6
V	4826.000	53.6	33	34.9	55.5	19.5	36.0	54.0	-18.0
V	7239.000	51.9	33	37.9	56.8	19.5	37.3	54.0	-16.7
V	9652.000	38.9	33	40.4	46.3	19.5	26.8	54.0	-27.2
V	12065.000	43.6	33	40.5	51.1	19.5	31.6	54.0	-22.4
V	14478.000	43.0	33	40.0	50.0	19.5	30.5	54.0	-23.5

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	2413.000	80.4	33	29.4	76.8	114.0	-37.2
V	2400.000	51.5	33	29.4	47.9	74.0	-26.1
V	4826.000	53.6	33	34.9	55.5	74.0	-18.5
V	7239.000	51.9	33	37.9	56.8	74.0	-17.2
V	9652.000	38.9	33	40.4	46.3	74.0	-27.7
V	12065.000	43.6	33	40.5	51.1	74.0	-22.9
V	14478.000	43.0	33	40.0	50.0	74.0	-24.0

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16070371HKG-002 5 of 17

Applicant: Toy Shock International Limited Date of Test: August 04, 2016

Model: 160000A

Worst-Case Operating Mode: Transmitting

# Table 2 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### Middle Channel

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	2452.000	77.1	33	29.4	73.5	19.5	54.0	94.0	-40.0
V	4904.000	55.7	33	34.9	57.6	19.5	38.1	54.0	-15.9
V	7356.000	52.0	33	37.9	56.9	19.5	37.4	54.0	-16.6
V	9808.000	40.3	33	40.4	47.7	19.5	28.2	54.0	-25.8
V	12260.000	41.6	33	40.5	49.1	19.5	29.6	54.0	-24.4
V	14712.000	41.6	33	38.4	47.0	19.5	27.5	54.0	-26.5

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari- zation	Frequency (MHz)	Reading (dBµV)	Gain (dB)	Factor (dB)	3m - Peak (dBµV/m)	at 3m (dBµV/m)	Margin (dB)
V	2452.000	77.1	33	29.4	73.5	114.0	-40.5
V	4904.000	55.7	33	34.9	57.6	74.0	-16.4
V	7356.000	52.0	33	37.9	56.9	74.0	-17.1
V	9808.000	40.3	33	40.4	47.7	74.0	-26.3
V	12260.000	41.6	33	40.5	49.1	74.0	-24.9
V	14712.000	41.6	33	38.4	47.0	74.0	-27.0

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.

6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16070371HKG-002 6 of 17

Applicant: Toy Shock International Limited Date of Test: August 04, 2016

Model: 160000A

Worst-Case Operating Mode: Transmitting

# Table 3 Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

#### **Highest Channel**

			Pre-Amp	Antenna	Net at	Average	Calculated	Average Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	Factor	at 3m	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	2467.000	78.0	33	29.4	74.4	19.5	54.9	94.0	-39.1
V	2483.500	52.3	33	29.4	48.7	19.5	29.2	54.0	-24.8
V	4937.000	55.5	33	34.9	57.4	19.5	37.9	54.0	-16.1
V	7401.000	52.1	33	37.9	57.0	19.5	37.5	54.0	-16.5
V	9868.000	46.0	33	40.4	53.4	19.5	33.9	54.0	-20.1
V	12335.000	41.5	33	40.5	49.0	19.5	29.5	54.0	-24.5
V	14802.000	42.5	33	38.4	47.9	19.5	28.4	54.0	-25.6

			Pre-Amp	Antenna	Net at	Peak Limit	
Polari-	Frequency	Reading	Gain	Factor	3m - Peak	at 3m	Margin
zation	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	2467.000	78.0	33	29.4	74.4	114.0	-39.6
V	2483.500	52.3	33	29.4	48.7	74.0	-25.3
V	4937.000	55.5	33	34.9	57.4	74.0	-16.6
V	7401.000	52.1	33	37.9	57.0	74.0	-17.0
V	9868.000	46.0	33	40.4	53.4	74.0	-20.6
V	12335.000	41.5	33	40.5	49.0	74.0	-25.0
V	14802.000	42.5	33	38.4	47.9	74.0	-26.1

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16070371HKG-002 7 of 17

Applicant: Toy Shock International Limited Date of Test: August 04, 2016

Model: 160000A

Worst-Case Operating Mode: Transmitting

# Table 4 Radiated Emissions Pursuant to FCC Part 15 Section 15.209 Requirement

			Pre-	Antenna	Net	Limit	
	Frequency	Reading	amp	Factor	at 3m	at 3m	Margin
Polarization	(MHz)	(dBµV)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)
V	56.348	26.3	16	11.0	21.3	40.0	-18.7
V	78.456	32.3	16	6.0	22.3	40.0	-17.7
V	136.726	27.1	16	14.0	25.1	43.5	-18.4
V	215.589	25.1	16	17.0	26.1	43.5	-17.4
Н	335.248	14.5	16	24.0	22.5	46.0	-23.5
Н	522.477	10.2	16	27.0	21.2	46.0	-24.8

NOTES: 1. Peak Detector Data unless otherwise stated.

- 2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
- 3. Negative sign in the column shows value below limit.
- 4. Horn antenna is used for the emission over 1000MHz.
- 5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205.
- 6. Measurement Uncertainty is ±5.3dB at a level of confidence of 95%.

Report No.: 16070371HKG-002 8 of 17

#### 4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

#### 5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

#### 6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

### 7.0 <u>Instruction Manual</u>

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

Report No.: 16070371HKG-002 9 of 17

#### 8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

#### 8.1 Radiated Emission on the Bandedge

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

The test data of bandedge emissions were shown on the above radiated emissions table 1 and table 3 respectively.

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74 dB $\mu$ V/m (Peak Limit) but exceeded 54 dB $\mu$ V/m (Average Limit).

Report No.: 16070371HKG-002 10 of 17

#### 8.2 Discussion of Pulse Desensitization

Pulse desensitivity is not applicable for this device. The effective period (Teff) is approximately 0.18 ms for a digital "1" bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse desensitivity factor is 0dB.

### 8.3 Calculation of Average Factor

The duty cycle is simply the on-time divided by the period:

The duration of one cycle =5.1 ms


Effective period of the cycle =  $0.18 \times 3 = 0.54 \text{ ms}$ 


DC = 0.54/5.1 = 0.106

Therefore, the averaging factor is found by  $20\log 0.106 = -19.5 \text{ dB}$ .

Report No.: 16070371HKG-002 11 of 17


### **Average Factor**





Report No.: 16070371HKG-002 12 of 17

## **Average Factor**



Report No.: 16070371HKG-002 FCC ID: 2AHUVGWRS0001

#### 8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately 0.8m in height above the ground plane for emission measurement at or below 1GHz and 1.5m in height above the ground plane for emission measurement above 1GHz. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

Report No.: 16070371HKG-002 14 of 17

#### 8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.10 (2013).


The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 3 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.


Report No.: 16070371HKG-002 15 of 17

#### 8.4.1 Radiated Emission Test Setup

The figure below shows the test setup, which is utilized to make these measurements.



Test setup of radiated emissions up to 1GHz



Test setup of radiated emissions above 1GHz

Report No.: 16070371HKG-002 16 of 17 FCC ID: 2AHUVGWRS0001

## 9.0 **Equipment List**

## 1) Radiated Emissions Test

Equipment	EMI Test Receiver	Spectrum Analyzer	BiConical Antenna
Registration No.	EW-3156	EW-2253	EW-0571
Manufacturer	R&S	R&S	EMCO
Model No.	ESR26	FSP40	3104C
Calibration Date	Nov. 03, 2015	Jun. 10, 2016	Jun. 23, 2015
Calibration Due Date	Nov. 03, 2016	Jun. 10, 2017	Dec. 23, 2016

Equipment	Double Ridged Guide Antenna	Log Periodic Antenna
Registration No.	EW-1133	EW-0447
Manufacturer	EMCO	EMCO
Model No.	3115	3146
Calibration Date	Nov. 05, 2015	Mar. 16, 2015
Calibration Due Date	May 05, 2017	Sep. 16, 2017

## 2) Average factor Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-2249
Manufacturer	R&S
Model No.	FSP30
Calibration Date	Nov. 27, 2015
Calibration Due Date	Nov. 27, 2016

**END OF TEST REPORT** 

Report No.: 16070371HKG-002 17 of 17 FCC ID: 2AHUVGWRS0001