

RF Exposure	Reference Test Report No: ULR- TC56882030000022F	Seite 1 von 2 Page 1 of 2
-------------	---	------------------------------

RF Exposure Report

Following FCC KDB 447498 D01 General SAR test exclusion guidelines

The corresponding SAR exclusion threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation Distances \leq 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g.

Extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion (447498 D01 General RF Exposure Guidance v06)

2) At 100 MHz to 6 GHz and for test separation distances $>$ 50 mm, the SAR test exclusion threshold is determined according to the following

- $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz
- $[\text{Power allowed at numeric threshold for 50 mm in step 1} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at $>$ 1500 MHz and \leq 6 GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion,

- The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for *test separation distances* $>$ 50 mm and $<$ 200 mm
- The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for *test separation distances* \leq 50 mm
- SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

RF Exposure		Reference Test Report No: ULR- TC568820300000022F				Seite 2 von 2 Page 2 of 2
SAR Test Exclusion Thresholds						
RF Protocol	Measured Frequency (GHz)	Maximum measured RF output power at antenna terminal (dBm)	Tune-up tolerance (dB)	Max power Including tune-up tolerance * (mW)	Exclusion threshold ** for separation distance of 5 mm	SAR Test required (Yes/No)
Wi-Fi	2.412	-0.19	±2	1.51705	0.4712	No

*Max power is rounded to two decimal place for reporting

**separation distance of 5 mm is used for the calculation

Hence RF exposure evaluation or SAR testig is not required for Wi-Fi 2.4 GHz frequency range

Note:

1. Calculate SAR exclusion threshold from condition 1) formulas.