

ORTHOFIX US LLC

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – AccelStim, Model: 4301

REPORT NUMBER

105890996DAL-002

ISSUE DATE

August 27, 2024

REVISION DATE

September 18, 2024

PAGES

9

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017
© 2017 INTERTEK



**RF Exposure Exhibit
(Portable Devices)**

Report Number: 105890996DAL-002

Project Number: G105890996

Report Issue Date: August 27, 2024

Report Revision Date: September 18, 2024

Product Designation: AccelStim

Model Tested: 4301

FCC ID: 2AHVN-OFIX-4301-001

IC ID: 21309-4301OFIX001

to

47CFR 2.1093

RSS-102 Issue 6

for

Orthofix US LLC.

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

ORTHOFIX US LLC
3451 Plano Parkway
Lewisville, TX 75056-9453 USA

Report prepared by:



Kenenth Roque
EMC Project Engineer

Report reviewed by:



Anderson Soungpanya
EMC Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 105890996DAL-002	
Equipment Under Test:	Accelstim
Model(s) Tested:	4301
Applicant:	Orthofix US LLC
Contact:	Daniela Behzad
Address:	3451 Plano Parkway Lewisville, TX 75056-9453 USA
Country:	USA
Email:	danielabehzad@orthofix.com
Applicable Regulation:	47CFR 2.1093 RSS-102 Issue 6



TABLE OF CONTENTS

ORTHOFIX US LLC 1

1.0 RF Exposure Summary..... 5

2.0 RF Exposure Limits 5

3.0 Test Results (Portable Configuration) 6

4.0 Document History 9

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1093	RSS-102 Issue 6	Complies

2.0 RF Exposure Limits

2.1 FCC Limits

According to FCC KDB 447498 D01 v06, at frequency 2450 MHz and separation distance of ≤ 5 mm the equation and threshold in section 4.3.1 must be applied to determine the SAR exclusion.

The SAR exclusion threshold is determined by the following formula (KDB 447498 D01 Section 4.3.1(a))

$$\left[\frac{\text{Max. tune up Power (mW)}}{\text{Min. Test Separation Distance (mm)}} \right] * \sqrt{F(\text{GHz})} \leq 3$$

2.2 Industry Canada Limits

According to RSS-102 sec. 2.5.1, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 4 mW.

3.0 Test Results (Portable Configuration)

3.1 Classification

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 5 centimeters of the body of the user.

3.2 EIRP calculations

The AccelStim, Model: 4301 consists of one BLE 2.4GHz radio.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2402-2480	-5.29	-3.86	Conducted power measurements were taken from FCC Test Report 105890996DAL-001

Note: Antenna gains below 0 are considered as 0dBi.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for FCC KDB 447498 D01 v06

Max Peak Conducted Power measured = -5.29 dBm or 0.296 mW

No duty cycle was considered.

Therefore, the Maximum EIRP calculated is -5.29 dBm (RF Conducted Power) + 0 dBi (Antenna Gain) = -5.29 dBm or 0.296 mW.

According to KDB 447498 D01 Section 4.3.1 the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula (KDB 447498 D01 Section 4.3.1(a))

$$\left[\frac{\text{Max. tune up Power (mW)}}{\text{Min. Test Separation Distance (mm)}} \right] * \sqrt{F(\text{GHz})} \leq 3$$

$$\left[\frac{0.3 \text{ (mW)}}{5 \text{ (mm)}} \right] * \sqrt{2.45} = 0.09$$

Which is less than 3

Results: The Measurement result comply with the FCC limit per 47 CFR 2.1093 for the RF Exposure and SAR Exclusion per KDB 447498 D01 v06 so the SAR evaluation is not required for this device.

Note: Antenna gains below 0 are considered as 0dBi.

3.4.2 RF Exposure calculation for RSS-102 Issue 6

According to RSS-102 sec. 2.5.1, at frequency 2450 MHz and separation distance of ≤ 5 mm SAR Exemption limit is ≤ 3 mW.

Max Peak Conducted Power measured = -5.29 dBm or 0.296 mW

No duty cycle was considered.

Therefore, the Maximum EIRP calculated is -5.29 dBm (RF Conducted Power) + 0 dBi (Antenna Gain) = -5.29 dBm or 0.296 mW.

Results: SAR evaluation is not required since the higher of the maximum conducted or equivalent isotopically radiated power (EIRP) source-based, time averaged output power is below the exemption limit.

Note: Antenna gains below 0 are considered as 0dBi.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/G105890996	KR	AS	August 27, 2024	Original document
1.1/G105890996	KR	AS	September 18, 2024	FCC KDB 447498 D01 Version changed to V06 The equation from the FCC KDB 447498 D01 Section 4.3.1(a) applied to determine the SAR test exclusion. In Section 3.4.2 SAR Exemption limit changed to 3 mW